iTALONG: A MOBILE APPLICATION FOR MEASURING EGGPLANT LEAF DIMENSION USING IMAGE PROCESSING

MARIA TERESA LAYANTE PAGTANANAN

PRESENTED TO THE FACULTY OF THE INSTITUTE OF COMPUTER SCIENCE, UNIVERSITY OF THE PHILIPINES LOS BAÑOS IN PARTIAL FULFILLMENT FOR THE DEGREE OF

BACHELOR OF SCIENCE IN COMPUTER SCIENCE

The Faculty of the Institute of Computer Science of the University of the Philippines Los Baños accepts the Special Problem entitled

iTALONG: A MOBILE APPLICATION FOR MEASURING EGGPLANT LEAF DIMENSION USING IMAGE PROCESSING

MARIA TERESA LAYANTE PAGTANANAN

In partial fulfillment of the requirements for the Degree Bachelor of Science in Computer Science Prof. VAL RANDOLF M. MADRID Adviser Date Signed Prof. JADERICK P. PABICO Director, Institute of Computer Science

Date Signed

iTALONG: A MOBILE APPLICATION FOR MEASURING EGGPLANT LEAF DIMENSION USING IMAGE PROCESSING

ABSTRACT

PAGTANANAN, MARIA TERESA LAYANTE. 2020. iTalong: A Mobile Application for Measuring Eggplant Leaf Dimension Using Image Processing. University of the Philippines Los Baños, College of Arts and Sciences, Institute of Computer Science.

iTalong is a mobile application with computer-aided measuring of the dimensions of eggplant leaves. It was built using Android Studio with OpenCV library for image processing and SQLite3 for database. The results from using the application were tested using dependent sample t-test. The test found that difference of the means of measuring the width was not significant, while in measuring the length was significant at 95% confidence level. Despite that there was a difference between the means in measuring the length manually and automatically, the error on the average was only at 2. 34%.

BIOGRAPHICAL SKETCH

Maria Teresa L. Pagtananan, most commonly known as Tesa, is a loving daughter and the youngest child of Martin C. Pagtananan and Lilian L. Pagtananan. She is a graduating student taking up Bachelor of Science in Computer Science at the University of the Philippines Los Baños. Her hobbies are watching TV and baking.

ACKNOWLEDGEMENT

I would like to thank my whole family for helping and supporting me throughout my college journey. Ate Aiza or King, thank you for sacrificing your dreams for yourself in order to fulfill mine; I promise to make it all worthy and also to help you chase your dreams this time. I would also like to thank my parents for their unconditional love and unending support that continue to keep and inspire me to work harder. I also dedicate this to my late sister, ate Ana; I believe that you have guided me. I miss you a lot.

This research would not be possible without the guidance of my SP adviser, Prof. Val Randolf Madrid. Thank you, sir, for being understanding and for your patience and assistance throughtout my entire SP terms. I promise to keep and remember all the wisdom you shared with us. I would like to thank the Institute of Plant Breeding, especially Dr. Lourdes Taylo for allowing me to be part of their research and Mr. Bryan Diamante for assisting me with the process of characterization.

I would also like to thank my roommates and constant friends, Tine, Yuri, Antonette, Arshly, Kuya Prince, and Francis for being so supportive about everything and also for helping whenever I needed it. You have all been there for me ever since we were on high school. To my boyfriend, Francis Rafael, thank you for helping me and accompanying me always.

Finally, I would like to thank the Lord Almighty. I might have forgotten to pray and ask sometimes, but He still continues to give me everything I need.

TABLE OF CONTENTS

BIOGRAPHICAL SKETCH	iv			
ACKNOWLEDGEMENT	v			
INTRODUCTION	1			
A. Background of the Study	1			
B. Significance of the Study	2			
C. Objectives of the Study	2			
D. Scope and Limitations				
REVIEW OF RELATED LITERATURE	3			
MATERIALS AND METHODS	6			
A. Materials	6			
B. Methods on Measuring Leaf Dimension	7			
1. Image Capture	7			
2. Image Processing	8			
3. Computation of the Leaf Dimension	9			
C. Testing	10			
D. Flow of the System in Application View	10			
RESULTS AND DISCUSSION	12			
CONCLUSION AND FUTURE WORK	17			
REFERENCES	18			

I. INTRODUCTION

A. Background of the Study

Eggplant is considered to be an important, economical, and popular harvest in most parts of Asia. Since it is inexpensive, it is also one of the most consumed vegetable. Furthermore, the production of eggplant is a popular source of income of farmers and it can be planted almost anywhere. In the Philippines, eggplant production represents over 30% of the total volume of production of vegetables of the country [15]. But the greatest constraint of growers in eggplant production is the infestation of the eggplant fruit-and-shoot borer (EFSB) [16]. The larvae damage the eggplant by boring into the petiole and midrib of leaves and soft shoots resulting in wilting and stem desiccation. Flowers also are fed upon resulting in flower drop or misshapen fruit. The maximum damage that EFSB can be done is when it generates holes to the fruit, feeding tunnels and frass (or larval excrement), making it unmarketable and not safe for human consumption. At high pest strain, EFSB damage inside the Philippines results in yield loss of up to 80% of the crop [5]. To aid the problem, most of the farmers apply chemical insecticides [4] to the eggplants to get rid of EFSB because other method such as manual removal of EFSB is inefficient and impractical. However, the use of insecticides also increases the production cost of the eggplant and it is also risky to human health and environment [7].

Studies are being conducted to solve the problem led by the infestation of the EFSB.

Researchers from Institute of Plant Breeding focus on improving the eggplant varieties. To make this possible, a lot of study should be conducted to improve and propagate the eggplant with new plant defense genes for multiple insect-resistant. They would need to get the plant genetic

resources or the characters of different varieties of eggplant; this process is called eggplant characterization. One of the characters is the leaf dimension. Gathering these data takes a lot of time and effort since it is done manually using ruler for measuring and pen and paper for taking note of the data gathered.

In the Philippines, eggplant characterization for some characters is still done manually. This is prone to human error and inefficient because it will consume a very large amount of time since researchers collect the data from hundreds or even thousands of eggplants.

This study presents a solution to the problem by developing a system with computer-aided measuring of the dimensions of the leaf.

B. Significance of the Study

The system makes the manual process of measuring leaf dimension from eggplant easier by using a mobile application. This will make the process computer-aided. Also, human error is minimized because of minimal human action needed in this experiment.




Figure 1: Characterization Data Sheet for collecting Seedling data

C. Objectives of the Study

The main objective of the study is to develop a system with computer-aided measuring of the leaf dimension of the eggplants.

Specifically, this study aims to:

- 1) develop a mobile application where the user can add, view, update, delete, and export characterization (leaf dimension) entries
- 2) create a module that uses image processing techniques to detect the leaf on the image and get its length and width
- 3) evaluate and verify the results by comparing it with the actual measurements or results

D. Scope and Limitations

This study is to create a mobile application that can do computer-aided measuring of leaf dimension for the study of improving the defense genes for multiple insect-resistant of eggplants by Institute of Plant Breeding. The app is only available for those who are involved in the research. Also, the application does not cover all the all characters that need to be observed when conducting eggplant characterization, only the leaf dimension. Moreover, the mobile application can only be run on Android at minimum API level 19.

II. REVIEW OF RELATED LITERATURE

Several studies have been conducted focusing on automated data gathering using image processing algorithms.

One of the studies that involve automated data collection is the automated counting of chromosomes present in the image that was implemented by Wenzhong and Shuqun from the School of Electronic Engineering, Beijing University of Posts and Telecommunications [17]. The algorithm for this study consists of several image processing techniques. First, they used histogram equalization to the input image for better contrast. Then, using thresholding, they binarized the image. After that, they

implemented erosion to remove false negative. Then, they performed the labeling algorithm to distinguish objects present in the image. However, the algorithm used was unsuitable in counting the human diploid cell resulting into a greater or lesser number than the actual number of chromosomes. With so, they proposed the used of iterative thresholding and mathematical morphology for edge detection method [18]. First, they performed iterative thresholding to enhance the edges of the chromosomes and improve contrast. Then, they implemented contour extraction algorithm to detect the edges and count the detected regions or the chromosomes. Using iterative thresholding and edge detection algorithm, they found out that it is more efficient than using the commonly differential operators for the study.

The image processing techniques implemented in the said research could be used in this study for the detection of the object in the image since the contrast between the background and the foreground of the

Another study involving automated data gathering is the detection of abnormalities in red blood cells using shape analysis conducted by Manalang in 2009. The research automated the manual process that observes the sample under the microscope, and the professionals examine the shape and color of the cells to tell whether there are abnormalities present [9]. He used various image processing techniques namely binarization, component filling, and shape analysis. Because of the promising result of the said research, the study will also make use of binarization on pre-processing images, to remove the noise in the images.

image was high, similar to the images that this study will used for characterization.

Mustafa et al. [10] attempted to determine the quality of the banana using its size and ripeness from its image using a certain image processing toolbox on his study. He proposed using a reference object and its dimension must be known to be able to determine the size of the banana. There had been studies that were similar to this. A similar technique was also implemented by Canare and Reyes [3]. They used flatbed scanner instead of camera for capturing the images of the rice seeds. They performed various image processing techniques in pre-processing the images such as binary operations and filtering methods to enhance the objects in the image and for better detection. Also, they found out that linear regression is a good method in determining the measurement of a rice seed and that ellipse fitting is also a

good method for getting the dimensions of the rice seed. Furthermore, a study made by Paje in 2010 also involved getting the distance between veins of rice seed leaf in an image with the use of ruler as a guide to pixels to metric system conversions [12]. The objective of this said research was very similar to this study; getting measurements using image processing. The formula of getting the measurements will be based on the said methods of this study since the results of this research were accurate.

Another study that used image processing for automating data gathering was conducted by Peralta [14]. He presented his solution to the problem in the process of wood characterization. He also used image processing algorithms to solve this. In pre-processing the images, he performed histogram stretching and filtering method. Then, he used connected component algorithm to determine the pores on the wood that are important in evaluating the wood. The image processing techniques used in the said research are very similar to the techniques used in the former works; performing connected component algorithm for detection. This could be used for detecting the object of interest in the image.

There are also studies that focus on performing the non-contact measurement techniques with the help of image processing. However, the main approach that these studies used to solve the problem is more of machine vision than computer vision. But this review will focus mainly on to the image processing techniques the studies used. Bharathi, Sathiyamoorthy from the Indian Institute of Technology Madras conducted a study about non-contact measurement using machine vision [2]. The objective of their study is to make usual process of monitoring the condition of the rubber gaskets in a faster way. They implemented edge detection algorithm in other to find the edges of the rubber gaskets. Then, they performed contour analysis to find the texture defects on the rubber gaskets. The study was able to increase the speed of manufacturing process. The said research only proves that automation of the process of getting dimensions is possible, but it was implemented through machine vision.

Unlike the said research, this study implemented the measuring through computer vision. All the studies cited above used image processing techniques and successfully automated the process of data gathering or collection. Variables used in the cited works and objectives were quite similar with the

variables that will be used in this study; it all used images and then extracted the object from the image to further study that particular object.

With the promising results of the said works, this study mainly used image processing for automating the data collection.

III. MATERIALS AND METHODS

A. Materials

The following were used for development the application:

- 1. Laptop
 - Intel i7-3537U 2.50 GHz
 - 64-bit processor
 - 8.00GB RAM
 - Windows 7
- 2. Software technologies
 - Android Studio 3.4.2
 - OpenCV 4.1.0
 - Java 7
 - SQLite3

For testing the application, a mobile phone was used with the following specifications:

- Android 9.0 (Pie)
- 4.00GB RAM
- 16 MP Main camera

B. Methods used on Measuring Leaf Dimension


1. Image Capture

- a. The leaf was placed parallel to the side of the reference object, a 4 in x 4 in, green-colored square printed on a white sheet of paper (see Fig. 2) when capturing its image. This mimicked the background used by the IPB.
 The user must rotate the device horizontally or in a landscape orientation (see Fig. 3) to fit the objects inside the frame and to minimize the distance of the camera from the objects.
- b. The dimension of the reference object was known since it was used for computing the dimension [6].



Figure 2: Collecting the leaf samples






(a) The use of tape to stick the leaf

(b) Image capture setup



(a) Capturing the image in landscape orientation



(b) Camera view

Figure 4: Image capture

2. Image Processing

In processing the image, built-in functions from OpenCV library were used and applied.

After capturing the image, it was converted from RGB to LAB color space. Then, the channels were split to get the L-channel or the lightness. CLAHE or Contrast Limited Adaptive Histogram Equalization was applied on the L-channel to enhance illumination. Then, the A, B, and the CLAHE-enhanced L-channel were merged together.

To further enhance the illumination, the image was converted to YUB color space, then the Y-channel or brightness was extracted and histogram equalization was applied on the said channel. After that, all the Y, U, B channels were merged together.

The enhanced image was then converted to grayscale before segmentation. For image segmentation, combined built-in functions of OpenCV for thresholding were used the *THRESH_OTSU* for otsu thresholding, and *THRESH_BINARY_INV* for inverted

binary thresholding. This was done to partition the foreground, the leaf and the reference object; and the background of the image. After the segmentation, morphological operation, opening, was applied to remove noise in the image.

The built-in function called *Canny* which implements Canny Edge Detection was done to prepare the image for finding the contours. The significance of finding the contours was to detect the leaf and the reference object in the image.

3. Computation of the Leaf Dimension

The built-in function boundingRect was used to mark the connected components or regions in the list of contours found in the image. It was also used to get the area of each detected regions.

The width of the reference object was known and fixed at 10.16 cm, since this would be the used for converting the acquired dimension of the leaf from pixel to its approximate real-world dimension. *approxPolyDP* was used to detect the square and to assure that it was the reference object. Then, the next detected region with the largest area would be the leaf.

The width of the bounding rectangle that marks the reference object was also the width of the reference object in pixel. Finally, to get the approximate width and approximate length of the leaf, the dimension of the bounding box of the leaf in pixel was divided by the width of the reference object in pixel, and was then multiplied to 10.16 to convert it to cm. The values needed to set up the formula were the following:

 $\frac{\textit{width or height of the bounding box of the leaf in px}}{\textit{width of the bounding box of square in px}} \times 10.16 \, \textit{cm}$

Equation 1

C. Testing

Manual measurements of the leaves was compared to the automated measurements from using the app. When measuring the length of the leaf manually, start from the base of the leaf blade (petiole not included) down to the tip. On the other hand, width was measured on the widest portion of the leaf. While measuring using the application, the leaf was captured next and parallel to the reference object or the green square.

The researcher gathered two dependent samples from the actual measurements done manually and from the computed measurements by the mobile application. These were used for the paired t-tests that determine if there was a significant difference between the measurements of two data vectors: one for the length of the leaf, and one for the width of the leaf; manually computed and automatically computed by the application [19]. The researcher also computed for the percent error of the two data vectors.

The null hypothesis H_o assumed that the difference of the paired population mean of the manually obtained dimensions of the leaves and the population mean of automatically computed dimensions of the leaves would be equal to zero. The alternative hypothesis H_a suggested the opposite of the null hypothesis.

D. Flow of the System in Application View

User is directed to the Home page (see Fig. 5) when the application is opened. "START" button will take the user to the Menu page (see Fig. 6) displaying the options to choose from; add entry, search entry, delete entry, and export records.

In the Add Entry page, it will first ask for accession no., plot no. and plant I.D. of the entry (see Fig. 7.a) before proceeding to capturing image of the leaf (see Fig. 7.b). After capturing the image (see Fig. 7.c), image processing techniques would be applied, then the processed image will be shown along with the result. The user may press "SAVE" button to save the result to the records, or "RETAKE" button to retake the image.

With search entry option (see Fig. 8), the user can search a specific entry or display all entries. When searching for a specific entry (see Fig. 8.a), the app will ask for the plant I.D. of the entry being searched for. Then, click "SEARCH" button to display the all the information of the entry (see Fig. 8.b). The user may delete the entry or edit the accession no. or plot no. of the entry. On the other hand, when the user opts to view all the entries, the app will display all the entries together with the information of each one in a list view (see Fig. 8.c). The user may delete an entry by long pressing that listed item.

Clear all records option allows the user to delete the entire record of entries. Three dialog boxes will pop out showing the confirmation message before deleting all entries.

Under the export records option, press the tab of the option to export records to a csv file that will be saved in the storage of the device.




Figure 5: Home Page

Figure 6: Menu Page




Figure 7: Add Dimension Entry




Figure 8: Search Entry

IV. RESULTS AND DISCUSSION

specific entry

iTalong was able to capture image and to process it to compute the measurements (see Fig. 9). Image processing techniques applied were able to detect the objects and data needed for measuring the dimension were gathered (see Fig. 10). Also, the application could store the records in the database making it useful for the users to view and retrieve the records anytime they need it (see Fig. 15).




Figure 9: Add feature of iTalong; used image processing for computing dimension

Manual measuring of the leaves (see Fig. 11) for testing was done by the researcher using a ruler. The process of measuring was instructed by an expert. Thirty leaves from bougainvillea tree were set as the samples for the test. After manual measuring, the researcher used the application to get the dimension of the leaves. The distance of the camera or the device used for taking the images was approximately from 12cm to 20 cm away from the objects. The distance of the camera may vary depends on the size of the leaf; the whole leaf should be inside the camera frame. However, the camera view should be within the white background. The result of measuring the dimension of the leaf using the application was compiled in a csv file (see Fig. 15).




Figure 10: Image processing techniques applied; errors of 0.34% (width) and 1.22% (length) for this particular entry




Figure 11: Dimensions of the leaf samples obtained from manual measuring

The t-values computed from the t-test for the widths and lengths were 1.94 and 6.31 respectively. The t-value for the width is less than the critical value. Therefore, accept the null hypothesis that stated the means of the widths from manual and automated measuring has no significant difference (see Table 1). On the other hand, the t-value for the length is greater than the critical value; therefore, reject the null hypothesis and the difference of the means of the lengths from manual and automated measuring is not equal to zero. Despite that, the error in automated measurements of length on the average was only at 2.34%.

Table 1: Results of Independent Samples t-test

	t-value	Critical value	Analysis	Decision	Error
Width	1.94	2.05	1.94<2.05	Accept H _o	2.25%
Length	6.31	2.05	6.31>2.05	Reject H _o	2.34%

Percent error was also computed individually to determine the errors occurred when measuring using the app. The highest error in measuring the width was at 6.85% and error was suspected to be caused by alignment of the objects in the image. The midrib of the leaf and the side of the square must be perfectly parallel to avoid increasing or decreasing the size. (see Fig. 12) This error can also be observed from the other entries. On the other hand, the highest error in measuring the length was at 5.93% and the error was observed to be caused by the tip of the leaf blade being too thin that it was identified as a noise (see Fig. 13).




Figure 12: plantID: D7 (93.15% accurate at measuring width)




Figure 13: plantID: D1 (94.10% accurate at measuring length)

Most of the errors at measurements might be caused by the creases on the background and the alignment of the objects in the image (as mentioned above). Appearance of wrinkles was unavoidable because the background was a paper. It was responsible for the deformation of the sides of the square, decreasing the measurement of the side of the square and increasing the result measurements.

plantID	width	height
1	6.1	9.3
2	5.9	8.1
3	5.8	8
4	5.6	7.6
5	5.7	8.1
6	5.8	9.5
7	5.1	8.4
8	8.4	5.3
9	9.4	6.2
10	5.4	8.4
11	5.8	8.7
12	5.7	9
13	5.8	9.5
14	5.2	7.7
15	6.2	9.1
16	5.9	8.1
17	5.6	7.9
18	5.6	8.6
19	6	8.6
20	5.1	8.6
21	5.5	8.7
22	6.3	9.9
23	6.1	8.9
24	6.5	9.3
25	6.8	10.5
26	6.4	9.8
27	7.2	10.5
28	6.7	10.5
29	6.5	11.1
30	6.2	8.8

plantID	accessio	plotNo	width	height	date	position
D1	D1	D1	5.92667	8.74889	******	36
D2	D2	D2	5.50729	7.78617	#######	37
D3	D3	D3	5.92667	7.80815	#######	38
D4	D4	D4	5.35214	7.52929	#######	39
D5	D5	D5	5.60224	7.78617	######	40
D6	D6	D6	5.98714	9.07143	#######	41
D7	D7	D7	5.44945	8.31273	#######	42
D8	D8	D8	5.27538	8.30385	#######	43
D9	D9	D9	6.07701	9.11551	#######	44
D10	D10	D10	5.31738	8.07103	#######	45
D11	D11	D11	5.73128	8.42325	#######	46
D12	D12	D12	5.76649	8.78703	#######	47
D13	D13	D13	5.91845	9.37087	#######	48
D14	D14	D14	5.3219	7.64419	#######	49
D15	D15	D15	6.15758	8.92848	#######	50
D16	D16	D16	5.88211	8.28842	#######	51
D17	D17	D17	5.64444	7.81538	#######	52
D18	D18	D18	5.57451	8.18195	#######	53
D19	D19	D19	6.00364	8.40509	#######	54
D20	D20	D20	5.12577	8.4209	#######	55
D21	D21	D21	5.26815	8.74889	#######	56
D22	D22	D22	6.17196	9.78019	#######	57
D23	D23	D23	6.15462	8.59692	#######	58
D24	D24	D24	6.26692	9.40037	******	59
D25	D25	D25	6.63921	10.3612	******	60
D26	D26	D26	6.42189	9.68075	#######	61
D27	D27	D27	6.83664	10.3499	******	62
D28	D28	D28	6.70757	10.2586	******	63
D29	D29	D29	6.25231	10.6485	******	64
D30	D30	D30	5.98206	8.7357	******	65

Figure 15: Generated csv file from the app

Figure 14: Results of manual measuring the leaves

V. CONCLUSION AND FUTURE WORK

This study was feasible to measure the dimension of the leaf. Combined image processing techniques from OpenCV Library used were able to detect the leaf and the reference object.

Necessary data for computing the dimension were gathered with the help of the image processing techniques. The difference of the means of manual and automated measuring of the width was not statistically significant. However, the difference of the means of manual and automated measurements of length was not equal to zero. Despite that, computed error on the average was only at 2.34%.

Errors observed were mostly caused by the creases on the background since it was made of paper.

Creases reduced the measurement of the square; increasing the computed measurements of the app.

The alignment of the objects in the image was also observed to cause errors in computing the measurements.

To further enhance the application, future developers can extend and expand the modules of the application to cater all the characters. They can also make the same application except that the user will not need to use a reference object or background when capturing images. They can also change the design of the background and interpolate the shape of the leaf. Furthermore, they can opt to improving the image segmentation by using different techniques aside from thresholding for greater accuracy.

VI. REFERENCES

- [1] Bastan, M., Bukhari, S., Breuel, T. (2016). Active Canny: Edge Detection and Recovery with Open Active Contour Models [Online image]. Retrieved November 22, 2018 from https://arxiv.org/pdf/1609.03415.pdf
- [2] Bharathi, S. S., Sathiyamoorthy, S. (2014). Non-Contact Measurement Techniques Using Machine Vision.
- [3] Canare, A., Reyes, P. G. (2011). "Image-based Measurement of Rice Seed Dimension Using 2-Dimensional Models"
- [4] Chupungco AR, Elazegui DD, Nguyen MR. Seed system, production and marketing of eggplant in three major producing provinces in the Philippines. Philippine Journal of Crop Science. 2011; 36: 9 " Ea19.
- [5] Francisco, S.R. (2009). Costs and benefits of UPLB Bt Eggplant with Resistance to Fruit and Shoot Borer in the Philippines In: Norton GW, Hautea DM, editors. Projected Impacts of Agricultural Biotechnologies for Fruits and Vegetables in the Philippines and Indonesia. Ithaca, NY and Los Banos, Laguna: International Services for the Acquisition of Agri-Biotech Applications and the Southeast Asian Ministers of Education Organization-Southeast Asia Regional Center for Graduate Study and Research in Agriculture. pp. 35-54
- [6] Icban, H. G. (2010). "Pineapple Volume Estimation Using Sillhouttes Generated from Image Processing"
- [7] Insecticide residues in soil, water, and eggplant fruits and farmers a health effects due to exposure to pesticides. Del Prado-Lu JL. Environment Health Prev Med. 2015 Jan; 20(1):53-62
- [8] Kanjalkar, H. P., Lokhande, S. S. (2014). Feature extraction of leaf diseases. Int. J. Adv. Res. Comput. Eng. Technol.(IJARCET), 3(1), 153-155.
- [9] Manalang, M. A. L. (2009). "Detection of Red Blood Cell Abnormalities through Shape Analysis"

- [10] Mustafa, N. B. A., Fuad, N. A., Ahmed, S. K., Abidin, A. A. Z., Ali, Z., Yit, W. B., Sharrif, Z. A. M. (2008, August). Image processing of an agriculture produce: Determination of size and ripeness of a banana. In 2008 International Symposium on Information Technology (Vol. 1, pp. 1-7). IEEE.
- [11] Otsu thresholding [Online image]. Retrieved November 22, 2018 from https://www.scipy-lectures.org/packages/scikitimage/auto examples/plothreshold.html
- [12] Paje, F. M. (2010). "Image Processing Applied in Measuring Rice-leaf Interveinal Characteristics"
- [13] Pasahol, C. (2010). "Chromosome Detection and Extraction Using Image Processing"
- [14] Peralta, P. B. (2011). "Shape Characterization of Features on Wood Images"
- [15] Philippines Statistics Authority-Bureau of Agricultural Statistics. Crop-Stat for 2005-2014. Retrieved from http://countrystat.psa.gov.ph/
- [16] Talekar N.S. (May 2002). Controlling Eggplant Fruit and Shoot Borer: A Simple, Safe and Economical Approach. Taiwan: Asian Vegetable Research and Development Center; 4p. International Cooperators a Guide. AVRDC Publication No. 02-534.
- [17] Yan, W., Shen, S. (2008, May). An automatic counting algorithm for chromosomes. In 2008 2nd International Conference on Bioinformatics and Biomedical Engineering(pp. 2492-2494). IEEE.
- [18] Yan, W., Shen, S. (2008, May). An Edge Detection Method for Chromosome Images. In 2008 2nd International Conference on Bioinformatics and Biomedical Engineering(pp. 2390-2392). IEEE.
- [19] Kent State University Libraries. (2017 Mar 6). SPSS tutorials: Independent samples t test. Retrieved November 20, 2018, from http://libguides.library.kent.edu/SPSS/IndependentTTest