Pague SMS API V2

Client Integration Guide

Base URL: http://api.pague.co.uk:9000/api

Send SMS messages and track their delivery status over a simple JSON API.

Authentication

Include your Pague API key in the Authorization header of every request:

```
Authorization: Bearer YOUR_API_KEY
```

Your key identifies your account, so you never send a client ID. Keep it secret: do not commit it to source control, embed it in browser or mobile front-end code, or share it with unauthorised people.

1. Send Messages

POST /messages/send Headers: Authorization, Content-Type: application/json

The body is always a **JSON array**, even for one message. Send many messages in a single request by adding more objects.

```
[
  {
    "destination": "265991234567",
    "body": "Your verification code is 123456.",
    "sender": "Pague"
  }
]
```

Field	Required	Description
destination	Yes	Recipient number in international format, e.g. 265991234567. Do not use local format (0991234567).
body	Yes	Text of the SMS.
sender	No	An approved Sender ID for your account. If omitted, your default Sender ID is used; if none is configured, the request fails.
encoding	No	Message encoding. Defaults to GSM7.

cURL example

```
curl -X POST "http://api.pague.co.uk:9000/api/messages/send" \
  -H "Authorization: Bearer YOUR_API_KEY" \
  -H "Content-Type: application/json" \
  -d '[{"destination":"265991234567","body":"Hello from Pague","sender":"Pague"}]'
```

Success response (HTTP 200) returns one publicId per accepted message. Store it to check the status later.

```
{
  "success": true,
  "data": { "messages": [ { "publicId": "B0KT9RA7zXOWQg" } ] },
  "meta": { "requestId": "", "timestamp": "2026-09-29T19:37:19.986Z" }
}
```

2. Check Message Status

GET /messages/{publicId}/status Header: Authorization: Bearer YOUR_API_KEY

```
curl "http://api.pague.co.uk:9000/api/messages/B0KT9RA7zXOWQg/status" \
  -H "Authorization: Bearer YOUR_API_KEY"

{ "success": true,
  "data": { "publicId": "B0KT9RA7zXOWQg", "status": "QUEUED" },
  "meta": { "requestId": "", "timestamp": "2026-09-29T19:50:20.049Z" } }
```

You can only retrieve messages that belong to your own account. Poll as needed and update your own records.

Status	Meaning
QUEUED	Accepted and queued for processing. This does not mean it has been delivered.

Status	Meaning
ROUTED	A route has been selected for the message.
SUBMITTED	Submitted to a messaging provider.
DELIVERED	Delivery confirmation received.
FAILED	Could not be delivered, or processing failed.
EXPIRED	Expired before successful delivery.

Errors

Failed requests return "success": false with an error object:

```
{ "success": false,
  "error": { "code": "BAD_REQUEST", "message": "Insufficient float balance.",
          "details": [], "path": "/api/messages/send" },
  "meta": { "requestId": "", "timestamp": "2026-09-29T19:23:57.118Z" } }
```

HTTP	Meaning
200	Request accepted.
400	Invalid request or business-rule failure, e.g. insufficient float balance, or no valid or default Sender ID.
401	Missing or invalid API key.
403	Your API key does not have the required capability.
404	Message or resource not found.
500	Internal server error.

Messages are not accepted when your float balance is insufficient. Top up before retrying.

Integration Flow

1. POST /messages/send with your message(s).
2. Save the returned publicId for each message.
3. GET /messages/{publicId}/status to follow progress.
4. Update your application’s records from the returned status. DELIVERED, FAILED and EXPIRED are final.