

Week 1

What I did

****Set up the React frontend**** Created the client under `code/frontend` using Vite and React, with routing, a shared set of design tokens, and a mobile-first layout throughout. The whole app runs on a phone-sized screen.

****Built the donor submission form.**** One screen, six inputs, no multi-step wizard. Food type and collection window are tap targets rather than dropdowns and date pickers, because the proposal commits to a donor's entire obligation fitting in one short form on a phone.

****Built the recipient registration form and the offer inbox.**** Registration captures the three hard constraints the matcher filters on — service radius, daily capacity and accepted food types. The inbox shows each offer with a live countdown on the response window and an accept/decline pair, plus a "why was this offered to us?" panel that explains the match in plain language.

****Built the status timeline.**** Posted → Matched → Accepted → Picked Up → Completed, showing the timestamp of each stage rather than just a tick, and stopping honestly where an expired donation actually stopped.

****Built the admin impact dashboard.**** Servings redistributed, median time-to-match against its 20-minute target, rescue rate and donations lost to expiry, with two charts.

****Built the in-app notification UI.**** Bell with an unread count, a panel of recent notifications, and mark-all-read.

****Added a recipient "Collections" screen.**** Accepted offers were disappearing with nowhere to see the pickup deadline, the pickup code or the donor's contact.

****Made the app role-aware.**** Donor, recipient and administrator each see only their own screens and land on the right one.

****Wrote the API contract**** (`code/API_CONTRACT.md`) covering every endpoint the UI needs, and a mock implementation of it, so the frontend can be built and demonstrated without waiting for the backend.

Problems I found and fixed

The pickup code was shown to the donor ****and**** the donor was asked to type in the code the collector reads out, so the check proved nothing. The collecting organisation now holds the code and the donor verifies it.
Any recipient could see and answer offers made to a different organisation.
The donor could mark a donation completed that they had not received.
Two donations could end up with the same ID after a page reload, so lookups returned the wrong record.

Testing

Walked a donation through all five states in the browser, playing both the donor and the recipient side: posted, matched, accepted, verified the pickup code, completed. Confirmed the donor's phone number stays hidden until an organisation accepts, and that a wrong pickup code is rejected.