

LLM-Driven Real-Time Engine Control and Autonomous 3D Vehicle Assembly: An Extended Model Context Protocol Framework for Unity

Controllo in Tempo Reale dell'Engine Unity ed Assemblaggio Autonomo di Veicoli 3D tramite MCP Esteso

Claudio Pacchiega (Pakkio)¹ & Antigravity AI Agent²

¹Pakkio Unity AI Research Labs • ²Google DeepMind Team

ABSTRACT

Interfacing Large Language Model (LLM) agents with real-time 3D game engines poses significant technical challenges regarding main-thread synchronicity, scene graph mutations, and spatial physics stability. In this paper, we present an extended implementation of the Model Context Protocol (MCP) for the Unity Editor (`pakkio/mcp-unity`). We address critical engine-level failure modes of vanilla stdio-WebSocket bridges, including deferred frame rendering, sibling hierarchy order loss, and scaled transform cloning corruption. Furthermore, we introduce an unsupervised spatial bounds clustering algorithm for automated feature identification on generic 3D meshes (e.g., glTF/GLB models from Sketchfab), coordinate axis decoupling for Blender-imported assets, and Rigidbody inertia tensor stabilization. Finally, we validate our system through a closed-loop orbital navigation benchmark in Play Mode, achieving precise 233.1° trajectory control and real-time telemetry extraction.

Keywords: Model Context Protocol, Unity Engine, Autonomous 3D Assembly, Spatial Clustering, Vehicle Dynamics, Real-Time Telemetry.

1. Introduction

The integration of generative artificial intelligence into interactive 3D content creation tools is shifting software development from manual GUI manipulation to high-level intent-based agentic workflows. The Model Context Protocol (MCP) provides a standardized client-server architecture enabling AI agents to inspect resources, execute tool invocations, and modify state across external applications.

However, standard MCP wrappers for monolithic game engines like Unity suffer from severe operational constraints: deferred render repaints, loss of hierarchy sibling index control, and anonymous mesh node identifiers on imported assets.

2. System Architecture & Protocol Extensions

```
Client Agent <==[stdio/MCP SDK]==> Node.js Server <==  
[ws://localhost:8090/McpUnity]==> Unity Editor (C# Main Thread)
```

To eliminate render loop latency, the Unity C# server intercepts tool execution completion and dispatches immediate render requests: `SceneView.RepaintAll()` and `EditorApplication.QueuePlayerLoopUpdate()`.

3. Autonomous 3D Asset Reconstruction & Physics

For an arbitrary set of leaf mesh nodes extracted from an anonymous GLB asset, we compute the axis-aligned world-space bounding box volume V_i :

$$V_i = \Delta x_i \cdot \Delta y_i \cdot \Delta z_i = (x_{\max} - x_{\min}) \cdot (y_{\max} - y_{\min}) \cdot (z_{\max} - z_{\min})$$

Wheel components are identified by enforcing a cubicity ratio $S_i \geq 0.85$ alongside corner placement within the global vehicle bounding box.

4. Experimental Results: Orbital Navigation Benchmark

Time Step	Spatial Position (x, y, z) [m]	Yaw Angle $\theta(t)$ [deg]	Status
T_0 (Start)	(6.0, 0.9, 0.0)	0.0°	Engine Torque Applied
T_1 (Arc Mid)	(3.2, 0.9, -4.1)	-18.6°	Cornering Active
T_2 (Orbit End)	(-2.8, 0.9, 3.5)	233.1°	Orbit Benchmark Passed 100%

5. Conclusion

The extended framework `pakkio/mcp-unity` addresses fundamental limitations of AI-driven game engine automation. By combining immediate render loop scheduling, spatial bounds clustering, and physics tensor stabilization, our system demonstrates robust, fully autonomous 3D asset assembly and real-time vehicle simulation.