

Ways to Use Bootstrap

A simple, presentation-style guide for including Bootstrap in an HTML website

Bootstrap can be added to a web project in different ways depending on the project requirements. The three common methods are **CDN**, **downloaded local files**, and **npm installation**.

1. Using Bootstrap CDN ■

CDN stands for **Content Delivery Network**. You do not download Bootstrap manually. Instead, you directly add Bootstrap's CSS and JavaScript links to your HTML file.

Example:

```
<!DOCTYPE html>
<html>
<head>
<title>Bootstrap CDN</title>

<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet">
</head>

<body>

<button class="btn btn-primary">Click Me</button>

<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js">
</script>
</body>
</html>
```

Advantages:

- No installation is required.
- Easy and quick to use.
- Good for lab and practical work.
- Internet is usually required to load Bootstrap from the CDN.

2. Downloading Bootstrap Files

You can download Bootstrap and keep its CSS and JavaScript files inside your own project folder. This is useful when you want the project to work without depending on an online CDN.

Example project structure:

```
MyProject/
■
■■■ index.html
■■■ css/
■ ■■■ bootstrap.min.css
■
```

```
■■■ js/  
■■■ bootstrap.bundle.min.js
```

Link the local files:

```
<link rel="stylesheet" href="css/bootstrap.min.css">  
  
<script src="js/bootstrap.bundle.min.js"></script>
```

Advantages:

- Works without an internet connection.
- Bootstrap files are stored locally in the project.
- Useful for offline projects and practical demonstrations.

3. Installing Bootstrap using npm

Bootstrap can also be installed using **Node.js and npm**. This approach is commonly used in modern development projects such as Vite, React, Angular, and other JavaScript-based projects.

Installation command:

```
npm install bootstrap
```

After installation, Bootstrap is available inside:

```
node_modules/bootstrap/
```

Example:

```
import 'bootstrap/dist/css/bootstrap.min.css';  
import 'bootstrap/dist/js/bootstrap.bundle.min.js';
```

Quick Comparison

Method	Installation	Internet Required	Common Use
CDN	No	Usually	Simple HTML / Lab
Download	Download files	No	Offline projects
npm	npm install	No after installation	Vite / React / Node projects

For Your Web Designing Lab

If your practical simply says "**Use Bootstrap**", the easiest method is usually **CDN**. It requires no installation and can be added directly to your HTML file.

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet">
```

If you need Bootstrap components such as **Modal, Carousel, Dropdown, or Navbar toggler**, also include the Bootstrap JavaScript bundle:

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js">
</script>
```

Remember: Bootstrap CSS provides the styling and layout classes, while the Bootstrap JavaScript bundle enables interactive components such as modals, dropdowns, carousels, and navbar toggling.