VarDictRust: A Memory-Bounded, Oracle-Equivalent Rust Consolidation of the VarDict Variant-Calling Pipeline for Deep Whole-Genome and Ultra-Low-VAF Sequencing

Authors: Palak Sheth[1,*]

[1]Independent Researcher, rewrites.bio Initiative
[*]Correspondence: palak@rewrites.bio

Abstract

Background

Clinical and translational genomics increasingly rely on deep whole-genome sequencing (WGS), tumor-normal somatic profiling, and ultra-deep circulating tumor DNA (ctDNA) minimal residual disease (MRD) panels to detect single-nucleotide variants (SNVs), complex multinucleotide variants (MNVs), insertions/deletions (indels), splice-site alterations, and structural variants (SVs) across allele frequencies spanning germline heterozygosity down to sub-percent somatic mosaicism. For a decade, the VarDict algorithm (`VarDictJava` v1.8.3) has served as a cornerstone heuristic-aware local realigner and variant caller across oncology and rare-disease pipelines. However, its fragmented three-language execution architecture—streaming binary alignment maps (BAMs) through a Java Virtual Machine (JVM) pileup engine into external R (`teststrandbias.R` / `testsomatic.R`) and Perl (`var2vcf_valid.pl` / `var2vcf_paired.pl`) post-processors—imposes severe memory retention, inter-process serialization bottlenecks, and unhandled runtime crashes on modern high-depth datasets. Existing C++ reimplementations (`vardictcpp`) improve speed on pre-chunked exome targets but omit critical modes (splicing, amplicon, structural variants, CRAM), introduce silent algorithmic divergences, and retain unbounded per-interval memory growth on full chromosomes.

Results

Under the rewrites.bio engineering specification, we developed `VarDictRust` (`v1.0.6`), a single-binary, memory-safe Rust consolidation of the complete `VarDictJava` v1.8.3 pipeline (`#![forbid(unsafe_code)]` across the core engine). `VarDictRust` achieves `100%` intermediate (`.var`) and VCF equivalence (`ε = 1e-6`) with `VarDictJava v1.8.3 (0886261)` across all `13/13` operational calling modes (`95%` Clopper-Pearson confidence interval [CI] `75.29%–100.00%`), `17/17` functional modalities (`95%` CI `80.49%–100.00%`), `18/18` multimodal slices (`95%` CI `81.47%–100.00%`), `18/18` unfiltered (`-f 0`) somatic noise-floor sweeps (`95%` CI `81.47%–100.00%`), `10` short-read sequencing chemistries, and `70/70` GA4GH `v3.5` genomic strata (`95%` CI `94.87%–100.00%`) after replicating R's 5-decimal round-half-to-even (`HALF_EVEN`) Fisher exact test semantics. On contiguous human chromosome 1 (`-R chr1:1-249250621`, `249.25` Mbp), `VarDictRust` completes in `9.75` s at `318.6` MB peak resident set size (RSS) versus `501.83` s and `106.47` GiB for `VarDictJava` (`-Xmx200g`)—a `51.5`× speedup and `342.2`× memory reduction (`10.9`× faster and `34.0`× lower RAM than `vardictcpp ae93fe39dc (Wolff 2026)`)—and achieves `11.98`× `32`-thread whole-exome scaling (`29.3`× faster and `29.8`× lower RAM than `VarDictJava`). Across unchunked `130.8` GB HG002 germline (`4.93` GB RAM) and `329.0` GB `364`× HG008 tumor/normal somatic (`12.14` GB RAM) WGS on a `128` GiB node, `VarDictRust` finishes cleanly where `VarDictJava` runs out of memory (`>213.7` GB) and `vardictcpp` times out (`91.85` GB). Eliminating `≤50` kbp BED pre-chunking unlocks `+0.23` Gbp of `NIST GIAB v5.0q T2T-Q100` sequence (`+5.01%` SNV recall, `+17.26%` indel recall), `+17.47%` SNV and `+27.98%` indel recall across the `273` `NIST CMRG v1.00` genes, and `84/85` (`98.82%`) `NIST Mosaic SNV v1.10` sensitivity.

Conclusions

`VarDictRust` demonstrates that a complex, heuristic-rich legacy bioinformatics pipeline can be consolidated into a statically linked (`4.56` MB static Linux binary), memory-bounded systems binary without sacrificing byte-level statistical and allele fidelity. By enforcing bounded tile-plus-halo streaming (`O(tile + halo)` memory) and eliminating `102` runtime JVM/R/Perl environment packages, `VarDictRust` enables deterministic, crash-free variant discovery from targeted clinical panels and RNA-seq splice analysis to unchunked deep whole genomes and `0.5%`-VAF liquid-biopsy titrations.

Keywords: Variant calling, Somatic mutation discovery, Whole-genome sequencing, Minimal residual disease, Rust, Scientific software engineering, Reproducibility, VarDict, GIAB v5.0q, HG008

Key Points

- **Single-Binary Consolidation with Exact Oracle Parity:** `VarDictRust` (`v1.0.6`, `#![forbid(unsafe_code)]`) replaces the legacy `VarDictJava -> R -> Perl` pipeline (`102` Conda packages) with a single `4.56` MB static Linux binary that achieves `100%` equivalence (`ε = 1e-6`) across all `13/13` operational modes, `17/17` extended modalities, `18/18` multimodal slices, and `70/70` GA4GH `v3.5` genomic strata across `10` short-read sequencing chemistries.
- **Bounded *O(*tile + halo*)* Streaming Memory:** Keeping intervals ≤ *1,000,000* bp untiled while auto-partitioning spans > *1,000,000* bp into `100` kbp ownership tiles with `10` kbp realignment halos (`200` kbp in `-i` splice mode) bounds chromosome 1 (`-R chr1:1-249250621`) peak RSS to `318.6` MB in `9.75` s—a `51.5` × speedup and `342.2` × memory reduction over `VarDictJava` (`-Xmx200g`, `106.47` GiB) and `34.0` × lower memory than `vardictcpp` (`10.58` GiB).
- **Unchunked Full-Genome Discovery on Next-Generation Truth Sets:** Streaming unchunked full chromosomes (`chr1` – `chr22`) on `130.8` GB HG002 germline (`4.93` GB RSS) and `329.0` GB `364` × HG008 somatic (`12.14` GB RSS) WGS eliminates `VarDictJava` out-of-memory crashes and unlocks `+0.23` Gbp of `NIST GIAB v5.0q T2T-Q100` sequence (`+5.01%` SNV recall, `+17.26%` indel recall) and `+17.47%` SNV / `+27.98%` indel recall across the `273` `NIST CMRG v1.00` clinical genes.
- **High Somatic Indel & Ultra-Low-VAF Sensitivity on Commodity CPUs:** On `NIST GIAB HG008 v0.4` full-genome somatic benchmarking (`11` callers), `VarDictRust` outperforms `ClairS`, `DeepSomatic`, `Lancet2`, and `Ultima DeepVariant Somatic` in somatic indel recall (`40.11%`), while retaining `25.1` × higher SNV recall than `Mutect2` and `Strelka2` at `0.5%` VAF (`1%` tumor purity).

Background

Accurate detection of somatic and germline sequence variants across heterogeneous sequencing chemistries and clinical assay modalities remains a central challenge in computational genomics [1, 2]. Whereas germline variant callers such as `FreeBayes` [3], `Strelka2` [4], `Octopus` [5], and `DeepVariant` [6] model diploid genotype likelihoods, clinical oncology assays must resolve somatic single-nucleotide variants (SNVs), complex multinucleotide variants (MNVs), insertions/deletions (indels), and structural variants (SVs) across variable tumor purities, subclonal architectures, and circulating cell-free DNA (cfDNA) fractions down to `0.5%` – `1.0%` variant allele frequency (VAF) [7, 8]. Originally introduced by Lai et al. in 2016 [1], `VarDict` (`VarDictJava` v1.8.3) uniquely combines local Smith-Waterman-like soft-clip and indel realignment (`CigarModifier` and `VariationRealigner`), composite complex-variant phasing, amplicon primer-edge filtering (`-a`), RNA-seq exon-junction splice-site accounting (`-i`), and inline structural variant breakpoint assembly within a unified statistical framework. Consequently, `VarDict` is widely deployed in clinical panel pipelines, `bcbio-nextgen`, `nf-core/sarek`, and multi-caller somatic consensus ensembles [9, 10].

Despite its algorithmic versatility, the reference `VarDictJava` v1.8.3 implementation suffers from four structural limitations that impede its deployment on modern deep whole-genome sequencing (WGS) and cloud-native clinical infrastructure:

1. **Fragmented Three-Language Pipeline and IPC Overhead.** `VarDictJava` does not directly emit Variant Call Format (VCF) records. Instead, the Java process emits an intermediate `36`- to `61`-column tab-delimited `.var` stream (`Simple` `36/38`, `Amplicon` `38/40`, `Somatic` `55/61` columns without/with `--fisher`), which is piped via standard output to an external R script (`teststrandbias.R` for single-sample strand-bias Fisher exact testing or `testsomatic.R` for paired tumor-normal allele and strand-bias Fisher exact tests), and subsequently piped into a Perl post-processor (`var2vcf_valid.pl` or `var2vcf_paired.pl`) to apply quality/frequency filters and format VCF 4.3 records (`Figure 1`). When the `--fisher` flag is invoked inside Java to bypass R, the Perl stage remains mandatory, requiring a runtime software stack comprising `102` Conda packages across OpenJDK, R (`statmod`), and Perl (`Getopt::Long`, `warnings`).
2. **Unbounded JVM Heap Retention on Contiguous Genomic Spans.** `VarDictJava` allocates dense per-position pileup maps (`Map<Integer, VariationMap<String, Variation>>` and reference base arrays) spanning the entire requested BED interval or `-R` region prior to variant finalization (`ToVarsBuilder`) and local realignment (`VariationRealigner`). While manageable on exome capture baits (`<10` kbp), invoking `VarDictJava` on contiguous megabase or chromosome-scale intervals causes Resident Set Size (RSS) to scale linearly with interval length (`O(L × depth)`), triggering fatal `java.lang.OutOfMemoryError: Java heap space` crashes or extreme garbage-collection stalls exceeding `100` – `200` GiB RAM on whole chromosomes (`Table 2`, `Table 5`).
3. **Silent Truncation and Crashes on Edge-Case Alignments.** Over `30` upstream GitHub issues in `VarDictJava` (`#7`, `#38`, `#187`, `#197`, `#243`, `#249`, `#253`, `#282`, `#283`, `#320`, `#341`, `#380`, `#384`) document `NullPointerException`, `StringIndexOutOfBoundsException`, `ArrayIndexOutOfBoundsException` in `CigarModifier.modifyCigar` on supplementary or heavily soft-clipped reads, non-deterministic output row ordering due to unseeded `java.util.HashMap` iteration (`#282`), broken CRAM reference decoding (`#249`, `#380`), and truncated `##contig` VCF header metadata (`#320`).
4. **Incomplete C++ Port (`vardictcpp`).** Recently, Wolff et al. (2026) introduced `vardictcpp ae93fe39dc (Wolff 2026)`, a C++/htslib reimplementation targeting single-sample and paired somatic speedups [11]. However, our systematic 3-way audit reveals ten functional and

statistical divergences in `vardictcpp` (`Table 8`; `Supplementary Table S6`): `vardictcpp` omits `##contig` lines and `INFO/END` schema fields in VCF headers, omits CRISPR (`-J`/`-j`), structural variant (`--nosv` is forced by default and SV calling is unsupported), and RNA splice (`-i`) modes, emits raw tab-separated text instead of VCF in amplicon (`-a`) mode, exits with an error on concatenated CLI flags, fails or diverges on CRAM reference decoding (`-G`), hardcodes `chr`-prefix assumptions that break GRCh37/`b37` contigs, diverges on complex MNP phasing and realignment tie-breaking, and—critically—allocates unbounded memory across large intervals (`31.91` GB on HG002 WGS and `91.85` GB with a `3`-hour wall-clock timeout on HG008 WGS) while emitting `+309,569` duplicate boundary calls when regions are pre-chunked into `50` kbp windows (`--chunk 50,000`).

To resolve these challenges without altering the clinically validated statistical behavior of `VarDict`, we engineered `VarDictRust` (`v1.0.6`) under the rewrites.bio prime directive: produce a memory-safe, single-binary Rust implementation whose output is byte- and float-equivalent (`ε = 1e-6`) to `VarDictJava` v1.8.3 on all valid inputs, while eliminating runtime panics and bounding peak memory to `O(tile + halo)` regardless of chromosome length or sequencing depth.




Figure 1. Pipeline consolidation and bounded tile-plus-halo streaming architecture of `VarDictRust`. (a) Legacy `VarDictJava` v1.8.3 three-language execution pipeline (`Java -> R -> Perl`, `102` Conda packages) versus the consolidated `VarDictRust` v1.0.6 static binary (`4.56` MB `musl` / `4.46` MB `glibc`, `0` runtime dependencies). **(b)** Bounded tile-plus-halo (`1,000,000` bp untiled span threshold; `100` kbp tile + `10` kbp realignment halo on spans *> 1,000,000* bp) streaming state machine with `Rayon` work-stealing concurrency and deterministic boundary deduplication, contrasted with unbounded whole-region heap allocation in `VarDictJava` and `vardictcpp`. **(c)** Summary of the `60`-experiment cloud benchmark architecture spanning six evaluation domains and the `87`-configuration multi-regime intermediate (`.var`) and VCF equivalence sweep.

Results

Exact Oracle Equivalence Across All Operational Modes and the 87-Configuration Equivalence Sweep

We first evaluated whether `VarDictRust` (`v1.0.6`) satisfies the rewrites.bio oracle-equivalence contract against `VarDictJava v1.8.3 (0886261)` across the full spectrum of clinical and research calling modes (`Table 1`, `Figure 2a`). Across our `60`-experiment verification campaign (`Supplementary Table S1`), we tested both intermediate `.var` table equivalence (`36/38` columns in Simple mode, `38/40` columns in Amplicon mode, and `55/61` columns in Somatic mode without and with `--fisher`) and end-to-end VCF 4.3 equivalence (`chrom`, `pos`, `ref`, `alt`, `QUAL`, `FILTER`, `INFO` tags including `SBF`, `ODDRATIO`, `SSF`, `MSI`, `MSILEN`, `SHIFT3`, `TYPE`, `STATUS`, and `FORMAT` genotypes).

Across the baseline ceiling, multi-region boundary deduplication, and tile-size invariance benchmarks, VarDictRust matched VarDictJava with zero allele, filter, or coordinate discrepancies (Table 1; Supplementary Table S1):

- On the EGFR/MRE11a amplicon ceiling benchmark (-a 10:0.95), VarDictRust produced an identical 2-variant callset in 0.01 s at 11.5 MB peak RSS, compared to 3.00 s (120.1 MB) for VarDictJava (300× speedup, 10.4× lower RSS). By contrast, vardictcpp (5.27 s, 119.7 MB) does not implement VCF emission in amplicon mode (Table 8; Supplementary Table S6), emitting raw tab-separated text instead of VCF.
- On the NIST GIAB HG008 paired tumor-normal somatic slice, VarDictRust matched all 18,426 somatic and germline candidate variants in 17.44 s at 502.8 MB RSS versus 79.94 s and 9.87 GiB for VarDictJava (4.58× faster, 20.1× lower RSS; vardictcpp required 17.57 s and 554.5 MB).
- On the HG002 chromosome 20 multi-region reference boundary benchmark, VarDictRust matched all 2,572 variants in 0.28 s (176.7 MB RSS) versus 7.28 s (1.50 GiB RSS) for VarDictJava (26.0× speedup, 8.7× RSS reduction).
- To verify that our bounded tile-plus-halo streaming engine (see the Methods section) never alters variant calls across tile boundaries, we swept four tile sizes (500,000, 1,000,000, 2,000,000, 10,000,000 bp, i.e., 0.5, 1.0, 2.0, and 10.0 Mbp) across the SEQC2 HCC1395 breast cancer dataset; all four runs produced the exact same 5,090 variants matching the single-region VarDictJava oracle (4/4 MATCH).

In the 13-mode functional parity sweep (Table 1, Supplementary Table S6), we evaluated Simple (--fisher and R pipe), Somatic (--fisher and R pipe), Amplicon (-a), Splice (-i), Structural Variant (SV enabled and --nosv), CRAM (-G), and all-positions (-f 0) calling. VarDictRust achieved 13/13 (100%, exact Clopper-Pearson 95% CI 75.29%–100.00%) oracle matches. On the full-sample 51.8 GiB HG002 GM24385 RNA-seq dataset (Table 1, Supplementary Table S1), VarDictRust -i splice mode reproduced all 12,668 .var and .splice.tsv exon-junction records in 4.94 s (n = 3 technical replicates, range 4.90–5.01 s) and 359.9 MB RSS, compared to 23.31 s (range 23.03–23.70 s) and 4.79 GiB for VarDictJava (4.72× speedup, 13.6× memory reduction), whereas vardictcpp lacks -i splice support (Supplementary Table S6). Similarly, across our extended functional and multimodal verification suites (Table 1, Supplementary Table S1), VarDictRust passed 17/17 extended coverage modalities (95% CI 80.49%–100.00%), 18/18 multimodal slices (1,129 variants, 95% CI 81.47%–100.00%), and lossless BAM-versus-CRAM twin verification (32.04 s, 297.7 MB RSS, zero diff).

Finally, we executed an 87-configuration multi-regime intermediate (.var) and VCF equivalence sweep (Supplementary Table S2) spanning standard -f 0.01, WGS MRD -f 0.001, ultra-deep 45000× MRD -f 0.0005, and unfiltered -f 0 calling. Across all 87/87 (100.00%, 95% CI 95.85%–100.00%) comparative sub-arms spanning all 12 sweep suites (Table 1, Supplementary Table S2), VarDictRust achieved 100% exact .var and .vcf parity with VarDictJava. On all standard BED-interval suites (≤ *1,000,000* bp), VarDictRust runs untiled by default; on the two multi-megabase single-region stress suites (10 Mbp chr1 -f 0 with 7,077 .var rows / 7,032 VCF variants, and 249.25 Mbp -R chr1:1-249250621 with 4,705 .var rows), matching VarDictJava's single-window scope via --tile-size 10000000 and --tile-size 250000000 likewise yields 100% byte-for-byte sorted .var and .vcf parity (Table 1, Supplementary Table S2).

Table 1. Multi-Modal Algorithmic Equivalence & Intermediate (.var) / VCF Parity Summary (87/87 Sweep Sub-Arms Exact Match)

Evaluation Suite	Assay / Modality Scope	Evaluated Regimes / Variants	VarDictRust vs. VarDictJava [1] Verdict[a]
Amplicon Baseline	EGFR/MRE11A amplicon (-a) calling & coordinate parity	2 variants	100% Exact Match
Somatic Benchmark Slice	NIST GIAB HG008 [19] tumor-normal somatic slice parity	18,426 variants	100% Exact Match
Multi-Region Reference Offset	GIAB HG002 [13, 18] Chr20 multi-region reference coordinate offset verification	2,572 variants	100% Exact Match
Tile-Size Invariance[b]	Halo-tiled equivalence (0.5, 1, 2, 10 Mbp tiles) on SEQC2 HCC1395 [10]	4 tile sizes x 5,090 variants	100% Exact Match across all tile sizes[b]
13-Mode Functional Suite	13-mode 3-way functional CLI equivalence sweep [1, 11]	13 CLI modes	100% Exact Match (13/13 modes)
Transcriptome Splice-Aware RNA-Seq	51.8 GiB GIAB HG002 GM24385 [13] mRNA (-i splice-aware mode)	12,668 splice rows	100% Exact Match (0 byte differences)
All-Positions Pileup (-f 0, Single-Window)[c]	Chromosome 1 10 Mbp all-positions pileup (-f 0; .var & VCF)[c]	7,032 VCF variants (7,077 .var rows)	100% Exact Match[c]
Lossless BAM-vs-CRAM Twin	GIAB HG008 [19] tumor-normal BAM-vs-CRAM [26] bitwise equivalence (-G)	Bitwise VCF & .var comparison	100% Exact Match (0 byte differences)
Extended & Multimodal Suites	17-modality extended coverage & 18-slice multimodal regression suites	17/17 modes; 18/18 slices (1,129 variants)	100% Exact Match
Full-Genome Germline WGS	Full-genome GIAB HG002 [13, 18] WGS on ≤50 kbp callable BED intervals	8,111,171 callable variants	100% Exact Match on callable intervals

Evaluation Suite	Assay / Modality Scope	Evaluated Regimes / Variants	VarDictRust vs. VarDictJava [1] Verdict[a]
Multi-Regime Sweep: 4-Assay Regression	Targeted amplicon, HG002 [13, 18], HG008 [19] & SEQC2 [10] slices (.var & VCF)	4 sub-arms	4/4 Sub-Arms Exact Match
Multi-Regime Sweep: Contiguous 249 Mbp -R chr1	Whole-chromosome -R chr1:1-249250621 [11] (.var)[c]	1 sub-arm	1/1 Sub-Arm Exact Match[c]
Multi-Regime Sweep: HG002 Chr20 Exome	GIAB HG002 Chromosome 20 whole-exome slice [11, 20] (.var & VCF)	2 sub-arms	2/2 Sub-Arms Exact Match
Multi-Regime Sweep: Multimodal & CRAM Twin	18-slice multimodal suite & CRAM-vs-BAM twin [26] (.var & VCF)	4 sub-arms	4/4 Sub-Arms Exact Match
Multi-Regime Sweep: 51.8 GiB RNA-Seq	GIAB HG002 GM24385 [13] splice-aware RNA-seq (-i; .splice.tsv & .var)	2 sub-arms	2/2 Sub-Arms Exact Match
Multi-Regime Sweep: 10 Mbp Chr1 (-f 0)	Chromosome 1 10 Mbp single BED interval (.var & VCF)[c]	2 sub-arms	2/2 Sub-Arms Exact Match[c]
Multi-Regime Sweep: 12-Sub-Arm CLI Matrix	12 CLI mode sub-arms across germline, somatic, amplicon & CRAM regimes (.var)	12 sub-arms	12/12 Sub-Arms Exact Match
Multi-Regime Sweep: AML Panel SRR15006540	Clinical AML germline panel SRR15006540 [11] (.var & VCF)	2 sub-arms	2/2 Sub-Arms Exact Match
Multi-Regime Sweep: AML Panel SRR8657348	Clinical AML germline panel SRR8657348 [11] (.var & VCF)	2 sub-arms	2/2 Sub-Arms Exact Match
Multi-Regime Sweep: AML Somatic Pair	Clinical AML tumor-normal somatic panel (SRR15006376 / SRR15006386) [11] (.var & VCF)	2 sub-arms	2/2 Sub-Arms Exact Match
Multi-Regime Sweep: Ultra-Deep MRD Stress	Ultra-deep MRD stress (-f 0.0005 / -f 0 + --fisher, up to 45kx depth)[d]	30 sub-arms	30/30 Sub-Arms Exact Match[d]
Multi-Regime Sweep: WGS Low-VAF MRD	Low-VAF WGS & WES MRD matrix (-f 0.001 / -f 0 + --fisher)[d]	24 sub-arms	24/24 Sub-Arms Exact Match[d]

[a]All parity comparisons align records by CHROM/POS/REF/ALT against the VarDictJava v1.8.3 [1] oracle with floating-point tolerance eps=1e-6 after replicating R 5-decimal round-half-to-even (HALF_EVEN) rounding; across all 87/87 (100.00%) comparative sub-arms, the exact two-sided Clopper-Pearson 95% binomial confidence interval is 95.85%–100.00%. [b]Halo-tiled streaming partitions intervals >1 Mbp into 100 kbp tiles with 10 kbp overlap halos and deterministic boundary deduplication, yielding identical calls across 0.5, 1.0, 2.0, and 10.0 Mbp tile sizes. [c]Standard BED intervals (<=1 Mbp) execute untiled by default; for the two multi-megabase single-interval stress suites (10 Mbp chr1 at -f 0 and 249.25 Mbp -R chr1), VarDictRust was invoked with a single window (--tile-size 10000000 and --tile-size 250000000, respectively) so that single-window VarDictRust is compared directly against single-window VarDictJava [1]. [d]Evaluated both without --fisher (replicating R teststrandbias.R / testsomatic.R) and with --fisher (native two-sided Fisher exact test and root-finding MLE odds ratio).

Replication and Extension of the Wolff et al. Acute Myeloid Leukemia Benchmark

To benchmark `VarDictRust` directly against the dataset and claims of Wolff et al. [11], we replicated the Wolff et al. [11] acute myeloid leukemia (AML) targeted panel cohort (`SRR15006375` with `12,292` intervals, `SRR15006376` with `105,949` intervals, `SRR15006386` with `11,732` intervals, `SRR15006540` with `135,145` intervals, ultra-dense `SRR8657348` with `773,667` intervals, and paired tumor-normal `SRR15006376|SRR15006386`) at `1` and `8` threads (`Table 2` , `Figure 2` , `Supplementary Table S3`).

Across all `12` sample-by-thread configurations (`n = 3` technical replicates per engine per configuration), `VarDictRust` achieved `100%` `.var` (`4,056` to `54,448` rows) and `.vcf` (`3,966` to `53,224` variants) parity with `VarDictJava` , delivering a `2.36` ×– `5.56` × wall-clock speedup and a `4.3` ×– `26.5` × reduction in peak RSS (`187.5` – `493.2` MB for `VarDictRust` vs `2.03` – `7.44` GB for `VarDictJava` ; two-sided Mann-Whitney *U = 4.0*, *p = 9.735e-05* for wall time; *U = 0.0*, *p = 3.658e-05* for peak RSS; paired sign-flip permutation *p = 0.00024* across *N = 12* configurations). On the largest `773,667` -interval panel (`SRR8657348`), single-thread `VarDictRust` (`154.98` s, range `154.77–155.12` s) was faster than both `VarDictJava` (`861.18` s, `5.56` ×) and `vardictcpp` (`174.48` s). At `8` threads (`-th 8`), `vardictcpp` completed the pre-chunked AML panels in `12.85` – `31.66` s (`VarDictRust` `39.63` – `135.43` s) because `vardictcpp` omits structural variant discovery (`--nosv` hardcoded) and omits `##contig` and `INFO/END` VCF schema validation (`Table 8` ; `Supplementary Table S6`).

When we replicated Table 3 of Wolff et al. [11]—calling a single contiguous `249.25` Mbp region spanning human chromosome 1 (`-R chr1:1-249250621` on `SRR8657348` ; `Table 2` , `Figure 2b` , `Supplementary Table S1`)—the architectural divide between tile-bounded streaming (`VarDictRust`) and whole-interval allocation (`VarDictJava` and `vardictcpp`) became clear:

- `VarDictJava` with a standard `-Xmx4g` heap crashed with `java.lang.OutOfMemoryError` at `31.08` s (`4.16` GiB RSS). Provisioning an extreme `-Xmx200g` heap allowed `VarDictJava` to finish in `501.83` s (`n = 3` range `492.93–509.65` s) at `106.47` GiB peak RSS.
- `vardictcpp` required `105.89` s (`n = 3` range `105.07–106.58` s) and `10.58` GiB peak RSS because a single `-R` region bypasses external BED chunking.
- `VarDictRust` automatically tiled `-R chr1:1-249250621` into `100` kbp windows with `10` kbp halos, completing in `9.75` s (`n = 3` range `9.64–9.81` s) at `318.6` MB peak RSS— `51.5` × faster and `342.2` × more memory-efficient than `VarDictJava` (`-Xmx200g`), and `10.9` × faster and `34.0` × more memory-efficient than `vardictcpp` .

We also replicated the field-caller runtime and somatic concordance comparisons across `FreeBayes`, `LoFreq`, `Mutect2`, `Octopus`, and `Strelka2` (`Table 2`, `Supplementary Table S1`). On `SRR8657348` (`8` threads), `VarDictRust` (`39.63` s, `493.2` MB) outperformed `FreeBayes` (`57.14` s, `3057.6` MB), `LoFreq` (`160.64` s, `3319.1` MB), `Mutect2` (`1297.75` s, `1659.0` MB), and `Octopus` (`1823.58` s, `1581.2` MB). On the paired somatic run (`SRR15006376|SRR15006386`, `8` threads), `VarDictRust` completed in `135.43` s (`382.1` MB) versus `199.96` s for `Strelka2`, `373.34` s for `VarDictJava`, `450.87` s for `Octopus`, `521.82` s for `LoFreq`, and `969.01` s for `Mutect2`, while yielding identical somatic Venn overlap (`358` filtered somatic SNVs across a `576`-variant 4-caller union with `Mutect2` [`371`], `LoFreq` [`111`], and `Octopus` [`17`]).




Figure 2. Multi-regime oracle equivalence and AML targeted panel replication. (a) Exact parity summary across the `13` operational modes, `17/17` extended coverage modalities, `18/18` multimodal slices, and `87/87` multi-regime parameter-sweep configurations (`Supplementary Table S2`). **(b)** Contiguous chromosome 1 (`-R chr1:1-249250621`, `249.25` Mbp on `SRR8657348`) scaling showing `VarDictJava` `-Xmx4g` out-of-memory failure, `-Xmx200g` heap expansion (`106.47` GiB), `vardictcpp` growth (`10.58` GiB), and `VarDictRust` bounded streaming (`318.6` MB, `9.75` s). **(c, d)** Wall-clock runtime across the Wolff et al. [11] AML panel cohort (`n = 3` technical replicates) and field callers (`FreeBayes`, `LoFreq`, `Mutect2`, `Octopus`, `Strelka2`).

Table 2. Direct Replication of vardictcpp [11] Across Clinical AML Panels, Field Callers & Unchunked Chromosome 1 (-R chr1)

Sample / Cohort [11]	Threads	BED Intervals	VarDictJava [1] Wall (s) / Peak RSS[a,b]	vardictcpp [11] Wall (s) / Peak RSS[a,c]	VarDictRust Wall (s) / Peak RSS[a]	Rust vs. Java Speedup / Memory Reduction[d]	Parity Verdict
SRR15006375	1	12,292	408.19 (400.74–418.94) s / 2537.2 MB	109.66 (109.19–109.90) s / 63.8 MB	121.93 (121.14–122.38) s / 210.3 MB	3.35x faster / 12.1x leaner	100% Exact Match (.var & VCF)
SRR15006375	8	12,292	232.70 (229.14–235.27) s / 4410.5 MB	15.35 (15.30–15.42) s / 328.3 MB	49.47 (49.39–49.59) s / 270.1 MB	4.70x faster / 16.3x leaner	100% Exact Match (.var & VCF)
SRR15006376	1	105,949	334.16 (326.10–340.26) s / 4244.4 MB	83.71 (83.03–84.32) s / 74.0 MB	80.41 (80.08–80.84) s / 225.7 MB	4.16x faster / 18.8x leaner	100% Exact Match (.var & VCF)

Sample / Cohort [11]	Threads	BED Intervals	VarDictJava [1] Wall (s) / Peak RSS[a,b]	vardictcpp [11] Wall (s) / Peak RSS[a,c]	VarDictRust Wall (s) / Peak RSS[a]	Rust vs. Java Speedup / Memory Reduction[d]	Parity Verdict
SRR15006376	8	105,949	164.36 (150.76–174.29) s / 7442.2 MB	12.85 (12.50–13.09) s / 354.0 MB	48.74 (48.65–48.86) s / 281.0 MB	3.37x faster / 26.5x leaner	100% Exact Match (.var & VCF)
SRR15006386	1	11,732	334.94 (331.87–338.80) s / 2423.4 MB	98.20 (98.09–98.37) s / 56.2 MB	113.52 (113.17–114.04) s / 187.5 MB	2.95x faster / 12.9x leaner	100% Exact Match (.var & VCF)
SRR15006386	8	11,732	180.62 (178.99–182.17) s / 4434.7 MB	15.55 (14.95–16.69) s / 298.6 MB	43.78 (43.64–43.88) s / 305.4 MB	4.13x faster / 14.5x leaner	100% Exact Match (.var & VCF)
SRR15006540	1	135,145	407.11 (402.18–412.42) s / 4572.5 MB	111.51 (111.32–111.66) s / 76.3 MB	126.00 (125.49–126.91) s / 194.6 MB	3.23x faster / 23.5x leaner	100% Exact Match (.var & VCF)
SRR15006540	8	135,145	184.38 (179.54–187.21) s / 4087.8 MB	16.69 (16.31–17.00) s / 339.0 MB	78.04 (77.89–78.24) s / 224.8 MB	2.36x faster / 18.2x leaner	100% Exact Match (.var & VCF)
SRR8657348	1	773,667	861.18 (857.96–863.07) s / 2028.7 MB	174.48 (173.98–175.43) s / 143.5 MB	154.98 (154.77–155.12) s / 474.3 MB	5.56x faster / 4.3x leaner	100% Exact Match (.var & VCF)
SRR8657348	8	773,667	215.85 (212.70–217.72) s / 3697.7 MB	24.68 (24.64–24.71) s / 251.8 MB	39.63 (39.50–39.76) s / 493.2 MB	5.45x faster / 7.5x leaner	100% Exact Match (.var & VCF)
SRR15006376 / SRR15006386 (Somatic Pair)	1	105,949	726.09 (720.47–729.27) s / 4307.4 MB	215.16 (214.94–215.50) s / 144.9 MB	230.53 (229.92–230.96) s / 247.8 MB	3.15x faster / 17.4x leaner	100% Exact Match (.var & VCF)
SRR15006376 / SRR15006386 (Somatic Pair)	8	105,949	373.34 (371.55–374.68) s / 5679.9 MB	31.66 (31.60–31.75) s / 786.0 MB	135.43 (133.83–137.51) s / 382.1 MB	2.76x faster / 14.9x leaner	100% Exact Match (.var & VCF)
SRR8657348 (Unchunked -R chr1, 249 Mbp)[e]	8	1 (249.25 Mbp)	501.83 (492.93–509.65) s / 106.47 GiB (4 GiB Heap = OOM)[e]	—	—	Rust 51.5x faster / 342.2x leaner	4 GiB Heap OOM Crash; Completes at 200 GiB Heap (n=3)[e]
SRR8657348 (Unchunked -R chr1, 249 Mbp)[e]	8	1 (249.25 Mbp)	—	105.89 (105.07–106.58) s / 10.58 GiB	9.75 (9.64–9.81) s / 0.31 GiB	Rust 10.9x faster / 34.0x leaner vs. C++	Both Complete in Bounded Memory (n=3)[e]
SRR8657348 & SRR15006376 / SRR15006386 (7-Caller Panel) [3–5, 7, 8][f]	1 & 8	773,667 / 105,949	373.34 s (Somatic, 8 threads)[f]	31.66 s (Somatic, 8 threads)[f]	135.43 s (Somatic, 8 threads)[f]	2.76x faster; 358 concordant VarDict SNVs[f]	100% Exact Match (VarDictRust == VarDictJava); 16 Field-Caller Runs Profiled[f]

[a]Timed runs report technical replicate mean (min–max) across n=3 runs on identical GCP n2-standard-32 (Intel Xeon Platinum 8373C Ice Lake) silicon. [b]VarDictJava v1.8.3 [1] timings measure the full three-process pipeline (vardict-java / teststrandbias.R/testsomatic.R / var2vcf_valid.pl/var2vcf_paired.pl). [c]vardictcpp (commit ae93fe39dc) [11] timings measure its default --chunk 50,000 binary execution, which omits R Fisher exact strand/somatic p-value scripts and Perl VCF formatting. [d]Across the 12 paired AML panel conditions, VarDictRust reduces wall time (two-sided Mann-Whitney U=4.0, p=9.735e-05; paired sign-permutation p=0.00024) and peak RSS (U=0.0, p=3.658e-05) relative to VarDictJava. [e]On unchunked -R chr1:1-249250621 (249.25 Mbp), VarDictJava crashes with OutOfMemoryError (rc=3) at 31.08 s under the 4 GiB heap cap (-Xmx4g) used by Wolff et al. [11], but completes in 501.83 (492.93–509.65) s at 106.47 GiB RSS when provisioned with -Xmx200g. [f]Row 15 summarizes the 16-run field-caller benchmark comparing VarDictRust, VarDictJava [1], vardictcpp [11], FreeBayes [3], Strelka2 [4], Octopus [5], LoFreq [7], and Mutect2 [8]; the 4-caller somatic Venn intersection (VarDict, Mutect2, Strelka2, LoFreq) identifies 358 concordant VarDict somatic SNVs with 100% identity between VarDictRust and VarDictJava.

Germline and Somatic Truth Accuracy and `QUAL` Operating-Point Characterization

Next, we evaluated whether `VarDictRust` reproduces the exact biological variant-calling accuracy (`rtg vcfeval` [12] genotype-level precision, sensitivity, and F_1) of `VarDictJava` across gold-standard germline and somatic truth sets, and compared both against widely used field callers (`Table 3`, `Figure 3`, `Supplementary Table S4`).

On the hg19 HG002 chromosome 20 exome truth benchmark (`2.31` Mbp target, `8,233` total candidate calls, `7,422` filtered calls; `Table 3`), `VarDictRust` and `VarDictJava` achieved identical SNV precision (`0.9981`), sensitivity (`0.9738`), and F_1 (`0.9858`), as well as identical indel precision (`0.9747`), sensitivity (`0.8283`), and F_1 (`0.8956`), surpassing `Mutect2` (`SNV` $F_1 = 0.9651$, `Indel` $F_1 = 0.8241$) and matching the top germline callers `Octopus` (`SNV` $F_1 = 0.9925$, `Indel` $F_1 = 0.9194$), `FreeBayes` (`SNV` $F_1 = 0.9867$, `Indel` $F_1 = 0.9038$), and `LoFreq` (`SNV` $F_1 = 0.9803$, `Indel` $F_1 = 0.9047$).

Because `VarDict` is designed as a high-sensitivity, low-VAF-capable caller (default `-f 0.01`), unfiltered `PASS` calls on `35`×–`60`× germline WGS/chr20 datasets include low-depth or low-VAF artifacts unless stratified by the VCF `QUAL` field (`Table 3`, `Supplementary Table S4`, `Figure 3b`). Across all five GIAB and SEQC2 truth cohorts, `VarDictRust` and `VarDictJava` produced identical `rtg vcfeval` operating points:

- **HG002 GRCh38 chr20 (`NIST GIAB v4.2.1`):** Unfiltered (`QUAL >= 0`) sensitivity is `0.9659` (`23,062` TP, `22,458` FP, `813` FN, precision `0.5038`, $F_1 = 0.6622$). Applying `rtg vcfeval`'s optimal `QUAL >= 128.000` threshold eliminates `97.5%` of false positives

(553 FP) while retaining 0.9635 sensitivity (23,004 TP, 871 FN), raising precision to 0.9763 and combined F_1 to 0.9699 (with HG005 GIAB truth reaching $F_1 = 0.9667$ vs unfiltered 0.9508 and NA24385-b37 reaching $F_1 = 1.0000$ vs 0.1099 ; Table 3 , Supplementary Table S4).

- **SEQC2 HCC1395/HCC1395BL Somatic Exome (v1.2.1):** Across 623,444 total candidate calls (120,307 PASS , 594,344 SNVs, 8,966 insertions, 15,716 deletions, 4,383 MNPs, 35 SVs), optimal QUAL >= 126.000 filtering raises combined somatic F_1 from 0.1555 (1,069 TP, 11,334 FP, sensitivity 0.8842) to 0.6905 (794 TP, 293 FP, precision 0.7279 , sensitivity 0.6567). In the native GRCh38 multi-caller comparison (Table 3), VarDictRust and VarDictJava (SNV $F_1 = 0.7433$, Indel $F_1 = 0.3750$) outperformed Mutect2 (SNV $F_1 = 0.7089$) and Strelka2 (SNV $F_1 = 0.4509$) in SNV F_1 while running in 279.29 s (514.3 MB RSS) vs 3967.00 s (14275.5 MB) for VarDictJava and 2641.05 s (1580.9 MB) for Mutect2 .
- **NIST GIAB HG008 Somatic Slice (v0.3):** Across 18,426 candidate variants (11,358 PASS , 15,213 SNVs, 1,161 insertions, 1,410 deletions, 614 MNPs, 28 SVs), QUAL >= 176.000 boosts combined F_1 from 0.3856 to 0.7696 (593 TP, 38 FP, precision 0.9354 , sensitivity 0.6538). Under standard somatic StrongSomatic / LikelySomatic PASS filtering (Table 3), VarDictRust and VarDictJava achieved identical SNV $F_1 = 0.7840$ (precision 0.9757 , sensitivity 0.6552) and the highest Indel $F_1 = 0.5640$ (precision 0.9370 , sensitivity 0.4034), outperforming Mutect2 (SNV $F_1 = 0.7779$, Indel $F_1 = 0.5537$), Strelka2 (Indel $F_1 = 0.4386$), and LoFreq (Indel $F_1 = 0.0000$, as LoFreq somatic mode did not emit somatic indels under default flags), while running in 17.14 s (510.5 MB RSS) vs 79.15 s (17448.2 MB) for VarDictJava and 447.31 s for Mutect2 .




Figure 3. Germline and somatic truth concordance, QUAL operating points, runtime-accuracy frontier, and low-VAF titration. (a) rtg vcfeval SNV and indel precision, sensitivity, and F_1 across 7 callers on the HG002 chromosome 20 exome (Table 3). **(b)** Unfiltered PASS (QUAL >= 0) versus optimal QUAL cutoff F_1 across five truth cohorts (HG002 , HG005 , NA24385-b37 , SEQC2 HCC1395 , and HG008 v0.3 ; Supplementary Table S4). **(c)** Native GRCh38 multi-caller SNV F_1 versus wall-clock runtime across HG002 germline, HG008 v0.3 somatic, and SEQC2 somatic benchmarks (Table 3). **(d)** Controlled *in silico* tumor-purity titration (20% down to 1% purity / 10.0% down to 0.5% VAF) demonstrating VarDictRust 's 25.1 × recall and 16.7 × F_1 advantage at 0.5% VAF (Table 3).

Table 3. Germline & Somatic Truth Accuracy [12], Native GRCh38 Field Callers & Low-VAF Tumor-Purity Titration (20% to 1% Purity)

Cohort / Purity Stratum	Caller / Engine	Runtime / Evaluated Calls	SNV (or Combined) Precision / Recall / F1 [12][b]	InDel Precision / Recall / F1 [12][b,c]	Concordance / Parity Verdict
GIAB HG002 Chr20 Exome [11, 13, 20][a]	VarDictRust	7,422 calls	0.9981 / 0.9738 / 0.9858	0.9747 / 0.8283 / 0.8956	100% Exact Match (VarDictRust == VarDictJava)
GIAB HG002 Chr20 Exome [11, 13, 20][a]	VarDictJava [1]	7,422 calls	0.9981 / 0.9738 / 0.9858	0.9747 / 0.8283 / 0.8956	100% Exact Match (VarDictRust == VarDictJava)
GIAB HG002 Chr20 Exome [11, 13, 20][a]	vardictcpp [11]	7,421 calls	0.9981 / 0.9738 / 0.9858	0.9747 / 0.8283 / 0.8956	External Germline Caller
GIAB HG002 Chr20 Exome [11, 13, 20][a]	Octopus [5]	2,436 calls	0.9973 / 0.9878 / 0.9925	0.9336 / 0.9056 / 0.9194	External Germline Caller
GIAB HG002 Chr20 Exome [11, 13, 20][a]	FreeBayes [3]	4,292 calls	0.9972 / 0.9765 / 0.9867	0.9439 / 0.8670 / 0.9038	External Germline Caller
GIAB HG002 Chr20 Exome [11, 13, 20][a]	LoFreq [7]	2,598 calls	0.9908 / 0.9701 / 0.9803	0.9358 / 0.8755 / 0.9047	External Germline Caller
GIAB HG002 Chr20 Exome [11, 13, 20][a]	Mutect2 [8]	2,246 calls	0.9995 / 0.9330 / 0.9651	0.9939 / 0.7039 / 0.8241	External Germline Caller
GIAB HG002 GRCh38 Slice [13, 18] (Optimal QUAL ≥ 128.0)[b]	VarDictRust == VarDictJava [1]	TP=23,004, FP=553	0.9763 / 0.9635 / 0.9699	Combined SNV + InDel evaluation[b]	100% Exact Match (0 site differences)
GIAB HG002 GRCh38 Slice [13, 18] (All-PASS, -f 0.01)[b]	VarDictRust == VarDictJava [1]	TP=23,062, FP=22,458	0.5038 / 0.9659 / 0.6622	Combined SNV + InDel evaluation[b]	100% Exact Match (0 site differences)
SEQC2 HCC1395 Somatic Exome [10] (Optimal QUAL ≥ 126.0)[b]	VarDictRust == VarDictJava [1]	TP=794, FP=293	0.7279 / 0.6567 / 0.6905	Combined SNV + InDel evaluation[b]	100% Exact Match (0 site differences)
SEQC2 HCC1395 Somatic Exome [10] (All-PASS, -f 0.01)[b]	VarDictRust == VarDictJava [1]	TP=1,069, FP=11,334	0.0852 / 0.8842 / 0.1555	Combined SNV + InDel evaluation[b]	100% Exact Match (0 site differences)
GIAB HG008 Somatic Slice v0.3 [19] (Optimal QUAL ≥ 176.0)[b]	VarDictRust == VarDictJava [1]	TP=593, FP=38	0.9354 / 0.6538 / 0.7696	Combined SNV + InDel evaluation[b]	100% Exact Match (0 site differences)
GIAB HG008 Somatic Slice v0.3 [19] (All-PASS, -f 0.01)[b]	VarDictRust == VarDictJava [1]	TP=619, FP=1,565	0.2687 / 0.6825 / 0.3856	Combined SNV + InDel evaluation[b]	100% Exact Match (0 site differences)
GIAB HG005 GRCh38 v4.2.1 [13] (Optimal QUAL ≥ 226.0)[b]	VarDictRust == VarDictJava [1]	TP=29, FP=1	0.9667 / 0.9667 / 0.9667	Combined SNV + InDel evaluation[b]	100% Exact Match (0 site differences)
GIAB HG005 GRCh38 v4.2.1 [13] (All-PASS, -f 0.01)[b]	VarDictRust == VarDictJava [1]	TP=29, FP=2	0.9355 / 0.9667 / 0.9508	Combined SNV + InDel evaluation[b]	100% Exact Match (0 site differences)
GIAB NA24385 GRCh37 v4.2.1 [13] (Optimal QUAL ≥ 160.0)[b]	VarDictRust == VarDictJava [1]	TP=5, FP=0	1.0000 / 1.0000 / 1.0000	Combined SNV + InDel evaluation[b]	100% Exact Match (0 site differences)
GIAB NA24385 GRCh37 v4.2.1 [13] (All-PASS, -f 0.01)[b]	VarDictRust == VarDictJava [1]	TP=5, FP=81	0.0581 / 1.0000 / 0.1099	Combined SNV + InDel evaluation[b]	100% Exact Match (0 site differences)
GIAB HG002 GRCh38 Benchmark Slice [13, 18]	VarDictRust	0:21.30 (21.30 s) / 474.8 MB	0.5041 / 0.9634 / 0.6619	0.5781 / 0.9463 / 0.7177	100% Exact Match (VarDictRust == VarDictJava)
GIAB HG002 GRCh38 Benchmark Slice [13, 18]	VarDictJava [1]	2:39.59 (159.59 s) / 10732.2 MB	0.5041 / 0.9634 / 0.6619	0.5781 / 0.9463 / 0.7177	100% Exact Match (VarDictRust == VarDictJava)
GIAB HG002 GRCh38 Benchmark Slice [13, 18]	vardictcpp [11]	0:21.14 (21.14 s) / 859.1 MB	0.5043 / 0.9634 / 0.6620	0.5783 / 0.9463 / 0.7179	MNP / SV Divergence vs. Java[e]
GIAB HG002 GRCh38 Benchmark Slice [13, 18]	FreeBayes [3]	6:08.72 (368.72 s) / 206.7 MB	0.9686 / 0.9598 / 0.9642	0.9373 / 0.9538 / 0.9455	Native GRCh38 Comparator
GIAB HG002 GRCh38 Benchmark Slice [13, 18]	LoFreq [7]	6:16.78 (376.78 s) / 119.0 MB	0.8924 / 0.9909 / 0.9391	0.5809 / 0.9601 / 0.7238	Native GRCh38 Comparator
GIAB HG002 GRCh38 Benchmark Slice [13, 18]	Strelka2 [4]	8:22.19 (502.19 s) / 130.1 MB	0.9931 / 0.9909 / 0.9920	0.9438 / 0.9836 / 0.9633	Native GRCh38 Comparator
GIAB HG002 GRCh38 Benchmark Slice [13, 18]	Octopus [5]	3:11.50 (191.50 s) / 3558.9 MB	0.9911 / 0.9861 / 0.9886	0.9051 / 0.9810 / 0.9415	Native GRCh38 Comparator
GIAB HG008 v0.3 Somatic Slice [19]	VarDictRust	0:17.14 (17.14 s) / 510.5 MB	0.9757 / 0.6552 / 0.7840	0.9370 / 0.4034 / 0.5640	100% Exact Match (VarDictRust == VarDictJava)
GIAB HG008 v0.3 Somatic Slice [19]	VarDictJava [1]	1:19.15 (79.15 s) / 17448.2 MB	0.9757 / 0.6552 / 0.7840	0.9370 / 0.4034 / 0.5640	100% Exact Match (VarDictRust == VarDictJava)
GIAB HG008 v0.3 Somatic Slice [19]	vardictcpp [11]	0:17.30 (17.30 s) / 565.1 MB	0.9757 / 0.6552 / 0.7840	0.9444 / 0.4034 / 0.5653	MNP / SV Divergence vs. Java[e]
GIAB HG008 v0.3 Somatic Slice [19]	Mutect2 [8]	7:27.31 (447.31 s) / 1263.1 MB	0.9825 / 0.6438 / 0.7779	0.9355 / 0.3932 / 0.5537	Native GRCh38 Comparator
GIAB HG008 v0.3 Somatic Slice [19]	Strelka2 [4]	0:36.35 (36.35 s) / 119.0 MB	0.9896 / 0.7794 / 0.8720	0.9545 / 0.2847 / 0.4386	Native GRCh38 Comparator
GIAB HG008 v0.3 Somatic Slice [19]	LoFreq [7]	1:18.71 (78.71 s) / 251.5 MB	1.0000 / 0.6814 / 0.8105	0.0000 / 0.0000 / 0.0000[c]	Native GRCh38 Comparator

Cohort / Purity Stratum	Caller / Engine	Runtime / Evaluated Calls	SNV (or Combined) Precision / Recall / F1 [12][b]	InDel Precision / Recall / F1 [12][b,c]	Concordance / Parity Verdict
SEQC2 HCC1395 v1.2.1 Somatic Exome [10]	VarDictRust	4:39.29 (279.29 s) / 514.3 MB	0.7336 / 0.7532 / 0.7433	0.3077 / 0.4800 / 0.3750	100% Exact Match (VarDictRust == VarDictJava)
SEQC2 HCC1395 v1.2.1 Somatic Exome [10]	VarDictJava [1]	1:06:07 (3967.00 s) / 14275.5 MB	0.7336 / 0.7532 / 0.7433	0.3077 / 0.4800 / 0.3750	100% Exact Match (VarDictRust == VarDictJava)
SEQC2 HCC1395 v1.2.1 Somatic Exome [10]	vardictcpp [11]	4:53.71 (293.71 s) / 2259.8 MB	0.7336 / 0.7532 / 0.7433	0.3077 / 0.4800 / 0.3750	MNP / SV Divergence vs. Java[e]
SEQC2 HCC1395 v1.2.1 Somatic Exome [10]	Mutect2 [8]	44:01.05 (2641.05 s) / 1580.9 MB	0.6152 / 0.8361 / 0.7089	0.6087 / 0.8400 / 0.7059	Native GRCh38 Comparator
SEQC2 HCC1395 v1.2.1 Somatic Exome [10]	Strelka2 [4]	2:52.88 (172.88 s) / 118.8 MB	0.3044 / 0.8689 / 0.4509	0.4324 / 0.6400 / 0.5161	Native GRCh38 Comparator
SEQC2 HCC1395 v1.2.1 Somatic Exome [10]	LoFreq [7]	9:01.90 (541.90 s) / 281.6 MB	0.9526 / 0.7627 / 0.8471	0.0000 / 0.0000 / 0.0000[c]	Native GRCh38 Comparator
GIAB HG008 20% Purity (10.0% VAF) [19][d]	VarDictRust	0:08.72 (8.72 s) / 762.3 MB	0.8790 / 0.6559 / 0.7512	0.6162 / 0.2075 / 0.3104	100% Exact Match (VarDictRust == VarDictJava)
GIAB HG008 20% Purity (10.0% VAF) [19][d]	VarDictJava [1]	1:06.76 (66.76 s) / 12027.7 MB	0.8790 / 0.6559 / 0.7512	0.6162 / 0.2075 / 0.3104	100% Exact Match (VarDictRust == VarDictJava)
GIAB HG008 20% Purity (10.0% VAF) [19][d]	vardictcpp [11]	0:10.94 (10.94 s) / 1048.3 MB	0.8770 / 0.5707 / 0.6914	0.5823 / 0.1565 / 0.2466	MNP / Tie-Break Divergence vs. Java[e]
GIAB HG008 20% Purity (10.0% VAF) [19][d]	Strelka2 [4]	0:36.62 (36.62 s) / 118.8 MB	1.0000 / 0.7070 / 0.8283	1.0000 / 0.1156 / 0.2073	External Somatic Caller
GIAB HG008 20% Purity (10.0% VAF) [19][d]	LoFreq [7]	1:18.14 (78.14 s) / 252.2 MB	1.0000 / 0.4072 / 0.5787	0.0000 / 0.0000 / 0.0000[c]	External Somatic Caller
GIAB HG008 20% Purity (10.0% VAF) [19][d]	Mutect2 [8]	7:10.48 (430.48 s) / 1130.0 MB	1.0000 / 0.5826 / 0.7363	0.9032 / 0.0952 / 0.1723	External Somatic Caller
GIAB HG008 10% Purity (5.0% VAF) [19][d]	VarDictRust	0:08.76 (8.76 s) / 839.4 MB	0.6726 / 0.5179 / 0.5852	0.4082 / 0.1361 / 0.2041	100% Exact Match (VarDictRust == VarDictJava)
GIAB HG008 10% Purity (5.0% VAF) [19][d]	VarDictJava [1]	1:06.58 (66.58 s) / 13019.7 MB	0.6726 / 0.5179 / 0.5852	0.4082 / 0.1361 / 0.2041	100% Exact Match (VarDictRust == VarDictJava)
GIAB HG008 10% Purity (5.0% VAF) [19][d]	vardictcpp [11]	0:10.91 (10.91 s) / 1020.3 MB	0.6726 / 0.5179 / 0.5852	0.4082 / 0.1361 / 0.2041	VCF Header / Non-Benchmark Indel Divergence[e]
GIAB HG008 10% Purity (5.0% VAF) [19][d]	Strelka2 [4]	0:36.61 (36.61 s) / 118.9 MB	1.0000 / 0.4719 / 0.6412	1.0000 / 0.0476 / 0.0909	External Somatic Caller
GIAB HG008 10% Purity (5.0% VAF) [19][d]	LoFreq [7]	1:14.64 (74.64 s) / 251.8 MB	1.0000 / 0.0716 / 0.1335	0.0000 / 0.0000 / 0.0000[c]	External Somatic Caller
GIAB HG008 10% Purity (5.0% VAF) [19][d]	Mutect2 [8]	7:16.35 (436.35 s) / 1171.3 MB	1.0000 / 0.3237 / 0.4891	0.9375 / 0.0510 / 0.0968	External Somatic Caller
GIAB HG008 5% Purity (2.5% VAF) [19][d]	VarDictRust	0:08.65 (8.65 s) / 822.7 MB	0.4932 / 0.3680 / 0.4215	0.2183 / 0.1054 / 0.1422	100% Exact Match (VarDictRust == VarDictJava)
GIAB HG008 5% Purity (2.5% VAF) [19][d]	VarDictJava [1]	1:06.17 (66.17 s) / 12117.8 MB	0.4932 / 0.3680 / 0.4215	0.2183 / 0.1054 / 0.1422	100% Exact Match (VarDictRust == VarDictJava)
GIAB HG008 5% Purity (2.5% VAF) [19][d]	vardictcpp [11]	0:10.90 (10.90 s) / 1077.7 MB	0.4932 / 0.3680 / 0.4215	0.2183 / 0.1054 / 0.1422	VCF Header / Non-Benchmark Indel Divergence[e]
GIAB HG008 5% Purity (2.5% VAF) [19][d]	Strelka2 [4]	0:36.56 (36.56 s) / 118.8 MB	1.0000 / 0.1891 / 0.3181	1.0000 / 0.0272 / 0.0530	External Somatic Caller
GIAB HG008 5% Purity (2.5% VAF) [19][d]	LoFreq [7]	1:14.67 (74.67 s) / 251.5 MB	1.0000 / 0.0051 / 0.0102	0.0000 / 0.0000 / 0.0000[c]	External Somatic Caller
GIAB HG008 5% Purity (2.5% VAF) [19][d]	Mutect2 [8]	7:14.72 (434.72 s) / 1131.1 MB	1.0000 / 0.0988 / 0.1798	0.8889 / 0.0272 / 0.0528	External Somatic Caller
GIAB HG008 2% Purity (1.0% VAF) [19][d]	VarDictRust	0:08.60 (8.60 s) / 813.6 MB	0.2430 / 0.1175 / 0.1584	0.1391 / 0.0544 / 0.0782	100% Exact Match (VarDictRust == VarDictJava)
GIAB HG008 2% Purity (1.0% VAF) [19][d]	VarDictJava [1]	1:05.16 (65.16 s) / 13443.3 MB	0.2430 / 0.1175 / 0.1584	0.1391 / 0.0544 / 0.0782	100% Exact Match (VarDictRust == VarDictJava)
GIAB HG008 2% Purity (1.0% VAF) [19][d]	vardictcpp [11]	0:11.00 (11.00 s) / 1088.3 MB	0.2430 / 0.1175 / 0.1584	0.1391 / 0.0544 / 0.0782	VCF Header / Non-Benchmark Indel Divergence[e]
GIAB HG008 2% Purity (1.0% VAF) [19][d]	Strelka2 [4]	0:36.70 (36.70 s) / 118.8 MB	1.0000 / 0.0187 / 0.0368	0.0000 / 0.0000 / 0.0000[c]	External Somatic Caller
GIAB HG008 2% Purity (1.0% VAF) [19][d]	LoFreq [7]	1:14.80 (74.80 s) / 251.5 MB	0.0000 / 0.0000 / 0.0000[c]	0.0000 / 0.0000 / 0.0000[c]	External Somatic Caller
GIAB HG008 2% Purity (1.0% VAF) [19][d]	Mutect2 [8]	6:59.88 (419.88 s) / 1178.6 MB	1.0000 / 0.0119 / 0.0236	0.0000 / 0.0000 / 0.0000[c]	External Somatic Caller
GIAB HG008 1% Purity (0.5% VAF) [19][d]	VarDictRust	0:08.53 (8.53 s) / 803.0 MB	0.0856 / 0.0426 / 0.0569	0.0660 / 0.0238 / 0.0350	100% Exact Match (VarDictRust == VarDictJava)

Cohort / Purity Stratum	Caller / Engine	Runtime / Evaluated Calls	SNV (or Combined) Precision / Recall / F1 [12][b]	InDel Precision / Recall / F1 [12][b,c]	Concordance / Parity Verdict
GIAB HG008 1% Purity (0.5% VAF) [19][d]	VarDictJava [1]	1:05.41 (65.41 s) / 12946.3 MB	0.0856 / 0.0426 / 0.0569	0.0660 / 0.0238 / 0.0350	100% Exact Match (VarDictRust == VarDictJava)
GIAB HG008 1% Purity (0.5% VAF) [19][d]	vardictcpp [11]	0:10.95 (10.95 s) / 1020.9 MB	0.0856 / 0.0426 / 0.0569	0.0660 / 0.0238 / 0.0350	VCF Header / Non-Benchmark Indel Divergence[e]
GIAB HG008 1% Purity (0.5% VAF) [19][d]	Strelka2 [4]	0:36.58 (36.58 s) / 119.0 MB	1.0000 / 0.0017 / 0.0034	0.0000 / 0.0000 / 0.0000[c]	External Somatic Caller
GIAB HG008 1% Purity (0.5% VAF) [19][d]	LoFreq [7]	1:14.51 (74.51 s) / 252.0 MB	0.0000 / 0.0000 / 0.0000[c]	0.0000 / 0.0000 / 0.0000[c]	External Somatic Caller
GIAB HG008 1% Purity (0.5% VAF) [19][d]	Mutect2 [8]	6:47.62 (407.62 s) / 1180.5 MB	1.0000 / 0.0017 / 0.0034	0.0000 / 0.0000 / 0.0000[c]	External Somatic Caller

[a]Truth-set accuracy evaluated with haplotype-aware rtg vcfeval [12] against NIST GIAB HG002/HG005/NA24385 v4.2.1 [13, 18] (including the Daniels et al. [20] Chr20 exome protocol replicated by Wolff et al. [11]), SEQC2 HCC1395 v1.2.1 [10], and GIAB HG008 v0.3 [19] high-confidence BED masks. [b]Rows 8–17 report combined all-variant (SNV + InDel) rtg vcfeval [12] precision, recall, and F1 at the unfiltered PASS baseline (-f 0.01) and at the F1-maximizing QUAL threshold across a 0..200 ROC sweep. [c]Undefined 0/0 precision and F1 values at 0.0000 recall (e.g., LoFreq [7] somatic runs without indel quality calibration tags or ultra-low-purity strata with 0 emitted calls) are normalized to 0.0000. [d]In silico tumor-purity titration admixtures were generated from GIAB HG008 [19] tumor and matched normal BAMs via samtools view -s [26] at 20%, 10%, 5%, 2%, and 1% tumor purity (10.0% to 0.5% expected clonal VAF) and called at -f 0.002. [e]While VarDictRust matches VarDictJava [1] across all 5 titration purities, vardictcpp [11] omits ##contig headers (CPP-6) and exhibits MNP/tie-break divergence at 20% purity (SNV F1 0.8407 vs. 0.8408) plus non-benchmark indel differences at 10%–1% purity.

Bounded Memory Scaling, Multicore Work-Stealing, and Multi-Tenant Node Packing

A central architectural claim of `VarDictRust` is that peak memory consumption is bounded by `O(threads × (tile + halo))` rather than scaling with chromosome span or BED interval count (`Figure 4` , `Table 4`). We tested this property across four complementary scaling experiments (`Table 4` , `Supplementary Table S3`):

1. **Four-Assay Regression and Performance Gate (`Table 4`):** Across `n = 3` technical replicates on the EGFR/MRE11a amplicon suite (`0.01` s vs `3.07` s Java, wall ratio `0.0033` , RSS ratio `0.0978`), HG002 chromosome 20 germline calling (`21.29` s vs `153.25` s Java, `475.7` MB vs `10509.5` MB, wall ratio `0.1389` , RSS ratio `0.0453`), HG008 paired somatic calling (`17.11` s vs `77.28` s Java, `515.9` MB vs `17318.4` MB, wall ratio `0.2214` , RSS ratio `0.0298`), and SEQC2 paired somatic exome calling (`277.52` s vs `4045.00` s Java, `516.7` MB vs `16085.0` MB, wall ratio `0.0686` , RSS ratio `0.0321`), `VarDictRust` satisfied all performance budgets by wide margins.
2. **Whole-Exome Multicore Scaling (`1` to `32` Threads, `Table 4` , `Figure 4c`):** On the SEQC2 HCC1395 whole exome (`339,698` total variants, `120,307 PASS` variants, `n = 3` technical replicates per thread count), `VarDictRust` scaled smoothly from `812.75` s (`343.5` MB RSS) at `1` thread to `409.14` s (`1.99` × self-speedup) at `2` threads, `212.30` s (`3.83` ×) at `4` threads, `118.90` s (`6.84` ×) at `8` threads, `75.77` s (`10.73` ×) at `16` threads, and `67.86` s (`11.98` × self-speedup, `747.2` MB RSS) at `32` threads. By contrast, `VarDictJava` 's runtime plateaued above `8` threads (`5757.67` s at `1` thread, `1814.63` s at `8` threads, `1991.64` s at `32` threads) due to single-threaded Perl/R post-processing and JVM GC contention, while its heap bloated from `1.79` GiB (`1` thread) to `21.77` GiB (`32` threads)—making `VarDictRust` `29.3` × faster and `29.8` × lower in peak RSS at `32` threads (`2.8` × lower RSS than `vardictcpp` at `2.06` GiB).
3. **Chromosome 1 Span-Invariance Verification (`Table 4` , `Figure 4d`):** When we varied contiguous chromosome 1 query span across `1,000,000` , `10,000,000` , `100,000,000` , and `248,956,422` bp (`1` Mbp to `249` Mbp, `250` × span increase), `VarDictRust` 's `249` Mbp-to- `10` Mbp peak RSS ratio remained tightly bounded below our `1.50` × memory-growth bound: `1.18` × (`1.17` GiB to `1.38` GiB, `27.39` s) at `8` threads, `1.29` × (`1.79` GiB to `2.31` GiB, `14.85` s) at `16` threads, and `1.41` × (`2.62` GiB to `3.69` GiB, `11.87` s) at `32` threads. Even under all-positions `-f 0` pileup stress across `10,000,000` bp (`7,032` variants), `VarDictRust` matched the oracle in `19.58` s (`5.90` GiB RSS).
4. **Concurrent Multi-Tenant Node Packing (`Table 4` , `Figure 4e`):** Running two concurrent `4` -core SEQC2 whole-exome jobs (`job1` and `job2`) on the same node completed in `211.38` s (`437.5` MB) and `211.05` s (`442.0` MB)—virtually identical to an isolated `4` -core run (`212.30` s)—with a combined two-job footprint of only `0.859` GiB. On a `128` GiB cloud node, a workflow scheduler (`Nextflow` / `Cromwell`) can pack `8` concurrent `4` -core `VarDictRust` exome jobs in `3.44` GiB total RAM (`4 × 0.859` GiB), whereas `8` concurrent `VarDictJava` jobs (`6.79` GiB each) consume `54.3` GiB and contend heavily on garbage collection.




Figure 4. Whole-exome multicore scaling, chromosome 1 span-to-RSS invariance, and node packing. (a, b) Peak memory across germline, somatic, `51.8` GiB RNA-seq, and contiguous chromosome 1 (`249.25` Mbp) workloads (`Table 4`). **(c)** SEQC2 HCC1395 whole-exome (`339,698` variants) wall-clock time and peak RSS from `1` to `32` threads (`n = 3` technical replicates; `Supplementary Table S3`). **(d)** Chromosome 1 contiguous span scaling (`1` Mbp to `249` Mbp) demonstrating `VarDictRust` 's `O(tile + halo)` memory bound (`1.18` ×– `1.41` × ratio over a `250` × span increase). **(e)** Concurrent multi-tenant node-packing efficiency (`2 × 4` cores, `0.859` GiB combined peak RSS) and chromosome 1 `-f 0` all-positions stress.

Table 4. Bounded Memory, Whole-Exome 1–32 Thread Scaling, Chromosome 1 Span Invariance & Concurrent Node Packing

Workload & Configuration[a]	VarDictJava [1] Wall / Peak RSS[a]	vardictcpp [11] Wall / Peak RSS[a]	VarDictRust Wall / Peak RSS[a]	Speedup / Memory Reduction Verdict
Targeted Amplicon Panel (8 Threads, n=3)	3.08 (3.06–3.12) s / 120.0 MB	5.28 (5.22–5.37) s / 119.7 MB	0.01 (0.01–0.01) s / 11.6 MB	308.00x faster, 10.4x leaner vs. Java
GIAB HG002 [13, 18] Germline Benchmark Slice (8 Threads, n=3)	154.99 (152.13–159.59) s / 10772.3 MB	20.64 (20.10–21.14) s / 860.1 MB	21.31 (21.29–21.33) s / 486.1 MB	7.27x faster, 22.2x leaner vs. Java
GIAB HG008 [19] Somatic Benchmark Slice (8 Threads, n=3)	78.32 (77.28–79.15) s / 17667.9 MB	17.13 (16.91–17.30) s / 568.4 MB	17.15 (17.11–17.19) s / 510.8 MB	4.57x faster, 34.6x leaner vs. Java
SEQC2 HCC1395 [10] Paired Somatic Exome Slice (8 Threads, n=3)	4014.00 (3967.00–4045.00) s / 14964.1 MB	292.03 (287.70–294.67) s / 2242.1 MB	278.16 (277.52–279.29) s / 515.2 MB	14.43x faster, 29.0x leaner vs. Java
51.8 GiB GIAB HG002 [13] RNA-Seq (-i splice, 8 Threads, n=3)[b]	23.31 (23.03–23.70) s / 4909.1 MB (4.79 GiB)	Unsupported (-i splice unimplemented)[b]	4.94 (4.90–5.01) s / 359.9 MB (0.35 GiB)	4.72x faster, 13.6x leaner vs. Java
SEQC2 HCC1395 [10] Single-Sample Whole Exome (1 Thread, n=3)	5757.67 (5717.00–5789.00) s / 1838.5 MB (1.79 GiB)	1005.71 (993.97–1012.37) s / 1234.5 MB (1.21 GiB)	812.75 (805.74–825.81) s / 343.5 MB (0.34 GiB)	Multi-thread self-speedup: 1.00x (7.1x faster, 5.3x leaner vs. Java)
SEQC2 HCC1395 [10] Single-Sample Whole Exome (2 Threads, n=3)	5802.33 (5762.00–5839.00) s / 4848.6 MB (4.74 GiB)	530.70 (529.51–531.93) s / 1325.3 MB (1.29 GiB)	409.14 (405.60–411.13) s / 415.1 MB (0.41 GiB)	Multi-thread self-speedup: 1.99x (14.2x faster, 11.7x leaner vs. Java)
SEQC2 HCC1395 [10] Single-Sample Whole Exome (4 Threads, n=3)	2270.51 (2254.41–2280.43) s / 6953.7 MB (6.79 GiB)	267.32 (267.11–267.51) s / 1403.1 MB (1.37 GiB)	212.30 (211.15–213.44) s / 443.1 MB (0.43 GiB)	Multi-thread self-speedup: 3.83x (10.7x faster, 15.7x leaner vs. Java)
SEQC2 HCC1395 [10] Single-Sample Whole Exome (8 Threads, n=3)	1814.63 (1752.96–1911.57) s / 9264.7 MB (9.05 GiB)	139.14 (138.32–140.40) s / 1530.0 MB (1.49 GiB)	118.90 (117.36–119.88) s / 536.9 MB (0.52 GiB)	Multi-thread self-speedup: 6.84x (15.3x faster, 17.3x leaner vs. Java)

Workload & Configuration[a]	VarDictJava [1] Wall / Peak RSS[a]	vardictcpp [11] Wall / Peak RSS[a]	VarDictRust Wall / Peak RSS[a]	Speedup / Memory Reduction Verdict
SEQC2 HCC1395 [10] Single-Sample Whole Exome (16 Threads, n=3)	1893.66 (1866.57–1929.42) s / 17859.8 MB (17.44 GiB)	74.17 (73.64–75.12) s / 1729.5 MB (1.69 GiB)	75.77 (74.66–76.76) s / 607.5 MB (0.59 GiB)	Multi-thread self-speedup: 10.73x (25.0x faster, 29.4x leaner vs. Java)
SEQC2 HCC1395 [10] Single-Sample Whole Exome (32 Threads, n=3)	1991.64 (1969.99–2003.54) s / 22290.1 MB (21.77 GiB)	63.68 (63.41–64.15) s / 2109.7 MB (2.06 GiB)	67.86 (67.27–68.20) s / 747.2 MB (0.73 GiB)	Multi-thread self-speedup: 11.98x (29.4x faster, 29.8x leaner vs. Java)
Chromosome 1 Contiguous Span 1–249 Mbp (8 Threads, n=3)[c]	4 GiB Heap OOM (see Table 2 for 200 GiB Heap)[c]	249 Mbp: 30.33 s / 0.79 GiB	249 Mbp: 27.39 s / 1.38 GiB (10 Mbp: 1.17 GiB)	249M/10M RSS ratio = 1.176x (Bounded Memory Verified)[c]
Chromosome 1 Contiguous Span 1–249 Mbp (16 Threads, n=3)[c]	4 GiB Heap OOM (see Table 2 for 200 GiB Heap)[c]	249 Mbp: 18.39 s / 1.14 GiB	249 Mbp: 14.85 s / 2.31 GiB (10 Mbp: 1.79 GiB)	249M/10M RSS ratio = 1.291x (Bounded Memory Verified)[c]
Chromosome 1 Contiguous Span 1–249 Mbp (32 Threads, n=3)[c]	4 GiB Heap OOM (see Table 2 for 200 GiB Heap)[c]	249 Mbp: 16.23 s / 1.70 GiB	249 Mbp: 11.87 s / 3.69 GiB (10 Mbp: 2.62 GiB)	249M/10M RSS ratio = 1.405x (Bounded Memory Verified)[c]
Chromosome 1 10 Mbp All-Positions (-f 0, 8 Threads, n=3)[e]	100% Exact Match via Oracle Baseline[e]	6.01 (5.99–6.04) s / 0.37 GiB	19.58 (19.24–20.09) s / 5.90 GiB	100% Exact Match (7,032 variants)[e]
Concurrent 2x4-Thread SEQC2 [10] Exome Node Packing (n=3)[d]	—	—	Job 1: 211.38 s (437.5 MB); Job 2: 211.05 s (442.0 MB)	Combined Peak RSS = 0.859 GiB (Zero OOMs)[d]

[a]All multi-core and span benchmarks were executed on GCP n2-standard-32 (Intel Xeon Platinum 8373C Ice Lake, 32 vCPUs, 128 GiB RAM) with n=3 technical replicates reported as mean (min–max); Rows 1–4 evaluate four targeted/slice workloads (including a paired somatic exome slice in Row 4), whereas Rows 6–11 scale single-sample whole-exome calling on SEQC2 HCC1395 [10] across 1–32 threads. [b]Transcriptome splice-aware mode (-i) uses a 200 kbp halo to retain split reads across canonical and non-canonical exon-exon junctions; vardictcpp [11] does not implement -i (CPP-10). [c]Span invariance sweeps single contiguous -R chr1:1-L intervals across L in {1, 10, 100, 249.25} Mbp on SEQC2 HCC1395 [10], confirming that 249 Mbp vs. 10 Mbp peak RSS remains below the 1.50x bounded-memory threshold at 8, 16, and 32 threads. [d]Two concurrent 4-thread SEQC2 exome jobs packed on the same node consume 0.859 GiB combined RSS, enabling 8 concurrent 4-thread jobs in 3.44 GiB vs. >54.3 GiB for VarDictJava [1]. [e]Evaluated on a single 10 Mbp Chromosome 1 interval at -f 0 using --tile-size 10000000 so that single-window VarDictRust matches single-window VarDictJava [1] with 0 differences.

Full-Genome WGS Scaling: Unchunked Full Chromosomes Versus Pre-Chunked Callable Intervals

To evaluate whole-genome scalability under realistic production conditions, we compared all three engines at `32` threads across two full-genome GRCh38 datasets: the `130.8` GB NIST HG002 `2×250` bp Illumina germline WGS BAM and the `329.0` GB NIST HG008 `364` × combined (`195` × tumor / `169` × normal) paired somatic WGS BAMs (`Table 5` , `Figure 5`). For each genome, we tested two region-definition protocols:

- **Unchunked full chromosomes (`chr1` – `chr22` , `22` autosomes):** Each chromosome (`chr1` – `chr22`) is passed as a single full-length BED line, testing whether the engine can natively stream whole chromosomes without external script intervention.
- **Pre-chunked callable intervals (`≤50` kbp GIAB BED):** High-confidence callable intervals (`2.51` Gbp for HG002; `2.37` Gbp for HG008) are pre-split at `≤50` kbp to accommodate `VarDictJava` and `vardictcpp` .

The contrast between unchunked full chromosomes and pre-chunked callable intervals exposes the fundamental limitation of whole-interval allocation (`Table 5` , `Figure 5`):

- **Unchunked Full Chromosomes (`chr1` – `chr22`):** On HG002 unchunked chromosomes, `VarDictJava` (`-Xmx200g`) exhausted `213.7` GB RAM and aborted with `java.lang.OutOfMemoryError` . `vardictcpp` completed in `18:50.80` but required `31.91` GB peak RSS (`6.5` × higher than `VarDictRust`) and emitted `9,953,338` variants (`309,569` excess un-deduplicated chunk-boundary artifacts relative to `VarDictRust` 's `9,643,769` variants). `VarDictRust` completed all `22` chromosomes in `25:16.61` at just `4.93` GB peak RSS. On the `329.0` GB `364` × HG008 paired somatic WGS, `VarDictJava` crashed with an out-of-memory error at `214.1` GB, and `vardictcpp` ballooned to `91.85` GB RSS (`7.6` × higher than `VarDictRust`) before exceeding the `3` -hour wall-clock limit. `VarDictRust` was the *only* engine to complete unchunked `364` × somatic WGS, finishing in `2:49:52` at `12.14` GB peak RSS and emitting `13,067,287` somatic/germline variants.
- **Pre-chunked Callable Intervals (`≤50` kbp GIAB BED):** When intervals were pre-split to `≤50` kbp, `VarDictJava` completed HG002 WGS in `3:08:15` at `34.14` GB RSS. `VarDictRust` finished in `20:21.21` at `1.43` GB RSS—a `9.25` × speedup and `23.8` × memory reduction over `VarDictJava` (and `19.8` × lower RSS than `vardictcpp` 's `28.35` GB in `11:40.98`), while matching `VarDictJava` across `8,111,171` variants (with `vardictcpp` differing by `394` variants at `8,111,565`) and achieving `rtg vcfeval` full-genome $F_1 = 0.9651$ (precision `0.9738` , sensitivity `0.9566` ; unfiltered $F_1 = 0.6624$, precision `0.5057` , sensitivity `0.9598`). On pre-chunked HG008 callable-interval WGS, `VarDictJava` (`62.51` GB RSS) exceeded the `4` -hour wall-clock limit (`4:00:00`) and `vardictcpp` (`21.16` GB RSS) exceeded the `3` -hour limit (`3:00:00`), whereas `VarDictRust` completed in `1:45:55` at `4.88` GB RSS (`4.3` × lower RSS than `vardictcpp`), emitting `10,195,118` variants and achieving full-genome somatic $F_1 = 0.6547$ (`GIAB v0.3`) and $F_1 = 0.6585$ (`GIAB v0.4`).




Figure 5. Full-genome WGS scaling across unchunked full chromosomes (`chr1` – `chr22`) and pre-chunked callable intervals (`≤50` kbp GIAB BED). (a) Peak RSS (GB) and completion status on `130.8` GB HG002 germline WGS and `329.0` GB `364` × HG008 paired somatic WGS across unchunked chromosomes and pre-chunked intervals (`32` threads; `Table 5`). **(b)** Wall-clock runtime comparison showing `VarDictJava` out-of-memory and wall-clock timeout failures alongside `VarDictRust` completion (`25:16.61` and `2:49:52`). **(c)** Full-genome `rtg vcfeval` precision, sensitivity, and F_1 across `HG002 GIAB v4.2.1` (optimal `QUAL` and all- `PASS`) and `HG008 GIAB v0.3` / `v0.4` (`Table 5`).

Table 5. Full-Genome Chromosomes 1–22 Germline (GIAB HG002 130.8 GB [13, 18]) & 364x Somatic (GIAB HG008 329.0 GB [19]) WGS Scaling Across Unchunked and Callable BED Geometries

Cohort & Calling Geometry (32 Threads)[a]	VarDictJava v1.8.3 [1] (-Xmx200g)[b]	vardictcpp [11] (--chunk 50,000)[b,c]	VarDictRust v1.0.6	Parity & Full-Genome rtg vcfeval [12] Concordance
GIAB HG002 [13, 18] 130.8 GB Germline WGS (22 Unchunked Chromosomes)[a]	OOM Crash (rc=3, >200 GB Heap) at 213.70 GB RSS (10:26.73)[b]	18:50.80 / 31.91 GB RSS (9,953,338 variants; +309,569 chunk-boundary duplicates)[c]	25:16.61 (1516.61 s) / 4.93 GB (4.70 GiB) RSS (9,643,769 variants)	Completes in bounded memory (Rust 6.5x leaner than C++, 0 chunk-boundary duplicates)[c]
GIAB HG002 [13, 18] 130.8 GB Germline WGS (≤50 kbp GIAB Callable BED)[a]	3:08:15 / 34.14 GB RSS (8,111,171 variants)	11:40.98 / 28.35 GB RSS (8,111,565 variants)[c]	20:21.21 (1221.21 s) / 1.43 GB (1.37 GiB) RSS (8,111,171 variants)	100% Exact Match on callable intervals (9.25x faster, 23.8x leaner vs. Java); GIAB v4.2.1 F1=0.9651 (P=0.9738, R=0.9566; VarDictRust == VarDictJava)
GIAB HG008 [19] 329.0 GB 364x T/N Somatic WGS (22 Unchunked Chromosomes, -U)[a,d]	OOM Crash (rc=3, >200 GB Heap) at 214.12 GB RSS (1:20:05)[b]	Timeout (rc=124, >3 h) at 91.85 GB RSS ()[b]	2:49:52 (10192.00 s) / 12.14 GB (11.57 GiB) RSS (13,067,287 variants)	Only VarDictRust completes (Rust 7.6x leaner than C++)
GIAB HG008 [19] 329.0 GB 364x T/N Somatic WGS (≤50 kbp GIAB Callable BED, -U)[a,d]	Timeout (rc=124, 4:00:00) at 62.51 GB RSS[b]	Timeout (rc=124, >3 h) at 21.16 GB RSS (3:00:00)[b]	1:45:55 (6355.00 s) / 4.88 GB (4.65 GiB) RSS (10,195,118 variants)	Only VarDictRust completes; GIAB v0.3 F1=0.6547, v0.4 F1=0.6585

[a] *Full-genome WGS benchmarks were executed on a 32-vCPU, 256 GiB RAM Intel Ice Lake instance across two BED geometries: 22 unchunked autosomal contigs (chr1..chr22, 2.88 Gbp) and NIST GIAB high-confidence callable BED intervals (<=50 kbp per interval; 2.51 Gbp on HG002 v4.2.1 [13, 18] and 2.37 Gbp on HG008 v0.4 [19]).* [b] *VarDictJava v1.8.3 [1] was provisioned with a 200 GiB JVM heap (-Xmx200g); rc=3 denotes an OutOfMemoryError abort and rc=124 denotes termination at the wall-clock timeout (3 h for vardictcpp [11] and 4 h for the 3-process VarDictJava pipeline).* [c] *On unchunked HG002 contigs, vardictcpp --chunk 50,000 [11] splits chromosomes without cross-window deduplication (CPP-5), emitting +309,569 duplicate boundary calls; on <=50 kbp callable intervals, vardictcpp still differs from the VarDictJava oracle on 394 calls due to MNP/tie-break divergences (CPP-9).* [d] *HG008 364x tumor-normal full-WGS runs use -U (--nosv) across all three engines to evaluate small-variant somatic calling without structural-variant realignment overhead.*

Cross-Platform Sequencing Chemistry Generalization and 70-Cell GA4GH v3.5 Stratification

To ensure that `VarDictRust` 's exact oracle parity and biological accuracy generalize beyond standard Illumina libraries, we evaluated `10` short-read sequencing chemistries across the entire `64.44` Mbp human chromosome 20 (`Table 6` , `Figure 6` , `Supplementary Table S4` , `Supplementary Table S5`):

- **HG002 Germline (`4` Chemistries):** `Illumina` , `Element AVITI` , `MGI DNBSEQ` , and `Ultima Genomics UG100` (evaluated across both standard GIAB and Ultima High-Confidence Region [`UG-HCR`] truth masks).
- **HG008 Paired Tumor-Normal Somatic (`6` Chemistries):** `Illumina` , `Element AVITI` , `PacBio Onso` , `Roche SBX` , `Ultima Genomics ppmSeq` , and `Ultima Genomics UG100` .

Across all `20` standard chromosome 20 calling (`-f 0.01`) and all-frequency (`-f 0`) runs, `VarDictRust` completed `20/20` (`100%`) runs cleanly. By contrast, `VarDictJava` completed only `11/20` runs and timed out on `9/20` deep chromosome 20 runs (`Table 6`). On all `11`

runs where `VarDictJava` finished, `VarDictRust` achieved `100%` (`11/11`, `95%` CI `71.51%–100.00%`) exact parity, yielding identical SNV F_1 across HG002 germline (`0.6622–0.9598` standard; `0.6622–0.9618` on `UG-HCR`) and HG008 somatic (`0.6870–0.8804` at `-f 0.01` standard; `0.7532–0.9048` on `UG-HCR`; `0.6498–0.8804` and `0.7505–0.9048` across all frequencies). In our unfiltered somatic noise-floor sweep (`-f 0`, `Supplementary Table S4`) across `18` chemistry-by-threshold configurations (`18,407` total candidates, `2,865` `PASS` somatic calls), `VarDictRust` achieved `18/18` (`100%`, `95%` CI `81.47%–100.00%`) byte-level equivalence with `VarDictJava`.

We then crossed all `10` sequencing chemistries with `7` GA4GH `v3.5` genomic context strata (`4–6 bp homopolymers`, `7–11 bp homopolymers`, `≥12 bp homopolymers`, `tandem repeats`, `segmental duplications`, `low-mappability regions`, and `RefSeq coding exons (CDS)`), yielding a `70`-cell stratification matrix (`100%` oracle parity across all completed cells, `95%` CI `94.87%–100.00%`, mean SNV F_1 = *0.7073*; `Supplementary Table S5`, `Figure 6c`).




Figure 6. Cross-platform short-read sequencing chemistry panel and `70`-cell GA4GH `v3.5` stratification heatmap. (a) Runtime, completion rate (`VarDictRust` `20/20` vs `VarDictJava` `11/20`), and accuracy across `10` germline and somatic chemistries on chromosome 20 (`64.44` Mbp; `Table 6`). **(b)** Byte-equivalent candidate and `PASS` somatic variant counts (`18/18` exact match) across the unfiltered somatic noise-floor sweep (`-f 0`; `Supplementary Table S4`). **(c)** `70`-cell (`10` chemistries × `7` GA4GH `v3.5` strata) SNV and indel F_1 heatmap (`Supplementary Table S5`).

Table 6. Ten-Platform Sequencing Chemistry Chromosome 20 Generalization (-f 0.01 & -f 0) and GA4GH v3.5 [17] Stratification Summary

Sequencing Platform[a]	Cohort & Min VAF	VarDictRust Wall / Peak RSS (PASS Variants)	VarDictJava [1] Wall / Parity Verdict[b]	vardictcpp [11] Wall / Verdict[b,c]	Standard GIAB SNV / InDel F1 [12, 13, 19][d]	UG-HCR v2.1 SNV / InDel F1 [6, 12][d]
HG002 Illumina	HG002 Germline (-f 0.01)	0:27.42 / 861.1 MB (162,637)	4:12.27 (100% Exact Match)	0:21.02 (MNP/SV Divergence[c])	0.6622 / 0.7066	0.6622 / 0.6568
HG002 Element AVITI	HG002 Germline (-f 0.01)	0:28.67 / 640.5 MB (85,612)	3:38.45 (100% Exact Match)	0:21.64 (MNP/SV Divergence[c])	0.9577 / 0.9669	0.9598 / 0.9599
HG002 MGI DNBSEQ	HG002 Germline (-f 0.01)	0:46.67 / 882.5 MB (157,238)	6:30.93 (100% Exact Match)	0:32.59 (MNP/SV Divergence[c])	0.6835 / 0.6472	0.6845 / 0.6181
HG002 Ultima UG100	HG002 Germline (-f 0.01)	0:21.72 / 1086.4 MB (348,289)	13:30.85 (100% Exact Match)	0:42.98 (MNP/SV Divergence[c])	0.8975 / 0.0621	0.9035 / 0.0488
HG002 Illumina	HG002 Germline (-f 0)	0:26.97 / 856.9 MB (161,264)	4:11.81 (100% Exact Match)	0:20.61 (MNP/SV Divergence[c])	0.6662 / 0.7099	0.6662 / 0.6608

Sequencing Platform[a]	Cohort & Min VAF	VarDictRust Wall / Peak RSS (PASS Variants)	VarDictJava [1] Wall / Parity Verdict[b]	vardictcpp [11] Wall / Verdict[b,c]	Standard GIAB SNV / InDel F1 [12, 13, 19][d]	UG-HCR v2.1 SNV / InDel F1 [6, 12][d]
HG002 Element AVITI	HG002 Germline (-f 0)	0:28.64 / 618.7 MB (85,273)	3:45.84 (100% Exact Match)	0:22.46 (MNP/SV Divergence[c])	0.9598 / 0.9675	0.9618 / 0.9607
HG002 MGI DNBSEQ	HG002 Germline (-f 0)	0:51.00 / 1154.5 MB (109,648)	7:16.31 (100% Exact Match)	0:34.46 (MNP/SV Divergence[c])	0.8538 / 0.7572	0.8560 / 0.7694
HG002 Ultima UG100	HG002 Germline (-f 0)	0:21.49 / 1110.3 MB (348,287)	14:21.92 (100% Exact Match)	0:43.58 (MNP/SV Divergence[c])	0.8975 / 0.0621	0.9035 / 0.0488
HG008 Illumina	HG008 Somatic (-f 0.01)	2:59.41 / 4387.1 MB (17,951)	38:30.03 (100% Exact Match)	5:19.09 (MNP/SV Divergence[c])	0.8308 / 0.4085	0.9048 / 0.5075
HG008 Element AVITI	HG008 Somatic (-f 0.01)	2:26.42 / 3218.6 MB (8,392)	22:34.27 (100% Exact Match)	3:29.05 (MNP/SV Divergence[c])	0.7065 / 0.6482	0.7603 / 0.5570
HG008 PacBio Onso	HG008 Somatic (-f 0.01)	7:23.36 / 3433.6 MB (24,987)	52:49.80 (100% Exact Match)	5:33.67 (MNP/SV Divergence[c])	0.6870 / 0.4206	0.7532 / 0.4000
HG008 Roche SBX	HG008 Somatic (-f 0.01)	13:15.84 / 8876.2 MB (1,306,027)	Timeout (rc=124, >3 h)[b]	38:39.75 (Oracle Timed Out[b,c])	0.8804 / 0.2741	0.9005 / 0.4839
HG008 Ultima ppmSeq	HG008 Somatic (-f 0.01)	30:51.77 / 4898.7 MB (376,695)	Timeout (rc=124, >3 h)[b]	1:41:18 (Oracle Timed Out[b,c])	0.8471 / 0.1310	0.8867 / 0.3438
HG008 Ultima UG100	HG008 Somatic (-f 0.01)	10:02.41 / 6410.1 MB (1,054,976)	Timeout (rc=124, >3 h)[b]	Timeout (rc=124, >3 h)[b]	0.8652 / 0.1410	0.8974 / 0.4444
HG008 Illumina	HG008 Somatic (-f 0)	5:40.39 / 4429.3 MB (25,904)	Timeout (rc=124, >3 h)[b]	3:13:59 (Oracle Timed Out[b,c])	0.8134 / 0.4000	0.9048 / 0.5075
HG008 Element AVITI	HG008 Somatic (-f 0)	12:08.63 / 3275.1 MB (8,682)	Timeout (rc=124, >3 h)[b]	Timeout (rc=124, >3 h)[b]	0.6585 / 0.6332	0.7505 / 0.5500
HG008 PacBio Onso	HG008 Somatic (-f 0)	30:29.96 / 3661.4 MB (27,195)	Timeout (rc=124, >3 h)[b]	Timeout (rc=124, >3 h)[b]	0.6498 / 0.4093	0.7516 / 0.4000
HG008 Roche SBX	HG008 Somatic (-f 0)	32:54.13 / 8238.1 MB (1,394,679)	Timeout (rc=124, >3 h)[b]	3:13:26 (Oracle Timed Out[b,c])	0.8804 / 0.2741	0.9005 / 0.4839
HG008 Ultima ppmSeq	HG008 Somatic (-f 0)	1:01:33 / 4872.8 MB (401,121)	Timeout (rc=124, >3 h)[b]	Timeout (rc=124, >3 h)[b]	0.8471 / 0.1310	0.8867 / 0.3438
HG008 Ultima UG100	HG008 Somatic (-f 0)	1:06:35 / 6956.7 MB (1,896,213)	Timeout (rc=124, >3 h)[b]	Timeout (rc=124, >3 h)[b]	0.8652 / 0.1429	0.8974 / 0.4444
All 10 Platforms x 7 Strata [17][e]	70 GA4GH v3.5 Cells	70/70 Completed	100% Exact Match (VarDictRust == VarDictJava)[b,e]	—	Mean SNV F1=0.7073	See Supplementary Table S5 for all 70 cells[e]

[a]Evaluates whole-chromosome Chromosome 20 (64.44 Mbp) across 4 GIAB HG002 [13, 18] germline chemistries (Illumina NovaSeq, Element AVITI, MGI DNBSEQ, Ultima UG100) and 6 GIAB HG008 [19] tumor-normal somatic chemistries (Illumina, Element AVITI, PacBio Onso, Roche SBX, Ultima ppmSeq, Ultima UG100) at both standard (-f 0.01) and zero-threshold (-f 0) VAF cutoffs. [b]VarDictRust achieves 100% exact equivalence against VarDictJava v1.8.3 [1] across all 11/11 completing Chromosome 20 runs and all 18/18 targeted singleton noise-floor runs (Supplementary Table S4); runs marked Timeout (rc=124, >3 h) exceeded the multi-hour stage wall-clock limit under extreme-depth somatic pileups. [c]On completing runs where VarDictJava also finished, vardictcpp [11] diverges from the oracle due to MNP splitting and omitted somatic SVs (CPP-2, CPP-9); rows marked Oracle Timed Out completed in vardictcpp while the VarDictJava reference run timed out. [d]Accuracy is evaluated via rtg vcfeval [12] against both the unmasked NIST GIAB high-confidence BED [13, 19] and the intersection with the Ultima Genomics High-Confidence Region (UG-HCR v2.1) [6] homopolymer-exclusion mask. [e]Summarizes the 70-cell GA4GH v3.5 [17] stratification matrix (10 platforms x 7 difficult genomic strata; full breakdown in Supplementary Table S5).

Unlocking Next-Generation GIAB v5.0q T2T-Q100, CMRG v1.00, and Mosaic v1.10 Discovery via Unchunked Calling

We next evaluated how removing the `≤50` kbp BED pre-chunking constraint affects biological variant discovery by comparing our full-genome HG002 callsets (unchunked full chromosomes `chr1` – `chr22` vs pre-chunked `≤50` kbp `GIAB v4.2.1` callable intervals) against three next-generation NIST truth benchmarks (`Table 7` , `Figure 7`):

1. **`NIST GIAB v5.0q T2T-Q100` (`2.74` Gbp, diploid Telomere-to-Telomere Q100 assembly truth):** Because `VarDictJava` cannot run on unchunked chromosomes without running out of memory, legacy workflows restrict calling to pre-chunked `GIAB v4.2.1` intervals (`2.51` Gbp). However, `GIAB v5.0q` expands benchmarkable truth regions by `+0.23` Gbp across newly resolved segmental duplications, pericentromeric satellites, and complex loci outside the `v4.2.1` mask. On `GIAB v4.2.1` (`Table 7`), unchunked chromosomes and pre-chunked intervals yielded identical accuracy (`SNV` sensitivity `0.9576` vs `0.9577` , `SNV` $F_1 = 0.6639$, `Indel` $F_1 = 0.6928$). On `GIAB v5.0q T2T-Q100` , however, `VarDictRust` 's ability to stream unchunked full chromosomes increased genome-wide SNV recall by `+5.01%` (`0.8866` on pre-chunked intervals to `0.9367` on unchunked chromosomes, F_1 from `0.6461` to `0.6650`) and boosted genome-wide indel recall by `+17.26%` (`0.5281` to `0.7007` , F_1 from `0.5487` to `0.6551`).
2. **`NIST Challenging Medically Relevant Genes` (`CMRG v1.00` , `273` clinical genes):** Many of the `273` CMRG genes fall in regions excluded by the `v4.2.1` `50` kbp BED mask. Unchunked `VarDictRust` calling increased CMRG SNV recall by `+17.47%` (`0.7173` to `0.8920` , F_1 from `0.6132` to `0.6791`) and CMRG indel recall by `+27.98%` (`0.4904` to `0.7702` , F_1 from `0.5316` to `0.6937`).
3. **`NIST Mosaic SNV v1.10` (`85` validated low-VAF somatic mosaic SNVs in HG002, VAF `1%–30%`):** Both `VarDictRust` and `VarDictJava` detected `84/85` (`98.82%` , `95%` CI `93.62%–99.97%`) of the `85` validated mosaic variants (`Table 7`).




Figure 7. Next-generation `GIAB v5.0q T2T-Q100`, `CMRG v1.00`, `Mosaic v1.10`, and `HG008 v0.4` truth evaluation. (a) Genome-wide and medically relevant gene SNV sensitivity unlocked by unchunked full-chromosome calling (`VarDictRust`) versus legacy `≤50` kbp `GIAB v4.2.1` interval calling on `NIST v4.2.1`, `NIST v5.0q T2T-Q100` (`+5.01%` SNV recall), and `CMRG v1.00` (`+17.47%` SNV recall; `Table 7`). **(b)** `NIST Mosaic v1.10` sensitivity (`84/85`, `98.82%`) and `CMRG v1.00` indel recovery (`+27.98%` indel recall; `Table 7`). **(c)** `NIST GIAB HG008 v0.4` somatic SNV and indel F_1 across `11` callers (`Table 7`).

Table 7. Next-Generation Truth Benchmarks (GIAB v5.0q T2T-Q100 [14, 16], CMRG v1.00 [15], Mosaic SNV v1.10 [19]) & HG008 GIAB v0.4 [19] Somatic Caller Landscape

Benchmark / Evaluation Scope	Caller / Configuration	Sequencing Chemistry	SNV Precision / Recall / F1 [12]	InDel Precision / Recall / F1 [12]
GIAB HG002 v4.2.1 (GRCh38 All) [13, 18][a]	VarDictRust (Unchunked Contigs)[b]	Illumina 2x250 bp WGS	0.5081 / 0.9577 / 0.6639	0.5698 / 0.8836 / 0.6928
GIAB HG002 v4.2.1 (GRCh38 All) [13, 18][a]	VarDictRust (≤50 kbp GIAB BED)	Illumina 2x250 bp WGS	0.5081 / 0.9576 / 0.6639	0.5697 / 0.8835 / 0.6928
GIAB HG002 v4.2.1 (GRCh38 All) [13, 18][a]	VarDictJava [1] (≤50 kbp GIAB BED)	Illumina 2x250 bp WGS	0.5081 / 0.9576 / 0.6639	0.5697 / 0.8835 / 0.6928
GIAB HG002 v5.0q (T2T-Q100 Assembly) [14, 16][a,b]	VarDictRust (Unchunked Contigs)[b]	Illumina 2x250 bp WGS	0.5155 / 0.9367 / 0.6650	0.6151 / 0.7007 / 0.6551
GIAB HG002 v5.0q (T2T-Q100 Assembly) [14, 16][a,b]	VarDictRust (≤50 kbp GIAB BED)	Illumina 2x250 bp WGS	0.5083 / 0.8866 / 0.6461	0.5708 / 0.5281 / 0.5487
GIAB HG002 v5.0q (T2T-Q100 Assembly) [14, 16][a,b]	VarDictJava [1] (≤50 kbp GIAB BED)	Illumina 2x250 bp WGS	0.5083 / 0.8866 / 0.6461	0.5708 / 0.5281 / 0.5487
GIAB HG002 CMRG v1.00 (273 Challenging Medically Relevant Genes) [15][a,b]	VarDictRust (Unchunked Contigs)[b]	Illumina 2x250 bp WGS	0.5482 / 0.8920 / 0.6791	0.6310 / 0.7702 / 0.6937
GIAB HG002 CMRG v1.00 (273 Challenging Medically Relevant Genes) [15][a,b]	VarDictRust (≤50 kbp GIAB BED)	Illumina 2x250 bp WGS	0.5355 / 0.7173 / 0.6132	0.5803 / 0.4904 / 0.5316
GIAB HG002 CMRG v1.00 (273 Challenging Medically Relevant Genes) [15][a,b]	VarDictJava [1] (≤50 kbp GIAB BED)	Illumina 2x250 bp WGS	0.5355 / 0.7173 / 0.6132	0.5803 / 0.4904 / 0.5316
GIAB HG002 Mosaic SNV v1.10 (Low-VAF Somatic-Like Benchmark) [19][c]	VarDictRust (Unchunked Contigs)[b]	Illumina 2x250 bp WGS	Recall = 0.9882 (98.82%)[c]	SNV-Only Truth Set (No Truth InDels)[c]
GIAB HG002 Mosaic SNV v1.10 (Low-VAF Somatic-Like Benchmark) [19][c]	VarDictRust (≤50 kbp GIAB BED)	Illumina 2x250 bp WGS	Recall = 0.9882 (98.82%)[c]	SNV-Only Truth Set (No Truth InDels)[c]

Benchmark / Evaluation Scope	Caller / Configuration	Sequencing Chemistry	SNV Precision / Recall / F1 [12]	InDel Precision / Recall / F1 [12]
GIAB HG002 Mosaic SNV v1.10 (Low-VAF Somatic-Like Benchmark) [19][c]	VarDictJava [1] (≤50 kbp GIAB BED)	Illumina 2x250 bp WGS	Recall = 0.9882 (98.82%)[c]	SNV-Only Truth Set (No Truth InDels)[c]
GIAB HG008 Somatic v0.4 (Full-Genome WGS, All Callable) [19][d]	VarDictRust v1.0.6	Illumina WGS (195x T / 169x N)	0.8262 / 0.7542 / 0.7886	0.6288 / 0.4011 / 0.4898
GIAB HG008 Somatic v0.4 (Full-Genome WGS, Excl. Genomic Instability) [19][d]	VarDictRust v1.0.6	Illumina WGS (195x T / 169x N)	0.8258 / 0.7810 / 0.8028	0.6703 / 0.4832 / 0.5616
GIAB HG008 Somatic v0.4 (Targeted Benchmark Regions) [19][e]	VarDictRust v1.0.6	Illumina WGS (195x T / 169x N)	0.9916 / 0.6048 / 0.7513	0.9479 / 0.3095 / 0.4667
GIAB HG008 Somatic v0.4 (Full-Genome WGS, All Callable) [19][d]	DRAGEN v4.2.4 Linear [21][d]	Illumina WGS	0.9546 / 0.8643 / 0.9072	0.9140 / 0.4320 / 0.5867
GIAB HG008 Somatic v0.4 (Full-Genome WGS, Excl. Genomic Instability) [19][d]	DRAGEN v4.2.4 Linear [21][d]	Illumina WGS	0.9570 / 0.8848 / 0.9195	0.9307 / 0.7067 / 0.8034
GIAB HG008 Somatic v0.4 (Targeted Benchmark Regions) [19][e]	DRAGEN v4.2.4 Linear [21][d]	Illumina WGS	0.9905 / 0.7104 / 0.8274	0.8585 / 0.3095 / 0.4550
GIAB HG008 Somatic v0.4 (Full-Genome WGS, All Callable) [19][d]	DRAGEN v4.2.4 Graph [21][d]	Illumina WGS	0.9591 / 0.8633 / 0.9087	0.9170 / 0.4323 / 0.5876
GIAB HG008 Somatic v0.4 (Full-Genome WGS, Excl. Genomic Instability) [19][d]	DRAGEN v4.2.4 Graph [21][d]	Illumina WGS	0.9615 / 0.8836 / 0.9209	0.9335 / 0.7067 / 0.8044
GIAB HG008 Somatic v0.4 (Targeted Benchmark Regions) [19][e]	DRAGEN v4.2.4 Graph [21][d]	Illumina WGS	0.9905 / 0.7104 / 0.8274	0.8585 / 0.3095 / 0.4550
GIAB HG008 Somatic v0.4 (Full-Genome WGS, All Callable) [19][d]	Lancet2 (NYGC) [24][d]	Illumina WGS	0.9933 / 0.7936 / 0.8823	0.9833 / 0.2179 / 0.3568
GIAB HG008 Somatic v0.4 (Full-Genome WGS, Excl. Genomic Instability) [19][d]	Lancet2 (NYGC) [24][d]	Illumina WGS	0.9960 / 0.8231 / 0.9013	0.9867 / 0.3618 / 0.5295
GIAB HG008 Somatic v0.4 (Targeted Benchmark Regions) [19][e]	Lancet2 (NYGC) [24][d]	Illumina WGS	1.0000 / 0.5843 / 0.7376	1.0000 / 0.1599 / 0.2757
GIAB HG008 Somatic v0.4 (Full-Genome WGS, All Callable) [19][d]	Hartwig SAGE [25][d]	Illumina WGS	0.9956 / 0.8161 / 0.8969	0.9710 / 0.6309 / 0.7649
GIAB HG008 Somatic v0.4 (Full-Genome WGS, Excl. Genomic Instability) [19][d]	Hartwig SAGE [25][d]	Illumina WGS	0.9958 / 0.8413 / 0.9121	0.9653 / 0.7883 / 0.8679
GIAB HG008 Somatic v0.4 (Targeted Benchmark Regions) [19][e]	Hartwig SAGE [25][d]	Illumina WGS	1.0000 / 0.6048 / 0.7537	0.9858 / 0.4728 / 0.6391
GIAB HG008 Somatic v0.4 (Full-Genome WGS, All Callable) [19][d]	DeepSomatic v1.6.0 [22][d]	PacBio HiFi	0.9886 / 0.8512 / 0.9148	0.9158 / 0.1845 / 0.3072
GIAB HG008 Somatic v0.4 (Full-Genome WGS, Excl. Genomic Instability) [19][d]	DeepSomatic v1.6.0 [22][d]	PacBio HiFi	0.9953 / 0.8763 / 0.9320	0.9140 / 0.3165 / 0.4702
GIAB HG008 Somatic v0.4 (Targeted Benchmark Regions) [19][e]	DeepSomatic v1.6.0 [22][d]	PacBio HiFi	1.0000 / 0.6627 / 0.7971	1.0000 / 0.1395 / 0.2448
GIAB HG008 Somatic v0.4 (Full-Genome WGS, All Callable) [19][d]	ClairS v0.4.1 [23][d]	PacBio HiFi	0.9793 / 0.8419 / 0.9054	0.9791 / 0.1302 / 0.2298
GIAB HG008 Somatic v0.4 (Full-Genome WGS, Excl. Genomic Instability) [19][d]	ClairS v0.4.1 [23][d]	PacBio HiFi	0.9793 / 0.8736 / 0.9234	0.9797 / 0.2264 / 0.3678
GIAB HG008 Somatic v0.4 (Targeted Benchmark Regions) [19][e]	ClairS v0.4.1 [23][d]	PacBio HiFi	1.0000 / 0.6491 / 0.7872	1.0000 / 0.1122 / 0.2018
GIAB HG008 Somatic v0.4 (Full-Genome WGS, All Callable) [19][d]	Ultima DeepVariant Somatic [6][d]	Ultima UG100	0.9749 / 0.9101 / 0.9414	0.9429 / 0.2459 / 0.3900
GIAB HG008 Somatic v0.4 (Full-Genome WGS, Excl. Genomic Instability) [19][d]	Ultima DeepVariant Somatic [6][d]	Ultima UG100	0.9751 / 0.9444 / 0.9595	0.9486 / 0.4218 / 0.5839
GIAB HG008 Somatic v0.4 (Targeted Benchmark Regions) [19][e]	Ultima DeepVariant Somatic [6][d]	Ultima UG100	1.0000 / 0.7700 / 0.8701	0.9859 / 0.2381 / 0.3836
GIAB HG008 Somatic v0.4 (Targeted Benchmark Regions) [19][e]	Mutect2 [8]	Illumina WGS (195x T / 169x N)	0.9874 / 0.6661 / 0.7955	0.9431 / 0.3946 / 0.5564
GIAB HG008 Somatic v0.4 (Targeted Benchmark Regions) [19][e]	Strelka2 [4]	Illumina WGS (195x T / 169x N)	0.9896 / 0.8075 / 0.8893	0.9545 / 0.2857 / 0.4398
GIAB HG008 Somatic v0.4 (Targeted Benchmark Regions) [19][e]	LoFreq [7]	Illumina WGS (195x T / 169x N)	1.0000 / 0.7053 / 0.8272	0.0000 / 0.0000 / 0.0000[e]

[a]Evaluates full-genome GIAB HG002 [13, 18] 2x250 bp WGS callsets across the legacy v4.2.1 benchmark (2.51 Gbp) [13], the T2T-Q100 assembly-backed v5.0q benchmark (2.74 Gbp) [14, 16], and the 273-gene Challenging Medically Relevant Genes (CMRG v1.00) benchmark [15]. [b]On v4.2.1 callable BED intervals (<=50 kbp), VarDictRust and VarDictJava v1.8.3 [1] achieve identical accuracy; on v5.0q and CMRG v1.00, unchunked full-contig calling in VarDictRust recovers +5.01% SNV / +17.26% InDel recall on v5.0q and +17.47% SNV / +27.98% InDel recall on CMRG loci located outside legacy v4.2.1 BED masks (where VarDictJava OOMs on unchunked contigs). [c]NIST GIAB HG002 Mosaic SNV v1.10 [19] is an SNV-only benchmark of 85 low-VAF (1%–30% VAF) somatic-like loci; because whole-genome calling was performed without restricting to the 89-locus mosaic target BED, unmasked sensitivity (84/85 = 98.82% recall) is the informative metric. [d]External full-genome HG008 GIAB v0.4 [19] callsets are sourced from the NIST GIAB Liss Lab repository for DRAGEN v4.2.4 [21], DeepSomatic v1.6.0 [22], ClairS v0.4.1 [23], Ultima DeepVariant Somatic [6], Lancet2 (NYGC) [24], and Hartwig SAGE [25], evaluated both across all callable regions and excluding genomic instability (NoGI) masks. [e]Targeted HG008 v0.4 slice evaluations compare VarDictRust, VarDictJava [1], Strelka2 [4], Mutect2 [8], and LoFreq [7] on identical 195x tumor / 169x normal Illumina alignments; LoFreq 0.0000 indel scores reflect absent indel quality calibration tags.

Benchmarking Against Modern Deep-Learning and Commercial Callers, Low-VAF Titration, and Supply-Chain Hardening

Finally, we benchmarked `VarDictRust` against contemporary deep-learning, graph, and haplotype somatic callers across three evaluations (`Table 3`, `Table 7`, `Table 8`, `Figure 3d`, `Figure 7c`, `Figure 8`, `Supplementary Table S6`):

- **`11`-Caller Benchmark on `NIST GIAB HG008 v0.4` (`27` benchmark evaluations; `Table 7`, `Figure 7c`):** Using official NIST GIAB somatic callsets alongside our local runs, we compared `VarDictRust` (`v1.0.6`) against `DRAGEN v4.2.4` (`Graph` and `Linear`), `DeepSomatic v1.6.0`, `ClairS v0.4.1`, `Lancet2` (`NYGC`), `Hartwig SAGE` (`2026`), `Ultima DeepVariant Somatic`, `Mutect2`, `Strelka2`, and `LoFreq` across full-genome (`All` and excluding genomic instability regions [`NoGI`]) and target-slice scopes. On full-genome HG008 `v0.4` (`All`), `VarDictRust` achieved `40.11%` somatic indel sensitivity (`Indel` $F_1 = 0.4898$, `SNV` $F_1 = 0.7886$; `48.32%` indel recall and `Indel` $F_1 = 0.5616$, `SNV` $F_1 = 0.8028$ excluding genomic instability regions), outperforming the deep-learning and local-assembly callers `ClairS v0.4.1` (`13.02%` indel recall, $F_1 = 0.2298$), `DeepSomatic v1.6.0` (`18.45%` indel recall, $F_1 = 0.3072$), `Lancet2` (`21.79%` indel recall, $F_1 = 0.3568$), and `Ultima DeepVariant Somatic` (`24.59%` indel recall, $F_1 = 0.3900$) in somatic indel recall, while approaching commercial `DRAGEN v4.2.4 Graph` (`43.23%` indel recall) without proprietary FPGA hardware or GPU accelerators.
- **Controlled *in silico* Tumor-Purity Titration (`20%` down to `1%` Purity / `10.0% to 0.5%` VAF; `Table 3`, `Figure 3d`):** When we titrated HG008 tumor reads into matched normal reads across five purity levels (`20%`, `10%`, `5%`, `2%`, and `1%`, corresponding to expected heterozygous somatic VAFs of `10.0%`, `5.0%`, `2.5%`, `1.0%`, and `0.5%`) at `-f 0.002`, `VarDictRust` and `VarDictJava` matched identically at every purity point while `VarDictRust` ran `7.6×–7.7×` faster (`8.53–8.76` s vs `65.16–66.76` s) at `14.7×–16.5×` lower RSS (`780,628–859,564` KB vs `12,316,396–13,765,960` KB). At `5%` purity (`2.5%` VAF), `VarDictRust` recovered `36.80%` of somatic SNVs ($F_1 = 0.4215$) and `10.54%` of indels ($F_1 = 0.1422$), compared to `18.91%` SNVs for `Strelka2`, `9.88%` for `Mutect2`, and `0.51%` for `LoFreq`. At `1%` purity (`0.5%` VAF), `VarDictRust` maintained `4.26%` SNV recall ($F_1 = 0.0569$)—a `25.1`× higher recall and `16.7`× higher F_1 than `Mutect2` (`0.17%` recall, $F_1 = 0.0034$) and `Strelka2` (`0.17%`).
- **Supply-Chain Hardening and `vardictcpp` Divergence Audit (`Table 8`, `Figure 8`, `Supplementary Table S6`):** Compiling `VarDictRust` to a single `4.56` MB statically linked Linux binary (`4.46` MB dynamic `glibc`) eliminates `102` runtime Conda packages (`OpenJDK`, `R`, `Perl`) required by `VarDictJava`, while resolving all ten functional and statistical divergences in `vardictcpp` (`Table 8`; `Supplementary Table S6`).




Figure 8. Software supply-chain footprint, multi-thread output determinism, and empirical variant discrepancies in `vardictcpp`. (a) Deployment artifact footprint (`4.46` MiB `glibc`, `4.56` MiB static `musl`, `0` runtime packages, `0` CVEs, SLSA Level 3) versus `VarDictJava` (`102` Conda packages) and `vardictcpp` (`Table 8`). **(b)** Multi-thread output determinism across `1`, `2`, `4`, `8`, `16`, and `32` threads on the SEQC2 HCC1395 whole exome (`120,307` emitted variants at every thread count, `0` diffs vs `VarDictJava`; `Table 4`). **(c)** Empirical variant-count discrepancies in `vardictcpp` relative to the `VarDictJava` oracle across unchunked (`+309,569` `50` kbp chunk-boundary duplicates) and pre-chunked (`394` MNP/tie-break divergences) HG002 WGS, HG002 chromosome 20, SEQC2 somatic exome, and HG008 somatic slice (`Table 5`, `Table 8`, `Supplementary Table S6`).

Table 8. Supply-Chain Security, Static musl Binary Equivalence, Functional Coverage & Divergence Summary

Engineering & Security Dimension	VarDictJava v1.8.3 [1] (0886261)	vardictcpp [11] (ae93fe39dc)	VarDictRust v1.0.6 (5865a2a0b24a8c17)[e]
Upstream Repository Maintenance Status	Archived Read-Only (EOL)[a]	Preprint Prototype (10 Divergences)[b]	Actively Maintained (MIT, v1.0.6)[a,e]
Runtime Dependency & Binary Footprint	JVM + R + Perl (102 Conda packages)[c]	C++17 + HTSlib [26] dynamic libraries	4.46 MiB GNU / 4.56 MiB Static musl (statically linked)[d]
Supply-Chain Attestation & Vulnerability Audit	Unpinned ecosystem dependencies[c]	No SLSA provenance	SLSA Level 3 + 0 RustSec CVEs[d]
13-Mode Functional Coverage & CRAM Support	12/13 (CRAM fails without htsjdk classpath)[c]	12/13 .var (simple_fisher FP=1, FN=1; Amplicon VCF & Splice -i unsupported)[b]	13/13 Modes (100% Exact Match)[d]
Empirical Divergence Classes vs. Oracle	Reference Oracle (Baseline)[a]	10 Cataloged Divergence Classes (CPP-1 to CPP-10)[b]	0 Divergences on Valid Inputs (#![forbid(unsafe_code)])[a,e]

[a]VarDictJava v1.8.3 [1] (commit 0886261; Perl/R submodule 009e017) is archived read-only; VarDictRust v1.0.6 preserves 100% valid-input output equivalence while eliminating >30 upstream crash, OOM, CRAM, and header defects (issues #7, #38, #181, #187, #197, #243, #249, #253, #282, #283, #320, #341, #356, #380, #384) by enforcing #![forbid(unsafe_code)] and checked bounds arithmetic. [b]On the 13-mode .var functional suite, vardictcpp [11] matches VarDictJava on 12/13 modes (diverging on simple_fisher with FP=1, FN=1) and additionally lacks amplicon VCF formatting (CPP-3) and RNA-seq -i splice support (CPP-10), while emitting +309,569 chunk-boundary duplicates on unchunked HG002 WGS (CPP-5; full CPP-1 to CPP-10 taxonomy in Supplementary Table S6). [c]The pinned Bioconda VarDictJava environment requires 102 runtime packages across OpenJDK, R, and Perl and fails with NoClassDefFoundError on CRAM inputs unless external htsjdk jars are injected. [d]VarDictRust compiles to a single 4.56 MiB statically linked x86_64-unknown-linux-musl binary (statically linked) with native pure-Rust BAM/CRAM decoding (noodles), 0 RustSec advisories, and automated SLSA Level 3 build provenance. [e]Hash 5865a2a0b24a8c17 denotes the certified VarDictRust v1.0.6 engine source fingerprint; under the project release governance, v1.0.x guarantees exact valid-input parity with VarDictJava v1.8.3, while opt-in biological output corrections ship behind explicit --fix flags in v1.1+.

Discussion

Scientific Software Consolidation Under the `rewrites.bio` Specification

A recurring tension in bioinformatics software engineering is the trade-off between computational performance and clinical backward compatibility. When a widely deployed variant caller is rewritten for speed, subtle changes in Smith-Waterman tie-breaking, read-quality Phred offsetting, floating-point rounding, or strand-bias p-value calculation frequently alter downstream clinical callsets, forcing diagnostic laboratories through costly re-validation cycles. Conversely, line-by-line transliterations preserve bugs and memory anti-patterns. By adhering to the rewrites.bio methodology—separating **v1.0.x oracle parity and memory/crash robustness** from **post-1.0 opt-in algorithmic corrections (`--fix <id>`)**— `VarDictRust` resolves this tension. In default mode (`v1.0.6`), `VarDictRust` reproduces the exact allele calls, `FILTER` flags, somatic `STATUS` classifications, and `HALF_EVEN`-rounded Fisher exact statistics of `VarDictJava v1.8.3 (0886261)` (`Table 1`, `Supplementary Table S2`), while eliminating JVM `OutOfMemoryError` crashes, `CigarModifier` index-out-of-bounds panics (`#![forbid(unsafe_code)]`), and `java.util.HashMap` output-order non-determinism (`#282`). Known upstream output-affecting quirks in `VarDictJava` (such as `VD > DP` under complex realignment `#92`, aggressive `NM` filtering `#62`, `SHIFT3` coordinate shifts `#292`, and `<dup-N>` symbolic allele naming `#342`) are meticulously documented and deferred to post-1.0 opt-in `--fix` flags with strict diff-confinement gates.

Why Bounded Tile-Plus-Halo Streaming Matters for Next-Generation T2T-Q100 and Clinical Genomics

Our unchunked full-chromosome versus pre-chunked callable-interval whole-genome experiments (`Table 5`, `Table 7`, `Figure 5`, `Figure 7`) highlight an underappreciated consequence of memory-unbounded bioinformatics tools: **software memory limits silently dictate biological discovery masks**. Because `VarDictJava` allocates pileup state across an entire BED interval before variant emission, whole-genome users have historically been forced to restrict calling to pre-chunked `≤50` kbp BED masks (`GIAB v4.2.1`, `2.51` Gbp) or external `50` kbp BED-splitting wrappers. While `vardictcpp` accelerates pre-chunked exomes, it retains whole-interval memory allocation (`10.58` GiB on `chr1`, `31.91` GB on unchunked HG002 WGS, and `91.85` GB with a `3`-hour timeout on unchunked HG008 WGS). By keeping intervals ≤ *1,000,000* bp untiled and auto-partitioning spans > *1,000,000* bp into `100` kbp tiles with a `10` kbp realignment halo and deterministic boundary deduplication (`Table 1`), `VarDictRust` processes unchunked full chromosomes in `4.93` – `12.14` GB RAM, unlocking `+0.23` Gbp of newly resolved `NIST GIAB v5.0q T2T-Q100` sequence (`+5.01%` SNV recall, `+17.26%` indel recall) and `+17.47%` SNV / `+27.98%` indel recall across the `273` `NIST CMRG v1.00` genes (`Table 7`).

Positioning Relative to Modern Deep-Learning and Commercial Somatic Callers and Throughput Trade-Offs

Our `11`-caller evaluation on `NIST GIAB HG008 v0.4` (`Table 7`, `Figure 7c`) clarifies the complementary strengths of heuristic pileup/realignment callers versus modern deep-learning (`DeepSomatic`, `ClairS`, `Ultima DeepVariant Somatic`), graph/local-assembly (`DRAGEN`, `Lancet2`, `Octopus`), and tumor-normal haplotype callers (`Hartwig SAGE`, `Mutect2`, `Strelka2`). At standard `364` × tumor-normal WGS depth, deep-learning and graph callers achieve higher SNV precision in repetitive genomic contexts. However, `VarDictRust` achieves higher somatic indel sensitivity (`40.11%` genome-wide, `48.32%` excluding genomic instability regions) than `ClairS` (`13.02%`), `DeepSomatic` (`18.45%`), `Lancet2` (`21.79%`), and `Ultima DeepVariant Somatic` (`24.59%`), while at `0.5%` VAF (`1%` tumor purity) in

our *in silico* titration (`Table 3` , `Figure 3d`), `VarDictRust` retains `4.26%` SNV sensitivity (`25.1` × higher than `Mutect2` and `Strelka2`). Moreover, `VarDictRust` runs purely on commodity CPUs in a single `4.56` MB binary without GPU or FPGA dependencies. On pre-chunked `773,667` -interval BED files (`SRR8657348` at `8` threads), `vardictcpp` achieves slightly lower raw `.var` wall time (`24.68` s vs `39.63` s for `VarDictRust`) because `vardictcpp` skips structural variant assembly (`--nosv` forced) and omits `##contig` and `INFO/END` VCF schema validation (`Table 8` ; `Supplementary Table S6`), whereas on unchunked chromosomes (`-R chr1`) and deep chromosome 20 runs where `VarDictJava` suffers `9/20` wall-clock timeouts, `VarDictRust` completes `100%` of runs with full SV and VCF emission.

Limitations, Boundary Conditions, and Post-1.0 Governance

Three operational boundary conditions merit explicit consideration by pipeline architects:

1. **Multi-Megabase Single-Region Calling (`--tile-size` vs. Bounded `100` kbp Auto-Tiling):** Across our `87` -configuration multi-regime intermediate (`.var`) and VCF equivalence sweep, `VarDictRust` achieves `87/87` (`100.00%` , `95%` CI `95.85%–100.00%`) exact parity against `VarDictJava` (`Table 1` , `Supplementary Table S2`). Intervals ≤ *1,000,000* bp run untiled by default; for unchunked > *1,000,000* bp single-interval queries, default `100` kbp auto-tiling bounds memory to `318.6` MB on whole-chromosome `-R chr1:1-249250621` (`Table 2`) and isolates tile state against `VarDictJava` 's cross-centromere `36` – `81` Mbp SV pairing and `VD = 74 > DP` state leak (`#92`), while passing `--tile-size` matching the region span (`--tile-size 10000000` on `10` Mbp `chr1` `-f 0` and `--tile-size 250000000` on `249.25` Mbp `-R chr1`) reproduces `VarDictJava` 's monolithic single-region output byte-for-byte (`7,077` `.var` / `7,032` `.vcf` and `4,705` `.var` rows, respectively).
2. **`QUAL` Stratification on Standard-Depth Germline WGS:** Because `VarDict` 's default `-f 0.01` threshold is tuned for low-VAF somatic discovery, unfiltered `PASS` callsets on `35` ×– `60` × germline WGS include low-VAF candidate calls (`HG002` unfiltered $F_1 = 0.6622$). Downstream germline workflows should apply `QUAL >= 128.000` (`F1 = 0.9699` , eliminating `97.5%` of false positives; `Table 3` , `Supplementary Table S4`) or raise `-f` to `0.10` – `0.20` .
3. **Strict `v1.0.x` Bug-for-Bug Parity Policy:** Under our release governance policy, all `v1.0.x` releases replicate upstream `VarDictJava` v1.8.3 output quirks on valid inputs (`#62` , `#92` , `#292` , `#342`) so clinical pipelines can migrate as a zero-diff drop-in replacement before enabling opt-in `--fix <id>` corrections in `v1.1+` .

Conclusions

`VarDictRust` (`v1.0.6`) consolidates the three-language `VarDictJava -> R -> Perl` variant-calling pipeline into a single, memory-safe, statically compiled Rust binary that preserves exact numerical and allele equivalence (`ε = 1e-6`) with `VarDictJava v1.8.3 (0886261)` across all `13` operational modes, `10` short-read sequencing chemistries, and `70` GA4GH `v3.5` genomic strata. By bounding memory to `O(tile + halo)` and accelerating execution by up to `51.5` × on contiguous chromosomes (`342.2` × lower RSS) and `29.3` × on `32` -core whole exomes (`29.8` × lower RSS), `VarDictRust` eliminates whole-genome out-of-memory failures and unlocks full-contig variant discovery across next-generation `T2T-Q100` and clinical `CMRG` benchmarks.

Methods

Consolidated Rust Architecture and Coordinate Type Safety

`VarDictRust` is implemented as a two-crate Rust workspace: `vardictrust-core` (the library engine, compiled with `#![forbid(unsafe_code)]` and zero `unwrap()` / `expect()` / `panic!()` calls outside unit tests) and `vardictrust` (the `clap` command-line interface, compatible with all `VarDictJava` v1.8.3 CLI flags). To prevent off-by-one coordinate defects between `0` -based half-open BAM/CRAM coordinates (`noodles`) and `1` -based inclusive VCF/VarDict internal coordinates, the type system enforces distinct `Pos0` and `Pos1` newtypes with explicit `.to_one_based()` and `.to_zero_based()` conversions. Sequence reads and reference slices are processed as raw byte slices (`&[u8]`) with Phred+33 saturation arithmetic (`Phred(byte.saturating_sub(33))`).

Bounded Tile-Plus-Halo Streaming and Deterministic Realignment

When given a BED interval or `-R` region ≤ *1,000,000* bp, `VarDictRust` processes the interval as a single untiled window; when an interval exceeds `1,000,000` bp (or when `--tile-size` is explicitly specified), `VarDictRust` partitions the interval into non-overlapping ownership tiles $[T_k^{\text{start}}, T_k^{\text{end}})$ of default width `100` kbp padded on both sides by a `10` kbp realignment halo (`200` kbp in `-i` splice mode; `Figure 1b`). Each tile is dispatched to a `Rayon` work-stealing thread pool, which streams alignments overlapping $[T_k^{\text{start}} - H, T_k^{\text{end}} + H)$ via `noodles` (supporting multi-threaded BGZF BAM and reference-decoded CRAM `-G`), performs read-level CIGAR modification (`cigar/modify.rs`), pileup accumulation (`cigar/parse.rs`), local indel/soft-clip realignment (`realign.rs`), structural variant assembly (`sv.rs`), and variant finalization (`tovars.rs`), and emits only variants whose canonical `Pos1` start coordinate falls within $[T_k^{\text{start}}, T_k^{\text{end}})$. All per-tile pileup maps

are dropped immediately upon tile completion (RAII), bounding peak heap memory to active tiles in flight. Where `VarDictJava`'s output depends on `java.util.HashMap` bucket iteration order (`#282`), `VarDictRust` emulates exact JDK8 `HashMap` hash-spread, bin, resize, and treeify semantics via a verified `JavaHashMap` container, while using `IndexMap` (`LinkedHashMap`) and `BTreeMap` (`TreeMap`) everywhere else.

In-Process Statistical Post-Processing and Banker's Rounding (`HALF_EVEN`)

To eliminate the external R (`teststrandbias.R` / `testsomatic.R`) and Perl (`var2vcf_valid.pl` / `var2vcf_paired.pl`) processes, `VarDictRust` implements hypergeometric Fisher exact two-sided p-value and conditional maximum-likelihood odds-ratio (`uniroot` zero-in with tolerance ulp$(1)^{0.25}$) computation directly in Rust (`stats/fisher.rs`), followed by native VCF 4.3 formatting (`output/`). Every floating-point metric (`AF`, `AdjAF`, `HIAF`, `SBF`, `ODDRATIO`, `SSF`, `MSI`, `QUAL`) passes through IEEE 754 round-half-to-even (`round_half_even` to 5 decimal places) matching R's `round(x, 5)` and Java's `DecimalFormat` (`HALF_EVEN`), reproducing both the no-`--fisher` trailing-zero format and the `--fisher` stripped-zero format within `ε = 1e-6` (`10^{-6}`).

Cloud Benchmarking Infrastructure, Reproducibility Protocol, and Statistical Analysis

All `60` benchmark evaluations were executed on Google Cloud Platform (`GCP n2-standard-32 (Intel Xeon Platinum 8373C Ice Lake, 32 vCPUs, 128 GiB RAM, 4x375 GB NVMe RAID0)`; `1.5` TB local NVMe RAID0 scratch; full command-line recipes and SHA-256 provenance manifests in `Supplementary Methods` and `Supplementary Table S1`). Each timing experiment was run with `n = 3` independent technical replicates wrapped in `/usr/bin/time -v` to record wall-clock elapsed seconds and peak `Maximum resident set size (kbytes)`. Binary concordance proportions are reported with exact Clopper-Pearson `95%` binomial confidence intervals ($\alpha = 0.05$). Non-parametric runtime and memory comparisons across the `12` AML panel configurations were evaluated using two-sided Mann-Whitney U tests and exact paired sign-flip permutation tests (2^{-12}). Variant truth evaluation was performed using `rtg vcfeval` (`v3.12.1`) with official NIST GIAB high-confidence BED masks (`HG002 v4.2.1`, `HG002 v5.0q T2T-Q100`, `CMRG v1.00`, `Mosaic v1.10`, `HG005 v4.2.1`, `SEQC2 v1.2.1`, and `HG008 v0.3`/`v0.4` including `7` modern deep-learning and commercial caller VCFs). Controlled *in silico* tumor-purity titrations (`20%`, `10%`, `5%`, `2%`, `1%`) were generated by deterministic seed-controlled `samtools view -s` subsampling and merging of HG008 tumor and matched normal BAMs (`Supplementary Methods`).

A canonical end-to-end single-command invocation of `VarDictRust` (replacing the 3-process `VarDictJava | teststrandbias.R | var2vcf_valid.pl` pipeline) is:

```
# Single-binary VarDictRust GERMLINE/SOMATIC calling with native Fisher exact test & VCF emission:
vardictrust -G GRCh38.fa -f 0.01 -N "TUMOR|NORMAL" \
  -b "tumor.bam|normal.bam" -th 32 --fisher -z -c 1 -S 2 -E 3 -g 4 \
  --vcf -A -E-filter 0.05 -P 0 target.bed > calls.vcf
```

Declarations

Ethics approval and consent to participate

Not applicable. All sequencing datasets analyzed in this study are publicly available, open-access reference materials from the NIST Genome in a Bottle (GIAB) Consortium (`HG002`, `HG005`, `HG008`), the FDA SEQC2 Consortium (`HCC1395`/`HCC1395BL`), and the NCBI Sequence Read Archive (`PRJNA744870` / `PRJNA523380`).

Consent for publication

Not applicable.

Availability of data and materials

- **Source Code and Binary Releases:** `VarDictRust` (`v1.0.6`, MIT License) is openly available at https://github.com/rewrites-bio/VarDictRust, with pre-compiled SLSA Level 3 static Linux binaries, Crates.io packages (`vardictrust` and `vardictrust-core`), Bioconda recipes, and `nf-core` modules.
- **Reproducible Benchmark Evidence and Manuscript Compiler:** All `60` benchmark summaries, SHA-256 provenance manifests, exact CLI scripts, `benchmarks/gcp-study-v106/master_gcp_metrics.json`, `benchmarks/gcp-study-v106/cells_60_inventory.tsv`, `paper/build_figures_and_tables.py`, and `paper/build_manuscript.py` are tracked in the repository and archived in `Supplementary Tables S1–S6` in the Supplementary Material.
- **Public Accession Numbers:** Wolff et al. [11] AML panel BAMs: NCBI SRA `SRR15006375`, `SRR15006376`, `SRR15006386`, `SRR15006540` (`PRJNA744870`), and `SRR8657348` (`PRJNA523380`). NIST GIAB reference datasets (`HG002 v4.2.1`/`v5.0q T2T-`

`Q100` / `CMRG v1.00` / `Mosaic v1.10`, `HG005`, and `HG008` `v0.3` / `v0.4` somatic callsets): `https://ftp-trace.ncbi.nlm.nih.gov/ReferenceSamples/giab/`. SEQC2 `HCC1395` / `HCC1395BL` (`v1.2.1`): `PRJNA506071`.

Competing interests

The author declares no competing financial or non-financial interests.

Funding

Cloud compute on Google Cloud Platform was self-funded under the open-source rewrites.bio initiative.

Authors' contributions (CRediT)

Palak Sheth: Conceptualization, Methodology, Software, Validation, Formal Analysis, Investigation, Resources, Data Curation, Writing – Original Draft, Writing – Review & Editing, Visualization, Project Administration. AI pair-programming assistance (`Claude` / `Gemini`) was used under human verification and strict automated differential oracle-testing gates in accordance with the rewrites.bio transparency commitment.

Acknowledgements

We thank Zhongwu Lai, Aleksandra Markovets, and the AstraZeneca-NGS team for creating and open-sourcing `VarDict` and `VarDictJava`, the NIST Genome in a Bottle Consortium and FDA SEQC2 Consortium for public truth benchmarks, and Lukas Wolff et al. for open-sourcing `vardictcpp`.

References

1. Lai Z, Markovets A, Ahdesmaki M, Chapman B, Hofmann O, McEwen R, et al. VarDict: a novel and versatile variant caller for next-generation sequencing in cancer research. *Nucleic Acids Res.* 2016;44(11):e108. doi:10.1093/nar/gkw227.
2. Koboldt DC. Best practices for variant calling in clinical sequencing. *Genome Med.* 2020;12(1):91. doi:10.1186/s13073-020-00791-w.
3. Garrison E, Marth G. Haplotype-based variant detection from short-read sequencing. *arXiv* [Preprint]. 2012;arXiv:1207.3907.
4. Kim S, Scheffler K, Halpern AL, Bekritsky MA, Noh E, Källberg M, et al. Strelka2: fast and accurate calling of germline and somatic variants. *Nat Methods.* 2018;15(8):591–4. doi:10.1038/s41592-018-0051-x.
5. Cooke DP, Wedge DC, Lunter G. A unified haplotype-based method for accurate and comprehensive variant calling. *Nat Biotechnol.* 2021;39(7):885–92. doi:10.1038/s41587-021-00861-3.
6. Poplin R, Chang PC, Alexander D, Schwartz S, Colthurst T, Ku A, et al. A universal SNP and small-indel variant caller using deep neural networks. *Nat Biotechnol.* 2018;36(10):983–7. doi:10.1038/nbt.4235.
7. Wilm A, Aw PPK, Bertrand D, Yeo GHT, Ong SH, Wong CH, et al. LoFreq: a sequence-quality aware, ultra-sensitive variant caller for uncovering cell-population heterogeneity from high-throughput sequencing datasets. *Nucleic Acids Res.* 2012;40(22):11189–201. doi:10.1093/nar/gks918.
8. Benjamin D, Sato T, Cibulskis K, Getz G, Stewart C, Lichtenstein L. Calling somatic SNVs and indels with Mutect2. *bioRxiv* [Preprint]. 2019;doi:10.1101/861054.
9. Garcia M, Juhos S, Larsson M, Olason PI, Martin M, Eisfeldt J, et al. Sarek: a portable workflow for whole-genome sequencing analysis of germline and somatic variants. *F1000Research.* 2020;9:63. doi:10.12688/f1000research.16665.2.
10. Fang LT, Zhu B, Zhao Y, Chen W, Yang Z, Kerrigan L, et al. Establishing community reference samples, data and call sets for benchmarking cancer mutation detection using whole-genome sequencing. *Nat Biotechnol.* 2021;39(9):1151–60. doi:10.1038/s41587-021-00993-6.
11. Wolff L, et al. vardictcpp: a high-performance C++ reimplementation of VarDict. *Bioinformatics.* 2026;42(2):btag042. doi:10.1093/bioinformatics/btag042.
12. Cleary JG, Braithwaite R, Gaastra K, Hilbush BS, Inglis S, Irvine SA, et al. Comparing variant call files for performance benchmarking of next-generation sequencing variant calling pipelines. *bioRxiv* [Preprint]. 2015;doi:10.1101/023754.
13. Wagner J, Olson ND, Harris L, Khan Z, Farek J, Mahmoud M, et al. Benchmarking challenging small variants with linked and long reads. *Cell Genomics.* 2022;2(5):100128. doi:10.1016/j.xgen.2022.100128.
14. Rhie A, Nurk S, Cechova M, Hoyt SJ, Taylor DJ, Altemose N, et al. The complete sequence of a human Y chromosome. *Nature.* 2023;621(7978):344–54. doi:10.1038/s41586-023-06457-y.
15. Wagner J, Olson ND, Harris L, Khan Z, Farek J, Mahmoud M, et al. Curated variation benchmarks for challenging medically relevant autosomal genes. *Nat Biotechnol.* 2022;40(5):672–80. doi:10.1038/s41587-021-01158-1.

16. Nurk S, Koren S, Rhie A, Rautiainen M, Bzikadze AV, Mikheenko A, et al. The complete sequence of a human genome. *Science.* 2022;376(6588):44–53. doi:10.1126/science.abj6987.
17. Krusche P, Trigg L, Boutros PC, Mason CE, De La Vega FM, Moore BL, et al. Best practices for benchmarking germline small-variant calls in human genomes. *Nat Biotechnol.* 2019;37(5):555–60. doi:10.1038/s41587-019-0054-x.
18. Zook JM, Catoe D, McDaniel J, Vang L, Spies N, Sidow A, et al. Extensive sequencing of seven human genomes to characterize benchmark reference materials. *Sci Data.* 2016;3:160025. doi:10.1038/sdata.2016.25.
19. McDaniel J, Olson ND, Wagner J, et al. Authoritative characterization of somatic variation in the pancreatic ductal adenocarcinoma reference cell line HG008. *NIST Genome in a Bottle Consortium Technical Report.* 2025;v0.4.
20. Daniels C, et al. Comprehensive evaluation of germline variant callers on human chromosome 20 exome sequencing benchmarks. *Brief Bioinform.* 2024;25(3):bbae142.
21. Behera S, Catreux S, Rossi M, Truong S, Huang Z, Ruehle M, et al. Comprehensive genome analysis and variant detection at scale using DRAGEN. *Nat Biotechnol.* 2024;43:1177–89. doi:10.1038/s41587-024-02382-1.
22. Park J, Cook DE, Chang PC, Kolesnikov A, Brambrink L, Miga KH, et al. DeepSomatic: accurate somatic small variant discovery for multiple sequencing technologies. *bioRxiv* [Preprint]. 2024;doi:10.1101/2024.08.16.608331.
23. Zheng Z, Su J, Chen L, Lee Yan V, Lam TW, Luo R. ClairS: a deep-learning method for long-read somatic small variant calling. *bioRxiv* [Preprint]. 2023;doi:10.1101/2023.08.17.553778.
24. Narzisi G, Corvelo A, Arora K, Bergmann EA, Shah M, Musunuri R, et al. Genome-wide somatic variant calling using localized colored de Bruijn graphs. *Commun Biol.* 2018;1:20. doi:10.1038/s42003-018-0023-9.
25. Priestley P, Baber J, Lolkema MP, Steeghs N, de Bruijn E, Shale C, et al. Pan-cancer whole-genome analyses of metastatic solid tumours. *Nature.* 2019;575(7781):210–6. doi:10.1038/s41586-019-1689-y.
26. Danecek P, Bonfield JK, Liddle J, Marshall J, Ohan V, Pollard MO, et al. Twelve years of SAMtools and BCFtools. *GigaScience.* 2021;10(2):giab008. doi:10.1093/gigascience/giab008.