

PRACTICAL WEEK-9

NAME:CH.SAI VIHAMSH

ROLL:2520090090

SESSION-9

Task1: Implement a file copy utility using low-level Linux file I/O system calls (open, read, write, lseek, close). Compare its performance with standard library functions (fopen, fread, fwrite).

```
saivihamsh@Varshini-PC: ~/practical$ mkdir -p week9/task1
saivihamsh@Varshini-PC: ~/practical$ cd week9/task1
saivihamsh@Varshini-PC: ~/practical/week9/task1$ nano file_copy.c
saivihamsh@Varshini-PC: ~/practical/week9/task1$ echo "This is the source
file for Week-9 Practical Task 1." > source.txt
saivihamsh@Varshini-PC: ~/practical/week9/task1$ cat source.txt
This is the source file for Week-9 Practical Task 1.
saivihamsh@Varshini-PC: ~/practical/week9/task1$ gcc file_copy.c -o T1
saivihamsh@Varshini-PC: ~/practical/week9/task1$ ./T1
=== Week-9 Practical: File Copy Performance ===

1. Low-level Linux file I/O
Low-level copy completed.
Time: 0.000138 seconds

2. Standard library file I/O
Standard library copy completed.
Time: 0.000052 seconds

File copy comparison completed successfully.
saivihamsh@Varshini-PC: ~/practical/week9/task1$ cat low_level_copy.txt
This is the source file for Week-9 Practical Task 1.
saivihamsh@Varshini-PC: ~/practical/week9/task1$ cat standard_copy.txt
This is the source file for Week-9 Practical Task 1.
saivihamsh@Varshini-PC: ~/practical/week9/task1$ cmp source.txt low_level_
copy.txt
saivihamsh@Varshini-PC: ~/practical/week9/task1$ cmp source.txt standard_c
opy.txt
saivihamsh@Varshini-PC: ~/practical/week9/task1$ ./T1
=== Week-9 Practical: File Copy Performance ===

1. Low-level Linux file I/O
Low-level copy completed.
Time: 0.000113 seconds

2. Standard library file I/O
Standard library copy completed.
Time: 0.000025 seconds

File copy comparison completed successfully.
saivihamsh@Varshini-PC: ~/practical/week9/task1$
```

```
GNU nano 8.7.1 file_copy.c *
#include <stdio.h>
#include <stdlib.h>
#include <fcntl.h>
#include <unistd.h>
#include <time.h>

#define BUFFER_SIZE 4096

double get_time(void)
{
    struct timespec ts;
    clock_gettime(CLOCK_MONOTONIC, &ts);
    return ts.tv_sec + ts.tv_nsec / 1e9;
}

/* Low-level file copy using open, read, write, lseek, close */
void low_level_copy(const char *source, const char *destination)
{
    int src, dest;
    char buffer[BUFFER_SIZE];
    ssize_t bytes_read;

    src = open(source, O_RDONLY);
    if (src == -1) {
        perror("open source");
        exit(EXIT_FAILURE);
    }

    dest = open(destination, O_WRONLY | O_CREAT | O_TRUNC, 0644);
    if (dest == -1) {
        perror("open destination");
        close(src);
        exit(EXIT_FAILURE);
    }

    while ((bytes_read = read(src, buffer, BUFFER_SIZE)) > 0) {
        if (write(dest, buffer, bytes_read) != bytes_read) {
            perror("write");
            close(src);
            close(dest);
            exit(EXIT_FAILURE);
        }
    }

    close(src);
    close(dest);
}

int main(void)
{
    const char *source = "source.txt";
    double start, end;

    printf("=== Week-9 Practical: File Copy Performance ===\n\n");

    printf("1. Low-level Linux file I/O\n");
    start = get_time();
    low_level_copy(source, "low_level_copy.txt");
    end = get_time();

    printf("Low-level copy completed.\n");
    printf("Time: %.6f seconds\n\n", end - start);

    printf("2. Standard library file I/O\n");
    start = get_time();
    standard_copy(source, "standard_copy.txt");
    end = get_time();

    printf("Standard library copy completed.\n");
    printf("Time: %.6f seconds\n\n", end - start);

    printf("File copy comparison completed successfully.\n");

    return 0;
}
```

^G Help ^O Write Out ^F Where Is ^K Cut ^T Execute
^X Exit ^R Read File ^\ Replace ^U Paste ^J Justify

```
GNU nano 8.7.1 file_copy.c *
    exit(EXIT_FAILURE);
}

fclose(src);
fclose(dest);
}

int main(void)
{
    const char *source = "source.txt";
    double start, end;

    printf("=== Week-9 Practical: File Copy Performance ===\n\n");

    printf("1. Low-level Linux file I/O\n");
    start = get_time();
    low_level_copy(source, "low_level_copy.txt");
    end = get_time();

    printf("Low-level copy completed.\n");
    printf("Time: %.6f seconds\n\n", end - start);

    printf("2. Standard library file I/O\n");
    start = get_time();
    standard_copy(source, "standard_copy.txt");
    end = get_time();

    printf("Standard library copy completed.\n");
    printf("Time: %.6f seconds\n\n", end - start);

    printf("File copy comparison completed successfully.\n");

    return 0;
}
```

^G Help ^O Write Out ^F Where Is ^K Cut ^T Execute
^X Exit ^R Read File ^\ Replace ^U Paste ^J Justify

Observation: The file copy utility was successfully implemented using low-level Linux system calls such as `open()`, `read()`, `write()`, `lseek()`, and `close()`. The same file was also copied using standard library functions `fopen()`, `fread()`, and `fwrite()`. Both methods successfully created identical copies of the source file. The execution time of both methods was measured and compared successfully.

Task2: Develop a program that redirects standard input and standard output using file descriptors and `dup2()`. Demonstrate how shells implement I/O redirection.

```
saiviamsh@Varshini-PC: ~/practical/week9/task1$ cd ~/practical/week9
saiviamsh@Varshini-PC: ~/practical/week9$ mkdir -p task2
saiviamsh@Varshini-PC: ~/practical/week9$ cd task2
saiviamsh@Varshini-PC: ~/practical/week9/task2$ nano io_redirect.c
saiviamsh@Varshini-PC: ~/practical/week9/task2$ echo "This is the input data for Task 2." > input.txt
saiviamsh@Varshini-PC: ~/practical/week9/task2$ cat input.txt
This is the input data for Task 2.
saiviamsh@Varshini-PC: ~/practical/week9/task2$ gcc io_redirect.c -o T2
saiviamsh@Varshini-PC: ~/practical/week9/task2$ ./T2
saiviamsh@Varshini-PC: ~/practical/week9/task2$ cat output.txt
Standard input and output redirected successfully.
This output is written to output.txt.
saiviamsh@Varshini-PC: ~/practical/week9/task2$ ls -l
total 28
-rwxr-xr-x 1 madhulika madhulika 16128 Sep 26 03:50 T2
-rw-r--r-- 1 madhulika madhulika   35 Sep 26 03:50 input.txt
-rw-r--r-- 1 madhulika madhulika  828 Sep 26 03:49 io_redirect.c
-rw-r--r-- 1 madhulika madhulika   89 Sep 26 03:50 output.txt
saiviamsh@Varshini-PC: ~/practical/week9/task2$ cat input.txt
This is the input data for Task 2.
saiviamsh@Varshini-PC: ~/practical/week9/task2$ cat output.txt
Standard input and output redirected successfully.
This output is written to output.txt.
saiviamsh@Varshini-PC: ~/practical/week9/task2$ ./T2
saiviamsh@Varshini-PC: ~/practical/week9/task2$ cat output.txt
Standard input and output redirected successfully.
This output is written to output.txt.
saiviamsh@Varshini-PC: ~/practical/week9/task2$
```

```
GNU nano 8.7.1 io_redirect.c *
#include <stdio.h>
#include <stdlib.h>
#include <fcntl.h>
#include <unistd.h>

int main(void)
{
    int input_fd, output_fd;

    input_fd = open("input.txt", O_RDONLY);
    if (input_fd == -1) {
        perror("open input.txt");
        return 1;
    }

    output_fd = open("output.txt", O_WRONLY | O_CREAT | O_TRUNC, 0644);
    if (output_fd == -1) {
        perror("open output.txt");
        close(input_fd);
        return 1;
    }

    if (dup2(input_fd, STDIN_FILENO) == -1) {
        perror("dup2 stdin");
        return 1;
    }

    if (dup2(output_fd, STDOUT_FILENO) == -1) {
        perror("dup2 stdout");
        return 1;
    }

    close(input_fd);
    close(output_fd);

    printf("Standard input and output redirected successfully.\n");
    printf("This output is written to output.txt.\n");
}
```

^G Help	^O Write Out	^F Where Is	^K Cut	^T Execute
^X Exit	^R Read File	^I Replace	^U Paste	^J Justify

Observation: The program successfully demonstrated standard input and output redirection using file descriptors and the dup2() system call. The input file was opened for reading and the output file was created for writing. The standard input and standard output file descriptors were redirected to these files, and the program output was successfully stored in output.txt.