



**PARTICLE  
MEASURING  
SYSTEMS\***  
a spectris company

5475 Airport Boulevard, Boulder, Colorado 80301-2339  
303.443.7100 800.238.1801

## Certificate of Calibration

Date: Aug-01-2024 12:58:29

Work Order: QTS/PO/INST/24-25/039  
Customer Name: Quality Technical Solutions  
Customer Address: PAP-R-289, Near Golden Garage, Rabale Midc, Navi Mumbai 400701,  
Calibration Lab: Aimil Mumbai  
Service Notes: PMS/MUM/24-25/25(QTS/HVAC/PC-18)

### Unit Under Test

Instrument: LasairIII\_5100 Serial Number: 140385  
Firmware Version: PCE: B2B53624 1.9 Calibration Due: Aug-01-2025

### Certification

*Particle Measuring Systems certifies that the instrument listed above meets or exceeds manufacturing specifications and meets the requirements of ISO 21501-4:2018. It has been calibrated using equipment and/or standards whose accuracies are traceable to the National Institute of Standards and Technology (NIST), or have been derived from acceptable values of natural physical constants, or by the ratio type of self-calibration. Counting Efficiency determined by digital output.*

*This Instrument was calibrated in accordance with the Particle Measuring Systems quality system documentation which meets ISO 9001:2015 requirements. The results contained within this calibration certificate relate only to the item calibrated. This certificate may not be reproduced, except in full, without written consent from Particle Measuring Systems.*

### Instrument Condition As Found

☒ In-Tolerance ☐ Out-of-Tolerance ☐ Operational Failure

### Condition As Left

☒ In-Tolerance

### Calibration Standards

Procedure Used: 2793G Program Used: 1000013097 Rev N

### Performed by

Technician Name: Pravin Lawangare





**PARTICLE  
MEASURING  
SYSTEMS®**  
a spectris company

5475 Airport Boulevard, Boulder, Colorado 80301-2339  
303.443.7100 800.238.1801

## Reference Information

Date: Aug-01-2024 12:58:29

Work Order: QTS/PO/INST/24-25/039  
Customer Name: Quality Technical Solutions  
Customer Address: PAP-R-289, Near Golden Garage, Rabale Midc, Navi Mumbai 400701.  
Calibration Lab: Aimil Mumbai  
Service Notes: PMS/MUM/24-25/25(QTS/HVAC/PC-18)

## Unit Under Test

Instrument: LasairIII\_5100 Serial Number: 140385  
Firmware Version: PCE: B2B53624 1.9 Laser Serial Number: No Change

## Particles Used: As Found

<u>Particle Size</u>	<u>Std Deviation</u>	<u>Lot Number</u>	<u>Expiration Date</u>	<u>Uncertainty</u>
0.510 micron	0.009	274149	Nov-30-2026	0.007
0.994 micron	0.010	268410	Jun-30-2026	0.021
2.020 micron	0.021	267195	May-31-2026	0.015
4.973 micron	0.050	265485	May-31-2026	0.054

## Particles Used: As Left

<u>Particle Size</u>	<u>Std Deviation</u>	<u>Lot Number</u>	<u>Expiration Date</u>	<u>Uncertainty</u>
0.510 micron	0.009	274149	Nov-30-2026	0.007
0.994 micron	0.010	268410	Jun-30-2026	0.021
2.020 micron	0.021	267195	May-31-2026	0.015
4.973 micron	0.050	265485	May-31-2026	0.054

## References Used

<u>Type</u>	<u>Serial Number</u>	<u>Calibration Due</u>
LasairII-110	81546	Dec-18-2024
Flow Meter	40430734011	Aug-30-2024





## Verification Data Record

Date: Aug-01-2024 12:45:06

Work Order: QTS/PO/INST/24-25/039  
Customer Name: Quality Technical Solutions

### Unit Under Test

Instrument: LasairIII\_5100 Serial Number: 140385  
Firmware Version: PCE: B2B53624 1.9 Laser Serial Number: No Change

### Environmental

Temperature: 23 Deg C Relative Humidity: 45%

### Threshold Information

<u>Channel Size (micron)</u>	<u>Measured Threshold/Gain</u>	<u>Received Threshold/Gain</u>	<u>Measurement Type</u>
Ch 1: 0.50	01853 / 0	02032 / 0	Distribution
Ch 2: 1.00	06426 / 0	07164 / 0	Distribution
Ch 3: 2.00	00911 / 1	00953 / 1	Distribution
Ch 4: 5.00	04493 / 1	04725 / 1	Distribution
Ch 5: 10.00	01132 / 2	01139 / 2	Extrapolate
Ch 6: 25.00	05422 / 2	05464 / 2	Extrapolate

### As Found Results

<u>Runtime Parameter</u>	<u>Results</u>	<u>Allowed Range</u>	<u>Expanded Uncertainty</u>	<u>Pass/Fail/ Skipped</u>
Flow Rate	100.0 L/min	95.0 to 105.0 L/min	n/a	Pass
Flow Error	0.00%	-5.00 to 5.00%	1.0%	Pass
Zero Count	0.00 Cnt/m <sup>3</sup>	<= 50.0 Cnt/m <sup>3</sup>	n/a	Pass (*1)
Zero Count 95% UCL	49.64 Cnt/m <sup>3</sup>	<= 50.0 Cnt/m <sup>3</sup>	n/a	Pass (*1)
CE(%) @ 0.50	41.2%	30.0% to 70.0%	0.29%	Pass
CE(%) @ 1.00	98.5%	90.0% to 110.0%	1.5%	Pass
Resolution @ 1.00	9.6%	0.0% to 15.0%	0.087%	Pass
Size Error @ 0.50	5.2%	-10.0% to 10.0%	2.0%	Pass
Size Error @ 1.00	5.7%	-10.0% to 10.0%	2.3%	Pass
Size Error @ 2.00	3.3%	-10.0% to 10.0%	1.4%	Pass
Size Error @ 5.00	2.9%	-10.0% to 10.0%	1.8%	Pass
Size Error @ 10.00	0.4%	-10.0% to 10.0%	1.9%	Pass
Size Error @ 25.00	0.4%	-10.0% to 10.0%	1.9%	Pass
<u>Design Parameter</u>	<u>Results</u>	<u>Allowed Range</u>		
Sampling Time	0.84%	0.0% to 1.0%		(*2)
Response Rate	0.006%	0.0 % to 0.5%		(*2)
Maximum particle number concentration	24313975 Cnt/m <sup>3</sup>	10% coincidence loss		(*2)

Note \*1: Calculated false count rate adjusted for 95% UCL  
Note \*2: Tested and verified during design and development





**PARTICLE  
MEASURING  
SYSTEMS\***  
a spectris company

5475 Airport Boulevard, Boulder, Colorado 80301-2339  
303.443.7100 800.238.1801

## Calibration Data Record

Date: Aug-01-2024 12:58:29

Work Order: QTS/PO/INST/24-25/039  
Customer Name: Quality Technical Solutions

### Unit Under Test

Instrument: LasairIII\_5100 Serial Number: 140385  
Firmware Version: PCE: B2B53624 1.9 Laser Serial Number: No Change

### Environmental

Temperature: 23 Deg C Relative Humidity: 45%

### Threshold Information

<u>Channel Size (micron)</u>	<u>Measured Threshold/Gain</u>	<u>Measurement Type</u>
Ch 1: 0.50	01825 / 0	Distribution
Ch 2: 1.00	06328 / 0	Distribution
Ch 3: 2.00	00927 / 1	Distribution
Ch 4: 5.00	04458 / 1	Distribution
Ch 5: 10.00	01066 / 2	Extrapolate
Ch 6: 25.00	05029 / 2	Extrapolate

### As Left Results

<u>Runtime Parameter</u>	<u>Results</u>	<u>Allowed Range</u>	<u>Expanded Uncertainty</u>	<u>Pass/Fail</u>
Flow Rate	100.0 L/min	97.0 to 103.0 L/min	n/a	Pass
Flow Error	0.00%	-3.00 to 3.00%	1.0%	Pass
Zero Count	0.00 Cnt/m <sup>3</sup>	<= 2.0 Cnt/m <sup>3</sup>	n/a	Pass (*1)
Zero Count 95% UCL	1.99 Cnt/m <sup>3</sup>	<= 2.0 Cnt/m <sup>3</sup>	n/a	Pass (*1)
CE(%) @ 0.50	50.8%	30.0% to 70.0%	1.5%	Pass
CE(%) @ 1.00	103.0%	90.0% to 110.0%	1.7%	Pass
Resolution @ 1.00	10.1%	0.0% to 15.0%	0.12%	Pass
Size Error @ 0.50	-0.76%	-10.0% to 10.0%	2.0%	Pass
Size Error @ 1.00	-0.45%	-10.0% to 10.0%	2.3%	Pass
Size Error @ 2.00	-0.58%	-10.0% to 10.0%	1.4%	Pass
Size Error @ 5.00	-0.71%	-10.0% to 10.0%	1.8%	Pass
Size Error @ 10.00	-0.82%	-10.0% to 10.0%	n/a	Pass
Size Error @ 25.00	-0.82%	-10.0% to 10.0%	n/a	Pass
<u>Design Parameter</u>	<u>Results</u>	<u>Allowed Range</u>		
Sampling Time	0.84%	0.0% to 1.0%		(*2)
Response Rate	0.006%	0.0 % to 0.5%		(*2)
Maximum particle number concentration	24313975 Cnt/m <sup>3</sup>	10% coincidence loss		(*2)

Note \*1: Calculated false count rate adjusted for 95% UCL  
Note \*2: Tested and verified during design and development

