

intel_mgmt_trans.vr

```
$VCS_HOME/doc/examples/nativetestbench/openvera/rvm/host_if/intel_mgmt/intel_mgmt_trans.vr
```

[illegible]

```

}
// Declare a specific rvm_channel of intel_mgmt_trans
rvm_channel(intel_mgmt_trans)

task intel_mgmt_trans::new()
{
    super.new(this.log);
}

function string intel_mgmt_trans::psdisplay(string prefix = "")
{
    sprintf(psdisplay, "%s%s Addr=%02X Data=%02X\n",
            prefix, this.kind, this.addr, this.data);
}

function rvm_data intel_mgmt_trans::allocate()
{
    intel_mgmt_trans tr = new;
    allocate = tr;
}

function rvm_data intel_mgmt_trans::copy(rvm_data cpy = null)
{
    intel_mgmt_trans to = null;
    if (cpy == null) {
        to = new;
    } else if (!cast_assign(to, cpy, CHECK)) {
        rvm_fatal(this.log, "Attempting to copy to a non-intel_mgmt_trans instance");
        copy = null;
        return;
    }
    super.copy_data(to);

    to.kind = this.kind;
    to.addr = this.addr;
    to.data = this.data;
    copy = to;
}

function bit intel_mgmt_trans::compare(rvm_data to,
                                       var string diff,
                                       integer kind = -1)
{
    intel_mgmt_trans tr;

```

```

diff = "";
if (!cast_assign(tr, to, CHECK)) {
    diff = "Not a intel_mgmt_trans instance";
    compare = 0;
    return;
}
if (this.kind != tr.kind) {
    diff = psprintf("Transaction kinds are different");
    compare = 0;
    return;
}
if (this.addr != tr.addr) {
    diff = psprintf("Transaction addresses are different");
    compare = 0;
    return;
}
if (this.data != tr.data) {
    diff = psprintf("Transaction data are different");
    compare = 0;
    return;
}
compare = 1;
}

function integer intel_mgmt_trans::byte_size(integer kind = -1)
{
    byte_size = 0;
}

function integer intel_mgmt_trans::byte_pack(var bit [7:0] bytes[*],
                                              integer offset = 0,
                                              integer kind    = -1)
{
    byte_pack = 0;
}

function integer intel_mgmt_trans::byte_unpack(bit [7:0] bytes[*],
                                              integer offset = 0,
                                              integer kind    = -1)
{
    byte_unpack = 0;
}

```