

my_xactor.vr

\$VCS_HOME/doc/examples/nativetestbench/openvera/rvm/restart/soft_stable/my_xactor.vr

```
#include <rvm_std_lib.vrh>
#include "my_data.vrh"
class my_xactor extends rvm_xactor {
    my_data data;
    local VeraRandomState data_rng_state;
    local VeraRandomState saved_data_rng_state;
    task new(string instance,
              integer stream_id = -1)
    {
        super.new("MyXactor", instance, stream_id);
        data = new;
    }

    virtual task reset_xactor(integer rst_type = 0)
    {
        super.reset_xactor(rst_type);
        if (rst_type >= XACTOR_FIRM_RST) {
            this.data = new;
        }
    }

    virtual task save_rng_state() {
        super.save_rng_state();
        getstate(this.saved_data_rng_state, this.data);
        this.data_rng_state = this.saved_data_rng_state;
        setstate(this.data_rng_state, this.data);
    }

    virtual task restore_rng_state() {
        super.restore_rng_state();
        this.data_rng_state = this.saved_data_rng_state;
        setstate(this.data_rng_state, this.data);
    }

    protected virtual task main_t()
    {
        fork
            super.main_t();
    }
}
```

```

        void = this.data.randomize();
        data.display(psprintf("%s.1.1: ", this.log.get_instance()));
        suspend_thread();
        void = this.data.randomize();
        data.display(psprintf("%s.1.2: ", this.log.get_instance()));
        suspend_thread();
        void = this.data.randomize();
        data.display(psprintf("%s.1.3: ", this.log.get_instance()));
    }
    {
        printf("%s.2.1: urnd =32'h%h\n", this.log.get_instance(), urandom());
        suspend_thread();
        printf("%s.2.2: urnd =32'h%h\n", this.log.get_instance(), urandom());
        suspend_thread();
        printf("%s.2.3: urnd =32'h%h\n", this.log.get_instance(), urandom());
    }
    join all
}
}

```