

test_03_directed.vr

\$VCS_HOME/doc/examples/nativetestbench/openvera/rvm/host_if/tests/test_03_directed.vr

```
/*
 *
 * Author:      Fabian Delguste
 * File:        $RCSfile: test_03_directed.vr,v $
 * Revision:    $Revision: 1.4 $
 * Date:        $Date: 2003/11/03 20:09:05 $
 *
 ****
 *
 * This test shows how to create directed test by generating
 * transactions on-the-fly (e.g on-demand).
 *
 * Basically, a transaction descriptor is directly generated
 * throughout the simulation run set in order to create a
 * directed test.
 *
 ****
 */

#include "dut_env.vrh"

program directed {
    // Instanciate the top level
    env the_env = new;
    the_env.start_t();
    // Will manually stop the simulation
    trigger(OFF, the_env.end_simulation);
    // Stop the generator
    the_env.gen.stop_xactor();
    // Fork the directed stimulus
    fork
    {
        integer i;
        for (i = 0; i < 31; i++) {
            the_env.gen.write(i, random());
            void = the_env.gen.read(i);
        }
    }
}
```

```
        // Terminate the simulation
        delay(100);
        trigger(the_env.end_simulation);
    }
    join none
    // Kick off the test now
    the_env.run_t();
}
```