Draft version April 28, 2026
Typeset using LaTeX **twocolumn** style in AASTeX631

Calibration Audit of Production Astronomical Transient Classifiers on ZTF Alert Streams

Pallavi Sati[1]

[1] *Independent Researcher*

ABSTRACT

Production transient classifiers deployed on the Zwicky Transient Facility (ZTF) alert stream are routinely used to prioritise spectroscopic follow-up, yet no prior work has evaluated calibration across multiple production brokers using standard metrics on real survey data. We present a systematic calibration audit of four classifiers: two production alert brokers (ALeRCE's Balanced Random Forest, and Fink's Random Forest and SuperNNova) and the standalone NEEDLE classification framework, using spectroscopically confirmed transients from the ZTF Bright Transient Survey as ground truth. We compute Expected Calibration Error (ECE) with equal-mass binning, classwise reliability diagrams, and Brier scores, then apply temperature scaling with five-fold cross-validation. We find that all four classifiers exhibit significant miscalibration. ALeRCE is systematically underconfident (ECE = 0.271); temperature scaling ($T = 0.357$) reduces ECE to 0.097 (65% improvement), increasing objects exceeding $p > 0.8$ from 20 to 425 at 91% precision. Fink's Random Forest, designed as an early-time SN Ia classifier (Leoni et al. 2022), abstains on 93.9% of BTS objects (1,161 of 1,237) with near-uniform abstention rates across true classes (90–99%); we identify this as operational regime mismatch rather than miscalibration and therefore exclude RF from probabilistic calibration analysis. Fink's SuperNNova classifier exhibits implicit selective classification, emitting non-zero scores for 64.1% of BTS objects (793/1,237) with strongly class-dependent abstention (χ^2, $p = 8 \times 10^{-37}$; non-Ia transients abstain at 2.6× the rate of SN Ia). On its accepted set, conditional ECE is 0.183 [0.154, 0.220], reducible to 0.051 with temperature scaling $T = 3.65$. However, this calibration improvement is operationally null at high thresholds: zero objects pass $p \geq 0.8$ post-scaling (versus 209 pre-scaling at 73% precision), because $T > 1$ compresses overconfident scores rather than exposing additional candidates as ALeRCE's $T < 1$ sharpening does. NEEDLE achieves good aggregate calibration at the object level (ECE = 0.048, $N = 278$ unique objects), but per-class analysis reveals severe class-imbalance-driven miscalibration: SLSN-I (superluminous supernovae type I, $n = 15$ true objects) are predicted with 73% mean confidence but only 31% accuracy (gap = −0.423), with three objects confidently misclassified as SNe at > 0.998 confidence. Global temperature scaling worsens calibration, and per-class scaling cannot resolve the structural miscalibration. These findings highlight the need for calibration-aware decision pipelines as the community prepares for LSST. Code and results are available at https://github.com/pallavi-2000/transient-calibration-audit.

Keywords: methods: statistical — surveys — supernovae: general — techniques: photometric

1. INTRODUCTION

The Vera C. Rubin Observatory's Legacy Survey of Space and Time (LSST) will generate approximately 10 million alerts per night at full operations (Ivezić et al. 2019), while global spectroscopic follow-up capacity remains fixed at roughly 100,000 spectra per year—a mismatch ratio of approximately 100:1. The first LSST alerts were issued in February 2026, with the full survey beginning later this year, making the calibration of broker classifiers an immediate operational concern rather than a future consideration. With the Zwicky Transient Facility (ZTF; Bellm et al. 2019) having served as the primary precursor survey, the community has developed automated alert brokers to triage this data deluge and identify the most scientifically valuable transients for follow-up.

pallavisati23@gmail.com

Several broker systems now operate in production on the ZTF alert stream, including ALeRCE (Förster et al. 2021), Fink (Möller et al. 2021), ANTARES (Narayan et al. 2018), and Lasair (Smith et al. 2019). These systems ingest alerts in real time, extract features from light curves and contextual information, and deploy machine learning classifiers to assign class probabilities to each transient. Astronomers routinely use these probability outputs to make follow-up decisions: a transient classified as "90% SN Ia" is far more likely to receive telescope time than one classified at "60% SN Ia." Additional frameworks such as NEEDLE (Sheng et al. 2024) extend classification to rare transient types including superluminous supernovae (SLSNe) and tidal disruption events (TDEs).

This decision-making process relies on an implicit but critical assumption: that the classifier's stated probabilities are *calibrated*—that is, among all objects assigned a probability p of belonging to a given class, a fraction p actually belongs to that class (Dawid 1982). Miscalibrated probabilities lead directly to misallocated resources: an overconfident classifier wastes telescope time on objects it is wrong about, while an underconfident one causes astronomers to overlook genuinely interesting transients. Despite the operational importance of calibration, no production transient classifier currently publishes calibration metrics such as the Expected Calibration Error (ECE; Naeini et al. 2015), reliability diagrams, or Brier score decompositions.

The machine learning calibration literature has established that modern neural networks are systematically overconfident (Guo et al. 2017), a finding that has driven the development of post-hoc calibration methods including temperature scaling (Guo et al. 2017), Platt scaling (Platt 1999), and Dirichlet calibration (Kull et al. 2019). However, Random Forests—the architecture underlying several production broker classifiers—exhibit the opposite calibration behavior: ensemble averaging over bagged trees pushes predictions toward intermediate values, producing systematic underconfidence (Niculescu-Mizil & Caruana 2005; Boström 2008). Class imbalance corrections such as those used in Balanced Random Forests further distort probability estimates by inflating minority-class probabilities (van den Goorbergh et al. 2022). These well-characterized calibration properties of different architectures have direct relevance for astronomical classifiers but have not been evaluated in this domain.

Two recent works include limited calibration analysis. de Soto et al. (2024) present per-class calibration curves for Superphot+ deployed on the ANTARES broker, noting overconfident SN Ib/c and underconfident SN Ia predictions but without computing formal calibration metrics. Tung (2025) evaluate calibration of ATCAT on simulated ELAsTiCC data, applying post-hoc corrections. However, no prior work has conducted a systematic calibration audit of production classifiers operating on real survey data using standard metrics.

In this paper, we present the first such audit. We evaluate four classifiers across three production systems: ALeRCE's Balanced Random Forest light curve classifier (lc_classifier v1.1.13; Sánchez-Sáez et al. 2021), Fink's Random Forest and SuperNNova classifiers (Leoni et al. 2022; Möller & de Boissière 2020), and the NEEDLE hybrid CNN+DNN framework (Sheng et al. 2024). We restrict our analysis to classifiers that output explicit class probabilities; other brokers such as Lasair, ANTARES, and AMPEL employ crossmatching or feature-based approaches that do not produce probability estimates amenable to calibration analysis. Using spectroscopically confirmed transients from the ZTF Bright Transient Survey (BTS; Fremling et al. 2020; Perley et al. 2020) as ground truth, we compute ECE with equal-mass binning (Roelofs et al. 2022), class-wise reliability diagrams (Nixon et al. 2019), and Brier scores, then apply temperature scaling with stratified five-fold cross-validation. We find that all four classifiers are significantly miscalibrated, each with a distinct failure mode, and that temperature scaling is effective for ALeRCE but inappropriate or counterproductive for the other systems.

The paper is organized as follows. Section 2 reviews relevant background on calibration metrics and post-hoc methods. Section 3 describes our data sources and sample construction. Section 4 presents our calibration analysis methodology. Section 5 reports our findings for each classifier. Section 6 interprets the results in the context of the calibration literature and discusses implications for LSST. Section 7 summarizes our conclusions.

2. BACKGROUND

2.1. *Calibration and its Importance*

A probabilistic classifier is said to be *calibrated* if, for all predicted probability values p, the empirical frequency of the positive class among predictions with confidence p equals p (Dawid 1982). Formally, for a classifier f producing predictions $\hat{Y}$ with associated confidence $\hat{P}$:

$$P(\hat{Y} = Y \mid \hat{P} = p) = p \quad \forall p \in [0, 1]. \tag{1}$$

Calibration is distinct from discrimination (the ability to separate classes). A classifier can achieve high accuracy while being poorly calibrated, and vice versa.

2.2. *Calibration Metrics*

The *Expected Calibration Error* (ECE; Naeini et al. 2015) is the most widely used scalar summary of calibration quality. It partitions predictions into M bins based on confidence and computes the weighted average of the absolute difference between accuracy and confidence in each bin:

$$\mathrm{ECE} = \sum_{m=1}^{M} \frac{|B_m|}{n} \left|\mathrm{acc}(B_m) - \mathrm{conf}(B_m)\right|, \tag{2}$$

where B_m is the set of samples in bin m, $\mathrm{acc}(B_m)$ is the empirical accuracy, and $\mathrm{conf}(B_m)$ is the mean confidence. We use $M = 15$ bins following Guo et al. (2017).

The choice of binning strategy significantly affects ECE estimates. Equal-width binning places bin boundaries at uniform intervals along the confidence axis, which can leave many bins empty or near-empty for classifiers with skewed confidence distributions. Roelofs et al. (2022) demonstrated that equal-mass (quantile) binning, which places approximately the same number of samples in each bin, produces lower-bias ECE estimates and recommended against equal-width binning. We adopt equal-mass binning throughout.

Standard ECE considers only the top-predicted class and can mask miscalibration of individual classes. Nixon et al. (2019) introduced the *Static Calibration Error* (SCE) and *Adaptive Calibration Error* (ACE), which evaluate calibration of all K class probabilities independently. We report classwise ECE following this approach.

The *Brier score* (Brier 1950) provides a complementary proper scoring rule:

$$\mathrm{BS} = \frac{1}{n} \sum_{i=1}^{n} \sum_{k=1}^{K} (p_{ik} - y_{ik})^2, \tag{3}$$

where p_{ik} is the predicted probability for class k and y_{ik} is the indicator for the true class.

2.3. *Temperature Scaling*

Temperature scaling (Guo et al. 2017) is a single-parameter post-hoc calibration method that rescales the logit vector $\mathbf{z}$ by a learned temperature $T > 0$:

$$\hat{q}_k = \frac{\exp(z_k/T)}{\sum_j \exp(z_j/T)}. \tag{4}$$

When $T > 1$, the output distribution is softened (reducing overconfidence); when $T < 1$, it is sharpened (reducing underconfidence). The temperature is fitted by minimizing the negative log-likelihood (NLL) on a held-out calibration set, as NLL is a strictly proper scoring rule (Gneiting & Raftery 2007).

Critically, temperature scaling applies a single global transformation and therefore cannot correct class-asymmetric miscalibration—where some classes are overconfident while others are underconfident. Kull et al. (2019) demonstrated that temperature scaling can appear to produce well-calibrated confidence-level reliability diagrams while individual classes remain miscalibrated, and proposed Dirichlet calibration as a more flexible alternative.

2.4. *Calibration of Random Forests*

Niculescu-Mizil & Caruana (2005) showed that Random Forests produce systematically underconfident predictions due to the averaging of base learner probabilities: if the true probability is near 0 or 1, the ensemble average is biased toward 0.5 because only consensus among all trees can produce extreme probabilities. This effect is amplified by feature subsetting, which increases base learner variance. Boström (2008) confirmed this finding and proposed sigmoid calibration to correct it. Loecher & Walters (2024) demonstrated through simulation that Random Forest probability estimates "are always underconfident" across 192 scenarios.

Balanced Random Forests (Chen et al. 2004) introduce an additional calibration-distorting mechanism. By undersampling the majority class during training, they alter the effective class prior, which van den Goorbergh et al. (2022) showed produces "strong and systematic overestimation of the probability for the minority class." The combined effect of standard RF underconfidence and minority-class inflation from balancing creates a complex but predictable calibration profile.

2.5. *Effects of Class Weighting on Calibration*

Many astronomical classifiers employ inverse-frequency class weighting or similar imbalance correction strategies to improve minority-class recall. van den Goorbergh et al. (2022) demonstrated that all common imbalance corrections—including random undersampling, oversampling, and SMOTE—harm probability calibration. Fernando & Tsokos (2021) confirmed that "probability estimates of minority classes are unreliable" when class weighting is applied. This is directly relevant to NEEDLE, which employs inverse-frequency weighting with extreme ratios (∼80:1 for common supernovae versus TDEs).

3. DATA

3.1. *Spectroscopic Ground Truth*

We use the ZTF Bright Transient Survey (BTS; Fremling et al. 2020; Perley et al. 2020) as our primary source of spectroscopic ground truth. BTS provides systematic spectroscopic classification of transients detected by

Table 1. Stratified Sample Composition

Class	Count	Fraction
SN Ia	600	41.8%
SN II	341	23.7%
SN Ibc	225	15.7%
SLSN	97	6.8%
TDE	39	2.7%
Other	134	9.3%

ZTF, yielding 7,167 objects with spectroscopic type assignments. We map the ∼30 BTS spectroscopic subtypes to the ALeRCE taxonomy using a conservative mapping: SN Ia and its subtypes (Ia-91T, Ia-91bg, Ia-02cx, Ia-CSM) map to SNIa; SN Ib, Ic, Ic-BL, Ib/c, and Ibn map to SNIbc; SN II, IIn, IIb, and IIP map to SNII; SLSN-I and SLSN-II map to SLSN; and TDE maps to TDE. Objects with types not present in any classifier taxonomy (novae, LRN, LBV) are excluded, yielding 7,116 mapped objects.

3.2. *Stratified Sampling*

Because rare classes (SLSN, TDE) constitute <2% of the BTS catalog, we construct a stratified sample to ensure adequate representation for per-class calibration analysis. We cap the dominant class (SN Ia) at 600 objects and include all available objects for rarer classes. This yields a sample of 1,436 objects with the distribution shown in Table 1. Stratified sampling is appropriate for calibration analysis because ECE is a conditional measurement—it evaluates accuracy within confidence bins—and does not require the evaluation set to match the population class distribution (Guo et al. 2017).

3.3. *Classifier Predictions*

ALeRCE. We query the ALeRCE API[1] for light curve classifier (lc_classifier v1.1.13) probabilities. This Balanced Random Forest outputs a 15-class probability vector spanning transient and variable star categories (Sánchez-Sáez et al. 2021). We successfully retrieve predictions for 1,149 of 1,436 sample objects. Since ALeRCE does not include a TDE class in its production taxonomy, we exclude 35 TDE objects, yielding 1,114 objects for analysis. We restrict to the four transient classes (SN Ia, SN Ibc, SN II, SLSN) and renormalize the probability vectors to sum to unity over these classes. To verify that this renormalization does not introduce artifacts, we compared ECE on the renormalized 4-class vector (0.271) against the raw 15-class vector (0.283) and found the renormalized ECE is slightly lower. The median probability mass assigned to transient classes is 0.996, with only 1.4% of objects (16/1,114) having >50% probability in non-transient classes. Per-class inflation factors are negligible (1.02–1.06×). Temperature scaling produces consistent results in both representations (post-calibration ECE of 0.097 vs. 0.092), confirming robustness to the renormalization choice. The absence of TDE from ALeRCE's production taxonomy is itself noteworthy: TDEs are a primary LSST science case, yet the most widely used ZTF transient classifier cannot identify them. Pavez-Herrera et al. (2025) have recently added TDE support in a beta classifier, but it is not yet deployed in production.

Fink. We query the Fink API[2] for two binary classifiers: the Random Forest SN Ia classifier (rf_snia_vs_nonia) and SuperNNova (snn_snia_vs_nonia; Möller & de Boissière 2020). Both output a single score $\in [0, 1]$ representing $P(\text{SN Ia})$. We retrieve the most recent alert for each object (corresponding to the most complete light curve), obtaining predictions for 1,237 objects.

NEEDLE. Unlike ALeRCE and Fink, NEEDLE (Sheng et al. 2024) does not provide a public API. We perform local inference using the five pre-trained models from the `lasair_th_r` model family, applied to the publicly available dataset. Each model was trained with a different random held-out test set recorded in `testset_obj.json`. We map test set ZTF IDs to dataset positions via the provided hash table, yielding 429 predictions across 278 unique objects in three classes (SN, SLSN-I, TDE). Of these, 43 objects appear in the held-out test sets of multiple models, contributing 151 duplicate predictions. Our primary analysis deduplicates to the object level by averaging model probabilities per object (278 unique objects); the 429-prediction model-instance set is retained as a sensitivity analysis (Section 5.3.4). The 100% inter-model class agreement (Section 5.3.4) validates the averaging methodology.

4. METHODS

4.1. *Calibration Evaluation*

For each classifier, we compute:

1. ECE with equal-mass binning (15 bins) and, for comparison, equal-width binning.

[1] https://api.alerce.online

[2] https://api.fink-portal.org

2. Classwise ECE following Nixon et al. (2019), evaluating calibration of each class probability independently.

3. Reliability diagrams showing empirical accuracy versus mean confidence per bin.

4. Brier score as a proper scoring rule.

5. Bootstrap confidence intervals (1,000 replicates, 95% level) on ECE.

For binary classifiers (Fink RF and SuperNNova), confidence is defined as $\max(p, 1-p)$ and predictions are thresholded at $p = 0.5$. We verified that ECE is robust to the choice of bin count for our smallest sample (NEEDLE, $N = 429$): ECE varies from 0.066 at $M = 10$ to 0.075 at $M = 20$, a range of 0.009.

4.2. *Temperature Scaling*

We fit the temperature parameter T by minimizing negative log-likelihood using bounded scalar optimization ($T \in [0.01, 10.0]$). To avoid fitting and evaluating on the same data, we use stratified five-fold cross-validation: folds are constructed to preserve class ratios (essential when rare classes such as SLSN constitute only 7.6% of the sample), T is fitted on four folds, and ECE is evaluated on the held-out fold, with results averaged across folds.

For Random Forest classifiers, which do not natively produce logits, we convert vote-fraction probabilities to pseudo-logits via $z_k = \log p_k$ before applying temperature scaling. We note that this conversion assumes a log-linear relationship that may not hold precisely for RF outputs.

We apply three decision rules to determine whether temperature scaling should be recommended:

1. **Bound detection:** If T reaches the optimizer bound ($T \geq 9.5$ or $T \leq 0.02$), scaling is rejected as inappropriate.

2. **Worsening detection:** If post-scaling ECE exceeds pre-scaling ECE, scaling is rejected.

3. **Redundancy detection:** If pre-scaling ECE $<$ 0.1, scaling is deemed unnecessary.

For classifiers where global temperature scaling fails, we additionally evaluate per-class temperature scaling (Fang & Orabona 2020), which fits an independent T_k for each class and re-normalizes via softmax.

5. RESULTS

Table 2 summarizes the calibration metrics for all four classifiers. We describe each in detail below.

5.1. *ALeRCE: Systematic Underconfidence*

The ALeRCE light curve classifier exhibits systematic underconfidence across all transient classes (Figure 1). The overall accuracy is 0.742, but the mean confidence is only 0.471—a gap of +0.271 indicating that the classifier is substantially more accurate than its confidence scores suggest. The reliability diagram shows all bins lying above the diagonal, with confidence values compressed into the range $[0.3, 0.75]$ and never exceeding 0.75.

This underconfidence is consistent with the known calibration behavior of Random Forests (Niculescu-Mizil & Caruana 2005; Boström 2008). The Balanced Random Forest architecture amplifies this effect: by undersampling the majority class during training, it alters the effective prior, and the averaging of base learner predictions across a 15-class taxonomy further pushes probabilities toward uniform values.

Per-class analysis (Figure 2) reveals that underconfidence is pervasive: SN Ia (ECE = 0.195, gap = +0.335), SN Ibc (ECE = 0.154, gap = +0.201), and SN II (ECE = 0.150, gap = +0.393) all exhibit strong underconfidence. SLSN is a notable exception with a slight overconfidence (gap = −0.055), potentially reflecting the Balanced Random Forest's inflation of minority-class probabilities (van den Goorbergh et al. 2022).

Temperature scaling with $T = 0.357 \pm 0.012$ (stratified five-fold CV) reduces the cross-validated ECE from 0.276 to 0.097—a 65% improvement (Figure 3). The sharpening effect ($T < 1$) is the correct direction for underconfident classifiers, spreading the compressed confidence range $[0.3, 0.75]$ out to $[0.35, 1.0]$. We note that $T = 0.357$ is more aggressive than values typically reported in the neural network calibration literature (where $T > 1$ is standard for overconfident models), reflecting the severity of RF underconfidence when distributed across 15 classes. The non-cross-validated ECE of 0.030 shown in Figure 3 illustrates the visual effect of calibration but overestimates improvement due to fitting and evaluating on the same data; the cross-validated estimate of 0.097 is the appropriate value for reporting.

5.2. *Fink: Implicit Selective Classification*

The Fink broker's two probabilistic classifiers—Random Forest (`rf_snia_vs_nonia`) and SuperNNova (`snn_snia_vs_nonia`)—both return score = 0 for objects that fail eligibility criteria (minimum-epoch re-

Table 2. Calibration Audit Summary

Classifier	Architecture	Classes	N	ECE	Brier	Post-hoc Method	$\mathrm{ECE}_{\mathrm{post}}$
ALeRCE	BRF	15 (4 transient)	1114	0.271 [0.249, 0.296]	0.486	Temp. ($T = 0.357$)	0.097
Fink RF[†]	RF	2	1237	—	—	N/A (regime mismatch)	—
Fink SNN[‡] (cond.)	RNN	2	793	0.183 [0.154, 0.220]	0.274	Temp. ($T = 3.65$)	0.051
NEEDLE (obj.-level)[‡]	CNN+DNN	3	278	0.048 [0.048, 0.111]	0.265	Global T worsens	0.169
(model-instance)			429	0.075 [0.062, 0.115]	0.241	(sensitivity; §5.3.4)	—

NOTE—ECE computed with equal-mass binning (15 bins). 95% confidence intervals via bootstrap (1,000 replicates). Post-hoc ECE for ALeRCE is the cross-validated estimate (stratified 5-fold). Brier score: 0 is perfect; for reference, random guessing gives ∼0.5 for binary classifiers and ∼1.5 for 4-class. [†]Fink RF abstains on 93.9% of BTS objects with near-uniform abstention across classes (regime mismatch; see §5.2.1); ECE on the 76 non-zero predictions is not population-representative and is omitted. [‡]Fink SNN conditional metrics on 793 non-zero predictions (64.1% coverage). Reweighting to BTS prevalence yields population-equivalent gap of 0.460 (abstention bias +0.024). Post-T value of 0.051 is operationally null at $p \geq 0.8$; see Table 3 and §5.2.2. [§]NEEDLE object-level (primary): 278 unique objects, deduplicated by averaging probabilities across models. See §5.3 and §6.5.



Figure 1. Reliability diagram for the ALeRCE light curve classifier showing systematic underconfidence: all bins lie above the perfect calibration diagonal. Confidence values are compressed into the range $[0.3, 0.75]$. ECE = 0.271 with equal-mass binning (15 bins).

quirements, host-galaxy cuts, light-curve length cuts; Leoni et al. 2022; Möller & de Boissière 2020). Score = 0 does not represent $P(\text{SN Ia}) = 0$; it represents classifier abstention. Treating zeros as ordinary probabilities yields meaningless ECE values and obscures the actual classifier behavior. We therefore reframe the Fink analysis as a **selective classification** problem (**?**): each classifier defines an acceptance gate $\pi(x) \in \{0, 1\}$ and a probability $p(y \mid x)$ on the accepted subset. We evaluate three properties separately: coverage (does the classifier emit a probability?), conditional calibration (are the emitted probabilities reliable?), and abstention bias (does the abstention pattern bias the conditional calibration estimate?).

Because BTS contains spectroscopically confirmed transients, every object in our sample is a real astrophysical event. Zero-score objects are therefore real transients on which the classifier did not emit a usable prediction, not non-transient distractors.

5.2.1. *Random Forest: Operational Regime Mismatch*

Fink's Random Forest classifier (Leoni et al. 2022) is the early SN Ia detector designed to identify SN Ia candidates from the rising-phase alert stream within ∼9 days of first detection. Its eligibility gate requires at least three observed epochs in each filter, fewer than 20 prior detections, and a host-galaxy cross-match filter, and was trained on the active-learning sample selected from ZTF alerts within this operational window.

Our BTS evaluation sample, by construction, contains well-evolved spectroscopically confirmed transients with extensive photometric histories—the opposite regime from RF's training distribution. As expected from this methodological mismatch, RF abstains on 1,161 of 1,237 BTS objects (93.9%, effective coverage 6.1%) with abstention rates that are statistically class-dependent (χ^2, $p = 7.2 \times 10^{-3}$) but operationally near-uniform across classes: SN Ia 93.0%, SN Ibc 90.2%, SN II 96.2%, SLSN 98.8%, TDE 97.3%. The non-Ia/Ia abstention rate ratio is 1.0, in contrast to SuperNNova's 2.6 (Section 5.2.2).

We therefore treat Fink RF as a coverage diagnostic rather than a calibration target on this sample. The 76 objects receiving non-zero scores cannot meaningfully



Figure 2. Per-class reliability diagrams for the ALeRCE classifier. SN Ia, SN Ibc, and SN II show consistent underconfidence (bars above diagonal). SLSN shows slight overconfidence, potentially due to minority-class probability inflation from the Balanced Random Forest architecture.

represent population-level calibration, since they are an idiosyncratic subset of BTS objects that happened to satisfy an early-classifier eligibility gate not designed for them. The classifier is performing as designed; it is simply not the right tool for post-discovery follow-up queries of the type represented by BTS.

5.2.2. *SuperNNova: Selective Classification with Class-Dependent Abstention*

Fink's SuperNNova classifier (Möller & de Boissière 2020) emits non-zero scores for 793 of 1,237 BTS objects (64.1% coverage). Abstention is strongly class-dependent (χ^2, $p = 8.4 \times 10^{-37}$): SN Ia objects abstain at 19.0%, SN Ibc at 29.8%, SN II at 55.7%, TDE at 62.2%, and SLSN at 67.5% (Figure 4). The monotonic increase from bright thermonuclear to faint core-collapse and rare classes is consistent with SuperNNova's photometric data-quality requirements: rarer, fainter classes have sparser light curves that more frequently fail the minimum-photometry gate. Non-SN Ia transients abstain at 2.6 times the rate of SN Ia (48.5% versus 19.0%), and the hard gap from exactly zero to the first non-zero score (0.0051) is diagnostic of an explicit gate rather than a continuous low-confidence regime (Figure 7).

Conditional calibration. On the 793 accepted objects, the classifier achieves overall accuracy 0.589 at threshold $p \geq 0.5$ with a conditional ECE of 0.183 [95% CI: 0.154, 0.220] and Brier score 0.274. Per-class analysis on the accepted set reveals that SuperNNova systematically issues moderate probabilities of SN Ia for non-Ia transients: mean predicted P(SN Ia) is 0.51 for SN II, 0.45 for SN Ibc, 0.68 for SLSN, and 0.73 for TDE objects that pass its eligibility gate, despite the true SN Ia fraction in each class being zero (Figure 5). This is the dominant source of conditional miscalibration.

Abstention bias. The conditional ECE measures calibration on a sample whose class composition differs from BTS: SN Ia is 53.8% of the accepted set versus 42.6% of BTS, while SN II drops from 27.9% to 19.3% and SLSN drops from 6.7% to 3.4% (Figure 6). Reweighting per-class calibration gaps to BTS prevalence yields a population-equivalent weighted-gap of 0.460 versus the conditional weighted-gap of 0.436, an absolute increase of 0.024. This +2.4 percentage-point bias quantifies how selective abstention masks population-level miscalibration.

Temperature scaling. On the accepted set, temperature scaling fits $T = 3.65$ (no bound hit) and reduces



Figure 3. ALeRCE reliability diagrams before (left) and after (right) temperature scaling with $T = 0.357$. The displayed ECE of 0.030 is computed on the full dataset; the cross-validated estimate is 0.097 (65% improvement). The sharpening effect spreads the compressed confidence distribution to span the full $[0.35, 1.0]$ range.

conditional ECE to 0.051—a 72% reduction. However, the operational consequence of $T = 3.65$ is fundamentally different from the ALeRCE case (Section 5.1, $T = 0.357$ sharpening). Because $T > 1$ compresses scores toward 0.5, the post-scaling distribution is restricted to [0.191, 0.708] (versus [0.005, 0.962] pre-scaling). Table 3 shows the consequences for high-threshold selection: pre-calibration, 209 objects pass $p \geq 0.8$ at 73.2% precision and 66 pass $p \geq 0.9$ at 74.2% precision; post-calibration, zero objects pass either threshold because the maximum post-scaled score is 0.708. The 72% ECE reduction reflects the classifier honestly expressing its inherent uncertainty rather than acquiring new discriminative power; classification decisions at $p \geq 0.5$ are unchanged (495 predicted SN Ia in both cases, identical 60.2% precision).

For *probability reporting* to astronomers, $T = 3.65$ produces honest output. For *high-precision triage*, pre-calibration scores remain operationally useful (209 candidates at 73% precision) despite their formal miscalibration. The contrast between underconfident classifiers (ALeRCE, where calibration unlocks high-confidence selection) and overconfident classifiers (Fink SNN, where calibration eliminates high-confidence selection) is a substantive finding of this audit (Section 6).

Table 3. Operational consequences of temperature scaling for Fink SuperNNova on the accepted set ($N = 793$). Temperature $T = 3.65$ compresses the score distribution from [0.005, 0.962] to [0.191, 0.708]. At $p \geq 0.5$, decisions are unchanged. At higher thresholds, post-calibration eliminates all predictions while pre-calibration retains operationally useful candidates.

Threshold	Pre-T (raw)		Post-T ($T = 3.65$)	
$p \geq$	N pass	Precision	N pass	Precision
0.5	495	0.602	495	0.602
0.6	448	0.607	188	0.745
0.7	355	0.639	2	1.000
0.8	209	0.732	0	—
0.9	66	0.742	0	—

5.3. *NEEDLE: Object-Level Calibration and Class Imbalance*

5.3.1. *Aggregate Calibration: Object-Level Results*

Our primary NEEDLE analysis evaluates 278 unique ZTF objects, deduplicated by averaging probabilities from all models that classified each object (Section 6.5). At the object level, NEEDLE achieves aggregate ECE =



Figure 4. Fink SuperNNova class-conditional abstention rates on the BTS evaluation sample ($N = 1237$). Error bars show 95% Wilson confidence intervals. Abstention is strongly class-dependent (χ^2, $p = 8.4 \times 10^{-37}$), with monotonic increase from bright thermonuclear (SN Ia, 19.0%) to faint core-collapse and rare classes (SLSN, 67.5%; TDE, 62.2%). The dashed line shows the overall abstention rate of 35.9%.



Figure 5. Fink SuperNNova per-class calibration on the accepted set (non-zero predictions, $n = 793$). Blue bars show mean predicted $P(\text{SN Ia})$ and orange bars show the true SN Ia fraction (with 95% Wilson CI). The classifier issues moderate $P(\text{SN Ia})$ values (0.45–0.73) for non-Ia transients that pass its eligibility gate, despite the true SN Ia fraction being zero in those classes. This is the dominant source of conditional miscalibration.



Figure 6. Class-composition shift induced by Fink SuperNNova's selective abstention. The accepted set is enriched in SN Ia (+11.2%) and depleted in SN II (−8.6%) and SLSN (−3.3%) relative to the BTS sample. This biases the conditional ECE estimate by approximately +0.024 when reweighted to BTS prevalence (Section 5.2.2).



Figure 7. Zero-score distribution for Fink SuperNNova. Left: full score distribution with 444 objects (35.9%) at exactly zero and a hard gap of 0.005 to the first non-zero score. Right: non-zero score distribution for SN Ia and non-SN Ia objects, showing active discrimination when predictions are made (mean = 0.564, median = 0.664).

Table 4. NEEDLE Per-Class Calibration (Object-Level, $N = 278$)

Class	n_{true}	n_{pred}	Accuracy	Mean Conf.	Gap	Direction
SN	242	193	0.984	0.865	+0.119	Underconfident
SLSN-I	15	39	0.308	0.730	−0.423	Overconfident
TDE	21	46	0.457	0.752	−0.296	Overconfident

Note—Gap = Accuracy − Mean Confidence (when class is predicted). Positive gap: classifier is more accurate than confident (underconfident). Negative gap: classifier is more confident than accurate (overconfident). n_{pred} exceeds n_{true} for SLSN-I and TDE because many non-rare objects are misclassified into those categories.

0.048 [95% CI: 0.048, 0.111] and overall accuracy 80.2% (Brier = 0.265). This aggregate ECE lies at the boundary of the "well-calibrated" threshold (ECE < 0.05), a markedly better result than the model-instance ECE of 0.075 that inflates rare-class contributions due to repeated appearances across held-out sets (Section 5.3.4).

Figure 8 shows the object-level reliability diagram. The aggregate bars track the diagonal reasonably well, consistent with the low ECE. However, as the per-class analysis below reveals, this aggregate view conceals severe, class-specific miscalibration driven by class imbalance.

5.3.2. *Per-Class Miscalibration and Class Imbalance*

Table 4 and Figure 9 show the classwise calibration decomposition at the object level. The three classes exhibit fundamentally different calibration behavior:

SN (majority class, $n = 242$). SN predictions are underconfident: when NEEDLE predicts SN, it achieves 98.4% accuracy but assigns only 86.5% mean confidence (gap = +0.119). This is consistent with the systematic suppression of majority-class probabilities under inverse-frequency weighting, which upweights rare class gradients at the expense of the dominant class.

Table 5. NEEDLE Object-Level Silent Failures (≥90% confidence, wrong)

ZTF ID	Predicted	True	Confidence
ZTF20aagikvv	SN	SLSN-I	1.000
ZTF21aakjkec	SN	SLSN-I	0.9997
ZTF19abzoyeg	SN	SLSN-I	0.999
ZTF21aagnwkk	TDE	SN	0.901
ZTF21aautijg	SLSN-I	SN	0.907

Note—Three of five silent failures are true SLSN-I objects misclassified as SN at near-certainty confidence. This pattern is consistent with the class-imbalance mechanism: rare objects are predicted as majority class with extreme confidence when they fall outside the learned minority-class decision region.

SLSN-I (rare class, $n = 15$). SLSN-I predictions are severely overconfident: when NEEDLE predicts SLSN-I, it achieves only 30.8% accuracy but assigns 73.0% mean confidence (gap = −0.423). Critically, 39 objects are predicted as SLSN-I despite only 15 being truly SLSN-I—meaning 24 of these predictions are false positives issued with high confidence. This is the dominant failure mode of the classifier.

TDE (rare class, $n = 21$). TDE predictions are similarly overconfident: 45.7% accuracy against 75.2% mean confidence (gap = −0.296). Of 46 TDE predictions, 25 are false positives. The pattern is analogous to SLSN-I, consistent with the same inverse-frequency weighting mechanism.

The asymmetry—SN underconfident while both rare classes are overconfident—is the canonical signature of inverse-frequency class weighting identified by van den Goorbergh et al. (2022). The aggregate ECE of 0.048 conceals this because the majority-class underconfidence (SN, $n = 242$) partially cancels the minority-class overconfidence (SLSN-I + TDE, $n = 36$) in the weighted average.

5.3.3. *Silent Failures and Confidence-Accuracy Mismatch*

At the object level, five objects are classified with ≥90% confidence but are incorrect (silent failures, 1.8% of 278 objects). Table 5 lists these objects.

Three of the five silent failures (ZTF20aagikvv, ZTF21aakjkec, ZTF19abzoyeg) are true SLSN-I objects classified as SN with confidence > 0.998. These objects fall outside NEEDLE's learned SLSN-I decision boundary despite their spectroscopic confirmation; the inverse-frequency weighting inflates the SLSN-I probabilities for objects *within* the boundary while leaving ambiguous cases assigned entirely to the SN class with extreme confidence. For spectroscopic triage, a near-certainty SN prediction from NEEDLE carries an embedded risk: three independently spectroscopically confirmed SLSN-I objects were classified this way.

5.3.4. *Model-Instance Sensitivity: Robustness Across Held-Out Models*

As a sensitivity analysis, we evaluate all 429 model-instance predictions, treating each model's prediction on its held-out test objects as independent (see Section 6.5 for the deduplication methodology). The model-instance aggregate ECE is 0.075 [0.062, 0.115], with 17 silent failures (4.0%).

The higher model-instance ECE (0.075 vs. 0.048 object-level) reflects an artifact of the evaluation design: rare-class objects (SLSN-I, TDE) appear in many more models' held-out test sets than SN objects (mean 5.0 models per rare object vs. 1.03 for SN), inflating the effective rare-class sample weight and shifting the aggregate ECE upward. The 100% inter-model class agreement across all 43 multi-model objects—zero objects show disagreement in predicted class across models—validates that the averaging methodology used in the primary analysis is sound.

5.3.5. *Interpretation: Class Imbalance and Learned Biases*

The class-asymmetric miscalibration we observe is a direct consequence of NEEDLE's training procedure. Sheng et al. (2024) employ inverse-frequency class weighting to address the extreme imbalance between common supernovae and rare transients, with approximately 80× more SN training examples than TDE examples. van den Goorbergh et al. (2022) demonstrated that such corrections systematically inflate minority-class probability estimates, which is precisely the pattern we observe for both SLSN-I (gap = −0.423) and TDE (gap = −0.296).

Global temperature scaling with $T = 1.552$ *worsens* ECE from 0.073 to 0.169 (model-instance). This failure is expected: a single T cannot simultaneously soften overconfident SLSN-I/TDE predictions ($T > 1$ needed) and sharpen underconfident SN predictions ($T < 1$ needed). Kull et al. (2019) documented this fundamental limitation. Per-class temperature scaling yields $T_{\mathrm{SN}} = 1.85$, $T_{\mathrm{SLSN\text{-}I}} = 2.03$, and $T_{\mathrm{TDE}} = 0.54$, confirming the opposing calibration directions, but worsens every individual classwise ECE—indicating structural miscalibration incompatible with post-hoc probability rescaling.

5.4. *Comparative Overview*



Figure 8. Aggregate reliability diagram for NEEDLE at the object level ($N = 278$ unique objects). ECE = 0.048 places NEEDLE at the boundary of the "well-calibrated" threshold, but this aggregate view conceals severe per-class miscalibration (Table 4 and Figure 9).

Figure 11 presents the ECE comparison across all four classifiers. At the object level, NEEDLE (ECE = 0.048) is the only classifier to reach the "well-calibrated" threshold (ECE < 0.05) in its aggregate form, but this masks severe per-class miscalibration for the rare transient classes. ALeRCE's temperature-scaled ECE of 0.097 falls below the "acceptable" threshold (ECE < 0.10). Fink RF is excluded from calibration comparison due to regime mismatch. Fink SNN achieves conditional ECE 0.051 post-calibration, but at the cost of eliminating high-confidence selections. NEEDLE at the class level requires class-aware calibration approaches.

6. DISCUSSION

6.1. *Architecture Determines Calibration Failure Mode*

Our results demonstrate a clear relationship between classifier architecture and the nature of miscalibration. The ALeRCE Balanced Random Forest exhibits underconfidence consistent with the well-established calibration properties of ensemble methods (Niculescu-Mizil & Caruana 2005; Boström 2008; Loecher & Walters 2024). This is distinct from the overconfidence typically found in deep neural networks (Guo et al. 2017), highlighting the importance of architecture-specific calibration analysis rather than assuming universal overconfidence.

NEEDLE's class-asymmetric miscalibration represents a qualitatively different failure mode that is invisible to standard aggregate ECE. This finding aligns with Nixon et al. (2019), who demonstrated that aggregate calibration metrics can conceal per-class miscalibration, and with Kull et al. (2019), who showed that confidence-level reliability diagrams can appear well-calibrated even when classwise diagrams reveal significant problems. We recommend that future calibration analyses of multi-class astronomical classifiers always include per-class evaluation.

6.2. *The Failure of Temperature Scaling as a Diagnostic*

The failure of global temperature scaling for NEEDLE and Fink is itself informative. When temperature scaling worsens calibration, it indicates that the miscalibration is structural—arising from the model's architecture or training procedure—rather than a simple uniform shift in confidence. For NEEDLE, the opposing per-class temperatures ($T_{\rm SN} = 1.85$ versus $T_{\rm TDE} = 0.54$) directly trace the effect of inverse-frequency class weighting, confirming the mechanism identified by van den Goorbergh et al. (2022). For Fink SuperNNova, the optimal temperature $T = 3.65$ (on the 793 non-zero accepted predictions) produces a 72% conditional ECE reduction, but compresses scores into [0.191, 0.708] and eliminates all $p \geq 0.8$ predictions—an operationally null outcome at high thresholds that reflects honest uncertainty expression rather than improved discrimination.

These diagnostic patterns suggest a practical recommendation: apply temperature scaling not only as a correction method but as a probe of miscalibration structure. If $T \approx 1$, the classifier is approximately calibrated. If T converges to a finite value away from 1 and ECE improves, the miscalibration is uniform and fixable. If T hits a bound or worsens ECE, deeper architectural or training-level interventions are needed.

6.3. *Implications for Spectroscopic Follow-up*

Uncalibrated probabilities have direct, quantifiable consequences for follow-up allocation. Table 6 shows the effect of calibration on ALeRCE follow-up decisions at various probability thresholds.

The operational impact is stark. At a $p > 0.8$ follow-up threshold—a reasonable requirement for committing telescope time—only 20 objects pass using raw probabilities, because ALeRCE's confidence never exceeds $\sim$0.75. After calibration, 425 objects pass at 91.1% precision: a 21$\times$ increase in usable classifications.

For NEEDLE, the operational concern is SLSN-I overconfidence. When the classifier predicts SLSN-I, the



Figure 9. Per-class reliability diagrams for NEEDLE revealing class-asymmetric miscalibration hidden by the aggregate ECE. SN is underconfident (bars above diagonal); SLSN-I is severely overconfident (high-confidence bars below diagonal, especially near 1.0); TDE is overconfident. This asymmetry arises directly from inverse-frequency class weighting during training.



Figure 10. Comparison of NEEDLE calibration at model-instance level ($N = 429$) and object level ($N = 278$, primary). Left: aggregate ECE with 95% bootstrap confidence intervals. Right: per-class ECE for SN, SLSN-I, and TDE. The object-level ECE is lower in aggregate because rare-class objects (which are more miscalibrated) appear in fewer models' test sets when counted once per object.

mean confidence is 73.0% but the true accuracy is only 30.8% (per-class gap $= -0.423$), exemplifying how inverse-frequency class weighting shifts learned decision boundaries without adjusting confidence calibration. For spectroscopic triage, this means: an SLSN-I prediction carries only ∼31% prior probability of being correct, far below the stated confidence. Astronomers relying on this classifier for rare-object discovery must understand this behavior. Three silently failing SLSN-I objects (ZTF20aagikvv, ZTF21aakjkec, ZTF19abzoyeg) are classified as SN at near-certainty confidence ($>$ 0.998), meaning per-class reliability diagrams—not just aggregate ECE—are essential for operational trust.

The ALeRCE result generalizes only to underconfident classifiers. For overconfident classifiers, calibration produces the opposite operational consequence. Fink SuperNNova's pre-calibration score distribution spans [0.005, 0.962] with 209 BTS objects passing $p \geq 0.8$ at 73.2% precision. Temperature scaling with $T = 3.65$ reduces conditional ECE by 72% but compresses the score distribution to [0.191, 0.708], eliminating all $p \geq 0.8$ predictions (Table 3). The ECE improvement is real in the calibration sense—a stated 0.6 post-T score corresponds to 60% empirical SN Ia rate—but operationally it reflects the classifier honestly expressing its inherent uncertainty rather than gaining discriminative power. For high-precision triage, pre-calibration scores remain operationally useful despite their miscalibration. We therefore recommend that broker outputs be reported with both calibration metrics and threshold-curve diagnostics, because calibration alone does not determine operational utility for overconfident classifiers.



Figure 11. ECE comparison across all four production classifiers. NEEDLE (object-level, ECE = 0.048) is the only classifier to meet the "well-calibrated" threshold (dotted line), but this conceals class-level miscalibration for SLSN-I and TDE. Only ALeRCE, after temperature scaling, meets the "acceptable" threshold (ECE < 0.10, dashed line). Error bars show 95% bootstrap confidence intervals.

Table 6. Follow-up Decisions Before and After Calibration

Threshold	Raw (uncalibrated)		Calibrated ($T = 0.357$)	
$p >$	N pass	Precision	N pass	Precision
0.5	392	0.898	972	0.784
0.6	134	0.940	812	0.828
0.7	40	1.000	627	0.871
0.8	20	1.000	425	0.911
0.9	1	1.000	194	0.948

Note—N pass: number of objects exceeding the confidence threshold. Precision: fraction of those objects correctly classified. Based on 1,114 ALeRCE predictions with stratified 5-fold cross-validated temperature scaling.

6.4. *Implications for LSST*

With LSST's first alerts already issued and the full survey beginning in 2026, the calibration problems we identify in ZTF-era classifiers demand immediate attention. The greater diversity of transient types, the increased class imbalance (rarer classes become proportionally rarer in a larger survey), and the higher volume of alerts all exacerbate miscalibration risk. Our findings suggest three concrete recommendations:

First, broker teams should publish calibration metrics alongside classification performance. ECE, reliability diagrams, and Brier scores should be standard evaluation outputs, not afterthoughts.

Second, post-hoc calibration should be architecture-aware. Temperature scaling is appropriate for Random Forest classifiers but can be counterproductive for class-weighted neural networks. Class-aware methods such as Dirichlet calibration (Kull et al. 2019) or focal calibration (Mukhoti et al. 2020) may be more appropriate for classifiers with extreme class imbalance.

Third, calibration should be evaluated on real survey data, not only on simulated datasets. Our finding that Fink's RF produces 94% zero scores when evaluated on BTS objects—behavior that would not appear in simulated data designed to match the classifier's training distribution—illustrates the gap between simulated and operational calibration.

6.5. *Robustness Checks*

We performed five robustness checks to verify that primary findings are not artefacts of data processing or methodological choices.

ALeRCE class restriction. Restricting ALeRCE's 15-class output to the 4-class transient subset does not drive the observed miscalibration: the 4-class renormalized ECE (0.271) matches the native 15-class ECE (0.283) within 4%, with negligible per-class probability inflation (1.02–1.06×). The 15-class analysis serves as a

harder baseline (more classes, lower accuracy) confirming the 4-class restriction is conservative.

NEEDLE object-level deduplication. The NEEDLE evaluation set contains 429 model-instance predictions across 278 unique objects, with 43 objects appearing in two or more held-out test sets. Deduplicating to object level via mean-of-model-probabilities yields ECE = 0.048 (model-instance: 0.075), a 36% reduction. The 100% inter-model class agreement across all 43 multi-model objects (zero class disagreements) validates the averaging methodology: model variance in predicted class is zero, and confidence uncertainty dominates. Per-class miscalibration patterns persist in both analyses. Object-level results are primary; model-instance results are reported in §5.3.4.

ALeRCE operational gain: held-out cross-validation. The paper's 21× operational gain (20 → 425 objects at $p > 0.80$) was originally computed on the full dataset with temperature $T = 0.357$. To address potential data leakage, we recomputed with stratified 5-fold cross-validation: T fitted on four folds, gain measured on the held-out fold. The pooled held-out result (20 → 418 objects, gain = 20.9×, precision = 0.907) is essentially identical to the full-dataset claim, because T is a single scalar that converges to 0.357 ± 0.012 regardless of which fold trains it. Per-fold gain shows high variance ($30 \times \pm 23\times$) due to tiny pre-scaling counts per fold (1–6 objects), but the pooled estimate is the appropriate metric (Figure 12).

Fink RF calibration method comparison: not applicable. We initially evaluated temperature scaling, Platt scaling, and isotonic regression on Fink RF's 76 non-zero predictions (5-fold CV) and observed nominal ECE values of 0.175 (T-scaling), 0.198 (Platt), and 0.123 (isotonic). However, because the 76 non-zero objects are an idiosyncratic subset of BTS that happened to pass the early-classifier eligibility gate (Section 5.2.1), this comparison does not reflect calibration performance on the intended Fink RF target population. We therefore omit Fink RF calibration-method recommendations from this paper and recommend that future calibration audits of the early-classifier evaluate on alert-stream samples within its design regime. Figure 13 is retained in Appendix B for transparency.

Bin-count sensitivity. ECE was computed at 5, 10, 15, and 20 equal-mass bins for all classifiers (Figure 14). ALeRCE ($N = 1114$) shows zero relative variation (0.0%), Fink SNN ($N = 793$) 6.3%, and Fink RF ($N = 76$) 9.2%, all below the "acceptable" threshold of 10%. NEEDLE ($N = 278$, 3 classes) shows 56.5% relative variation due to small sample size and rare-class imbalance: with 15 bins, only ≈18 objects occupy each bin, and the 15 SLSN-I and 21 TDE true objects span fractional bins. The wide CI $[0.048, 0.111]$ already captures this bin-count uncertainty; the 15-bin point estimate of 0.048 is neither the minimum nor maximum across bin counts (0.036 at 5–10 bins; 0.061 at 20 bins). For large-sample classifiers, 15 bins is well within the stable region.

6.6. *Limitations*

Several limitations should be noted. Our ground truth is limited to spectroscopically confirmed objects from BTS, which is itself magnitude-limited and subject to selection effects. The stratified sampling may not capture the full range of classifier behavior across the alert stream. For NEEDLE, our evaluation uses predictions from five models on their respective held-out test sets, which may not represent the classifier's performance on the broader alert stream.

The small sample sizes for rare classes at the object level ($n = 15$ SLSN-I, $n = 21$ TDE for NEEDLE) limit the statistical power of per-class calibration analysis. We emphasise that per-class reliability diagrams for these rare classes should be interpreted as indicating the *direction* of miscalibration (overconfident vs. underconfident) rather than as precise ECE estimates. The wide confidence intervals on the aggregate NEEDLE ECE [0.048, 0.111] reflect this fundamental sample-size constraint. More flexible calibration methods such as isotonic regression or Dirichlet calibration require larger samples to fit reliably (Vaicenavicius et al. 2019), which is why we do not attempt them here.

Our analysis uses the most recent alert for each Fink object, corresponding to the most complete light curve. In operational use, astronomers require classification decisions early in a transient's evolution, when light curves are incomplete and classifier confidence is lower. How calibration varies as a function of light curve completeness is a natural and important extension of this work, particularly for LSST where early classification will be critical.

The pseudo-logit transformation $z_k = \log p_k$ used to apply temperature scaling to Random Forest outputs lacks formal theoretical justification—temperature scaling was designed for softmax-based neural network outputs, not ensemble vote fractions. While the consistent cross-validated improvement (ECE reduction from 0.276 to 0.097 with T variance of ± 0.012) suggests the transformation is empirically effective, future work could compare alternative transformations such as Platt scaling applied directly to vote fractions.

Finally, even equal-mass ECE is a biased estimator of true calibration error (Roelofs et al. 2022). We re-

port bootstrap confidence intervals throughout to quantify estimation uncertainty. Bin-count sensitivity analysis (§6.5) shows that ECE is stable for all classifiers at large sample sizes; for NEEDLE ($N = 278$) the wide CI $[0.048, 0.111]$ already subsumes bin-count uncertainty.

7. CONCLUSIONS

We have presented the first systematic calibration audit of production machine learning classifiers deployed on ZTF transient alert streams. Our key findings are:

1. No production transient classifier currently publishes calibration metrics, yet astronomers routinely use their probability outputs for follow-up decisions.

2. ALeRCE's Balanced Random Forest is systematically underconfident (ECE = 0.271), consistent with known RF calibration behavior. Temperature scaling with $T = 0.357$ reduces ECE to 0.097 (65% improvement), increasing the number of objects passing a $p > 0.8$ follow-up threshold from 20 to 425 at 91% precision.

3. Fink's two classifiers exhibit fundamentally different behavior on BTS objects. The Random Forest, designed for early-time alert classification, abstains on 93.9% of BTS objects in a near-uniform pattern across classes—operational regime mismatch rather than miscalibration. SuperNNova exhibits implicit selective classification with class-dependent abstention (non-Ia transients abstain at 2.6× the SN Ia rate, χ^2 $p < 10^{-36}$), emitting non-zero scores for 64.1% of objects with conditional ECE 0.183. Temperature scaling reduces conditional ECE to 0.051 ($T = 3.65$) but eliminates all $p \geq 0.8$ predictions, producing operationally null calibration at high thresholds. Pre-calibration SuperNNova scores remain useful for high-precision triage (209 objects at $p \geq 0.8$ with 73% precision) despite formal miscalibration.

4. NEEDLE achieves aggregate ECE = 0.048 at the object level ($N = 278$ unique objects), meeting the well-calibrated threshold—but per-class analysis reveals severe class-imbalance-driven miscalibration. SLSN-I predictions are issued with 73% mean confidence but only 31% accuracy (gap $= -0.423$), and three true SLSN-I objects are classified as SN with near-certainty confidence ($>$ 0.998). TDE predictions show similar overconfidence (gap $= -0.296$). Global temperature scaling worsens calibration, and per-class scaling worsens every individual class—indicating structural miscalibration that post-hoc methods cannot resolve.

5. The failure mode of temperature scaling is itself diagnostic: worsening ECE indicates structural miscalibration requiring architectural intervention, not post-hoc correction.

As time-domain astronomy enters the LSST era, calibrated probabilities are essential for optimal spectroscopic resource allocation. We recommend that broker teams adopt calibration evaluation as a standard component of classifier assessment, using proper scoring rules and per-class reliability analysis.

DATA AND CODE AVAILABILITY

All analysis code, data acquisition scripts, and results are publicly available at https://github.com/pallavi-2000/transient-calibration-audit. The repository includes scripts to reproduce all figures and tables from the raw data. Spectroscopic ground truth is drawn from the publicly accessible ZTF Bright Transient Survey (Fremling et al. 2020; Perley et al. 2020). ALeRCE and Fink predictions were obtained via their respective public APIs. NEEDLE predictions were generated using publicly available pre-trained models and datasets.

We thank Matt Nicholl for encouragement and for suggesting connections with the NEEDLE team, and Xinyue Sheng for making the NEEDLE models and dataset publicly available. This work made use of the ALeRCE broker (Förster et al. 2021), the Fink broker (Möller et al. 2021), and data from the ZTF Bright Transient Survey (Fremling et al. 2020; Perley et al. 2020). This research has made use of NASA's Astrophysics Data System.

Software: `NumPy` (Harris et al. 2020), `SciPy` (Virtanen et al. 2020), `pandas` (McKinney 2010), `Matplotlib` (Hunter 2007), `TensorFlow` (Abadi et al. 2016)

REFERENCES

Abadi, M., et al. 2016, in Proceedings of the 12th USENIX Symposium on Operating Systems Design and Implementation, 265–283

Bellm, E. C., et al. 2019, PASP, 131, 018002, doi: 10.1088/1538-3873/aaecbe

Boström, H. 2008, in 2008 Seventh International Conference on Machine Learning and Applications (IEEE), 121–126, doi: 10.1109/ICMLA.2008.107

Brier, G. W. 1950, Monthly Weather Review, 78, 1

Chen, C., Liaw, A., & Breiman, L. 2004, in University of California, Berkeley Technical Report, 666

Dawid, A. P. 1982, Journal of the American Statistical Association, 77, 605

de Soto, K. D., et al. 2024, ApJ, 974, 169, doi: 10.3847/1538-4357/ad6869

Fang, L., & Orabona, F. 2020, in IEEE International Conference on Pattern Recognition

Fernando, T., & Tsokos, C. P. 2021, IEEE Transactions on Neural Networks and Learning Systems, 33, 2940, doi: 10.1109/TNNLS.2020.3047335

Förster, F., et al. 2021, AJ, 161, 242, doi: 10.3847/1538-3881/abe9bc

Fremling, C., et al. 2020, ApJ, 895, 32, doi: 10.3847/1538-4357/ab8943

Gneiting, T., & Raftery, A. E. 2007, Journal of the American Statistical Association, 102, 359, doi: 10.1198/016214506000001437

Guo, C., Pleiss, G., Sun, Y., & Weinberger, K. Q. 2017, in Proceedings of the 34th International Conference on Machine Learning (PMLR), 1321–1330

Harris, C. R., et al. 2020, Nature, 585, 357, doi: 10.1038/s41586-020-2649-2

Hunter, J. D. 2007, Computing in Science & Engineering, 9, 90, doi: 10.1109/MCSE.2007.55

Ivezić, Ž., et al. 2019, ApJ, 873, 111, doi: 10.3847/1538-4357/ab042c

Kull, M., Perello-Nieto, M., Kängsepp, M., et al. 2019, in Advances in Neural Information Processing Systems, Vol. 32

Leoni, B., et al. 2022, A&A, 663, A13, doi: 10.1051/0004-6361/202142715

Loecher, M., & Walters, S. 2024, Diagnostic and Prognostic Research, 8, 7, doi: 10.1186/s41512-024-00177-1

McKinney, W. 2010, in Proceedings of the 9th Python in Science Conference, 56–61

Möller, A., & de Boissière, T. 2020, MNRAS, 491, 4277, doi: 10.1093/mnras/stz3312

Möller, A., et al. 2021, MNRAS, 501, 3272, doi: 10.1093/mnras/staa3602

Mukhoti, J., Kulharia, V., Sanber, A., Torr, P. H. S., & Dokania, P. K. 2020, in Advances in Neural Information Processing Systems, Vol. 33

Naeini, M. P., Cooper, G. F., & Hauskrecht, M. 2015, in Proceedings of the AAAI Conference on Artificial Intelligence, Vol. 29, 2901–2907

Narayan, G., et al. 2018, ApJS, 236, 9, doi: 10.3847/1538-4365/aab781

Niculescu-Mizil, A., & Caruana, R. 2005, in Proceedings of the 22nd International Conference on Machine Learning (ACM), 625–632

Nixon, J., Dusenberry, M. W., Zhang, L., Jerfel, G., & Tran, D. 2019, in CVPR Workshops, 38–41

Pavez-Herrera, D., et al. 2025, A&A, 696, A153, doi: 10.1051/0004-6361/202451951

Perley, D. A., et al. 2020, ApJ, 904, 35, doi: 10.3847/1538-4357/abbd98

Platt, J. C. 1999, in Advances in Large Margin Classifiers (MIT Press), 61–74

Roelofs, R., Cain, N., Shlens, J., & Mozer, M. C. 2022, in Proceedings of the 25th International Conference on Artificial Intelligence and Statistics (PMLR)

Sánchez-Sáez, P., et al. 2021, AJ, 161, 141, doi: 10.3847/1538-3881/abd5c1

Sheng, X., et al. 2024, MNRAS, 531, 2474, doi: 10.1093/mnras/stae1253

Smith, K. W., et al. 2019, Research Notes of the AAS, 3, 26, doi: 10.3847/2515-5172/ab020f

Tung, A. 2025, arXiv e-prints. https://arxiv.org/abs/2511.00614

Vaicenavicius, J., Widmann, D., Andersson, C., et al. 2019, arXiv e-prints. https://arxiv.org/abs/1902.06977

van den Goorbergh, R., van Smeden, M., Timmerman, D., & Zwinderman, A. H. 2022, Journal of the American Medical Informatics Association, 29, 1525, doi: 10.1093/jamia/ocac093

Virtanen, P., et al. 2020, Nature Methods, 17, 261, doi: 10.1038/s41592-019-0686-2



Figure 12. Cross-validated operational gain for ALeRCE temperature scaling (5-fold stratified CV). *Left*: temperature T per fold; mean $T = 0.357 \pm 0.012$ is virtually identical to the full-dataset estimate, confirming that the scalar calibration parameter is insensitive to training-set composition and that no data leakage inflates the paper's operational gain claim. *Centre*: per-fold and pooled gain factor at $p > 0.80$; the pooled held-out result ($20 \rightarrow 418$ objects, gain $= 20.9\times$) matches the paper claim of $21\times$. High per-fold variance (15–$76\times$) arises because the pre-scaling count per fold is 1–6 objects. *Right*: per-fold ECE before (0.276 ± 0.033) and after (0.097 ± 0.016) temperature scaling, consistent with the full-dataset improvement.



Figure 13. Comparison of three post-hoc calibration methods for Fink RF non-zero predictions ($N = 76$, 5-fold CV). Temperature scaling (ECE $= 0.175 \pm 0.055$), Platt scaling (ECE $= 0.198 \pm 0.096$), and isotonic regression (ECE $= 0.123 \pm 0.058$) all reduce ECE from the raw value of 0.324. Isotonic regression achieves the lowest point estimate but with the highest variance; the overlapping uncertainty ranges and risk of overfitting on $\approx$12 test objects per fold make temperature scaling the more conservative recommendation at $N = 76$.

APPENDIX

A. CROSS-VALIDATED OPERATIONAL GAIN (ALERCE)

B. CALIBRATION METHOD COMPARISON FOR FINK RF

C. BIN-COUNT SENSITIVITY ANALYSIS



Figure 14. ECE as a function of bin count (5, 10, 15, 20 equal-mass bins) for all four classifiers. ALeRCE ($N = 1114$): 0.0% relative variation (excellent). Fink RF ($N = 76$): 9.2% (acceptable). Fink SNN ($N = 793$): 6.3% (acceptable). NEEDLE ($N = 278$): 56.5% (poor, driven by small sample and rare-class imbalance). The dashed vertical line marks the paper's choice of 15 bins; it is neither a minimum nor maximum for any classifier, and the choice is well within the stable region for ALeRCE and Fink SNN. For NEEDLE, the wide bootstrap CI $[0.048, 0.111]$ already subsumes the bin-count uncertainty.