File Edit View Query Database Server Tools Scripting Help

Navigator

SCHEMAS

Filter objects

- dummy
- **dummy1**
  - Tables
  - Views
  - Stored Procedures
  - Functions
- sys

Administration Schemas

Information

No object selected

Query 1

Limit to 1000 rows

```
use dummy1;
CREATE TABLE student (
    id INT PRIMARY KEY,
    name VARCHAR(50),
    department VARCHAR(30),
    marks INT,
    created_at DATETIME
);
```

SQLAdditions

Jump to

Automatic context help is disab
Use the toolbar to manually get
for the current caret position o
toggle automatic help.

Context Help Snippets

Output

Action Output

#	Time	Action	Message	Duration
1	09:42:52	use dummy1	0 row(s) affected	0.000 sec
2	09:42:56	CREATE TRIGGER trigger_name BEFORE INSERT ON table_name FOR EACH ROW BEGIN -- SQL statemen...	Error Code: 1146. Table 'dummy1.table_name' doesn't exist	0.078 sec
3	09:50:27	CREATE TABLE student (id INT PRIMARY KEY, name VARCHAR(50), department VARCHAR(30), m...	0 row(s) affected	0.188 sec

File Edit View Query Database Server Tools Scripting Help

Navigator

SCHEMAS

Filter objects

- dummy
- **dummy1**
  - Tables
  - Views
  - Stored Procedures
  - Functions
- sys

Administration Schemas

Query 1

Limit to 1000 rows

```sql
use dummy1;
CREATE TABLE student (
    id INT PRIMARY KEY,
    name VARCHAR(50),
    department VARCHAR(30),
    marks INT,
    created_at DATETIME
);
INSERT INTO student (id, name, department, marks)
VALUES
(1, 'Ravi', 'CSE', 78),
(2, 'Anita', 'ECE', 85);
```

SQL Additions

Jump to

Automatic context help is disabled. Use the toolbar to manually get help for the current caret position or to toggle automatic help.

Context Help Snippets

Information

No object selected

Object Info Session

Output

Action Output

#	Time	Action	Message	Duration / Fetch
1	09:42:52	use dummy1	0 row(s) affected	0.000 sec
2	09:42:56	CREATE TRIGGER trigger_name BEFORE INSERT ON table_name FOR EACH ROW BEGIN -- SQL statemen...	Error Code: 1146. Table 'dummy1.table_name' doesn't exist	0.078 sec
3	09:50:27	CREATE TABLE student (id INT PRIMARY KEY, name VARCHAR(50), department VARCHAR(30), m...	0 row(s) affected	0.188 sec
4	09:52:19	INSERT INTO student (id, name, department, marks) VALUES (1, 'Ravi', 'CSE', 78), (2, 'Anita', 'ECE', 85)	2 row(s) affected Records: 2 Duplicates: 0 Warnings: 0	0.032 sec

File Edit View Query Database Server Tools Scripting Help

Navigator

SCHEMAS

Filter objects

- dummy
- **dummy1**
  - Tables
  - Views
  - Stored Procedures
  - Functions
- sys

Query 1

Limit to 1000 rows

```
    created_at DATETIME
);
INSERT INTO student (id, name, department, marks)
VALUES
(1, 'Ravi', 'CSE', 78),
(2, 'Anita', 'ECE', 85);
SELECT * FROM student;
```

Result Grid | Filter Rows: | Edit: | Export/Import: | Wrap Cell Content:

id	name	department	marks	created_at
1	Ravi	CSE	78	NULL
2	Anita	ECE	85	NULL
NULL	NULL	NULL	NULL	NULL

File Edit View Query Database Server Tools Scripting Help

Navigator

SCHEMAS

Filter objects

- dummy
- **dummy1**
  - Tables
  - Views
  - Stored Procedures
  - Functions
- sys

Administration Schemas

Information

No object selected

Object Info Session

Query 1

Limit to 1000 rows

```
8   );
9   INSERT INTO student (id, name, department, marks)
10  VALUES
11  (1, 'Ravi', 'CSE', 78),
12  (2, 'Anita', 'ECE', 85);
13  SELECT * FROM student;
14  DELIMITER $$
15
16  CREATE TRIGGER trg_student_insert
17  BEFORE INSERT ON student
18  FOR EACH ROW
19  BEGIN
20      SET NEW.created_at = NOW();
21  END$$
22
23  DELIMITER ;
24
25
26
27
```

SQLAdditions

Jump to

Automatic context help is disabled. Use the toolbar to manually get help for the current caret position or to toggle automatic help.

Context Help Snippets

Output

Action Output

#	Time	Action	Message	Duration / Fetch
1	09:42:52	use dummy1	0 row(s) affected	0.000 sec
2	09:42:56	CREATE TRIGGER trigger_name BEFORE INSERT ON table_name FOR EACH ROW BEGIN -- SQL stateme...	Error Code: 1146. Table 'dummy1.table_name' doesn't exist	0.078 sec
3	09:50:27	CREATE TABLE student (id INT PRIMARY KEY, name VARCHAR(50), department VARCHAR(30), m...	0 row(s) affected	0.188 sec
4	09:52:19	INSERT INTO student (id, name, department, marks) VALUES (1, 'Ravi', 'CSE', 78), (2, 'Anita', 'ECE', 85)	2 row(s) affected Records: 2 Duplicates: 0 Warnings: 0	0.032 sec
5	09:52:48	SELECT * FROM student LIMIT 0, 1000	2 row(s) returned	0.000 sec / 0.000 sec
6	09:53:23	CREATE TRIGGER trg_student_insert BEFORE INSERT ON student FOR EACH ROW BEGIN SET NEW.cr...	0 row(s) affected	0.031 sec

File Edit View Query Database Server Tools Scripting Help

Navigator

SCHEMAS

Filter objects

- dummy
- dummy1
  - Tables
  - Views
  - Stored Procedures
  - Functions
- sys

Administration Schemas

Query 1

Limit to 1000 rows

```
10  VALUES
11  (1, 'Ravi', 'CSE', 78),
12  (2, 'Anita', 'ECE', 85);
13  SELECT * FROM student;
14  DELIMITER $$
15
16  CREATE TRIGGER trg_student_insert
17  BEFORE INSERT ON student
18  FOR EACH ROW
19  BEGIN
20      SET NEW.created_at = NOW();
21  END$$
22
23  DELIMITER ;
24  INSERT INTO student (id, name, department, marks)
25  VALUES (3, 'Kumar', 'CSE', 90);
26
27
28
29
```

SQL Additions

Jump to

Automatic context help is disabled. Use the toolbar to manually get help for the current caret position or to toggle automatic help.

Context Help Snippets

Information

No object selected

Object Info Session

Output

Action Output

#	Time	Action	Message	Duration / Fetch
2	09:42:56	CREATE TRIGGER trigger_name BEFORE INSERT ON table_name FOR EACH ROW BEGIN – SQL state...	Error Code: 1146. Table 'dummy1.table_name' doesn't exist	0.078 sec
3	09:50:27	CREATE TABLE student (id INT PRIMARY KEY, name VARCHAR(50), department VARCHAR(30), ...	0 row(s) affected	0.188 sec
4	09:52:19	INSERT INTO student (id, name, department, marks) VALUES (1, 'Ravi', 'CSE', 78), (2, 'Anita', 'ECE', 85)	2 row(s) affected Records: 2 Duplicates: 0 Warnings: 0	0.032 sec
5	09:52:48	SELECT * FROM student LIMIT 0, 1000	2 row(s) returned	0.000 sec / 0.000 sec
6	09:53:23	CREATE TRIGGER trg_student_insert BEFORE INSERT ON student FOR EACH ROW BEGIN SET NEW....	0 row(s) affected	0.031 sec
7	09:54:02	INSERT INTO student (id, name, department, marks) VALUES (3, 'Kumar', 'CSE', 90)	1 row(s) affected	0.015 sec

```
25      VALUES (3, 'Kumar', 'CSE', 90);
26 •    SELECT * FROM student;
```

Result Grid | Filter Rows: | Edit: | Export/Import: | Wrap Cell Content:

id	name	department	marks	created_at
1	Ravi	CSE	78	NULL
2	Anita	ECE	85	NULL
3	Kumar	CSE	90	2026-02-02 09:54:02
NULL	NULL	NULL	NULL	NULL

File Edit View Query Database Server Tools Scripting Help

Navigator

SCHEMAS

Filter objects

- dummy
- **dummy1**
  - Tables
  - Views
  - Stored Procedures
  - Functions
- sys

Administration Schemas

Query 1

Limit to 1000 rows

```
DELIMITER $$

CREATE TRIGGER trg_student_insert
BEFORE INSERT ON student
FOR EACH ROW
BEGIN
    SET NEW.created_at = NOW();
END$$

DELIMITER ;
INSERT INTO student (id, name, department, marks)
VALUES (3, 'Kumar', 'CSE', 90);
SELECT * FROM student;
CREATE INDEX idx_department
ON student(department);
```

SQL Additions

Jump to

Automatic context help is disabled. Use the toolbar to manually get help for the current caret position or to toggle automatic help.

Context Help Snippets

Information

No object selected

Object Info Session

Output

Action Output

#	Time	Action	Message	Duration / Fetch
4	09:52:19	INSERT INTO student (id, name, department, marks) VALUES (1, 'Ravi', 'CSE', 78), (2, 'Anita', 'ECE', 85)	2 row(s) affected Records: 2 Duplicates: 0 Warnings: 0	0.032 sec
5	09:52:48	SELECT * FROM student LIMIT 0, 1000	2 row(s) returned	0.000 sec / 0.000 sec
6	09:53:23	CREATE TRIGGER trg_student_insert BEFORE INSERT ON student FOR EACH ROW BEGIN SET NEW....	0 row(s) affected	0.031 sec
7	09:54:02	INSERT INTO student (id, name, department, marks) VALUES (3, 'Kumar', 'CSE', 90)	1 row(s) affected	0.015 sec
8	09:54:52	SELECT * FROM student LIMIT 0, 1000	3 row(s) returned	0.000 sec / 0.000 sec
9	09:55:21	CREATE INDEX idx_department ON student(department)	0 row(s) affected Records: 0 Duplicates: 0 Warnings: 0	0.078 sec

```
29 •  SELECT * FROM student
30    WHERE department = 'CSE';
```

Result Grid | Filter Rows: | Edit: | Export/Import: | Wrap Cell Content:

id	name	department	marks	created_at
1	Ravi	CSE	78	NULL
3	Kumar	CSE	90	2026-02-02 09:54:02
NULL	NULL	NULL	NULL	NULL

File Edit View Query Database Server Tools Scripting Help

Navigator

SCHEMAS

Filter objects

- dummy
- **dummy1**
  - Tables
  - Views
  - Stored Procedures
  - Functions
- sys

Administration Schemas

Query 1

Limit to 1000 rows

```
21  END$$
22
23  DELIMITER ;
24  INSERT INTO student (id, name, department, marks)
25  VALUES (3, 'Kumar', 'CSE', 90);
26  SELECT * FROM student;
27  CREATE INDEX idx_department
28  ON student(department);
29  SELECT * FROM student
30  WHERE department = 'CSE';
31  CREATE VIEW cse_students AS
32  SELECT name, marks
33  FROM student
34  WHERE department = 'CSE';
35
36
37
38
39
40
```

SQLAdditions

Jump to

Automatic context help is disabled. Use the toolbar to manually get help for the current caret position or to toggle automatic help.

Context Help Snippets

Information

No object selected

Object Info Session

Output

Action Output

#	Time	Action	Message	Duration / Fetch
6	09:53:23	CREATE TRIGGER trg_student_insert BEFORE INSERT ON student FOR EACH ROW BEGIN SET NEW....	0 row(s) affected	0.031 sec
7	09:54:02	INSERT INTO student (id, name, department, marks) VALUES (3, 'Kumar', 'CSE', 90)	1 row(s) affected	0.015 sec
8	09:54:52	SELECT * FROM student LIMIT 0, 1000	3 row(s) returned	0.000 sec / 0.000 sec
9	09:55:21	CREATE INDEX idx_department ON student(department)	0 row(s) affected Records: 0 Duplicates: 0 Warnings: 0	0.078 sec
10	09:55:45	SELECT * FROM student WHERE department = 'CSE' LIMIT 0, 1000	2 row(s) returned	0.000 sec / 0.000 sec
11	09:56:09	CREATE VIEW cse_students AS SELECT name, marks FROM student WHERE department = 'CSE'	0 row(s) affected	0.016 sec

```
35 •  SELECT * FROM cse_students;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

name	marks
Ravi	78
Kumar	90

e Edit View Query Database Server Tools Scripting Help

avigator

CHEMAS

Filter objects

- dummy
- **dummy1**
  - Tables
  - Views
  - Stored Procedures
  - Functions
- sys

Query 1

Limit to 1000 rows

```
WHERE department = 'CSE';
CREATE VIEW cse_students AS
SELECT name, marks
FROM student
WHERE department = 'CSE';
SELECT * FROM cse_students;
SELECT AVG(marks) AS average_marks FROM student;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

average_marks
84.3333

File Edit View Query Database Server Tools Scripting Help

Navigator

SCHEMAS

Filter objects

- dummy
- **dummy1**
  - Tables
  - Views
  - Stored Procedures
  - Functions
- sys

Query 1

Limit to 1000 rows

```
CREATE VIEW cse_students AS
SELECT name, marks
FROM student
WHERE department = 'CSE';
SELECT * FROM cse_students;
SELECT AVG(marks) AS average_marks FROM student;
SELECT MAX(marks) AS highest_marks FROM student;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

highest_marks
90

File Edit View Query Database Server Tools Scripting Help

Navigator

SCHEMAS

Filter objects

- dummy
- **dummy1**
  - Tables
  - Views
  - Stored Procedures
  - Functions
- sys

Query 1

Limit to 1000 rows

```
32  SELECT name, marks
33
34  WHERE department = 'CSE';
35  SELECT * FROM cse_students;
36  SELECT AVG(marks) AS average_marks FROM student;
37  SELECT MAX(marks) AS highest_marks FROM student;
38  SELECT COUNT(*) AS total_students FROM student;
```

Execute the selected portion of the script or everything, if there is no selection

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

total_students
3

File Edit View Query Database Server Tools Scripting Help

Navigator

SCHEMAS

Filter objects

- dummy
- dummy1
  - Tables
  - Views
  - Stored Procedures
  - Functions
- sys

Administration Schemas

Query 1

Limit to 1000 rows

```
43  DETERMINISTIC
44  BEGIN
45      IF m >= 40 THEN
46          RETURN 'PASS';
47      ELSE
48          RETURN 'FAIL';
49      END IF;
50  END$$
51
52  DELIMITER ;
53
54
55
56
57
58
59
60
61
62
```

SQLAdditions

Jump to

Automatic context help is disabled. Use the toolbar to manually get help for the current caret position or to toggle automatic help.

Context Help Snippets

Information

No object selected

Object Info Session

Output

Action Output

#	Time	Action	Message	Duration / Fetch
11	09:56:09	CREATE VIEW cse_students AS SELECT name, marks FROM student WHERE department = 'CSE'	0 row(s) affected	0.016 sec
12	09:56:33	SELECT * FROM cse_students LIMIT 0, 1000	2 row(s) returned	0.000 sec / 0.000 sec
13	09:57:12	SELECT AVG(marks) AS average_marks FROM student LIMIT 0, 1000	1 row(s) returned	0.000 sec / 0.000 sec
14	09:57:50	SELECT MAX(marks) AS highest_marks FROM student LIMIT 0, 1000	1 row(s) returned	0.000 sec / 0.000 sec
15	09:58:24	SELECT COUNT(*) AS total_students FROM student LIMIT 0, 1000	1 row(s) returned	0.000 sec / 0.000 sec
16	09:59:08	CREATE FUNCTION result_status(m INT) RETURNS VARCHAR(10) DETERMINISTIC BEGIN IF m >= 40 ...	0 row(s) affected	0.047 sec

File Edit View Query Database Server Tools Scripting Help

Navigator

SCHEMAS

Filter objects

- dummy
- **dummy1**
  - Tables
  - Views
  - Stored Procedures
  - Functions
- sys

Query 1

Limit to 1000 rows

```
48          RETURN 'FAIL';
49
50      END$$
51
52      DELIMITER ;
53      SELECT name, marks, result_status(marks) AS result
54      FROM student;
```

Execute the selected portion of the script or everything, if there is no selection

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

name	marks	result
Ravi	78	PASS
Anita	85	PASS
Kumar	90	PASS

File Edit View Query Database Server Tools Scripting Help

Navigator

SCHEMAS

Filter objects

- dummy
- **dummy1**
  - Tables
  - Views
  - Stored Procedures
  - Functions
- sys

Query 1

Limit to 1000 rows

```
    END IF;
END$$

DELIMITER ;
SELECT name, marks, result_status(marks) AS result
FROM student;
SELECT * FROM student;
```

Result Grid | Filter Rows: | Edit: | Export/Import: | Wrap Cell Content:

id	name	department	marks	created_at
1	Ravi	CSE	78	NULL
2	Anita	ECE	85	NULL
3	Kumar	CSE	90	2026-02-02 09:54:02
NULL	NULL	NULL	NULL	NULL