```
#include <iostream>
using namespace std;
int n;
class stud {
private:
  int rollNumber;
  string name;
  string address;
public:
  void accept();
  void display();
  int linearSearch(int rollNumber);
  int binarySearch(int rollNumber);
  void bubbleSort();
};
stud s[100];
void stud::accept() {
  cout << "Enter the roll number, name, and address of the student:\n";</pre>
  cin >> rollNumber >> name >> address;
}
void stud::display() {
  cout << "\n" << rollNumber << "\t" << name << "\t" << address;
}
int stud::linearSearch(int rollNumber) {
  int f=-1;
  for (int i = 0; i < n; i++) {
     if (s[i].rollNumber == rollNumber) {
        f=1;
        break;
     }
  }
   if (f!=-1) {
       cout << "Roll number " << rollNumber << " attended the training ";</pre>
     } else {
        cout << "Roll number " << rollNumber << " not attended training." << endl;</pre>
```

```
}
     return 0;
}
void stud::bubbleSort() {
  for (int i = 0; i < n - 1; i++) {
     for (int j = i + 1; j < n; j++) {
        if (s[i].rollNumber > s[j].rollNumber) {
           stud temp = s[i];
           s[i] = s[i];
           s[j] = temp;
        }
     }
}
int stud::binarySearch(int rollNumber) {
  int left = 0, right = n - 1, f=-1;
  while (left <= right) {
     int mid = left + (right - left) / 2;
     if (s[mid].rollNumber == rollNumber) {
        f=1;
        break;
     }
     if (s[mid].rollNumber < rollNumber)
        left = mid + 1;
     else
        right = mid - 1;
  }
    if (f!=-1) {
       cout << "Roll number " << rollNumber << " attended the training ";
        cout << "Roll number " << rollNumber << " not attended training";</pre>
     return 0;
}
int main() {
  int choice, rollNumber;
```

```
while (true) {
  cout << "\nChoose the option:\n";
  cout << "1. ACCEPT DATA\n";
  cout << "2. DISPLAY DATA\n";
  cout << "3. Linear Search\n";
  cout << "4. Binary Search\n";
  cout << "5. Exit\n";
  cout << "Enter your choice: ";
  cin >> choice;
  switch (choice) {
  case 1:
     cout << "Enter the number of students who attended the training program: ";
     cin >> n;
     for (int i = 0; i < n; i++) {
       s[i].accept();
     break;
  case 2:
     cout << "\nRoll No\tName\tAddress";</pre>
     for (int i = 0; i < n; i++) {
       s[i].display();
     }
     cout << endl;
     break;
  case 3:
     cout << "Enter the roll number to search: ";
     cin >> rollNumber;
       s[0].linearSearch(rollNumber);
     break;
  case 4:
     cout << "Enter the roll number to search: ";
     cin >> rollNumber;
     s[0].bubbleSort();
     s[0].binarySearch(rollNumber);
```

```
break;

case 5:
    return 0;

default:
    cout << "Invalid choice!" << endl;
}

return 0;
}</pre>
```