

Palmer Edholm
 Dr. Joe Koebbe
 MATH 4610
 September 27, 2021

Tasksheet 3

Task 1 The following is a table of the h values used, the error values from the approximations, and the calculated values using the centered difference approximation.

iter	h	error	dfVal
1	0.5	0.0085978	0.407549
2	0.25	0.00216292	0.413984
3	0.125	0.000541576	0.415605
4	0.0625	0.000135447	0.416011
5	0.03125	3.3865e-05	0.416113
6	0.015625	8.46646e-06	0.416138
7	0.0078125	2.11663e-06	0.416145
8	0.00390625	5.29157e-07	0.416146
9	0.00195312	1.32289e-07	0.416147
10	0.000976562	3.30163e-08	0.416147
11	0.000488281	7.98698e-09	0.416147
12	0.000244141	1.2349e-09	0.416147
13	0.00012207	4.35304e-09	0.416147
14	6.10352e-05	8.07833e-09	0.416147
15	3.05176e-05	3.78807e-08	0.416147
16	1.52588e-05	1.5709e-07	0.416147
17	7.62939e-06	1.34918e-06	0.416148
18	3.8147e-06	2.30286e-06	0.416149
19	1.90735e-06	6.11755e-06	0.416153
20	9.53674e-07	5.18939e-05	0.416199
21	4.76837e-07	0.000112929	0.41626
22	2.38419e-07	0.000845351	0.416992
23	1.19209e-07	0.00182191	0.417969
24	5.96046e-08	0.00572816	0.421875
25	2.98023e-08	0.0213532	0.4375
26	1.49012e-08	0.333853	0.75
27	7.45058e-09	0.583853	1
28	3.72529e-09	3.58385	4
29	1.86265e-09	15.5839	16
30	9.31323e-10	63.5839	64
31	4.65661e-10	255.584	256
32	2.32831e-10	1023.58	1024
33	1.16415e-10	0.416147	0
34	5.82077e-11	16383.6	16384
35	2.91038e-11	65535.6	65536
36	1.45519e-11	0.416147	0

	37		7.27596e-12		1.04858e+06		1.04858e+06	
	38		3.63798e-12		4.1943e+06		4.1943e+06	
	39		1.81899e-12		1.67772e+07		1.67772e+07	
	40		9.09495e-13		0.416147		0	
	41		4.54747e-13		0.416147		0	
	42		2.27374e-13		1.07374e+09		1.07374e+09	
	43		1.13687e-13		4.29497e+09		4.29497e+09	

Task 2 Figure 1 shows the log-log plot created from the table above. The figure shows how the error




Figure 1: log-log plot

is reduced as h approaches zero until the value is too small. Before the graph explodes, the slope is approximately -2 . Since this is a log-log plot, what that effectively means is that the error is being reduced at a rate of h^2 . Or, in other words, the approximation is second order accurate. At a value close to $\log(h) = -10$, the approximation begins to fail. The Python code used to generate the table and figure 1 is as follows:

```

1 from matplotlib import pyplot as plt
2 import numpy as np
3 from tabulate import tabulate

```

```

4  #
5  # initialize the exact value of the derivative
6  # -----
7  #
8  list=[]
9  aval = 2.0
10 exactVal = -np.cos(aval)
11 #
12 # set up the arrays for plotting the log-log plot we need
13 # -----
14 #
15 x = []
16 y = []
17 #
18 # initialize the array for the increment size and error in the
19 # finite difference approximation
20 # -----
21 #
22 h = []
23 error = []
24 #
25 # append the initial increment with a starting value - in this
26 # case, 1.0
27 # -----
28 #
29 h.append(1.0)
30 #
31 # compute the difference quotient for the increment value
32 # -----
33 #
34 dfVal = ( np.cos(aval + h[0]) - 2*np.cos(aval) +
35           np.cos(aval - h[0]) ) / (h[0]**2)
36 error.append(np.abs(exactVal - dfVal))
37 #
38 # append the log-log point for plotting at the end
39 # -----
40 #
41 x.append(np.log(h[0]))
42 y.append(np.log(error[0]))
43 #
44 # print the exact value for sanity
45 # -----
46 #
47 print('The_exact_derivative_value_is:', exactVal)
48 #
49 # set a loop counter
50 # -----
51 #

```

```

52 l=1
53 #
54 # the loop over ndiv increments
55 # -----
56 #
57 ndiv = 44
58 while l<44:
59     # print(dfVal)
60     #
61     # append the next increment of h
62     # -----
63     #
64     h.append(0.5 * h[l-1])
65     #
66     # compute the numerator and denominator for the difference
67     # approximation and compute the approximation from these
68     # -----
69     #
70     numval = np.cos(aval + h[l]) - 2*np.cos(aval) + \
71             np.cos(aval - h[l])
72     denom = (h[l]**2)
73     dfVal = numval / denom
74     #
75     # compute the error in the approximation
76     # -----
77     #
78     error.append(np.abs( dfVal - exactVal ))
79     #
80     # append the log-log point to the arrays for plotting below
81     # -----
82     #
83     x.append(np.log(h[l]))
84     y.append(np.log(error[l]))
85     #
86     # update the loop iterator
87     # -----
88     #
89     list.append([l,h[l],error[l],dfVal])
90     l += 1
91 #
92 # set up a plot for the data generated
93 # -----
94 #
95 plt.title('Error in the Difference Quotient of the Derivative')
96 plt.xlabel('Increment Values: h')
97 plt.ylabel('Error in the Approximation')
98 plt.plot(x, y, label='Log-Log Plot of Error for cos(2.0)')
99 plt.legend()

```

```

100 plt.show()
101 table = tabulate(list, headers=['iter', 'h', 'error', 'dfVal'],
102                  tablefmt='orgtbl')
103 print(table)

```

Task 3 The routine smaceps that produces single precision machine epsilon is

```

1 import numpy as np
2
3 def smaceps():
4     # Initialize variables to compute the machine value near 1
5     one = np.single(1)
6     seps = np.single(1)
7     appone = np.single(one + seps)
8     # Loop, dividing by 2 each time to determine when the difference
9     # between one and the approximation is zero in single precision
10    ipow = 0
11    # Break out of the loop if the comparison is small enough
12    while abs(appone - one) != np.single(0):
13        ipow += 1
14        # Update the perturbation and compute the approximation to
15        # one
16        seps = np.single(seps / 2)
17        appone = one + seps
18    return f'Bits: {ipow}, Value: {seps}'

```

and returns the following output:

```

1 Bits: 24, Value: 5.960464477539063e-08

```

The routine dmaceps that produces double precision machine epsilon is

```

1 def dmaceps():
2     # Initialize variables to compute the machine value near 1.0
3     one = 1.0
4     seps = 1.0
5     appone = one + seps
6     # Loop, dividing by 2 each time to determine when the difference
7     # between one and the approximation is zero in double precision
8     ipow = 0
9     # Break out of the loop if the comparison is small enough
10    while abs(appone - one) != 0.0:
11        ipow += 1
12        # Update the perturbation and compute the approximation to
13        # one
14        seps = seps / 2
15        appone = one + seps
16    return f'Bits: {ipow}, Value: {seps}'

```

and returns the following output:

```
1 Bits: 53, Value: 1.1102230246251565e-16
```

Task 4 A table of contents link was added to the home README.md document as seen in figure 2.




Figure 2: Table of contents link on home page

Software manual entries were created for both single and double precision machine epsilon as seen in figure 3.




Figure 3: Table of contents

Task 5 Since I've been using Python, I will create a python package which is analogous to creating a shared library. I'll be referencing [3] to create this. First, we'll create a package directory called maceps_package. Within the package directory, we'll create a src directory. Both of these steps are seen in figure 4.

```
palme@DESKTOP-G1A6VGK MINGW64 /d/Documents/MATH 4610/Tasksheet 3
$ mkdir maceps_package

palme@DESKTOP-G1A6VGK MINGW64 /d/Documents/MATH 4610/Tasksheet 3
$ ls
Home.PNG  Table_of_Contents.PNG  'Tasksheet 3'/  maceps_package/

palme@DESKTOP-G1A6VGK MINGW64 /d/Documents/MATH 4610/Tasksheet 3
$ cd maceps_package

palme@DESKTOP-G1A6VGK MINGW64 /d/Documents/MATH 4610/Tasksheet 3/maceps_package
$ mkdir src

palme@DESKTOP-G1A6VGK MINGW64 /d/Documents/MATH 4610/Tasksheet 3/maceps_package
$ cd src
```

Figure 4: File structure

Next, we'll create our package directory maceps inside of our src directory and cd into maceps as in figure 5.

```
palme@DESKTOP-G1A6VGK MINGW64 /d/Documents/MATH 4610/Tasksheet 3/maceps_package
src
$ mkdir maceps

palme@DESKTOP-G1A6VGK MINGW64 /d/Documents/MATH 4610/Tasksheet 3/maceps_package
/src
$ cd maceps
```

Figure 5: Package directory

Once there, we'll copy our python file into our package directory as in figure 6.

```
palme@DESKTOP-G1A6VGK MINGW64 /d/Documents/MATH 4610/Tasksheet 3/Tasksheet 3
$ cd D:\Documents\Math 4610\Tasksheet 3\Tasksheet 3

palme@DESKTOP-G1A6VGK MINGW64 /d/Documents/MATH 4610/Tasksheet 3/Tasksheet 3
$ cp maceps.py ../maceps_package/src/maceps
```

Figure 6: Move python file

Within our maceps directory, we'll also create an empty `__init__.py` file as in figure 7.

```
palme@DESKTOP-G1A6VGK MINGW64 /d/Documents/MATH 4610/Tasksheet 3/maceps_packag
e/src/maceps
$ vim __init__.py
```

Figure 7: init file

We now have the basic file structure needed to create our python package and can start creating the necessary package files in our maceps-package directory.

We'll create an empty tests directory and a pyproject.toml file. The pyproject file contains the following specifications:

```
[build-system]
requires = [
    "setuptools>=42",
    "wheel"
]
build-backend = "setuptools.build_meta"
```

Now, we need to configure our metadata. We do that by creating a static metadata file setup.cfg. The setup.cfg file contains the following specifications:

```
[metadata]
name = maceps_package-palmeredholm
version = 0.0.1
author = Palmer Edholm
author_email = palmer.edholm@usu.edu
description = A machine epsilon package
long_description = file: README.md
long_description_content_type = text/markdown
url = https://github.com/palmeredholm/math4610
project_urls =
    Bug Tracker = https://github.com/palmeredholm/math4610
classifiers =
    Programming Language :: Python :: 3
    License :: OSI Approved :: MIT License
    Operating System :: OS Independent

[options]
package_dir =
    = src
packages = find:
python_requires = >= 3.6
[options.packages.find]
where = src
```


We specified that our long description would be specified in a README.md file. Therefore, our next step is to create said README.md file. The markdown file, for our purposes, will contain a succinct description. The following is what I included:

```
# Machine Epsilon Package
```

```
This package computes single and double precision value for the  
machine epsilon.
```

Our last step is to create a license. We'll use the MIT license as it fits our purview best. The following is the MIT License that I included:


```
Copyright (c) 2018 The Python Packaging Authority
```

```
Permission is hereby granted, free of charge, to any person obtaining a copy  
of this software and associated documentation files (the "Software"), to deal  
in the Software without restriction, including without limitation the rights  
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell  
copies of the Software, and to permit persons to whom the Software is  
furnished to do so, subject to the following conditions:
```

```
The above copyright notice and this permission notice shall be included in all  
copies or substantial portions of the Software.
```

```
THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR  
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,  
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE  
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER  
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,  
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE  
SOFTWARE.
```

With a simple ls command, as in figure 8, I can see that I have everything I need to create this package.



```
palme@DESKTOP-G1A6VGK MINGW64 /d/Documents/MATH 4610/Tasksheet 3/maceps_packag  
e  
$ ls  
LICENSE  README.md  pyproject.toml  setup.cfg  src/  tests/
```

Figure 8: Package structure

All I need to do is run

```
py -m build
```

in my package directory and my python package will be created. After I run that command, I can run `ls` again (figure 9) and see that I now have a directory called `dist`.

```
palme@DESKTOP-G1A6VGK MINGW64 /d/Documents/MATH 4610/Tasksheet 3/maceps_package
$ ls
LICENSE  README.md  dist/  pyproject.toml  setup.cfg  src/  tests/
```

Figure 9: Directory after build

If I step into that directory (figure 10) I can see that it contains a `tar.gz` file which is a source archive and a `.whl` file which is a built distribution.

```
palme@DESKTOP-G1A6VGK MINGW64 /d/Documents/MATH 4610/Tasksheet 3/maceps_package
$ ls
LICENSE  README.md  dist/  pyproject.toml  setup.cfg  src/  tests/

palme@DESKTOP-G1A6VGK MINGW64 /d/Documents/MATH 4610/Tasksheet 3/maceps_package
$ cd dist

palme@DESKTOP-G1A6VGK MINGW64 /d/Documents/MATH 4610/Tasksheet 3/maceps_package/dist
$ ls
maceps_package-palmeredholm-0.0.1.tar.gz
maceps_package-palmeredholm-0.0.1-py3-none-any.whl
```

Figure 10: Archived file

Task 6 From [2] and [3], I learned a fair amount about the advantages and disadvantages of shared libraries. First of all, a shared library is a dynamic library that uses dynamic linking when compiling. The opposite of a dynamic library is a static library. While shared libraries are slower than static libraries, a single copy of the shared library is kept in RAM reducing the size of the executable.

References

- [1] <https://nickolasteixeira.medium.com/shared-dynamic-libraries-vs-static-libraries-differences-in-performance-2716f5b3c826>
- [2] <https://nickolasteixeira.medium.com/what-are-static-libraries-in-c-and-why-do-software-engineers-use-them-eb7022d89135>
- [3] <https://packaging.python.org/tutorials/packaging-projects/>