Forest Growth Modeling

Paloma Cartwright Joe DeCesaro Connor Flynn
2022-05-15

Consider the following model of forest growth (where forest size in measured in units of carbon (C))

 $dC/dt = r^*C$ for forests where C is below a threshold canopy closure

 $dC/dt = g^*(1-C/K)$ for forests where carbon is at or above the threshold canopy closure

 ${f K}$ is a carrying capacity in units of carbon

The size of the forest (C), Canopy closure threshold and carrying capacity are all in units of kgC. You could think of the canopy closure threshold as the size of the forest at which growth rates change from exponential to linear. You can think of \mathbf{r} , as early exponential growth rate and \mathbf{g} as the linear growth rate once canopy closure has been reached

1. Implement the model in R

```
source(here("R", "forest_growth.R"))
forest_growth
## function (time, C, params)
## {
       if (C < params$threshold) {</pre>
##
##
            dC_dt <- params$r * C</pre>
            return(list(dC_dt))
##
       }
##
##
       else {
##
            dC_dt <- params$g * (1 - C/params$K)</pre>
##
            return(list(dC_dt))
       }
##
```

2. Run the model for 300 years


- Start with an initial forest size of $10 \mathrm{kgC}$
- Parameters:

}

- Canopy Closure Threshold: 50kgC
- K: 250kgC
- r: 0.01
- g: 2kg/year

Graph the Results

Forest Growth over Time



3. Run a Sobol Sensitivity Analysis

Explore how the estimated maximum and mean forest size (e.g maximum and mean values of C over the 300 years) varies with the pre canopy closure growth rate (r) and post-canopy closure growth rate (g) and canopy closure threshold and carrying capacity(K)

Assume that parameters are all normally distributed with means as given above and standard deviation of 10% of mean value.

Graph the results of the sensitivity analysis

as a box plot of maximum forest size and a plot of the two Sobol indices (S and T).