University of Cape Town



Machine Learning Assignment 1


Pamela Afful

Student Number: AFFPAM001

October 18, 2026

Question 1

a) Legendre Polynomial Plots



As the order of the polynomial, q, increases, the more nonlinear/complex the$L_q(x)$ gets, albeit slowly.

1. At q=0, $L_q(x)$ devolves to a straight horizontal line $L_q(x)$ =0 over the domain [-1,1].


2. At q=1 $L_q(x)$ starts to have some slope attached, a straight line of the form $y = 2x$


3. At q=2, 4 the non-linear curvature/complexity of $L_q(x)$ starts to become more visible particularly towards the edges of the domain [-1,1;

function approximates a parabola/quadratic function

4. At q=3,5 non-linear curvature/complexity of $L_q(x)$ both take the same shape, albeit with different magnitudes of $L_q(x)$ over the same domain.

b) Random Target Functions






Observations:

1. $f(x) = \sum_{q=0}^{Q_f} \alpha_q x^q$: the functions only output values from 0 to negative values over the domain [-1,1]
2. $f(x) = \sum_{q=0}^{Q_f} \beta_q L_q(x)$: the functions output both positive and negative y values, however, over the domain [-1,1], the output values are only defined (or real) between 0.5 and -0.5. The appears to be a vertical asymptotic behaviour outside those bounds.
3. The two functions appear to either be reflections/inverses of ecah other (look into this)*

Question 2




b) A Priori expectation

Given that the underlying data generating process is non-linear, the non-linear hypothesis would be more suited to fit the data's non-linear behavior

and overall shape. This visually seems to be the case as well: the H2(x) hypothesis functions follows the shape of the data quite closely. The linear function only fits a straight line through the data with only a few values intersecting with the underlying function.

c) Bias Variance for H1 and H2

	Bias	Variance	Both:Bias+Var	OOS Error	Estimate Differance
h1(x)	0.0854	0.0044	0.0898	0.0841	0.0057
h2(x)	0.0022	0.0703	0.0725	0.1296	0.0571



(a) Bias vs Noise (b) Variance vs Noise (c) E[OOS Error] vs Noise

Figure 1: OOS Error Estimates

e) Interpretation

Bias-Variance Dynamics

The expected out-of-sample error as it relates to the bias and variance of a model is given by

$$E[Err_{oos}] = Bias^2 + Variance + IrreducibleNoise(\varepsilon)$$

- RHS:

  - The linear model, $h1(x)$, has better out-of-sample performance overall, averaged across 1000 simulations over varying values of the noise parameter, compared to the more complex model, $h2(x)$.
  - There is a small change in the average OOS error for both hypothesis functions. The steepest increase in the average OOS error is observed in the change of the noise parameter from 0.1 to 0.2 and levels thereafter.
  - A bit more variability is observed in the average out-of-sample error as sigma increases. The error sees a slight decrease as sigma increases up to 0.2, but mostly increases thereafter.

- LHS:

  - There is very little variability/ change observed in the variance as the noise parameter increases for both functions, whilst the bias for $h1(x)$, sees a small decrease when the noise level increases from 0.3 to 0.4.
  - Overall, the linear model, $h1(x)$, has lower average variance but higher bias across the various noise parameters; this is expected given the that the model is less complex relative to $h2(x)$


Model Choice

- Given the estimated OOS Error, it's better to go with the linear model as it is more parsimonious and less likely to overfit the data
- Rational: the combined estimate comparison $bias^2 + Var$ to $E[Err_{oos}]$ across sigmas :

  - $h1(x)$: its average RHS, 0.899 is closer to its LHS OOS estimate, 0.0854 providing a better estimate of the model's general OOS behavior than $h2 = (x)$; its average RHS, 0.0701, has a much larger deviation from its average LHS, 0.1323.

Question 4

a) Data Set Plot



Observation: The data does not appear to be linearly separable (in the given 2D feature space) as the data does not seem to have linear boundaries between categories/classes. Instead, the different classes of responses look to be spiraled around each other. A non-linear neural network seems well suited to capture the non-linear pattern/structure embedded in the data for the given feature space.

c) Feed Forward Neural Network


Numerical Pitfalls: The computation of log(yhat) in the objective function may cause the network to explode/ diverge given the undefined behavior of the log function at 0 (or values very close to 0), which can hamper the numerical stability of the network's computations.

d) Validation Analysis

```
[1] 10
```

Plot the validation error vs log (λ)

```
[1] 10
```




Model Parameters: number of hidden layer nodes, $\mathbf{m = 10}$

The lowest validation error is generated at $\lambda_{min} = 0.135$ with an associated validation error of 11.04, making for a less strict and more complex model (given the big budget that the sum of the model's parameters cannot exceed). The next best error to the right of this minimum is obtained at $\lambda_{1SE} = 0.24 (Val_{err} = 18.7)$, offering stricter control over the complexity of the network and thus more parsimonious model, decreasing the likelihood of the model over fitting to just the training data.

d) Response Curve

```
[1] 10
```



The model produces three distinct, rather jagged regions over the feature space that map to the respective probability assignments of each class:

- Class 1 labels were mostly misclassified by the model, with the predicted region for that class for the model containing few of the actual

observations for that label. The model is also quite confident in its predictions for that region, with high probability assignments of lattice points assigned to the class. It is most likely that the model would misclassify most new points that actually belong to that class to Class 2.

- The feature space is dominated by Class 2 predictions over the lattice points. For observations with values between [-4, ~1.6] for X2 and between [-4,.4], the model mostly predicts Class 2 with relatively high probabilities (close to 1). However, we still see a small fraction of actual observations belonging to this class (for observations that have values > 2 in the X2 dimension), that lie in the Class 3 color mapping over the feature space.

- Class 3 prediction mapping ranges between [>-4,0] in the X1 dimension and >~1.6 in the X2 dimension across the lattice space. The majority of misclassified points in this class (out side the aforementioned bounds), are predicted to be in Class 2 (which would likely happen for new observations as well) . Once again, the probabilities for assignment to Class 3 are relatively high as well.

Question 2 Optional Questions

a) Hypothesis Function Simulations