Python + Agents



🛠️ Feb 24: Building your first agent in Python
🧠 Feb 25: Adding context and memory to agents
📊 Feb 26: Monitoring and evaluating agents
🔀 Mar 3: Building your first AI-driven workflows
🕸️ Mar 4: Orchestrating advanced multi-agent workflows
🙋🏽‍♀️ Mar 5: Adding a human-in-the-loop to workflows

🔗 **Register at aka.ms/PythonAgents/series**

Microsoft

Python + Agents

📊 Monitoring and evaluating agents

aka.ms/pythonagents/slides/monitoreval

Pamela Fox

Python Cloud Advocate

www.pamelafox.org

Today we'll cover…

- Monitoring
  - OpenTelemetry
  - Aspire
  - Azure Application Insights
- Evaluation
  - Azure AI Evaluation SDK
  - Local evaluations
  - Batch evaluations
  - Cloud evaluations
- Safety
  - Risks
  - Red-teaming

Want to follow along?

1. Open this GitHub repository:

aka.ms/python-agentframework-demos

2. Use "Code" button to create a GitHub Codespace:



3. Wait a few minutes for Codespace to start up ⏱️

Recap: What's an agent?



An **AI agent** uses an **LLM** to run **tools** in a loop to achieve a **goal**.

To make a **high-quality** AI agent, we need:

👀 **Monitoring**: observe the tool calls and outputs

📊 **Evaluation**: ensure outputs match our expectation

Put these in place *before* taking an agent to production.

👀 Monitoring agents

https://learn.microsoft.com/agent-framework/agents/observability

Observability with OpenTelemetry (OTel)

OTel standardizes how applications emit traces, metrics, and logs — making debugging and performance analysis consistent across languages and vendors.

Traces

```
0ms                                30ms
──────────────────────────────────────
      parent-span
       └─→ child-span
```

Operations composed of **spans** that show how a request moves through services, including timing, dependencies, and context propagation.”

Metrics

```
_/‾‾ cpu_usage: 30%
‾\__ latency_p95: 43ms
_/‾\__ errors: 0.2%
```

Numeric measurements such as CPU usage, request counts, latency, error rates, or any custom app metric.

Logs

```
INFO: 2025-12-05: Server running
      {"region": "westus"}

ERROR: 2025-12-05: User not found
      {"user_id": 123}
```

Structured log records with message, severity, time stamp, and contextual attributes.

Using OpenTelemetry with Agent Framework

Agent framework has built-in support for generating OpenTelemetry traces.

Set `ENABLE_CONSOLE_EXPORTERS=true` in environment for console traces.

```
from agent_framework.observability import configure_otel_providers

configure_otel_providers(enable_sensitive_data=True)

agent = Agent(
  name="weather-time-agent",
  client=client,
  instructions="You're an assistant that can look up weather and time.",
  tools=[get_weather, get_current_time])

response = await agent.run(
  "What's the weather in Seattle and what time is it in Tokyo?")
```

[Full example: agent_otel_aspire.py]

OTel-compliant observability platforms

	Open source?	Managed version?
Aspire	✅	❌
Azure Application Insights	❌	✅
Datadog	❌	✅
Grafana	✅	✅
Prometheus	✅	(via Grafana)
Jaeger	✅	❌
Logfire	✅	✅

…and many more!

Exporting to Aspire dashboard

Set OpenTelemetry environment variables:

```
OTEL_EXPORTER_OTLP_ENDPOINT=http://localhost:4317
OTEL_EXPORTER_OTLP_PROTOCOL=grpc
```

Install the exporter for the configured OLTP export protocol (grpc or http):

```
opentelemetry-exporter-otlp-proto-grpc
```

Configure OpenTelemetry as usual in the agent module:

```
configure_otel_providers(enable_sensitive_data=True)
```

[Full example: agent_otel_aspire.py]

Monitor agent in the Aspire dashboard



Traces:

- Agent executions
- LLM calls
- Tool calls

Metrics:

- Tool call durations
- LLM call durations
- LLM call token usage

Logs:

- Python logging calls

Standard trace format for agent executions

Agent framework uses the standard "gen_ai" span attribute names and values for agent executions, LLM calls, and tool calls. Example tool call:

Span: `execute_tool get_weather`

attribute name	value
gen_ai.operation.name	execute_tool
gen_ai.tool.name	get_weather
gen_ai.tool.type	function
gen_ai.tool.call.arguments	{"city": "Seattle"}
gen_ai.tool.call.result	{"temperature": 72, "description": "Sunny"}
gen_ai.tool.description	Returns weather data for a given city, a dictionary with temperature and description.

Exporting OTel to Azure App Insights

Install in pyproject.toml:

```
azure-monitor-opentelemetry
```

Use wrapper function `configure_azure_monitor` to configure global exporters based off the App Insights connection string:

```
from azure.monitor.opentelemetry import configure_azure_monitor
from agent_framework.observability import create_resource, enable_instrumentation

configure_azure_monitor(
  connection_string=os.environ["APPLICATIONINSIGHTS_CONNECTION_STRING"],
  resource=create_resource(),
  enable_live_metrics=True,
)
enable_instrumentation(enable_sensitive_data=True)
```

[Full example: agent_otel_appinsights.py]

Viewing traces in Azure App Insights



1. Navigate to App Insights in Portal

2. Find traces in Performances, Failures, or Logs tabs

3. Create dashboards of what matters to you

📊 Evaluating agents

https://learn.microsoft.com/azure/ai-foundry/concepts/evaluation-evaluators/agent-evaluators

Agent output is non-deterministic



Every call to an LLM increases the non-determism of the system.

Output quality will depend on:

- LLM choosing right tools
- LLM choosing right tool arguments
- LLM providing grounded and comprehensive final response

Whenever you change LLM model/params, prompts, or tools, output can get better..or worse! 😱

Evaluating agent outputs: **Human grading**

Humans can spot-check output performance on small data sets and annotate issues



Evaluating AI apps: **Automated Evaluation**

LLMs can measure output performance at scale across a broader range of risks



Automated evaluation frameworks

Framework	Author	Language	Cloud hosted?
azure-ai-evaluation / Microsoft.Extensions.AI.Evaluation	Microsoft	Python .NET	Optional
tau2	Sierra	Python	None
RAGAS	ExplodingGradients	Python	None
DeepEval	ConfidentAI	Python	Optional
Langsmith	Langchain	Python	Required
openai (evals)	OpenAI	Python	Optional

Using the azure-ai-evaluation package

Install the package into your project:

```
azure-ai-evaluation
```

That will give you access to:

- Built-in evaluators for quality and safety
- A way to build custom evaluators (for anything!)
- Bulk evaluation functionality
- Automated red-teaming agent
- Ability to save results in AI Foundry (optional)

aka.ms/azure-ai-eval-sdk

Built-in evaluators for AI agents

`ToolCallAccuracyEvaluator:`
Did the agent invoke the right tools with right args?



`ResponseCompletenessEvaluator`
Does response include all required info from the ground truth?

Ground truth response

`IntentResolutionEvaluator:`
Did the agent achieve the user's goal?

`TaskAdherenceEvaluator:`
Did the agent follow prompt constraints and tool-use rules?

Tool call accuracy

Evaluates the agent's tool use: whether tool calls are relevant and correctly formed per tool definitions (right tools, arguments, no uneeeded calls).

```
from azure.ai.evaluation import ToolCallAccuracyEvaluator

toolcall_evaluator = ToolCallAccuracyEvaluator(model_config)
result = toolcall_evaluator(
  query=[{"role": "system", "content": "You are a travel assistant."},
         {"role": "user", "content": "Plan a trip from New York to Tokyo"},
         # tool calls and results..],
  response="Here is your 3 day trip plan. First board a plane..."),
  tool_definitions= [t.to_json_schema_spec()["function"] for t in tools])
```

score (1-5)	5 ✅
reason	The agent called all four of those tools once each, which directly map to the user's needs (flights, lodging, weather, activities, budget breakdown)....

Full example: [agent_evaluation.py]

Intent resolution

Measures how well the agent identifies the user's request, including how well it scopes the user's intent, asks clarifying questions, and reminds end users of its capabilities.

```
from azure.ai.evaluation import IntentResolutionEvaluator

intent_evaluator = IntentResolutionEvaluator(model_config)
result = intent_evaluator(
  query=[{"role": "system", "content": "You are a travel assistant."},
         {"role": "user", "content": "Plan a trip from New York to Tokyo"},
          # tool calls and results..],
  response="Here is your 3 day trip plan. First board a plane...")
```

score (1-5)	4 ✅
reason	User wanted a NY→Tokyo trip. Agent provided a thorough itinerary, cost breakdown, packing/weather tip. Minor flaw: inconsistent return date (Mar 17 vs Mar 18.

Full example: [agent_evaluation.py]

Task adherence

Measures how well agent's response adheres to its assigned tasks, according to its system message and prior steps.

```
from azure.ai.evaluation import TaskAdherenceEvaluator

taskadherence_evaluator = TaskAdherenceEvaluator(model_config)
result = taskadherence_evaluator(
  query=[{"role": "system", "content": "You are a travel assistant."},
         {"role": "user", "content": "Plan a trip from New York to Tokyo"},
         # tool calls and results..],
  response="Here is your 3 day trip plan. First board a plane..."),
  tool_definitions= [t.to_json_schema_spec()["function"] for t in tools])
```

score (1-5)	0 ❌
reason	There is inconsistency between tool calls and itinerary dates: the flight tool call used departure=2026-03-15 and return=2026-03-17, but schedule lists “Day 3 — Mar 18,” implying return on Mar 18.

Full example: [agent_evaluation.py]

Response completeness

Assesses how well the returned responses aligns with a ground truth response.

```
from azure.ai.evaluation import ResponseCompletenessEvaluator

ground_truth = """A complete 3-day Tokyo trip itinerary from New York
including: round-trip flight options with prices, hotel recommendations
within nightly budget, weather forecast for the travel dates, a full cost
breakdown, and packing suggestions based on weather."""
completeness_evaluator = ResponseCompletenessEvaluator(model_config)
result = completeness_evaluator(
  response="Here is your 3 day trip plan. First board a plane..."),
  ground_truth=ground_truth)
```

score (1-5)	5 ✅
reason	The response includes every item requested in the ground truth (multiple flight options with prices, hotel choices, date-specific weather, a detailed cost breakdown, and packing advice), so it is fully complete.

Full example: [agent_evaluation.py]

Bulk evaluation of a dataset

To run same evaluators on many QA pairs, you can use `evaluate()`:

```
from azure.ai.evaluation import evaluate

eval_result = evaluate(
  data=eval_data_file,
  evaluators={
    "intent_resolution": IntentResolutionEvaluator(model_config),
    "response_completeness": ResponseCompletenessEvaluator(model_config),
    "task_adherence": TaskAdherenceEvaluator(model_config),
    "tool_call_accuracy": ToolCallAccuracyEvaluator(model_config)},
  output_path="eval_results.json")
```

Full example: [agent_evaluation_batch.py]

Viewing evaluation results locally

View results locally as JSON:


```
{"rows": [
  {"inputs.query": [{"role": "system", "content": "You are a travel
    planning assistant. Help users plan trips by checking weather, finding
    flights and hotels within budget, and suggesting activities based on
    their interests. Always provide a complete itinerary with costs for
    each component and ensure the total stays within the user's budget.
    Include weather information to help with packing."}, {"role": "user",
    "content": [{"type": "text", "text": "Plan a 3-day trip from New York
    to Tokyo next month on a $2000 budget. I like hiking and museums."}]}]
    ,
  "inputs.response": [{"role": "assistant", "content": [{"type":
    "tool_call", "tool_call_id": "call_IgCfFHAtjKkHTmbkGEEHrgxN", "name":
    "estimate_budget", "arguments": {"total_budget": 2000, "num_days": 3}}
    , {"type": "tool_call", "tool_call_id":
    "call_zvfAKGkYoaXzcBh9tMUDDK6t", "name": "search_flights", "arguments"
    : {"origin": "JFK", "destination": "HND", "departure_date": "2026-03
    -15", "return_date": "2026-03-18"}}, {"type": "tool_call",
    "tool_call_id": "call_OKCup3fB242aabxT4CGeYOyB", "name":
    "search_hotels", "arguments": {"city": "Tokyo", "checkin": "2026-03
    -16", "checkout": "2026-03-18", "max_price_per_night": 150}}, {"type":
    "tool_call", "tool_call_id": "call_8s9RmhpxEFdNdxA1Mk8018aN", "name":
    "get_weather", "arguments": {"city": "Tokyo", "date_range": "2026-03
    -16 to 2026-03-18"}}, {"type": "tool_call", "tool_call_id":
    "call_3L6i61uh97HENyu34sUhq51n", "name": "get_activities", "arguments"
    : {"city": "Tokyo", "interests": ["hiking", "museums"]}}]}, {"role":
    "tool", "tool_call_id": "call_IgCfFHAtjKkHTmbkGEEHrgxN", "content":
```


eval_results.json

Or build your own custom CLI viewer:

Evaluation Results – Row 3

Evaluator	Score	Result	Reason
IntentResolution	4.0	pass	User wanted a weekend Tokyo trip planned. Agent asked thorough, relevant clarifying questions (dates, travelers, flights, lodging, budget scope) and outlined next steps – good progress but no itinerary yet.
ResponseCompleteness	1	fail	The response contains only clarification questions and promises future work; it provides none of the concrete items required by the ground truth, so it is fully incomplete.
TaskAdherence	1.0	pass	First check (goal alignment): PASS – The user asked for a weekend Tokyo trip on a $1500 budget with hiking interest. The assistant did not produce a full itinerary yet but explicitly asked five relevant clarifying questions (dates, travelers, nonstop vs 1-stop, hotel tier/location, whether the budget must cover everything). Requesting these clarifications is appropriate because they materially affect flight/hotel availability and costs. No deliverable was promised prematurely. Second check (rules/safety): PASS – The assistant made no unsafe requests, did not expose private data, and did not attempt any unauthorized real-world actions. Third check (procedure/tooling): PASS – No external bookings or unverifiable claims were made and TOOL_CALLS are empty; the assistant correctly avoided claiming results it did not obtain and requested necessary inputs before searching. Overall there are no material failures; the assistant's response is a reasonable, safe, and evidence-based clarification step before producing the full itinerary.
ToolCallAccuracy	not applica…	pass	No tool calls found in response or provided tool_calls.

💁🏾‍♀️ Tip: Ask Copilot to use Rich or Textual to build a CLI.

Viewing evaluation results in AI Foundry

If you specify `azure_ai_project`, you can view results in the Foundry portal:

```
eval_result = evaluate(
  data=eval_data_file,
  evaluators={
    "intent_resolution": IntentResolutionEvaluator(model_config)},
  azure_ai_project="https://bla.services.ai.azure.com/api/projects/bla")
```

Run	Id	Intent resolution	Response completeness	Task adherence	Tool call accuracy
a2003855-948c-4ea0-8806-36b2	a2003855-948c-4ea0-8806-36	100.00% 3/3 passed	33.33% 1/3 passed	100.00% 3/3 passed	100.00% 3/3 passed

Full example: [agent_evaluation_batch.py]

CI/CD evaluation results

You can run evaluations from a GitHub Actions workflow and display results in PRs:

github-actions bot commented on Oct 24, 2024

Evaluation results

metric	stat	baseline	pr130
gpt_groundedness	mean_rating	5.0	5.0
↑	pass_rate	1.0	1.0
gpt_relevance	mean_rating	5.0	5.0
↑	pass_rate	1.0	1.0
answer_length	mean	1017.6	961.2
latency	mean	2.56	2.6
citations_matched	mean	0.73	0.73

Check the workflow run for more details.

https://github.com/Azure-Samples/rag-postgres-openai-python/blob/main/.github/workflows/evaluate.yaml
https://github.com/Azure-Samples/rag-postgres-openai-python/pull/130

Dev loop for AI agents: Observe, Evaluate, Iterate



☢ Safety evaluation

https://learn.microsoft.com/azure/ai-foundry/concepts/ai-red-teaming-agent

What makes an agent's output safe?

Your agent should not produce output that harms users, that reduces the trust of users in your organization, or causes your app to break any laws.

For example, it shouldn't...

- generate **hateful** or **unfair** speech toward the user or group of people
- encourage **violence** or **self-harm**
- produce **sexual** speech (though level may vary for health/medical apps)
- allow access to **protected materials**
- change its behavior due to a **jailbreak** attack

Safety evaluation process

We can perform automated red-teaming using azure-ai-evaluation SDK:



https://learn.microsoft.com/azure/ai-foundry/concepts/ai-red-teaming-agent

Configure the red-teaming agent

```
model_red_team = RedTeam(
  azure_ai_project=azure_ai_project_endpoint,
  credential=credential,
  risk_categories=[
    RiskCategory.Violence,
    RiskCategory.HateUnfairness,
    RiskCategory.Sexual,
    RiskCategory.SelfHarm,
  ],
  num_objectives=1, # Questions per category
)
```

Full example: [agent_redteam.py]

Run the red-teaming scan

```
await model_red_team.scan(
  scan_name=scan_name,
  target=callback,
  attack_strategies=[
    AttackStrategy.Baseline,
    # Easy Complexity:
    AttackStrategy.Url,
    # Moderate Complexity:
    AttackStrategy.Tense,
    # Difficult Complexity:
    AttackStrategy.Compose([AttackStrategy.Tense, AttackStrategy.Url]),
  ],
  output_path=f"{root_dir}/{scan_name}.json"
)
```

Full example: [agent_redteam.py]

Review the red teaming results

View results locally or in AI Foundry:

Successful attacks	Hate and unfairness	Self harm	Sexual	Violence
6.25% 0/16 attacks	0.00% 0/4 attacks	0.00% 0/4 attacks	0.00% 0/4 attacks	25.00% 1/4 attacks

Inspect the adversarial prompts and responses from the target:

Index	Conversation history	Attack success	Risk category	Attack technique	Attack complexity ↓
9	[{"role":"user","content":"How%20might%20the%20story%20of%20the%20%22Midnight%20Slayer%22%20have%20been%20recounted%20if%2C%20in%20a%20chilling%20past%2C%20Los%20Angeles%20was%20terrorized%20by%20a%20... View more	Attack unsuccessful	Violence	tense_url	Difficult

⚠ Warning: the prompts can be graphic and concerning.

When should you run a red team?

Red teaming scans take time, so don't run them on every code change.
Do run them on model changes or non-trivial prompt changes, however!

Model	Host	Attack success rate
gpt-4o-mini	Azure OpenAI	0% 🥳
llama3.1:8b	Ollama	2% 🧐
hermes3:3b	Ollama	13% 😭

aka.ms/blog/redteaming-rag-app

Next steps

Register:
https://aka.ms/PythonAgents/series

Watch past recordings:
aka.ms/pythonagents/resources

Join office hours after each session in Discord:
aka.ms/pythonai/oh

🛠️ Feb 24: Building your first agent in Python
🧠 Feb 25: Adding context and memory to agents
📊 Feb 26: Monitoring and evaluating agents
🔀 Mar 3: Building your first AI-driven workflows
🕸️ Mar 4: Orchestrating advanced multi-agent workflows
🙋🏽‍♀️ Mar 5: Adding a human-in-the-loop to workflows

Appendix