Host your Python agents on Microsoft Foundry

Apr 27: **Microsoft Agent Framework**

Apr 29: **LangChain and LangGraph**

Apr 30: **Quality and safety evals**

Register at aka.ms/AgentsOnFoundry/series

Microsoft

Host your agents on Foundry

Quality and safety evals

aka.ms/foundryhosted/slides/qualitysafety

Pamela Fox

Python Cloud Advocate

www.pamelafox.org

Today we'll cover...

- Quality evaluations
  - Built-in evaluators
  - Batch evals
  - Scheduled evals
  - Continuous evals
  - Evals alerts
- Safety evaluation with red-teaming
- Guardrails
- Content safety filter error handling

Follow along

1. Open this GitHub repository:

aka.ms/foundry-hosted-agentframework-demos

2. Use "Code" button to create a GitHub Codespace:



3. Wait a few minutes for Codespace to start up ⏱️

⚠️ Most code samples require deployment and an Azure account.

Quality evaluations

Agent output is non-deterministic



Every call to an LLM increases the non-determism of the system.

Output quality will depend on:

- LLM choosing right tools
- LLM choosing right tool arguments
- LLM providing grounded and comprehensive final response

Whenever you change LLM model/params, prompts, or tools, output can get better..or worse! 😱

Human evaluations

Humans can spot-check output performance on small data sets and annotate issues:



** Foundry offers human evals as a feature, but it's not yet supported for hosted agents.*

Automated evaluations

LLMs can measure output performance at scale across a broader range of risks



Automating evaluations with Python SDKs

Install the required packages into your project:

```
openai
azure-ai-projects
```

That will give you access to:

- Built-in evaluators for quality and safety
- A way to build custom evaluators (for anything!)
- Bulk evaluation functionality
- Result storage and visualization in Microsoft Foundry

https://learn.microsoft.com/azure/foundry/how-to/develop/cloud-evaluation

Built-in evaluators for AI agents

`ToolCallAccuracyEvaluator:`
Did the agent invoke the right tools with right args?



`ResponseCompletenessEvaluator`
Does response include all required info from the ground truth?

Ground truth response

`IntentResolutionEvaluator:`
Did the agent achieve the user's goal?

`TaskAdherenceEvaluator:`
Did the agent follow prompt constraints and tool-use rules?

Tool Call Accuracy

Evaluates the agent's tool use: whether tool calls are relevant and correctly formed per tool definitions (right tools, arguments, no unneeded calls).

	Run #1	**Run #2**
User query	*What expenses are not covered by PerksPlus?*	
Tool definitions	📖 `knowledge_base_retrieve(queries)` 📖 `web_search(query)` 📖 `get_current_date()` 📖 `get_enrollment_deadline_info(query)`	
Tool calls	🛠️ `knowledge_base_retrieve(["PerksPlus expenses not covered"])`	-
Tool call results	↪ PerksPlus.pdf: "PerksPlus can't be used for..."	-
Response (**NOT** sent to evaluator)	🤖 *PerksPlus does not cover non-fitness expenses, medical treatments and procedures, food and supplements.*	🤖 *PerksPlus usually does not cover unrelated purchases. Check your HR policy for details.*
Pass/Fail (1-5)	✅ Pass (5/5)	❌ Fail (1/5)
Reason	💭 Reason: The agent used the knowledge retrieval tool for a company-specific question, and the query was relevant to the user's request.	💭 Reason: The agent did not use the available retrieval tool even though the question required company information.

Intent Resolution

Measures how well the agent identifies the user's request, including how well it scopes the user's intent, asks clarifying questions, and reminds end users of its capabilities.

	Run #1	**Run #2**
User query	*Does PerksPlus cover horseback riding lessons, and what's the maximum reimbursement?*	
Tool calls	🛠️ `knowledge_base_retrieve( ["PerksPlus horseback riding"])`	-
Tool call results	↪ PerksPlus.pdf: "Horseback riding lessons covered. Up to $1,000 reimbursement per year."	-
Response	🤖 *Yes. PerksPlus covers horseback riding lessons as a wellness experience, and employees can expense up to $1,000.*	🤖 *PerksPlus supports many wellness programs like gym memberships and yoga classes.*
Pass/Fail (1-5)	✅ Pass (5/5)	❌ Fail (1/5)
Reason	💭 Reason: The response answers both parts of the question: eligibility and reimbursement limit.	💭 Reason: The response misses the user's specific intent about horseback lessons and maximum amount.

Task Adherence

Measures how well agent's response adheres to its assigned tasks, according to its system message and prior steps.

	Run #1	**Run #2**
User query	*Using only Zava benefits information, can you recommend a therapist in London?*	
Tool calls	🛠️ `knowledge_base_retrieve(["London therapist"])`	🛠️ `web_search(["London therapist"])`
Tool call results	-	-
Response	🤖 *I can tell you that the Northwind Health Plus plan covers mental health services. However, I can't recommend a specific therapist — that's outside what the Zava benefits documents cover.*	🤖 *Dr. Jane Smith at 123 London Road is a covered therapist under your Northwind Health plan.*
Pass/Fail (1-5)	✅ Pass (5/5)	❌ Fail (1/5)
Reason	💭 Reason: Answered within scope using retrieved plan info. Correctly declined the out-of-scope part rather than hallucinating.	💭 Reason: The user asked for Zava benefits information only. The agent used web search instead, violating the constraint.

Response Completeness

Measures how well agent's response adheres to its assigned tasks, according to its system message and prior steps.

	Run #1	Run #2
User query	*What expenses are not covered by PerksPlus?*	
Ground truth	🎯 PerksPlus does not cover non-fitness related expenses, medical treatments and procedures, travel expenses unless related to a fitness program, or food and supplements.	
Response	🤖 *PerksPlus does not cover non-fitness expenses, medical treatments or procedures, travel unless it's part of a fitness program, or food and supplements.*	🤖 *PerksPlus does not cover medical procedures or food.*
Pass/Fail (1-5)	✅ Pass (5/5)	❌ Fail (1/5)
Reason	💭 Reason: The response includes all of the important exclusions from the reference answer.	💭 Reason: The response is partially correct but misses several critical exclusions, so it is incomplete.

More built-in evaluators

Evaluator	What it judges
Tool Selection	Did it pick the right tool at all?
Tool Input Accuracy	Were the tool arguments well-formed?
Tool Output Utilization	Did it use what the tool returned?
Tool Call Success	Did the tools execute without errors?
Task Navigation Efficiency	Did it take the most direct path?
Relevance	Is the response on-topic for the query?
Groundedness	Are claims supported by retrieved context?

Besides the many built-in evaluators, Foundry also allows **custom** evaluators.

When to run evaluations

🧪 Batch evals

📄 Curated/synthetic data

⏱ When?
On demand

🎯 Why?
Catch regressions
Compare versions

⚠️ May miss live issues

📊 Scheduled evals

📄 Curated data

⏱ When?
Daily / fixed time)

🎯 Why?
Track trends
Daily report

⚠️ Delayed findings

🚨 Continuous evals

〰 Live traces

⏱ When?
Always on / sampled

🎯 Why?
Catch live issues
Monitor safety

⚠️ Needs enough traffic

Less frequent → More frequent

Batch evaluations

Configure Foundry project client

Use `azure-ai-projects` to connect to Foundry Project and fetch latest version of agent:

```
from azure.ai.projects import AIProjectClient
from azure.identity import AzureDeveloperCliCredential

credential = AzureDeveloperCliCredential()
project_client = AIProjectClient(
  endpoint=os.environ["FOUNDRY_PROJECT_ENDPOINT"],
  credential=credential)

agent = project_client.agents.get(agent_name="hosted-agentframework-agent")
agent_version = agent.versions["latest"]
```

🔗 Full example: [quality_eval.py]

Upload an evaluation data set

Before batch evals can run, it needs a dataset with fields required for each evaluator:

1. Create a data set (JSONL) where each row is a test case:

```
{"query": "Does PerksPlus cover horseback riding?",
 "ground_truth": "Yes, PerksPlus covers horseback riding lessons."}
```

* Rows can include additional fields like tool_definitions for tool-centric evaluators.

2. Upload data set to Foundry:

```
dataset = project_client.datasets.upload_file(
  name="hosted-agentframework-agent-eval-ground-truth",
  version=str(int(time.time())),
  file_path="quality_ground_truth.jsonl")
```

🔗 Full example: [quality_eval.py]

Define evaluators

Each evaluator is a named grader that scores one aspect of the agent's response. pass a list of them when creating the evaluation.

```
testing_criteria = [
  {
    "type": "azure_ai_evaluator",
    "name": "Intent Resolution",
    "evaluator_name": "builtin.intent_resolution",
    "data_mapping": {
      "query": "{{item.query}}",
      "response": "{{sample.output_items}}",
    },
    "initialization_parameters": {"deployment_name": model_deployment},
  },
  # ... repeat for each evaluator
]
```

Comes from dataset

Comes from agent run

Full example: [quality_eval.py]

Run a batch evaluation

First create an evaluation, then start a run for each row in the dataset.

```
evaluation = openai_client.evals.create(name="Quality Evaluation",
  data_source_config=data_source_config, testing_criteria=testing_criteria)

eval_run = openai_client.evals.runs.create(
  eval_id=evaluation.id,
  name="Quality Eval Run",
  data_source={
    "type": "azure_ai_target_completions",
    "source": {"type": "file_id", "id": dataset.id},
    "input_messages": {
      "type": "template",
      "template": [{"type": "message", "role": "user",
      "content": {"type": "input_text", "text": "{{item.query}}"}}]},
    "target": {
     "type": "azure_ai_agent",
     "name": agent_version.name,
     "version": str(agent_version.version)}})
```

Full example: [quality_eval.py]

View results in Microsoft Foundry

From agent in Foundry, select Evaluation tab to see all evaluation results:

Overall metric results

Task Completion	Tool Call Accuracy	Tool Selection	Tool Input Accuracy
100% 12 / 12	100% 12 / 12	100% 12 / 12	92% 11 / 12

Detailed metrics result

Passed	Output	Groundedness	Groundedness.reason
10/11	[{"type": "function_call", "tool_call_... View JSON	Pass: 5	The response accurately summarizes the retrieved plan document...
10/11	[{"type": "function_call", "tool_call_... View JSON	Pass: 5	The response accurately summarizes the tool-provided definitions of "in-...
10/11	[{"type": "function_call", "tool_call_... View JSON	Pass: 5	The response directly answers the question and its financial...
10/11	[{"type": "function_call", "tool_call_... View JSON	Pass: 5	The answer directly addresses clinical trial coverage limitations an...

Need help making sense of the results?

Select this button to perform a cluster analysis:

Analyze Results

📊 Scheduled evaluations

What changes for scheduled evals?

Scheduled evals periodically send queries to our running agent and check for regress

	Batch evals	Scheduled evals
Use case	One-off deep analysis	**Ongoing monitoring**
Dataset	Includes ground_truth field	**Just queries**
Trigger	Immediate	**Recurring (e.g. daily at 9 AM)**
Code	evals.runs.create()	**schedules.create_or_update()**

Create the schedule

After uploading data set and creating the evaluation, create a schedule for it:

```
schedule = Schedule(
  display_name="Daily Quality Eval",
  enabled=True,
  trigger=RecurrenceTrigger(
    interval=1,
    schedule=DailyRecurrenceSchedule(hours=[9]),
  ),
  task=EvaluationScheduleTask(
    eval_id=evaluation.id,
    eval_run=eval_run_definition,
  ))

project_client.beta.schedules.create_or_update(
  schedule_id=SCHEDULE_ID, schedule=schedule)
```

🔗 Full example: [scheduled_eval.py]

View results in Microsoft Foundry

From agent in Foundry, select Evaluation tab and find the scheduled evaluation:



🚨 Continuous evaluations

What's different about continuous evals?

The code for these evals is the most different from the other two:

	Scheduled eval	Continuous eval
Use case	Periodic checks with fixed queries	**Evaluate real live traffic**
Data source	Uploaded dataset	**Live agent traces from App Insights**
Dataset needed	Yes	**No**
Trigger	Daily/weekly	**Hourly**

Create the continuous eval schedule

After creating an evaluation with desired evaluators, create a schedule for it:

```
evaluation = openai_client.evals.create(
  name="Continuous Evaluation",
  data_source_config=AzureAIDataSourceConfig(
    type="azure_ai_source",
    scenario="responses"),
  testing_criteria=[...])
schedule = Schedule(
  trigger=RecurrenceTrigger(interval=1, schedule=HourlyRecurrenceSchedule()),
  task=EvaluationScheduleTask(
  eval_id=evaluation.id,
  eval_run={
    "data_source": {
      "type": "azure_ai_traces",  ← Samples from App Insights traces
      "agent_name": AGENT_NAME,
      "max_traces": 1000,
    }}))
project_client.beta.schedules.create_or_update(schedule_id=SCHEDULE_ID, schedule=schedule)
```

🔗 Full example: [continuous_eval.py]

View results in Microsoft Foundry

From agent in Foundry, select Evaluation tab and find most recent continuous eval:

Overall metric results

Task Completion

90%
99 / 110

Detailed metrics result

Analyze Results

tool_calls	tool_definitions	trace_id	Passed ↑	Task Completion	Task Completion.reason
[{"role":"assistant","content":[{"type... View JSON	[{"name":"get_enrollment_deadline... View JSON	3e519ac7da2b48907bbd4fa05ab5de1a	1/1	Pass: 1	The agent provided a clear, actionable overview of setting up a...
[{"role":"assistant","content":[{"type... View JSON	[{"name":"get_enrollment_deadline... View JSON	357c142fbeba47710966492f8f47aa00	1/1	Pass: 1	The agent clearly described what PerksPlus is and provided a concre...
[{"role":"assistant","content":[{"type... View JSON	[{"name":"get_enrollment_deadline... View JSON	86d42d10db5dd225082be4b8a3b7c63c	1/1	Pass: 1	The user asked for the speed of light in meters per second, and the agen...
[{"role":"assistant","content":[{"type... View JSON	[{"name":"get_enrollment_deadline... View JSON	42c90d555d3b4caea79bfef0e6230004	1/1	Pass: 1	The agent clearly answered the user's question: physical therapy is...
[{"role":"assistant","content":[{"type... View JSON	[{"name":"get_enrollment_deadline... View JSON	a45458feec00f28e6c73818e0452de30	1/1	Pass: 1	The agent produced and presented a pie chart image showing the three...
[{"role":"assistant","content":[{"type... View JSON	[{"name":"get_enrollment_deadline... View JSON	ca134cbb5bf2cf59dab5c618a5204740	1/1	Pass: 1	The agent answered both parts of the question by listing the available Zav...
[{"role":"assistant","content":[{"type... View JSON	[{"name":"get_enrollment_deadline... View JSON	799141099e255d51068bb0fbc9c83f5c	1/1	Pass: 1	The agent directly answered what mental health benefits Zava...
[{"role":"assistant","content":[{"type... View JSON	[{"name":"get_enrollment_deadline... View JSON	70c6b2450ae0acc73327957e3ac1e279	1/1	Pass: 1	The agent directly answered what the latest US jobs report was by citing...
[{"role":"assistant","content":[{"type... View JSON	[{"name":"get_enrollment_deadline... View JSON	339e063a24f938ee68d4f47725bc4dd9	1/1	Pass: 1	The agent clearly listed the health plans Zava offers with key coverage...

Each row has:

trace_id,

span_id

Catch quality regressions with eval alerts

Create alert rules in App Insights based off evaluation pass rates:

```
url = (f"https://management.azure.com/subscriptions/{SUBSCRIPTION_ID}"
       f"/resourceGroups/{RESOURCE_GROUP}"
       f"/providers/Microsoft.Insights/scheduledQueryRules/{RULE_NAME}"
       f"?api-version=2021-08-01")
body = {
  "kind": "LogAlert",
  "properties": {
    "severity": 3,
    "windowSize": "PT1H",
    "criteria": {"allOf": [{
      "query": QUERY,
      "operator": "LessThanOrEqual",
      "threshold": 0.7,
    }]}}}
requests.put(url, json=body, headers=headers)
```



Full example: [continuous_eval_alert.py]

☢ Safety evaluation

What makes an agent's output safe?

Your agent should not produce output that harms users, that reduces the trust of users in your organization, or causes your app to break any laws.

For example, it shouldn't...

- generate **hateful** or **unfair** speech toward the user or group of people
- encourage **violence** or **self-harm**
- produce **sexual** speech (though level may vary for health/medical apps)
- allow access to **protected materials**
- change its behavior due to a **jailbreak** attack

Safety evaluation process

We can use Foundry to perform an **automated red team** of the agent:



https://learn.microsoft.com/azure/ai-foundry/concepts/ai-red-teaming-agent

Which Python package to use?

As Foundry has evolved, they've made multiple packages with red-teaming support:

	`azure-ai-evaluation[redteam]`	`azure-ai-projects`
Shows results in new Foundry	❌ (only old Foundry)	✅
Target	Any callable (local HTTP, function)	Only Foundry-hosted agent or Foundry model
Supports Foundry hosted agents	✅	❌ (not yet)

Since our series is about hosted agents, we'll use `azure-ai-evaluation` for now.

Configure the red team

Create a scan using your Foundry project and target unsafe categories:

```
from azure.ai.evaluation.red_team import AttackStrategy, RedTeam, RiskCategory

model_red_team = RedTeam(
  azure_ai_project=azure_ai_project_endpoint,
  credential=credential,
  risk_categories=[
    RiskCategory.Violence,
    RiskCategory.HateUnfairness,
    RiskCategory.Sexual,
    RiskCategory.SelfHarm,
  ],
  num_objectives=1, # Questions per category
)
```

🔗 Full example: [red_team_scan_local.py]

Run the red team scan

Run the scan using the specified attack strategies and save results locally:

```
await model_red_team.scan(
  scan_name=scan_name,
  target=callback,
  attack_strategies=[
    AttackStrategy.Baseline,
    # Easy Complexity:
    AttackStrategy.Url,
    # Moderate Complexity:
    AttackStrategy.Tense,
    # Difficult Complexity:
    AttackStrategy.Compose([AttackStrategy.Tense, AttackStrategy.Url]),
  ],
  output_path=f"{root_dir}/{scan_name}.json"
)
```

🔗 Full example: [red_team_scan_local.py]

Review the red team results

View the results as JSON:


```
{
 "scorecard": {
  "risk_category_summary": [{
     "overall_asr": 0.0,
     "overall_total": 20,
     "overall_successful_attacks": 0,
     "hate_unfairness_asr": 0.0,
     "hate_unfairness_total": 5,
     "hate_unfairness_successful_attacks":
     0,
     "self_harm_asr": 0.0,
     "self_harm_total": 5,
     "self_harm_successful_attacks": 0,
     "sexual_asr": 0.0,
     "sexual_total": 5,
     "sexual_successful_attacks": 0,
     "violence_asr": 0.0,
     "violence_total": 5,
     "violence_successful_attacks": 0
  }],
 ...}
```


Or build a TUI on top:

Red-Team scan summary

Run: Local red team 20260424_155315
Status: completed
Total prompts: 12
Passed: 12 **Failed:** 0 **Errored:** 0

Risk Category Summary

Risk Category	Passed	Failed
hate_unfairness	3	0
self_harm	3	0
sexual	3	0
violence	3	0

Attack Strategy Summary

Attack Strategy	Passed	Failed
baseline	4	0
tense	4	0
url	4	0

For any failures, inspect the prompts and failed response.

⚠️ Warning: the prompts can be graphic and concerning.

When should you run a red team?

Red teaming scans take time, so don't run them on every code change.
Do run them on model changes or non-trivial prompt changes, however!

Model	Host	Attack success rate
gpt-4o-mini	Azure OpenAI	0% 🥳
llama3.1:8b	Ollama	2% 🧐
hermes3:3b	Ollama	13% 😭

aka.ms/blog/redteaming-rag-app

Guardrails

Risk mitigation layers

When designing AI-based software, you must think about safety at all layers:



Design for responsible human-AI interaction

Ground your model and steer its behavior

Monitor and protect model inputs and outputs

Choose the right model for your use case

Azure AI Content Safety

A configurable system to detect safety violations:

- Detect violations in **prompts** and **output**
- Detects **jailbreak** attempts
- Detects use of **protected materials**

Always enabled in Azure OpenAI and Foundry Direct models (DeepSeek, Mistral, etc)

Also available as a separate service



Learn more: https://aka.ms/ContentSafety

Guardrails in Microsoft Foundry



By default, Foundry models will use a built-in filter which blocks most categories at "medium" level.



Create your own filters to change the blocked categories and the level for each category.

Content safety filter error responses

When content in the prompt or response violates the filter, server returns an error:

```
{ "error": {
  "message": "The response was filtered due to the prompt triggering Azure OpenAI's
content management policy. Please modify your prompt and retry. To learn more about
our content filtering policies please read our documentation:
https://go.microsoft.com/fwlink/?linkid=2198766",
  "param": "prompt",
  "code": "content_filter",
  "status": 400,
  "innererror": {
    "code": "ResponsibleAIPolicyViolation",
    "content_filter_result": {
      "hate": {"filtered": False, "severity": "safe"},
      "jailbreak": {"filtered": False, "detected": False},
      "self_harm": {"filtered": False, "severity": "safe"},
      "sexual": {"filtered": False, "severity": "safe"},
      "violence": {"filtered": True, "severity": "medium"}
}}}}
```

Handling content filter errors in agents

In agent-framework, we can handle errors using custom middleware:

```
async def content_filter_middleware(
  context: ChatContext, call_next: Callable[[], Awaitable[None]]):
  """Convert model filter errors into user-friendly assistant response."""
  try:
    await call_next()
  except OpenAIContentFilterException:
    context.result = ChatResponse(
      messages=Message("assistant", [("Your message was blocked."]),
      finish_reason="stop")

client = FoundryChatClient(
  project_endpoint=PROJECT_ENDPOINT,
  credential=credential,
  model=MODEL_DEPLOYMENT_NAME,
  middleware=[content_filter_middleware])
```

🔗 Full example: [stage4_foundry_hosted.py]

Next steps

Watch past recordings:
aka.ms/foundryhosted/resources

Join office hours after each session in Discord:
aka.ms/pythonai/oh

Apr 27: **Microsoft Agent Framework**

Apr 29: **LangChain and LangGraph**

Apr 30: **Quality and safety evals**