

Basic concepts with R (part 1)

Rodrigo Esteves de Lima-Lopes
State University of Campinas
rll307@unicamp.br

Introduction

In this tutorial we will try to do get some introductory concepts on R language, mostly getting some basic conventions.

Some very basic stuff

R is a good arithmetic tool. If we type the following lines in our script and run each at a time:

```
1+5
```

```
## [1] 6
```

```
5-4
```

```
## [1] 1
```

```
100/33
```

```
## [1] 3.030303
```

```
5^2
```

```
## [1] 25
```

```
5**2
```

```
## [1] 25
```

```
9/4
```

```
## [1] 2.25
```

```
9*4
```

```
## [1] 36
```

```
(300 * 9) + (500 / 2)
```

```
## [1] 2950
```

```
x <- 2L
```

```
x
```

```
## [1] 2
```

```
typeof(x)
```

```
## [1] "integer"
```

```

y <- 2.5
y

## [1] 2.5
typeof(y)

## [1] "double"
z <- 3+2i
z

## [1] 3+2i
typeof(z)

## [1] "complex"
h <- "h"
typeof(h)

## [1] "character"
h

## [1] "h"
q1 <- TRUE
typeof(q1)

## [1] "logical"
q1

## [1] TRUE
q2 <- FALSE
q2

## [1] FALSE
typeof(q2)

## [1] "logical"
a <- seq(0,100, 2)
a

## [1] 0 2 4 6 8 10 12 14 16 18 20 22 24 26 28 30 32 34 36
## [20] 38 40 42 44 46 48 50 52 54 56 58 60 62 64 66 68 70 72 74
## [39] 76 78 80 82 84 86 88 90 92 94 96 98 100
typeof(a)

## [1] "double"
repetition <- rep("repetition",100)
repetition

## [1] "repetition" "repetition" "repetition" "repetition" "repetition"
## [6] "repetition" "repetition" "repetition" "repetition" "repetition"
## [11] "repetition" "repetition" "repetition" "repetition" "repetition"
## [16] "repetition" "repetition" "repetition" "repetition" "repetition"
## [21] "repetition" "repetition" "repetition" "repetition" "repetition"

```

```
## [26] "repetition" "repetition" "repetition" "repetition" "repetition"
## [31] "repetition" "repetition" "repetition" "repetition" "repetition"
## [36] "repetition" "repetition" "repetition" "repetition" "repetition"
## [41] "repetition" "repetition" "repetition" "repetition" "repetition"
## [46] "repetition" "repetition" "repetition" "repetition" "repetition"
## [51] "repetition" "repetition" "repetition" "repetition" "repetition"
## [56] "repetition" "repetition" "repetition" "repetition" "repetition"
## [61] "repetition" "repetition" "repetition" "repetition" "repetition"
## [66] "repetition" "repetition" "repetition" "repetition" "repetition"
## [71] "repetition" "repetition" "repetition" "repetition" "repetition"
## [76] "repetition" "repetition" "repetition" "repetition" "repetition"
## [81] "repetition" "repetition" "repetition" "repetition" "repetition"
## [86] "repetition" "repetition" "repetition" "repetition" "repetition"
## [91] "repetition" "repetition" "repetition" "repetition" "repetition"
## [96] "repetition" "repetition" "repetition" "repetition" "repetition"

typeof(repetition)

## [1] "character"
```

In a nutshell

These commands taught us a couple of things:

1. R can make some basic calculations
2. R can store values in its memory
 - But be aware that data is not saved until you tell R to do so
1. We use “<-” for variable attribution
 - “=” is also possible, but “<-” is a better choice because
 1. “=” is already present inside some commands, so “<-” is exclusive of variable attribution
 2. “<-” brings us some direction regarding the attribution
1. There are some kinds of data in R, the basic ones are:
 - **Integer**: whole numbers, without decimals
 - **Double**: numbers with decimals
 - **Complex**: numbers with scientific notation
 - **Character**: words or letters
 - **Logical** (or Boolean): meanings between TRUE (true) and FALSE (false)
 - **Vector**: ordered sequence of numbers or characters
1. Commands in R are always a sequence of letters followed by “()” like `seq()`
2. The way to tell R a value ought to be understood as a character is to write between quotations marks
3. Each command might get a set of arguments