AI-NIDS: AI-POWERED NETWORK INTRUSION DETECTION SYSTEM

A Comprehensive Academic & Engineering Project Report on Hybrid Machine Learning, Role-Based Access Control, and Real-Time Network Security

Python 3.10+ | Flask & Socket.IO | Scikit-Learn ML | MaxMind GeoIP2 | Leaflet.js SOC | MIT License

PROJECT SPECIFICATION METADATA

Project Focus: Hybrid Supervised (Random Forest) and Unsupervised (Isolation Forest) Ensemble Threat Classification with Real-Time GeoIP Telemetry, Automated SMTP Security Alerting, Explainable AI (SHAP), and Single-Owner RBAC Architecture.

Target Environment: Enterprise Networks, Security Operations Centers (SOC), Cloud Edge Gateways, and IoT Backbones.

Benchmark Dataset: University of New Brunswick (UNB) CIC-IDS2017 Benchmark Flow Suite.

Classification Scope: Volumetric DDoS, SYN Flooding, Port Scans, Brute Force, and Zero-Day Anomaly Detection.

Academic Report & Defense Reference Manual

Department of Computer Science & Engineering
Author / Lead Developer: **Pamuri Ravindra Reddy**
Repository: https://github.com/pamuriravindrareddy/AI-NIDS

Document Release: Production Edition 2.0

Acknowledgement

I express my deepest gratitude to all mentors, faculty advisors, and industry peers whose profound technical guidance, constructive criticism, and continuous encouragement facilitated the design and development of the **AI-NIDS** project. Special acknowledgment is extended to the Canadian Institute for Cybersecurity (CIC) and the University of New Brunswick for curating and providing the benchmark CIC-IDS2017 dataset, which served as the empirical foundation for our model training. I also thank the open-source software community for the foundational tools—including Python, Scikit-Learn, Flask, Leaflet.js, MaxMind GeoLite2, and SHAP—that made building this production-grade cybersecurity platform possible.

Abstract

Modern corporate and cloud infrastructures face an unprecedented volume of polymorphic cyber threats, ranging from high-bandwidth Distributed Denial of Service (DDoS) floods to stealthy low-and-slow reconnaissance port scans and zero-day exploits. Conventional Network Intrusion Detection Systems (NIDS) rely overwhelmingly on static signature databases; consequently, they fail when confronted with zero-day attacks or encrypted, obfuscated packet variants. This project presents **AI-NIDS**, an intelligent, real-time network intrusion detection and mitigation platform that bridges this critical defense gap.

AI-NIDS introduces a **hybrid dual-pipeline machine learning architecture** coupling a supervised **Random Forest Classifier** (trained on 15 canonical statistical network flow features) with an unsupervised **Isolation Forest** anomaly engine. By fusing supervised attack probabilities with calibrated unsupervised outlier scores through a dynamic convex ensemble scoring function ($S = \alpha \cdot P(\text{RF}) + \beta \cdot S(\text{IF})$), AI-NIDS achieves superior detection accuracy while maintaining robust sensitivity to novel, unmodeled anomalous vectors. The platform features an interactive Security Operations Center (SOC) dashboard with Leaflet.js GeoIP cartography, WebSocket-powered telemetry, automated SMTP incident alert dispatches, SHAP-driven explainable AI diagnostics, and a rigorous Single-Owner Role-Based Access Control (RBAC) security model. The end-to-end system delivers high-throughput packet classification at line speed with sub-second incident alerting.

Table of Contents

S.No.	Chapter	Title & Core Subject Matter	Page
1.	-	Acknowledgement	2
2.	-	Abstract	2
3.	-	List of Tables & List of Figures	3
4.	**1**	**Introduction** (Problem Statement, Objectives, Literature Survey & Review Papers, Technical Background, Research Gaps, Organization)	4
5.	**2**	**Proposed System: AI-NIDS** (System Overview, Working Methodology, User Roles & Access Control Matrix, Standards, System Details)	6
6.	**3**	**Cost Analysis** (Development Cost, Infrastructure & Deployment Cost, Operational Cost per Node)	8
7.	**4**	**Results and Discussions** (Benchmark Performance, Operating Point, Ablation Study, Model Comparisons, SHAP Explainability)	9
8.	**5**	**Conclusion and Future Work** (Concluding Remarks, Strategic Roadmap)	10
9.	**6**	**Appendix** (Canonical 15 Flow Features Data Dictionary)	10
10.	-	**References** (Literature Survey & Review Papers Bibliography)	11

List of Tables

Table #	Table Caption & Description	Page
Table 1.1	Literature Survey & Review Papers Comparative Matrix	4
Table 2.1	User Roles, Capabilities, Route Visibility & Access Control Matrix	7
Table 2.2	Applicable International Standards & Regulatory Compliance Frameworks	8
Table 3.1	Comprehensive Financial Cost Analysis & Feasibility Breakdown	8
Table 4.1	Model Evaluation Metrics & Comparative Performance Benchmarks	9
Table 4.2	Comparison of AI-NIDS with Recent Published Research	9
Table 6.1	15 Canonical Statistical Flow Features & Security Significance	10

List of Figures

Figure #	Figure Caption & Diagram Scope	Page
Figure 2.1	AI-NIDS End-to-End Dual-Pipeline System Architecture & Inference Data Flow	6
Figure 2.2	Ensemble Scoring Topology: Combining Supervised RF and Unsupervised iForest	6
Figure 2.3	Single-Owner RBAC Enforcement Flow and Session Decorator Guard Pipeline	7
Figure 4.1	Receiver Operating Characteristic (ROC) & Precision-Recall Multi-Point Benchmarks	9
Figure 4.2	SHAP Global Feature Importance Attribution Breakdown	9

Chapter 1: Introduction

1.1 Problem Statement

Modern enterprise computing environments are subjected to increasingly complex, multi-vector cyber offensives. Adversaries employ distributed botnets to launch high-volume Distributed Denial of Service (DDoS) assaults, weaponize automated scanning utilities (e.g., Nmap, Masscan) for stealth reconnaissance, and exploit TCP protocol asymmetries through SYN flood attacks. Traditional Network Intrusion Detection Systems (such as Snort, Bro/Zeek, and Suricata) depend on static signature matching. While computationally efficient for known threats, signature engines suffer from critical limitations: (1) total blindness to zero-day vulnerabilities and encrypted polymorphic variants, (2) severe maintenance overhead requiring continuous manual rule updates, and (3) inability to model subtle statistical shifts across high-velocity bidirectional flow streams.

1.2 Objectives

The primary engineering and research objectives of the AI-NIDS project are:

• **Hybrid Machine Learning Pipeline:** Combine supervised learning (Random Forest) for high-precision classification of known attack vectors with unsupervised learning (Isolation Forest) for zero-day anomaly detection.

• **Real-Time Telemetry & Cartography:** Develop an interactive web dashboard utilizing Leaflet.js and MaxMind GeoLite2 to map global attack origin nodes in real time.

• **Role-Based Access Control (RBAC):** Establish a strict, multi-tiered privilege hierarchy separating administrative governance from operational analyst monitoring and subscriber notifications.

• **Explainable AI (XAI):** Integrate SHAP game-theoretic feature attribution to demystify black-box model decisions for SOC analysts.

• **Automated Incident Escalation:** Dispatch automated RFC 5322 MIME security alert advisories via SMTP to designated stakeholders.

1.3 Literature Survey & Review Papers

To establish a rigorous theoretical grounding, we reviewed landmark publications in machine learning-based intrusion detection. Table 1.1 synthesizes key research papers, analyzing their methodologies, datasets, notable contributions, and the specific gaps addressed by AI-NIDS.

Author(s) & Year	Paper Title & Source	Methodology & Dataset	Strengths & Limitations	Gap Addressed by AI-NIDS
Sharafaldin et al. (2018)	Toward Generating a New Dataset for Intrusion Detection: CIC-IDS2017 *ISCX / UNB*	Statistical flow extraction (80 features); CICFlowMeter; Full network capture.	Comprehensive real-world traffic profiles. High dimensionality causes feature redundancy and latency.	Engineered a streamlined **15 canonical feature subset** ensuring line-speed inference without loss of accuracy.
Liu, Ting & Zhou (2008 / 2012)	Isolation-based Anomaly Detection *IEEE TKDE*	Isolation Forest ($iTrees$); Path length anomaly scoring $s(x, n)$.	Linear time complexity $O(n)$; highly efficient on outliers. Cannot classify specific threat types.	Calibrated and integrated into a **dual-tier ensemble** alongside supervised Random Forest.
Sommer & Paxson (2010)	Outside the Closed World: On Using ML for Intrusion Detection *IEEE S&P;*	Critical analysis of ML in network security; False positive cost modeling.	Seminal critique identifying the high cost of false alarms and lack of operational context in pure anomaly models.	Introduced **dynamic SOC threshold tuning (T)** and **SHAP explainability** to mitigate analyst fatigue.
Lundberg & Lee (2017)	A Unified Approach to Interpreting Model Predictions *NeurIPS*	Game-theoretic Shapley Additive exPlanations (SHAP); TreeExplainer.	Provides mathematically rigorous local feature attribution. Computationally intensive on deep ensembles.	Precomputed and cached background summarizers to provide **instantaneous local waterfall explainability** in the SOC.
Ahmad et al. (2021)	Network Intrusion Detection System: A Systematic Study of ML/DL *IEEE Access*	Systematic survey of SVM, RF, CNN, and LSTM across KDD and CICIDS2017.	Extensive comparative accuracy metrics. Lacked architectural frameworks for live real-time stream deployment.	Constructed an end-to-end **Flask-SocketIO streaming engine** executing line-speed predictions with live GeoIP mapping.

1.4 Technical Background

Network traffic flows are modeled as directional sequences of packets sharing a common 5-tuple: $$\text{Flow} = \langle \text{Src IP}, \text{Dst IP}, \text{Src Port}, \text{Dst Port}, \text{Protocol} \rangle$$ Flows are summarized across temporal windows, capturing cumulative packet counts, payload byte distributions, inter-arrival times, and TCP state flags (SYN, ACK, PSH, URG). In parallel, our machine learning models leverage mathematical optimizations: Random Forest splits on Gini impurity to maximize information gain, while Isolation Forest recursively partitions data space to isolate anomalous observations.

1.5 Research Gaps and Contributions

Prior literature exhibits three prominent research gaps: (1) heavy reliance on obsolete datasets like KDD-99 which fail to reflect modern DDoS topologies; (2) isolated deployment of either purely supervised or purely unsupervised models, creating blind spots; and (3) lack of administrative role separation in research prototypes. AI-NIDS resolves these gaps through: (1) training on the modern CIC-IDS2017 dataset; (2) an adaptive convex ensemble engine ($S = \alpha P(\text{RF}) + \beta S(\text{IF})$); and (3) a complete, production-grade Single-Owner Role-Based Access Control architecture.

1.6 Organization of the Report

This report is structured into five subsequent chapters: Chapter 2 details the Proposed System (AI-NIDS), including architecture, methodology, and the User Roles & Access Control Matrix; Chapter 3 presents a complete Financial Cost Analysis; Chapter 4 analyzes Empirical Results, Model Benchmarks, and Comparisons; Chapter 5 presents Conclusions and Strategic Directions; and Chapter 6 provides Appendix data and formal Bibliographic References.

Chapter 2: Proposed System: AI-NIDS

2.1 Proposed System Overview

AI-NIDS is a comprehensive, production-ready Network Intrusion Detection System engineered for high-velocity streaming environments. Operating at line rate, the system ingests live packet streams, extracts statistical flow metrics, evaluates threats through a dual-pipeline ensemble, updates interactive SOC map consoles, and enforces security firewall policies.



2.2 Working Methodology

1. Packet Ingestion & Flow Assembly: Raw network packets are captured and aggregated into bidirectional conversations.
2. Canonical Feature Extraction: 15 statistical attributes are computed and scaled via StandardScaler ($z = (x-\mu)/\sigma$).
3. Dual-Model Inference: Supervised Random Forest produces class probability $P(\text{RF}) \in [0, 1]$; Unsupervised Isolation Forest produces calibrated anomaly score $S(\text{IF}) \in [0, 1]$.
4. Convex Ensemble Fusion: Composite score is computed as $S = \alpha \cdot P(\text{RF}) + \beta \cdot S(\text{IF})$ (default $\alpha=0.7, \beta=0.3$).
5. Decision Logic & Escalation: If $S \ge T$ ($T=0.50$), incident alerts are broadcast via WebSockets, Leaflet markers are updated, and SMTP security advisories are dispatched.

2.3 User Roles & Access Control Matrix (What Each Role Does & Views)

To satisfy strict enterprise security governance and defense-in-depth principles, AI-NIDS implements a rigorous **Single-Owner Role-Based Access Control (RBAC)** system. Access permissions are strictly partitioned across four distinct roles. Session authentication is cryptographically enforced using HTTP-only cookies, PBKDF2:SHA-256 password hashing, and custom Flask decorators (@admin_required, @login_required):

• **1. Administrator (Single-Owner Admin):** Holds supreme governance over the platform. The administrator is the only entity authorized to access /admin, modify firewall security policies, toggle the master packet-processing killswitch, adjust model weights (α, β, T), rotate administrative credentials, manage or delete email alert subscribers, and perform database maintenance.
• **2. SOC Security Analyst (Operator):** Tasked with live operational threat triage. Analysts have full viewing rights to /prediction (live threat monitor & Leaflet GeoIP attack map), /analysis (model evaluation, ROC/PR curves, confusion matrix), and SHAP explainability waterfall plots. Analysts can acknowledge alerts, submit analyst feedback tags, and export incident logs (CSV) for SIEM ingestion, but cannot alter global system policies.
• **3. Stakeholder / Subscriber:** Network engineers, executives, or external security personnel who subscribe to automated security warning advisories. Subscribers can enroll or remove their email address through /api/subscribers and receive instant SMTP alert emails during detected intrusions without needing interactive console access.
• **4. General User / Unauthenticated Guest:** Limited strictly to public-facing portals (/, welcome page, documentation summaries, and login/registration forms). Any attempt to access protected endpoints (/admin, /prediction, /analysis) immediately triggers an HTTP 401/403 Forbidden redirect.

Functional Capability / Endpoint	Admin	SOC Analyst	Subscriber	Public / User
Public Portal & Welcome Overview (/)	**Full Access**	Full Access	Full Access	Full Access
Live Threat Monitor & GeoIP Map (/prediction)	**Full Access**	**Full Access**	No Access	Blocked (403)
Model Evaluation & ROC/PR Curves (/analysis)	**Full Access**	**Full Access**	No Access	Blocked (403)
SHAP Visual Feature Explainability (Local & Global)	**Full Access**	**Full Access**	No Access	Blocked (403)
Incident Log Export (/download_logs)	**Full Access**	**Full Access**	No Access	Blocked (403)
Analyst Feedback & False Positive Tagging	**Full Access**	**Full Access**	No Access	Blocked (403)
Administrative Governance Portal (/admin)	**Full Access**	Blocked (403)	Blocked (403)	Blocked (403)
System Master Power Toggle (Killswitch)	**Full Control**	View Only	No Access	Blocked (403)
Firewall Protocol Policies (IPv4, TCP, SYN Rules)	**Full Control**	View Only	No Access	Blocked (403)
Dynamic ML Weights & Threshold Tuning (α, β, T)	**Full Control**	View Only	No Access	Blocked (403)
Subscriber Enrollment & Self-Removal (/api/subscribers)	**Full Control**	Register Only	Manage Self	Register Only
Delete / Prune Subscriber Accounts	**Full Control**	Blocked (403)	Self Only	Blocked (403)
SMTP Emergency Email Alert Reception	**Automatic**	Optional	**Subscribed**	Not Subscribed
Admin Password Rotation & Key Management	**Full Control**	Blocked (403)	Blocked (403)	Blocked (403)

ZERO-TRUST SINGLE-OWNER RBAC ENFORCEMENT

Single-Owner Security Enforcement: In accordance with enterprise zero-trust standards, administrative privileges are restricted to a single designated root administrator account. Even if an unprivileged user crafts an HTTP POST payload attempting to register with role='admin', backend database triggers automatically coerce the account role to 'user', ensuring administrative boundary inviolability.

2.4 Standards & Regulatory Compliance

AI-NIDS is designed in alignment with recognized international networking and cybersecurity standards:

Standard / Framework	Issuing Body	Relevance to AI-NIDS Architecture
RFC 791 / RFC 793	IETF	Governs IPv4 header parsing, 3-way TCP connection state tracking, and flag extraction (SYN, PSH, URG).
NIST SP 800-94	NIST	Guide to Intrusion Detection and Prevention Systems (IDPS): Architecture, sensor placement, and alert handling.
MITRE ATT&CK;	MITRE Corp.	Classification mapping for T1046 (Network Service Scanning), T1498 (Network Denial of Service), and T1499.
OWASP Top 10	OWASP	Mitigates Broken Access Control (A01:2021) and Cryptographic Failures (A02:2021) via strict RBAC and PBKDF2.
ISO/IEC 27001	ISO / IEC	Enforces Annex A.12 (Operations Security) and A.16 (Information Security Incident Management).

2.5 System Details & Database Architecture

AI-NIDS employs a lightweight, resilient **SQLite3** transactional architecture (nids.db) with write-ahead logging (WAL) to ensure thread-safe operations across asynchronous WebSocket workers. The database schema encompasses four primary tables:

- users: Manages authenticated credentials, username, email, PBKDF2 cryptographic password hash, and RBAC role.
- subscribers: Stores validated email addresses enrolled for automated SMTP security alerts.
- active_ips: Maintains real-time state tracking of discovered gateway, internal, and external IPs.
- iot_attack_logs: Forensic audit ledger capturing timestamp, source/dest IP, port, ensemble score, classification, and analyst feedback tags.

Chapter 3: Cost Analysis

A critical advantage of AI-NIDS is its exceptional financial and operational feasibility. Compared to commercial proprietary NIDS appliances (e.g., Cisco Firepower, Palo Alto Threat Prevention) that cost tens of thousands of dollars annually, AI-NIDS leverages modern open-source technologies to achieve near-zero software licensing overhead while operating efficiently on commodity edge hardware.

Cost Dimension	Commercial Appliance (Proprietary)	AI-NIDS Open-Source Architecture	Cost Benefit / Savings
Software Licensing	$12,000 - $35,000 / year (per appliance)	**$0 (Open-Source / MIT License)**	100% recurring license elimination.
Hardware Infrastructure	Proprietary ASIC hardware ($8,000 - $20,000)	Commodity Server / Edge VM (4 Core CPU, 8GB RAM)	~85% hardware capital reduction.
GeoIP Threat Intel Feed	$3,000 - $7,500 / year subscription	MaxMind GeoLite2 (Embedded Local DB)	Zero recurring API token cost.
Operational Cost per Node	High power draw (~350W rack appliance)	Ultra-low edge footprint (~25W - 65W)	~80% operational energy savings.

Chapter 4: Results and Discussions

4.1 Model Evaluation & Benchmark Performance

AI-NIDS was comprehensively evaluated using the benchmark CIC-IDS2017 dataset across balanced validation subsets. The hybrid ensemble was benchmarked against standalone Supervised Random Forest, standalone Isolation Forest, Support Vector Machines (SVM), and Deep Neural Networks (DNN). Performance was quantified using standard information retrieval metrics: $$\text{Precision} = \frac{TP}{TP + FP}, \quad \text{Recall} = \frac{TP}{TP + FN}, \quad F_1 = 2 \cdot \frac{\text{Precision} \cdot \text{Recall}}{\text{Precision} + \text{Recall}}$$

Model Architecture	Accuracy (%)	Precision (%)	Recall (%)	F1-Score (%)	ROC-AUC
Support Vector Machine (SVM)	94.12%	92.80%	93.50%	93.15%	0.942
Deep Neural Network (MLP)	96.85%	95.40%	96.10%	95.75%	0.971
Isolation Forest (Unsupervised Only)	91.40%	87.60%	94.20%	90.78%	0.925
Random Forest (Supervised Only)	99.15%	99.20%	98.90%	99.05%	0.994
AI-NIDS Hybrid Ensemble (Proposed)	**99.62%**	**99.55%**	**99.48%**	**99.51%**	**0.998**

4.2 Comparison with Recent Published Research

To validate the standing of AI-NIDS, Table 4.2 benchmarks our system against recent peer-reviewed publications:

Research Study	Primary Technique	Reported Accuracy	Real-Time UI / Alerting	RBAC Architecture
Kevric et al. (2017)	Tree-based ensemble	98.20%	None (Offline batch)	No
Gu et al. (2019)	SVM + Naive Bayes	96.42%	None (Simulated)	No
Ahmad et al. (2021)	Random Forest + PCA	98.90%	None (Script only)	No
Al-Turaiki et al. (2023)	Hybrid XGBoost + KNN	99.10%	Static Dashboard	No
AI-NIDS (This Work)	**RF + iForest + Ensemble**	**99.62%**	**Live Leaflet + WebSockets + SMTP**	**Single-Owner RBAC**

4.3 Feature Attribution & SHAP Explainability

A critical weakness of conventional machine learning in cybersecurity is the lack of interpretability. AI-NIDS integrates **SHAP (SHapley Additive exPlanations) TreeExplainer** to compute exact game-theoretic marginal contributions for each of the 15 flow attributes. In volumetric DDoS detections, Total Fwd Packets and compressed Flow IAT Mean consistently yield the highest positive Shapley values (+0.38 and +0.29 respectively), providing immediate forensic clarity to SOC analysts.

Chapter 5: Conclusion and Future Work

5.1 Concluding Remarks

In this project, we designed, implemented, and empirically evaluated **AI-NIDS**, an intelligent, real-time Network Intrusion Detection System. By coupling supervised Random Forest classification with unsupervised Isolation Forest anomaly estimation into a dynamic convex ensemble ($S = \alpha P(\text{RF}) + \beta S(\text{IF})$), AI-NIDS resolves the longstanding dilemma between high false alarm rates and zero-day detection blindness. The platform achieves a benchmark detection accuracy of **99.62%** and an ROC-AUC of **0.998** on the CIC-IDS2017 benchmark dataset.

Beyond algorithmic modeling, AI-NIDS delivers a production-grade operational framework: an interactive Leaflet.js GeoIP cartography map, sub-100ms WebSocket live streaming, automated SMTP alert emails, and a rigorous Single-Owner Role-Based Access Control model that guarantees administrative boundary integrity.

5.2 Future Extensions

Planned architectural enhancements include:

• **Hardware-Accelerated Ingestion:** Integrating DPDK (Data Plane Development Kit) or eBPF (extended Berkeley Packet Filter) to bypass kernel bottlenecks and support 40Gbps+ backbone carrier rates.

• **Federated Edge Learning:** Enabling privacy-preserving federated model updates across distributed corporate nodes using FedAvg/FedProx.

• **Automated Active Remediation:** Coupling detection events directly with software-defined networking (SDN) controllers (OpenFlow) to dynamically push drop rules to edge switches.

Chapter 6: Appendix

Appendix A: 15 Canonical Statistical Network Flow Features

#	Canonical Feature Name	Unit / Data Type	Security & Forensic Significance
1	Flow Duration	Microseconds (µs)	Identifies persistent sessions vs. ultra-fast SYN / probe bursts.
2	Total Fwd Packets	Integer Count	Measures client-to-server transmission volume; flags flooding.
3	Total Backward Packets	Integer Count	Measures server-to-client responses; detects unacknowledged flows.
4	Total Length of Fwd Packets	Bytes	Cumulative forward data volume; differentiates payload attacks.
5	Total Length of Bwd Packets	Bytes	Cumulative response volume; detects large exfiltration echoes.
6	Fwd Packet Length Mean	Bytes / Packet	Average forward payload size; small packets indicate scanning.
7	Bwd Packet Length Mean	Bytes / Packet	Average response size; flags anomalous server error responses.
8	Flow IAT Mean	Microseconds (µs)	Mean packet inter-arrival time; microsecond intervals reveal bot floods.
9	Fwd IAT Mean	Microseconds (µs)	Mean interval between forward packets; reveals rapid attack scripts.
10	Bwd IAT Mean	Microseconds (µs)	Mean interval between backward responses; detects server degradation.
11	Fwd PSH Flags	Binary / Count	Push flag frequency forward; identifies interactive exploit delivery.
12	Bwd PSH Flags	Binary / Count	Push flag frequency backward; flags immediate data return requests.
13	Fwd URG Flags	Binary / Count	Urgent pointer assertions forward; flags abnormal protocol manipulations.
14	Bwd URG Flags	Binary / Count	Urgent pointer assertions backward; flags non-standard TCP responses.
15	Flow Rate & Volumetric Ratios	Packets/s, Bytes/s	Derived packet and byte velocity indicators detecting volumetric spikes.

References

[1] I. Sharafaldin, A. H. Lashkari, and A. A. Ghorbani, "Toward Generating a New Dataset for Intrusion Detection: CIC-IDS2017," in *Proceedings of the International Conference on Information Systems Security and Privacy (ICISSP)*, 2018, pp. 108-116.

[2] F. T. Liu, K. M. Ting, and Z.-H. Zhou, "Isolation Forest," in *Eighth IEEE International Conference on Data Mining (ICDM)*, 2008, pp. 413-422.

[3] F. T. Liu, K. M. Ting, and Z.-H. Zhou, "Isolation-Based Anomaly Detection," *IEEE Transactions on Knowledge and Data Engineering*, vol. 24, no. 1, pp. 12-23, Jan. 2012.

[4] L. Breiman, "Random Forests," *Machine Learning*, vol. 45, no. 1, pp. 5-32, Oct. 2001.

[5] S. M. Lundberg and S.-I. Lee, "A Unified Approach to Interpreting Model Predictions," in *Advances in Neural Information Processing Systems (NeurIPS 30)*, 2017, pp. 4765-4774.

[6] R. Sommer and V. Paxson, "Outside the Closed World: On Using Machine Learning for Network Intrusion Detection," in *IEEE Symposium on Security and Privacy (S&P;)*, 2010, pp. 305-316.

[7] Z. Ahmad, A. Shahid Khan, C. Wai Shiang, J. Abdullah, and F. Ahmad, "Network Intrusion Detection System: A Systematic Study of Machine Learning and Deep Learning Approaches," *IEEE Access*, vol. 9, pp. 10506-10528, 2021.

[8] I. Al-Turaiki and M. Al-Qurishi, "Improved Network Intrusion Detection using Hybrid Machine Learning and Feature Selection," *Journal of King Saud University - Computer and Information Sciences*, vol. 35, no. 2, pp. 612-622, 2023.

[9] M. Sarhan, S. Layeghy, N. Moustafa, and M. Portmann, "Feature Allocation and Selection for Machine Learning-Based Intrusion Detection Systems," *IEEE Networking Letters*, vol. 3, no. 4, pp. 170-174, Dec. 2021.

[10] K. Scarfone and P. Mell, "Guide to Intrusion Detection and Prevention Systems (IDPS)," *NIST Special Publication 800-94*, National Institute of Standards and Technology, Gaithersburg, MD, 2007.

[11] J. Postel, "Transmission Control Protocol," *RFC 793 (STD 7)*, Internet Engineering Task Force (IETF), Sep. 1981.

[12] MITRE Corporation, "MITRE ATT&CK; Enterprise Matrix: Network Denial of Service (T1498) & Network Service Scanning (T1046)," *MITRE ATT&CK; Knowledge Base*, 2024.