Feature Vector Difference based Authorship Verification for Open-World Settings

PAN at CLEF 2021

Janith Weerasinghe janith@nyu.edu

Rhia Singh rhia.singh@macaulay.cuny.edu

Rachel Greenstadt greenstadt@nyu.edu



MACAULAY HONORS COLLEGE



PAN 2021 Authorship Verification Task

 Predict if two documents are written by the same author. The documents are written by previously unseen authors on previously unseen topics

```
1.{"id": "6cced668-6e51-5212-873c-717f2bc91ce6", "fandoms": ["Fandom 1", "Fandom 2"], "pair": ["Text 1...", "Text 2..."]}
2.{"id": "ae9297e9-2ae5-5e3f-a2ab-ef7c322f2647", "fandoms": ["Fandom 3", "Fandom 4"], "pair": ["Text 3...", "Text 4..."]}

1.{"id": "6cced668-6e51-5212-873c-717f2bc91ce6", "same": true, "authors": ["1446633", "1446633"]}
2.{"id": "ae9297e9-2ae5-5e3f-a2ab-ef7c322f2647", "same": false, "authors": ["1535385", "1998978"]}
```


Training Dataset:

Small: 52,590 Document pairs

Large: 275,486 Document pairs

~ 21,000 characters, ~4,800 tokens per document

Approach



Features

- Character tri-grams (TF IDF)
- Special Characters (TF IDF)
- Frequency of Function Words
- Average number of characters per word
- Distribution of word-lengths (1-10)
- Vocabulary Richness measures*
- Unique Spellings (fraction of tokens)*
 - Commonly misspelled words, British spelling of words, and popular online abbreviations

Features

Example:

The Soviets had already been merciless, ruthless as the next army.

POS Tags:

```
[('The', 'DT'), ('Soviets', 'NNPS'), ('had', 'VBD'),
('already', 'RB'), ('been', 'VBN'), ('merciless',
'NN'), (',', ','), ('ruthless', 'NN'), ('as', 'IN'),
('the', 'DT'), ('next', 'JJ'), ('army', 'NNP'), ('.',
'.')]
```

Parse Tree:

```
(S
          (NP The/DT Soviets/NNPS)
          (VP had/VBD already/RB been/VBN)
          (NP merciless/NN)
          ,/,
          (NP ruthless/NN)
          as/IN
          (NP the/DT next/JJ army/NNP)
```

- POS-Tag tri-grams (TF IDF)
- POS-Tag chunk tri-grams (TF IDF) :
 - [NP VP NP , NP IN NP .]
- POS tag chunk construction (TF IDF) :
 - NP[DT NNPS], VP[VBD RB VBN], NP[NN], NP[NN], NP[DT JJ NNP]
- Function-word and POS tag hybrid trigrams*:
 - $^{\circ}$ [The NNPS had already been NN , NN as the JJ NNP]
- POS tag ratios*

* New in this year's model

Classifier

- Logistic Regression Classifier
 - Trained using Stochastic Gradient Descent
- Trained using 75% data
 - No training set authors in the test set

Results

Dataset / Model Version	AUC	C@1	F0.5U	F1-Score	Brier
Small Dataset, early submission	0.955	0.890	0.894	0.889	0.919
Small Dataset, local test set	0.965	0.903	0.928	0.903	0.925
Small Dataset (trained on full	0.967	0.910	0.907	0.927	0.929
dataset), final evaluation	0.307	0.310	0.307	0.327	0.929
•	0.967	0.909	0.918	0.915	0.928

Thank You!

Questions:

Janith Weerasinghe: janith@nyu.edu

Source Code and Models:

https://github.com/janithnw/pan2021 authorship verification

Acknowledgements:

PAN 2021 organizers and reviewers
Funded by NSF Grant 1931005 and the McNulty Foundation

