

Operational Architecture and Implementation of Case Classification Sheets in NVivo: Advanced Data Modeling, Structural Metadata Integration, and Cross-Case Analytics

Architectural Foundations of Case Classifications in Qualitative Inquiry

Ontological Separation of Thematic Coding and Structured Metadata

In computer-assisted qualitative data analysis software (CAQDAS), research materials are systematically organized by establishing a boundary between interpretive thematic coding and structured categorical metadata. Qualitative inquiry requires computational environments that preserve the descriptive richness of unstructured textual, audio, or visual data while simultaneously enabling systematic, comparative querying across structured descriptive dimensions. Within platforms such as NVivo, this operational dichotomy is resolved by separating codes (formerly termed thematic nodes) from cases and their corresponding classifications.

Thematic coding captures conceptual, theoretical, or emerging phenomena identified by the researcher within the data, such as institutional trust, barriers to healthcare access, or professional identity renegotiation. Conversely, structural metadata captures fixed, descriptive properties inherent to the entities being studied, including demographic markers, organizational parameters, or geographic coordinates. Conflating these two layers introduces severe confounding into qualitative research designs. When an analyst creates thematic codes for descriptive demographic characteristics—such as coding interview fragments directly to a node labeled "Female"—the analytical model loses the capability to dynamically intersect conceptual themes with participant demographics.

Case classification architecture establishes an underlying relational database structure within the qualitative project. This metadata layer transforms unstructured narrative fragments into structured entities suitable for cross-tabulation, comparative hypothesis testing, and mixed-methods triangulation. By isolating qualitative coding within thematic nodes and assigning demographic characteristics to structured case classifications, researchers can interrogate complex datasets to determine whether specific experiential patterns correlate with defined participant attributes.

The Case Construct and Units of Analysis

A case in NVivo represents the fundamental unit of analysis selected for an investigation. While a file or source corresponds to an empirical data asset—such as an interview transcript

document, an audio recording, a video file, or an open-ended survey spreadsheet—a case represents the real-world entity to which that data pertains. Depending on the research design, the unit of analysis embodied by a case can be operationalized as an individual human participant, a collective social unit such as a family or household, an organizational entity like a hospital clinic or small business enterprise, a bounded geographical district, or a specific temporal epoch within longitudinal research.

In complex qualitative research designs, a single empirical data file frequently spans multiple units of analysis. In a focus group transcript containing spoken interactions among six participants, treating the transcript document as the unit of analysis obscures individual contributions. By establishing each participant as an independent case, the qualitative text can be segmented and coded to individual case containers, ensuring that each speaker's contributions remain linked to their specific demographic profile.

Conversely, a single case often spans multiple distinct data files. In longitudinal studies, an individual participant may complete a baseline semi-structured interview, a six-month follow-up interview, a series of recorded journal entries, and an exit survey. The case construct serves as the unifying analytical container, consolidating qualitative evidence gathered across diverse sources and temporal intervals under a single entity. All narrative data across these disparate files are coded directly to the participant's case node, which is linked to a single row within the classification sheet, preserving structural integrity across the research lifecycle.

Relational Taxonomy: Classifications, Attributes, and Values

The structural integrity of metadata within NVivo relies on a four-tier relational taxonomy spanning the classification schema, case entities, attributes, and attribute values.

The case classification constitutes the overarching schema, model, or template that defines a category of analytical units. A project may maintain multiple case classifications if it investigates diverse categories of entities, such as a "Participant" classification for interviewed individuals alongside an "Organization" classification for corporate case studies.

Cases represent the specific entity instances assigned to a given case classification. Attributes are the descriptive variables, dimensions, or characteristics governed by the classification schema, such as age group, gender, highest educational attainment, or industrial sector. Every case assigned to the parent classification inherits these attribute fields.

Finally, attribute values represent the specific qualitative states, numerical measures, or categorical designations recorded for an individual case across its defined attributes. The case classification sheet serves as the primary matrix interface, presenting cases as rows and attributes as columns, with the intersecting grid cells housing specific attribute values.

Structural Layer	Relational Database Analogue	NVivo Entity Representation	Operational Function within Qualitative Inquiry
Schema	Database Table Definition	Case Classification	Establishes the structural template and defines which variables apply to a group of entities.
Record / Row	Primary Key Record	Case Node	Represents the unique unit of analysis containing all

Structural Layer	Relational Database Analogue	NVivo Entity Representation	Operational Function within Qualitative Inquiry
			associated qualitative text references.
Field / Column	Data Field Definition	Attribute	Defines an analytical dimension, variable property, and associated data type constraint.
Cell Data	Record Value	Attribute Value	The discrete qualitative or quantitative state recorded for a specific case instance.

Distinguishing Case Classifications from File Classifications

A common architectural error in qualitative database setup is conflating case classifications with file classifications, historically termed source classifications. Both systems use attributes and attribute values within the NVivo framework, but they serve distinct epistemological and analytical functions.

File classifications store bibliographic, operational, and provenance metadata regarding the data files themselves. Common file classification templates include journal article, archival document, interview audio, or field notes. The attributes defined under file classifications capture document-level characteristics such as author, publication year, interviewer name, date of recording, or file transcriber. These properties describe the document rather than the human participant or institution under investigation.

Case classifications capture the socio-demographic, organizational, or contextual properties of the units of analysis. When an interview conducted by a research assistant involves a senior clinical administrator, the document attributes (such as recording date and interviewer identity) belong to the file classification, whereas the analytical entity attributes (such as administrative role, years of clinical experience, and hospital setting) belong to the case classification. Failing to preserve this boundary prevents the researcher from accurately executing comparative cross-case analyses, as document metadata cannot substitute for entity-level classifications during analytical querying.

Methodological Pathways for Constructing Case Classification Sheets

Researchers can construct case classification sheets within NVivo through two primary operational pathways: direct manual authoring inside the software workspace, or batch generation via external structured tabular ingestion using Microsoft Excel or CSV formats. The selection of the operational workflow depends on cohort size, existing data structures, and the stability of the variable schema.

Pathway A: Manual Workspace Generation

Manual configuration is appropriate for small-scale qualitative studies, exploratory pilot projects, or research where attribute dimensions emerge inductively as fieldwork progresses.

The manual configuration workflow begins with schema initialization within the software navigation hierarchy. The researcher navigates to the navigation view, selects the cases container, right-clicks on case classifications, and creates a new classification. A descriptive, singular structural title is assigned that reflects the primary unit of analysis, such as "Participant" or "Community Stakeholder".

Attribute specification follows schema creation. Selecting the newly generated classification in the detail view allows the researcher to create new attributes. In the attribute properties dialog, the researcher assigns a variable title alongside an operational definition in the description field to maintain inter-coder consistency. Crucially, the researcher assigns the appropriate data type—such as text, integer, decimal, date/time, or boolean—to enforce input validation constraints.

Under the values tab of the attribute dialog, the researcher establishes permissible categorical values. NVivo automatically initializes two system default values: "Unassigned" and "Not Applicable". The researcher manually adds discrete levels, such as defining full-time, part-time, unemployed, and retired under an employment status attribute. Pre-populating these categories prevents typographical variations that can compromise subsequent comparative queries.

Once all attributes and their allowable values are configured, opening the case classification displays the classification sheet grid. Cases associated with this classification populate the row indices, allowing attribute cells to be updated via interactive drop-down menus or direct value entry.

Pathway B: Automated Batch Ingestion via Structured Spreadsheets

For medium-to-large qualitative cohorts, mixed-methods designs, or studies where demographic survey data has already been recorded, manually inputting variables into NVivo is inefficient and prone to transcription errors. Batch ingestion via an external comma-separated values (.csv) or Microsoft Excel (.xlsx) workbook enables immediate schema generation and value population.

The external tabular matrix must adhere to strict structural constraints prior to import:

- The leftmost column must contain the primary identifiers for the cases, such as participant pseudonyms or numerical identification codes. Every row entry in this initial column represents a distinct case instance to be generated or updated in NVivo.
- The remaining row-one column headers define the attribute names within the classification schema. These headers should be succinct, avoiding non-standard symbols or excessive syntax.
- Data cells must contain clean, standardized data entries. Variations in formatting—such as entering "Female" in some rows and "female" or "F" in others—force NVivo to treat each variant as a distinct attribute value, introducing analytical fragmentation into subsequent queries. Unrecorded observations should be left completely blank, allowing the software to map them to the system default "Unassigned" state.

The programmatic import process is executed through the software's classification sheet ingestion wizard:

- The researcher navigates to the import menu and selects the classification sheet tool.
- After selecting the prepared workbook, the wizard prompts the user to select "Case Classification" as the destination classification type.
- The researcher can select an existing classification schema to update or choose to create a new classification, entering an explicit schema title such as "Interviewees". The option to

create new attributes if they do not exist must remain enabled.

- In the subsequent mapping interface, the system confirms that the first column contains the case identifiers. The researcher ensures that the option to create new cases if they do not exist is checked. This setting instructs NVivo to automatically generate new case nodes in the cases repository if matching entities are not already present.
- Upon completing the import wizard, NVivo processes the sheet, generates the classification schema, creates the attribute dimensions, establishes the case nodes, links the entities, and populates the classification grid.

Operational Parameter	Pathway A: Native Workspace Authoring	Pathway B: External Spreadsheet Batch Ingestion
Recommended Sample Size	Small cohorts (N < 15) and pilot explorations.	Medium to large cohorts (N ≥ 15) and mixed-methods datasets.
Schema Evolution Mode	Iterative, inductive, and emergent during fieldwork.	Deductive, standardized, and pre-established via surveys.
Ingestion Velocity	Manual; requires multi-step dialog configurations.	Rapid batch execution via automated ingestion wizard.
Data Validation Control	High real-time enforcement via predefined dialog value sets.	Dependent on external data cleaning; susceptible to typographical splits.
Case Node Synchronization	Cases must be manually generated and assigned individually.	Cases and attribute bindings are created simultaneously.

Technical Specifications: Attributes, Data Types, and Value Taxonomies

Attribute Typology and Computational Validation Constraints

Attributes within NVivo are constrained database fields that govern how the software sorts, validates, and calculates data during downstream query operations. Selecting the correct data type ensures analytical integrity and prevents computational errors during advanced cross-case queries.

Text attributes represent the most versatile data type in qualitative research, accommodating categorical, nominal, or ordinal variables such as geographic categories (urban, suburban, rural) or subjective ordinal ratings. Text types also support free-form string entries, such as capturing brief contextual annotations.

Integer attributes constrain entries strictly to whole numerical values without fractional components. This format is essential for metrics such as chronological age in years, number of medical clinic visits, or household size. Configuring an attribute as an integer enables mathematical inequalities and range-based scoping within matrix queries, allowing researchers to isolate cases based on numerical thresholds.

Decimal attributes accommodate continuous real numbers with fractional components, supporting quantitative variables such as clinical biomarker levels, physiological indices, or standardized psychometric scores.

Date/Time attributes enforce standardized temporal formatting, which is critical for longitudinal studies. This formatting allows queries to filter qualitative narratives that occurred before, after,

or within specific chronological observation windows.

Boolean attributes restrict data entries strictly to binary logic states of true or false. This configuration is ideal for recording binary research parameters, such as clinical trial completion, intervention exposure, or the presence versus absence of specific diagnostic markers.

Missing Data Logic: System Defaults and Operational Differentiation

NVivo maintains two immutable system defaults to differentiate between distinct categories of absent data:

$\text{Missing Data Differentiation} = \begin{cases}$

$\mathbf{Un}$ (start_span)(end_span)(start_span)(end_span)assigned:) & $\text{Data exists or is expected, but has not yet been recorded.} \setminus \mathbf{Not}$ Applicable:) & The

variable (start_span)(end_span)(start_span)(end_span) is logically irrelevant to the specific case entity. $\end{cases}$

The Unassigned status indicates that an attribute applies to a given case, but the actual value is missing, pending verification, or omitted from the participant's record. For example, if an interviewee declined to state their annual household income, the cell should remain designated as Unassigned.

Conversely, Not Applicable indicates that the attribute is structurally irrelevant to the entity. In an organizational study assessing public and private healthcare facilities, an attribute labeled "Corporate Tax Number" is relevant to private institutions, but structurally Not Applicable to public non-profit municipal health clinics.

Conflating these two states distorts qualitative query validity. If missing survey responses are designated as Not Applicable rather than Unassigned, subsequent filtering queries will mischaracterize missing baseline data as intentional cohort exclusions.

Attribute Label	Data Type	Permissible Value Taxonomy	Methodological Purpose
Participant ID	Text	Alphanumeric string identifiers (e.g., P_001, P_002)	Serves as primary case identifier; guarantees pseudonymization.
Gender Identity	Text	Female, Male, Non-Binary, Self-Describe, Unassigned	Standardized categorical levels prevent typographical discrepancies.
Age Cohort	Text	18-29, 30-44, 45-59, 60+, Unassigned	Categorizes continuous age into cohorts to streamline matrix queries.
Years in Role	Integer	Non-negative integers (≥ 0)	Supports numerical range filtering (e.g., isolating junior staff).
Study Arm	Text	Control, Intervention A, Intervention B	Structural design variable for

Attribute Label	Data Type	Permissible Value Taxonomy	Methodological Purpose
		[span_80](end_span)[span_90](start_span)[span_90](end_span)tervention B	quasi-experimental qualitative evaluations.
Intake Date	Date/Time	YYYY-MM-DD	Enables chronological sequencing and longitudinal cross-case tracking.
Protocol Met	Boolean	True, False	Verifies adherence to clinical or experimental inclusion criteria.

Entity-to-Schema Integration and Qualitative Data Binding

Transforming Source Files into Case Nodes

Raw qualitative data assets imported into the software workspace—such as text transcripts, audio files, or digital notes—represent structural inputs rather than analytical units. To transform a raw file into an analytical case entity, the source material must be converted into a dedicated case node.

For individual, one-to-one interviews, the conversion workflow involves selecting the transcript file within the files workspace, accessing the context menu, and executing the command to create the file as a case. This operation generates a new case node carrying the file title and codes the entire textual content of the document into that case container.

In multi-speaker environments, such as focus group sessions or community meetings, a single document must be segmented into multiple distinct cases. To achieve this, researchers use automated speaker-based coding.

The transcript must first be formatted with consistent speaker naming conventions, such as prefixing interviewer inquiries with INT: and participant statements with explicit labels like BASEL: or CLARA:. Selecting the auto-code tool from the document context menu allows the researcher to select auto-coding by speaker name. The wizard prompts the user to select the target classification schema, such as an existing "Interviewees" classification.

The researcher enters the exact speaker labels used in the text, allowing the system to parse the document, extract the qualitative passages corresponding to each speaker, generate dedicated case nodes for each individual, and code their respective contributions directly into their case containers.

Binding Case Containers to Classification Schemas

Generating a case node does not automatically link it to an attribute matrix; the node must be explicitly bound to its parent classification schema. This link can be established through context menu assignment or direct classification sheet entry.

Context menu assignment is performed directly within the cases list workspace. The researcher selects one or more target case nodes, opens the context menu, navigates to the classification

options, and selects the desired case classification schema. This operation can also be executed within the case properties dialog under the attribute values tab, where individual attributes can be assigned values directly.

Alternatively, direct classification sheet entry is executed by opening the case classification sheet grid. When case nodes are assigned to a classification, their labels populate the row headers of the matrix. The researcher navigates through the grid cells, assigning attribute values using drop-down menus for categorical text attributes or typing values directly into numeric and date cells.

Longitudinal Tracking and Multi-Source Consolidation

Longitudinal and multi-method qualitative studies require consolidating multiple source documents into a single case container to maintain analytical coherence. When an individual participant provides data across multiple stages—such as a baseline interview, an audio diary, and an exit evaluation—creating separate cases for each interaction fragments the participant's analytical identity.

To preserve metadata links, the researcher establishes a single case node representing the participant within the classification schema. As new data files are imported across successive collection waves, the researcher highlights the narrative segments within each new document and codes them directly to the participant's existing case container.

This consolidation aggregates qualitative data across multiple points in time within a single case container. The participant's row on the case classification sheet remains stable, preserving baseline demographic variables while allowing analysts to track evolving thematic expressions across the research timeline.

Analytical Exploitation: Cross-Case Syntheses and Mixed-Methods Queries

Crosstabulation Analytics

The primary operational purpose of constructing a case classification sheet is to enable systematic qualitative analysis through computational queries. By binding structured metadata to unstructured text, researchers can run comparative, cross-case queries that reveal subtle patterns across participant cohorts.

The crosstab query interface provides an environment for examining intersections between thematic codes and categorical case attributes. For example, in an organizational study investigating workplace experiences, a crosstab query can evaluate how the thematic distribution of professional burnout varies across different tiers of organizational seniority. The researcher specifies the thematic codes of interest along the row axis and designates the target case classification and attribute dimension across the column axis. NVivo parses the database, cross-referencing coding instances against case metadata, and populates a comparative matrix.

The resulting grid displays the frequency of coding references, the number of distinct cases contributing to each theme, or percentage coverage across groups. This transformation enables researchers to evaluate qualitative patterns across defined demographic cohorts.

Thematic Coding Focus	Junior Staff Cohort (n=12)	Mid-Level Management (n=8)	Executive Leadership (n=4)	Aggregate Coding References
Institutional Cynicism	34	18	2	54
Work-Life Imbalance	45	29	7	81
Strategic Optimism	3	12	28	43
Resource Constraints	28	21	5	54

Matrix Coding Queries

Matrix coding queries provide flexible computational parameters, allowing researchers to evaluate relationships between multiple thematic codes and complex, multi-variable demographic criteria.

While a basic crosstab query evaluates a single attribute dimension, matrix coding queries allow researchers to build complex Boolean filters. An analyst can test whether expressions of treatment resistance appear disproportionately among older male participants with low educational attainment. In the query configuration interface, thematic codes are assigned to rows, while columns are scoped using compound attribute expressions:

```
\text{Cohort Filter} = \left(\text{Person.Gender} = \text{"Male"}\right) \ \mathbf{AND} \ \left(\text{Person.AgeCohort} = \text{"60+"}\right) \ \mathbf{AND} \ \left(\text{Person.Education} = \text{"Secondary"}\right)
```

This query isolates cases that meet these multi-attribute criteria and intersects them with the selected thematic codes. Double-clicking any resulting matrix cell opens the underlying qualitative excerpts in a detail tab, allowing the researcher to examine the narrative context behind the numerical distributions.

Framework Matrix Synthesis Framework matrices provide a structured environment for qualitative synthesis, making them particularly useful in health services research, clinical trials, and policy evaluations. The tool displays qualitative data in an organized comparative grid:

- Each row represents a specific case entity linked to its classification sheet attributes, displaying the case label alongside its demographic profile.
- Columns correspond to active thematic codes from the coding schema.
- The intersecting cells display the raw qualitative passages coded to that case and theme, which researchers can distill into concise summaries.

This structured layout allows researchers to compare participant experiences systematically across multiple thematic areas, ensuring that all data is examined consistently before drawing theoretical conclusions.

Data Integrity Protocols, Operational Pitfalls, and Quality Assurance

Common Architectural and Data Ingestion Failures

Configuring classification sheets improperly can compromise data integrity and undermine

downstream analysis. Addressing these issues early prevents errors during query execution and ensures rigorous findings.

Entity-source conflation represents a frequent architectural failure in qualitative database design. When researchers code qualitative data directly into files or source folders rather than establishing dedicated case nodes, narrative data remains bound to raw documents. Because metadata classifications cannot be linked to raw text files in the same way they are to analytical units, the researcher cannot include those participants in case-level cross-tabulations.

Typographical fragmentation poses a major threat during tabular batch ingestion. NVivo's classification engine is case-sensitive and character-sensitive. If external spreadsheet columns contain minor typing discrepancies—such as entries for "Nurse", "nurse", and " Nurse " with leading whitespace—NVivo creates three distinct attribute values rather than a single category. This fragments subsequent matrix columns and undercounts coding references.

Case mismatch during tabular import frequently results in duplicate, unlinked nodes. When importing an external classification sheet, the primary identifiers in the first column must match the names of existing case nodes in the project exactly. A minor discrepancy—such as "Case 01" in NVivo versus "Case_01" in Excel—causes the software to generate a duplicate, empty case node rather than linking to the existing container, leaving the original case unclassified.

Misuse of free-text attribute formatting encourages inconsistent data entry. Selecting the text data type without defining fixed categorical values leads to spelling variations and synonyms that complicate comparative queries. Categorical variables should always have predefined value sets, while numerical measures should use integer or decimal types to preserve mathematical functionality.

Systematic Quality Assurance and Verification Protocols

To ensure data integrity, research teams should implement structured verification checks throughout the data entry and management lifecycle:

- **Pre-Import Data Audits:** External workbooks must be thoroughly cleaned in spreadsheet software before import. Text fields should be standardized using cleanup formulas to eliminate trailing whitespace, normalize capitalization, and confirm that empty cells are unpopulated rather than filled with non-standard placeholders.
- **Post-Import Sheet Verification:** Immediately following import, the researcher should open the case classification sheet to inspect the matrix layout. Reviewing each attribute column confirms that the unique value lists contain only intended categories, without unintended variants or duplicates.
- **Empty Case Node Scans:** The researcher should inspect the files and references count columns in the cases workspace to confirm that all generated case nodes contain coded data. A case displaying zero references indicates that data was not properly coded to the entity container, leaving it as an unlinked shell.
- **Pilot Query Validation:** The research team should run a preliminary crosstab query across core demographic variables to verify that the totals align with known sample sizes. Identifying discrepancies at this stage ensures that analytical outputs remain accurate before entering the final stages of data synthesis.

Standard Operating Guidelines and Methodological Synthesis

The case classification sheet in NVivo bridges qualitative narrative evidence and structured demographic, organizational, and contextual metadata. Without this metadata architecture, qualitative research remains limited to isolated thematic descriptions, unable to conduct systematic cross-case comparisons or support mixed-methods designs.

To maintain rigor, consistency, and analytical efficiency throughout the qualitative research lifecycle, research teams should follow established standard practices:

- **Define Units of Analysis Early:** Establish the study's analytical units during initial project setup, ensuring that data is coded into dedicated case nodes rather than remaining trapped in raw document files.
- **Enforce Clean Structural Separation:** Maintain a clear boundary between file classifications (used for document provenance and bibliographic details) and case classifications (used for participant and organizational attributes) to prevent confounding in downstream comparative queries.
- **Use Automated Batch Ingestion for Scalability:** For studies with fifteen or more participants, organize demographic data in external spreadsheets and import them via the classification sheet wizard to prevent manual entry errors and automatically link cases to metadata schemas.
- **Apply Strict Data Typing and Standardized Values:** Restrict qualitative variables to predefined categorical sets, assign numerical data to integer or decimal types, and distinguish between "Unassigned" and "Not Applicable" to prevent distorted query results.
- **Leverage Mixed-Methods and Cross-Case Queries:** Use crosstabs, matrix coding queries, and framework matrices to systematically test theoretical relationships between thematic codes and participant attributes, ensuring evidence-based qualitative synthesis and theoretical saturation.

Works cited

1. NVivo Data Analysis Procedures | PDF | Qualitative Research - Scribd, <https://www.scribd.com/document/715379946/DataanalysisusingNVivoThesis>
2. NVivo for Qualitative Data Analysis Guide | PDF - Scribd, <https://www.scribd.com/document/874546651/Doing-Qualitative-Data-Analysis-With-NVivo>
3. (PDF) Chapter 5: Data analysis using NVivo - ResearchGate, https://www.researchgate.net/publication/349821390_Chapter_5_Data_analysis_using_NVivo
4. 5: Sample of case classification sheet-case attributes and values, https://www.researchgate.net/figure/Sample-of-case-classification-sheet-case-attributes-and-values_fig1_349821390
5. Case Classification Sheet Participants Demography in NVivo, https://www.researchgate.net/figure/Case-Classification-Sheet-Participants-Demography-in-NVivo_fig1_346937490
6. NVivo 12 Plus's New Qualitative Cross-Tab Analysis Function, <https://scalar.usc.edu/works/c2c-digital-magazine-fall-2018--winter-2019/nvivo-12-plus-new-qual-cross-tab-analysis-function>
7. How to create a case for a number of sources belonging ... - YouTube, <https://www.youtube.com/watch?v=QWbObHUU95Y>
8. Introduction to NVivo 14/15 for Mac | Map and Data Library, <https://mdl.library.utoronto.ca/technology/tutorials/introduction-nvivo-1415-mac>
9. How to connect your cases to a case classification sheet - YouTube, <https://www.youtube.com/watch?v=kYtxxoJbueo>
10. Introduction To NVivo - A Tool For Qualitative Data Analysis | PDF, <https://www.scribd.com/document/1039564021/Introduction-to-NVivo-A-Tool-for-Qualitative-Data-Analysis>
11. Introduction to NVivo 12 for Mac | Map and Data Library,

<https://mdl.library.utoronto.ca/technology/tutorials/introduction-nvivo-12-mac> 12. How to create a case classification sheet - YouTube, <https://www.youtube.com/watch?v=LHbUuZqadys>