

---

# EBU5405

## 3D Graphics Programming Tools

### 3D Computer Graphics Software

#### Introduction to OpenGL

Dr. Marie-Luce Bourguet  
(marie-luce.bourguet@qmul.ac.uk)

EBU5405



1

## Today's agenda

---


- Some popular 3D computer graphics software:
  - Blender
  - Unity 3d
  - Autodesk Maya
  - Autodesk 3ds Max (Gmax)
- Introduction to OpenGL

EBU5405



2

# How to compare 3D Computer Graphics Software?




EBU5405



3

# How to compare 3D Computer Graphics Software?























EBU5405



4

## How to compare 3D Computer Graphics Software?

	Modelling	Rendering	Animation	Free
Blender				
Unity 3D				
OpenGL				
Maya				
3ds Max				

EBU5405



5

## Blender

- Blender is a public project, made by hundreds of people from around the world, by studios and individual artists, professionals and hobbyists, scientists, students, etc.  
<https://www.blender.org/>
- Blender is a free and open source 3D creation suite, that supports modelling and the entirety of the 3D pipeline.

EBU5405



6

## Unity 3D

- **Unity** is a cross-platform game engine developed by Unity Technologies, which is primarily used to develop both three-dimensional and two-dimensional video games and simulations for computers, consoles, and mobile devices.


<https://unity3d.com/>

EBU5405



7

## Blender




EBU5405



8

## Unity 3D



EBU5405



9

## OpenGL

OpenGL is a platform-independent API that is

- Easy to use
- Close enough to the hardware to get excellent performance
- Focus on rendering

<http://www.opengl.org>

What you need:

- **OpenGL core library**
  - OpenGL32 on Windows
- **OpenGL Utility Library (GLU)**
  - Uses OpenGL core but avoids having to rewrite code
- **OpenGL Utility Toolkit (GLUT)**
- a C/C++ compiler

10



10

# OpenGL

---

Programming OpenGL in C (with Eclipse):

[https://www.ntu.edu.sg/home/ehchua/programming/opengl/HowTo\\_OpenGL\\_C.html#zz-1](https://www.ntu.edu.sg/home/ehchua/programming/opengl/HowTo_OpenGL_C.html#zz-1)

<https://bohr.wlu.ca/cp411/eclipseCDT.php>

11



11

## A very simple C/OpenGL programme

---

```
#include <GL/glut.h>

void display() {
    glClearColor(0.0, 0.0, 0.0, 0.0);
    glClear(GL_COLOR_BUFFER_BIT);
    glFlush();
}

int main(int argc, char** argv) {
    glutInit(&argc, argv);
    glutCreateWindow("Hello GLUT!");
    glutDisplayFunc(display);
    glutMainLoop();
}
```

12



12

# GLUT

---

- OpenGL Utility Toolkit (GLUT)
  - Links with window system (e.g. AGL for Macintosh)
  - Provides functionality common to all window systems
    - Open a window
    - Get input from mouse and keyboard
    - Menus
    - Event-driven
  - Code is portable but GLUT lacks the functionality of a good toolkit for a specific platform
    - E.g. No slide bars

13



13

## A very simple C/OpenGL programme

---

```
#include <GL/glut.h>

void display() {
    glClearColor(1.0, 0.0, 0.0, 0.0);
    glClear(GL_COLOR_BUFFER_BIT);
    glFlush();
}

int main(int argc, char** argv) {
    glutInit(&argc, argv);
    glutCreateWindow("Hello GLUT!");
    glutDisplayFunc(display);
    glutMainLoop();
}
```

14



14

## The main function

---

- Note that the **main** function of the simple.c program defines a **display callback** function named **display**
  - Every program must have a display callback
  - The display callback is executed whenever OpenGL decides the display must be refreshed, for example when the window is opened.
- The **main** function ends with the program entering an **event loop**

15

15

## main

---

```
int main(int argc, char** argv) {  
    glutInit(&argc, argv);  
    glutCreateWindow("Hello GLUT!");  
    glutDisplayFunc(display);  
    glutMainLoop();  
}
```

16

16



## Another Simple Program:

Generating a square on a solid background

```
#include <GL/glut.h>

void mydisplay() {
    glClear(GL_COLOR_BUFFER_BIT);
    glBegin(GL_POLYGON);
        glVertex2f(-0.5, -0.5);
        glVertex2f(-0.5, 0.5);
        glVertex2f(0.5, 0.5);
        glVertex2f(0.5, -0.5);
    glEnd();
    glFlush();
}

int main(int argc, char** argv){
    glutInit(&argc, argv);
    glutCreateWindow("simple");
    glutDisplayFunc(mydisplay);
    glutMainLoop();
}
17
```



17

## Lack of Object Orientation

---

- OpenGL is not object oriented so there are **multiple functions for a given logical function**

- glVertex3f
- glVertex2i
- glVertex3dv



18

18

## OpenGL function format

---

function name      dimensions

`glVertex3f(x, y, z)`

belongs to core GL library      `x, y, z` are floats

`glVertex3fv(p)`

`p` is a pointer to an array

19



19

## OpenGL function format

---

`glVertex3fv`

How many versions of the `glVertex` function exist ?



20



20

## OpenGL function format

---

```
glBegin(GL_POLYGON);  
    glVertex2f(-0.5, -0.5);  
    glVertex2f(-0.5, 0.5);  
    glVertex2f(0.5, 0.5);  
    glVertex2f(0.5, -0.5);  
glEnd();
```

How to replace `glVertex2f` with  
`glVertex2fv`?

21



21

## OpenGL function format

---

```
GLfloat vertices[4][2] = {{-0.5, -0.5},  
{-0.5, 0.5}, {0.5, 0.5}, {0.5, -0.5}};
```

```
glBegin(GL_POLYGON);  
    glVertex2fv(vertices[0]);  
    glVertex2fv(vertices[1]);  
    glVertex2fv(vertices[2]);  
    glVertex2fv(vertices[3]);  
glEnd();
```

22



22

## OpenGL #defines


- Most constants are defined in the include files `gl.h`, `glu.h` and `glut.h`
  - Note `#include <GL/glut.h>` should automatically include the others
  - Examples:
    - `glBegin(GL_POLYGON)`
    - `glClear(GL_COLOR_BUFFER_BIT)`
- include files also define OpenGL data types: `GLfloat`, `GLdouble`, ....

23



23

## OpenGL Primitives



24



24

## Defaults

---

- Note that this program makes heavy use of variable default values for:
  - Colours (background and foreground)
  - Window parameters (e.g. size)
  - Viewing (camera parameters, e.g. where the square appears in the window ...)

25