



# PanpanGIS 文档

PostgreSQL, PostGIS, SQLCarto, Apache, PHP, QT, QML

作者：麓山老将，PcWang，隔壁老王

组织：CSU.GIS.250 + 1

时间：2024 年 9 月 2 日

版本：1.0

邮箱：sqlcarto@163.com

GIS  
PanPan

支离东北风尘际，漂泊西南天地间。三峡楼台淹日月，五溪衣服共云山。  
羯胡事主终无赖，词客哀时且未还。庾信平生最萧瑟，暮年诗赋动江关。  
—— 杜甫（唐）

# 目录

第一章 缘起	1
1.1 还是干点啥吧	1
第二章 Apache 安装	2
2.1 Apache 跨域设置	2
第三章 Windows WSL(Ubuntu) 子系统	3
3.1 WSL 安装	3
3.2 将 WSL 迁移到非系统盘	3
3.2.1 查看所有分发版本	3
3.2.2 导出分发版为 tar 文件	3
3.2.3 注销当前分发版	3
3.2.4 重新导入并安装分发版	3
3.2.5 设置默认登陆用户为安装时用户名	3
第四章 使用 msys2 系统编译 postgis/postgresql	4
4.1 安装 msys2	4
4.2 启动 msys2 ucrt	4
4.3 安装 ucrt 编译工具链	5
4.3.1 查询工具链	5
4.3.2 安装工具链	5
4.4 编译 postgresql	5
4.4.1 设置环境变量	5
4.4.2 安装支持库	6
4.4.3 安装 uuid	6
4.4.4 安装 postgresql	7
4.4.5 安装 geos	7
4.4.6 安装 gdal	8
4.4.7 安装 postgis	16

# 第一章 缘起

## 1.1 还是干点啥吧

去年冬日，麓山的树被冰雪压弯，折断不少枝叶，掉落在地。初春上午，孤独行走山间，绕过断枝残叶，漫无目的爬向山顶。路边的小野花开得正旺，串串的淡黄，间或有几只蜜蜂起落其间。这种灌木开出的小花被父亲叫做青叶子花，是初春重要的蜜源。脚下的残枝败叶与枝梢间的嫩芽正昭示着世间真理：旧的已去，新的正来。当一个人在某个行当久了，成为资深，是否也正如这掉落的枝叶，在某个时间节点，无可奈何地要随风去！？

外观落幕，内自落寞。离开吧！过去五年，这个声音一直耳边响着。从五楼搬到二楼，换到规律而 boring 的工作。无人打扰，时间充足。Tong 对我说，一个人一天接不到几个电话，接到的电话还是亲朋好友打过来的，说明没有希望了。

## 第二章 Apache 安装

### 2.1 Apache 跨域设置

如果 web 服务器的跨域参数设置不正确，在客户端为 webassembly、服务端为 https 时，会出现 “a breakdown in protocol was detected (parsing error, invalid or unexpected responses, etc.)” 的错误。

修改 apache.conf, 添加如下设置：

---

```
<Directory />
    AllowOverride none
    Require all denied
    Header set Access-Control-Allow-Origin *
    Header set Cross-Origin-Embedder-Policy 'require-corp'
    Header set Cross-Origin-Opener-Policy 'same-origin'
</Directory>
```

---

## 第三章 Windows WSL(Ubuntu) 子系统

### 3.1 WSL 安装

### 3.2 将 WSL 迁移到非系统盘

wsl 默认安装位置是 C 盘，众所周知 C 盘总是不够用的，所以才有了把 wsl 的系统迁移到其它位置的需求。在下列情况出现时需要将 WSL 从系统盘迁移 (C) 到非系统盘 (D,E 等):

- 系统盘空间有限
- 数据库目录存在于 WSL 文件系统，但是预期数据库空间占用非常巨大

#### 3.2.1 查看所有分发版本

```
wsl -l --all -v
```

#### 3.2.2 导出分发版为 tar 文件

```
wsl --export Ubuntu-20.04 D:\ubuntu20.04.tar
```

#### 3.2.3 注销当前分发版

```
wsl --unregister Ubuntu-20.04
```

#### 3.2.4 重新导入并安装分发版

```
wsl --import Ubuntu-20.04 D:\wsl\ubuntu D:\ubuntu20.04.tar --version 2
```


#### 3.2.5 设置默认登陆用户为安装时用户名

```
ubuntu2004 config --default-user Username
```


## 第四章 使用 msys2 系统编译 postgres/postgresql


### 4.1 安装 msys2

从<https://www.msys2.org>网站下载 msys 安装包，双击安装 msys2。



### 4.2 启动 msys2 ucrt






## 4.3 安装 ucrt 编译工具链

### 4.3.1 查询工具链

```
pacman -Ss gcc | grep ucrt
```



### 4.3.2 安装工具链

```
pacman -S mingw-w64-ucrt-x86_64-toolchain
pacman -S ucrt64/mingw-w64-ucrt-x86_64-cmake
pacman -S msys/make
```

## 4.4 编译 postgresql

### 4.4.1 设置环境变量

编辑/etc/profile，在最末尾添加下列内容：

```
export PGSQL=/usr/local/pgsql
export PATH=$PGSQL/bin:$PGSQL/lib:$PATH
export LD_LIBRARY_PATH=$PGSQL/lib:$LD_LIBRARY_PATH
export PKG_CONFIG_PATH=$PKG_CONFIG_PATH:$PGSQL/lib/pkgconfig
```

重新启动 msys2 ucrt 命令行。

#### 4.4.2 安装支持库

```
# postgis利用cgal支持3D空间分析
# sfcgal为cgal的c语言wrapper, 只有c语言的库才能链接到postgresql
pacman -S ucrt64/mingw-w64-ucrt-x86_64-sfcgal

# cairo为图形库, sqlcarto使用cairo进行二维地图绘制
pacman -S ucrt64/mingw-w64-ucrt-x86_64-cairo

# libgeotiff为geotiff栅格文件的读写库, gdal需要
pacman -S ucrt64/mingw-w64-ucrt-x86_64-libgeotiff

# netcdf读取大数据文件, 地理空间栅格数据
pacman -S ucrt64/mingw-w64-ucrt-x86_64-netcdf

pacman -S ucrt64/mingw-w64-ucrt-x86_64-protobuf-c
```

#### 4.4.3 安装 uuid

```
cd ~
mkdir -p software/sdb
cd software/sdb
curl --output uuid-1.6.1.tar.gz ftp://ftp.ossdp.org/pkg/lib/uuid/uuid-1.6.1.tar.gz
tar -zxvf uuid-1.6.1.tar.gz
cd uuid-1.6.1
```

使用编辑器打开 shtool 脚本文件, 找到 dsttmp 变量赋值语句:

```
...
# make a temp file name in the destination directory
dsttmp=`echo $dst | \
    sed -e 's;[~/]*$;;' -e 's;\(.\)/$;1;' -e 's;^$;.;' \
    -e "s;\$;/#INST@$$$#;"`
...
```

在后面添加一行, 改成:

```
...
# make a temp file name in the destination directory
dsttmp=`echo $dst | \
    sed -e 's;[~/]*$;;' -e 's;\(.\)/$;1;' -e 's;^$;.;' \
    -e "s;\$;/#INST@$$$#;"`
```



```
# 添加下面这一行
dsttmp=$dsttmp.exe
...
```

保存 shtool 文件，在控制台运行下列命令行，配置及安装 uuid:

```
./configure --prefix=$PGSQL
make
make install
```

#### 4.4.4 安装 postgresql

```
cd ~/software/sdb

# 下载源代码
# 注意curl命令使用的参数，此处模拟chrome来下载文件
# 如直接使用:
# curl 'https://ftp.postgresql.org/pub/source/v16.4/postgresql-16.4.tar.bz2' --output postgresql-16.4.tar.bz2
# 则不能成功下载源码文件
# 可以根据需要改变版本号来下载对应的版本的postgresql源码
# curl 'https://ftp.postgresql.org/pub/source/v16.4/postgresql-16.4.tar.bz2' \
# -H 'Referer: https://www.postgresql.org/' \
# -H 'Upgrade-Insecure-Requests: 1' \
# -H 'User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/128.0.0.0 Safari/537.36' \
# -H 'sec-ch-ua: "Chromium";v="128", "Not;A=Brand";v="24", "Google Chrome";v="128"' \
# -H 'sec-ch-ua-mobile: ?0' \
# -H 'sec-ch-ua-platform: "Windows"' \
# --output postgresql-16.4.tar.bz2
# 使用curl的-LJO 参数下载文件
curl -LJO 'https://ftp.postgresql.org/pub/source/v16.4/postgresql-16.4.tar.bz2'

tar -jvxf postgresql-16.4.tar.bz2
cd postgresql-16.4
# 由于uuid没有安装在/usr目录，而是安装在$PGSQL目录下，因此在配置时
# 应该指定LDFLAGS和CPPFLAGS环境变量，否则会提示找不到uuid库
LDFLAGS="-L$PGSQL/lib" CPPFLAGS="-I$PGSQL/include" ./configure --prefix=$PGSQL --with-oss-pg-uuid
make
make install

# 编译postgresql的uuid扩展
cd contrib/uuid
make
make install
```

#### 4.4.5 安装 geos

geos 提供空间分析功能。

```
cd ~/software/sdb
curl -LJO https://download.osgeo.org/geos/geos-3.12.2.tar.bz2
tar -jvxf geos-3.12.2.tar.bz2
cd geos-3.12.2
mkdir build
cd build
cmake -DCMAKE_INSTALL_PREFIX=$PGSQL -DCMAKE_BUILD_TYPE=Release ..
# 某些geos版本已经不能使用make构建工具，只能使用下列的cmake命令进行构建和安装
cmake --build .
cmake --build . --target install
```

#### 4.4.6 安装 gdal

gdal 提供地理空间数据矢量、栅格文件读取 api。如需使用 postgres 的 raster 扩展功能，必须安装 gdal。

```
cd ~/software/sdb

# 下载源代码
# 注意curl命令使用的参数
curl -LJO https://github.com/OSGeo/gdal/releases/download/v3.9.2/gdal-3.9.2.tar.gz
tar -zxvf gdal-3.9.2.tar.gz
cd gdal-3.9.2
mkdir build
cd build
cmake -DCMAKE_INSTALL_PREFIX=$PGSQL -DCMAKE_BUILD_TYPE=Release ..
```

配置完成，会输出如下信息：

```
...
# 此次编译完成后 gdal 支持的功能: gdal 前缀对应栅格数据操作, ogr 前缀对应矢量数据操作
-- Enabled drivers and features and found dependency packages
-- The following features have been enabled:

* gdal_JPEG, JPEG image format
* gdal_RAW, Raw formats:EOSAT FAST Format, FARSITE LCP and Vexcel MFF2 Image
* gdal_GTIFF, GeoTIFF image format
* gdal_MEM, Read/write data in Memory
* gdal_VRT, Virtual GDAL Datasets
* gdal_HFA, Erdas Imagine .img
* gdal_SDTS, SDTS translator
* gdal_NITF, National Imagery Transmission Format
* gdal_GXF, GXF
* gdal_AAIGRID, Arc/Info ASCII Grid Format.
* gdal_CEOS, CEOS translator
* gdal_SAR_CEOS, ASI CEOS translator
* gdal_XPM, XPM image format
* gdal_DTED, Military Elevation Data
* gdal_JDEM, JDEM driver
* gdal_ENVISAT, Envisat
```

```

* gdal_ELAS, Earth Resources Laboratory Applications Software
* gdal_FIT, FIT driver
* gdal_L1B, NOAA Polar Orbiter Level 1b Data Set (AVHRR)
* gdal_RS2, RS2 -- RadarSat 2 XML Product
* gdal_ILWIS, Raster Map
* gdal_RMF, RMF --- Raster Matrix Format
* gdal_LEVELLER, Daylon Leveller heightfield
* gdal_SGI, SGI Image driver
* gdal_SRTMHGT, SRTM HGT File Read Support
* gdal_IDRISI, Idrisi Raster Format
* gdal_GSG, Implements the Golden Software Surfer 7 Binary Grid Format.
* gdal_ERS, ERMapper .ERS
* gdal_JAXAPALSAR, JAXA PALSAR Level 1.1 and Level 1.5 processed products support
* gdal_DIMAP, SPOT Dimap Driver
* gdal_GFF, Ground-based SAR Applitcations Testbed File Format driver
* gdal_COSAR, COSAR -- TerraSAR-X Complex SAR Data Product
* gdal_PDS, USGS Astrogeology ISIS Cube (Version 2)
* gdal_ADRG, ADRG reader and ASRP/USRP Reader
* gdal_COASP, DRDC Configurable Airborne SAR Processor (COASP) data reader
* gdal_TSX, TerraSAR-X XML Product Support
* gdal_TERRAGEN, Terragen&trade; Terrain File
* gdal_BLX, Magellan BLX Topo File Format
* gdal_MSGN, Meteosat Second Generation (MSG) Native Archive Format (.nat)
* gdal_TIL, EarthWatch .TIL Driver
* gdal_R, R Object Data Store
* gdal_NORTHWOOD, NWT_GRD/NWT_GRC -- Northwood/Vertical Mapper File Format
* gdal_SAGA, SAGA GIS Binary Driver
* gdal_XYZ, ASCII Gridded XYZ
* gdal_ESRIC, ESRI compact cache
* gdal_HF2, HF2/HFZ heightfield raster
* gdal_KMLSUPEROVERLAY
* gdal_CTG, CTG driver
* gdal_ZMAP, ZMAP
* gdal_NGS GEOID, NOAA NGS Geoid Height Grids
* gdal_IRIS, IRIS driver
* gdal_MAP, OziExplorer .MAP
* gdal_CALS, CALS type 1
* gdal_SAFE, SAFE -- Sentinel-1 SAFE XML Product
* gdal_SENTINEL2, Driver for Sentinel-2 Level-1B, Level-1C and Level-2A products.
* gdal_PRF, PHOTOMOD Raster File
* gdal_MRF, Meta raster format
* gdal_WMTS, OGC Web Map Tile Service
* gdal_GRIB, WMO General Regularly-distributed Information in Binary form
* gdal_BMP, Microsoft Windows Device Independent Bitmap
* gdal_TGA, TGA
* gdal_STACTA, STACTA
* gdal_BSB, Maptech/NOAA BSB Nautical Chart Format
* gdal_AIGRID, Arc/Info Binary Grid Format
* gdal_USGSDEM, USGS ASCII DEM (and CDED)

```

```

* gdal_AIRSAR, AirSAR Polarimetric Format
* gdal_OZI, OZF2/OZFX3 raster
* gdal_PCIDSK, PCI Geomatics Database File
* gdal_SIGDEM, Scaled Integer Gridded DEM .sigdem Driver
* gdal_RIK, RIK -- Swedish Grid Maps
* gdal_STACIT, STACIT
* gdal_PDF, Geospatial PDF
* gdal_PNG, PNG image format
* gdal_GIF, Graphics Interchange Format
* gdal_WCS, OGC Web Coverage Service
* gdal_HTTP, HTTP driver
* gdal_NETCDF, NetCDF network Common Data Form
* gdal_ZARR, ZARR
* gdal_DAAS, Airbus DS Intelligence Data As A Service(DAAS)
* gdal_EEDA, Earth Engine Data API
* gdal_HDF5, Hierarchical Data Format Release 5 (HDF5)
* gdal_PLMOSAIC, PLMosaic (Planet Labs Mosaics API)
* gdal_WMS, Web Map Services
* gdal_OGCAPI, OGCAPI
* gdal_WEBP, WebP
* gdal_RASTERLITE, Rasterlite - Rasters in SQLite DB
* gdal_MBTILES, MBTile
* gdal_POSTGISRASTER, PostGIS Raster driver
* gdal_PCRASTER, PCRaster CSF 2.0 raster file driver
* ogr_MEM, Read/write driver for MEMORY virtual files
* ogr_GEOJSON, GeoJSON/ESRIJSON/TopoJSON driver
* ogr_TAB, MapInfo TAB and MIF/MID
* ogr_SHAPE, ESRI shape-file
* ogr_KML, KML
* ogr_VRT, VRT - Virtual Format
* ogr_AVC, AVC
* ogr_GML, GML
* ogr_CSV, CSV
* ogr_DGN, DGN
* ogr_GMT, GMT
* ogr_NTF, NTF
* ogr_S57, S57
* ogr_TIGER, U.S. Census TIGER/Line
* ogr_GEOCONCEPT, GEOCONCEPT
* ogr_GEORSS, GEORSS
* ogr_DXF, DXF
* ogr_PGDUMP, PGDump
* ogr_GPSBABEL, GPSBABEL
* ogr_EDIGEO, EDIGEO
* ogr_SXF, SXF
* ogr_OPENFILEGDB, OPENFILEGDB
* ogr_WASP, WAsP .map format
* ogr_SELAFIN, OSELAFIN
* ogr_JML, JML

```

```

* ogr_VDV, VDV-451/VDV-452/INTREST Data Format
* ogr_FLATGEOBUF, FlatGeobuf
* ogr_MAPML, MapML
* ogr_JSONFG, JSONFG
* ogr_MIRAMON, MiraMonVector
* ogr_SDTS, SDTS
* ogr_GPX, GPX - GPS Exchange Format
* ogr_SVG, Scalable Vector Graphics
* ogr_CSW, CSW
* ogr_PLSCENES, PLSCENES
* ogr_WFS, OGC WFS service
* ogr_NGW, NextGIS Web
* ogr_ELASTIC, ElasticSearch
* ogr_IDRISI, IDRISI
* ogr_PDS, Planetary Data Systems TABLE
* ogr_SQLITE, SQLite3 / Spatialite RDBMS
* ogr_GPKG, GeoPackage
* ogr_OSM, OpenStreetMap XML and PBF
* ogr_VFK, Czech Cadastral Exchange Data Format
* ogr_MVT, MVT
* ogr_PMTILES, PMTiles
* ogr_AMIGOCLOUD, AMIGOCLOUD
* ogr_CARTO, CARTO
* ogr_PG, PostGIS
* ogr_MSSQLSPATIAL, MSSQLSPATIAL
* ogr_ODBC, ODBC
* ogr_PGEO, PGEO
* ogr_XLSX, Microsoft Office Excel(xlsx)
* ogr_CAD, OpenCAD
* ogr_GTFS, GTFS
* ogr_ODS, ODS
* ogr_LVBAG, LVBAG

# 此次编译完成后 gdal 支持的可选功能，其实也就是支持
-- The following OPTIONAL packages have been found:

* Threads
* ODBC
Enable DB support through ODBC
* Iconv
Character set recoding (used in GDAL portability library)
* LibXml2
Read and write XML formats
* Deflate
Enable libdeflate compression library (complement to ZLib)
* PROJ
* ZSTD
ZSTD compression library
* SFCGAL

```

```
gdal core supports ISO 19107:2013 and OGC Simple Features Access 1.2 for 3D operations
```

```
* ZLIB
```

```
zlib (external)
```

```
* GIF
```

```
GIF compression library (external)
```

```
* PCRE2
```

```
Enable PCRE2 support for sqlite3
```

```
* HDF5
```

```
Enable HDF5
```

```
* WebP
```

```
WebP compression
```

```
* NetCDF
```

```
Enable netCDF driver
```

```
* PostgreSQL
```

```
* LibLZMA
```

```
LZMA compression
```

```
* LZ4
```

```
LZ4 compression
```

```
* Blosc
```

```
Blosc compression
```

```
* ARCHIVE
```

```
Multi-format archive and compression library (used for /vsi7z/
```

```
* LIBAEC
```

```
Adaptive Entropy Coding implementing Golomb-Rice algorithm (used by GRIB)
```

```
* JNI
```

```
SWIG_JAVA: Java binding
```

```
* Java
```

```
# 此次编译完成后 gdal 支持的建议功能，其实也就是支持
```

```
-- The following RECOMMENDED packages have been found:
```

```
* EXPAT
```

```
Read and write XML formats
```

```
* CURL
```

```
Enable drivers to use web API
```

```
* GeoTIFF
```

```
libgeotiff library (external)
```

```
* PNG (required version >= 1.6)
```

```
PNG compression library (external)
```

```
* JPEG
```

```
JPEG compression library (external)
```

```
* LERC
```

```
Enable LERC (external)
```

```
* GEOS
```

```
Geometry Engine - Open Source (GDAL core dependency)
```

```
# 以下功能被禁止
```

```
-- The following features have been disabled:
```

```

* gdal_HEIF, HEIF
* gdal_MSG, Meteosat Second Generation
* gdal_FITS, FITS Driver
* gdal_GTA, Generic Tagged Arrays
* gdal_HDF4, Hierarchical Data Format Release 4 (HDF4)
* gdal_DDS, DirectDraw Surface
* gdal_KEA, Kea
* gdal_JP2OPENJPEG, JPEG2000 driver based on OpenJPEG library
* gdal_TILEDB, TileDB tiledb.io
* gdal_EXR, EXR support via OpenEXR library
* gdal_RDB, RIEGL RDB Map Pixel (.mpx) driver
* gdal_JPEGXL, JPEG-XL
* gdal_BASISU_KTX2, Basis Universal and KTX2 texture formats
* gdal_JP2KAK, JPEG-2000 (based on Kakadu)
* gdal_JPIP_KAK, JPIP Streaming
* gdal_JP2LURA, JPEG-2000 (based on Luratech)
* gdal_SDE, ESRI ArcSDE Raster
* gdal_MRSID, Multi-resolution Seamless Image Database
* gdal_GEOR, Oracle Spatial GeoRaster
* gdal_ECW, ERDAS JPEG2000 (.jp2)
* ogr_GMLAS, GMLAS
* ogr_DWG, DWG
* ogr_FILEGDB, FileGDB
* ogr_LIBKML, LibKML
* ogr_NAS, NAS/ALKIS
* ogr_SOSI, SOSI: Systematic Organization of Spatial Information
* ogr_ILI, ILI
* ogr_MYSQL, MySQL
* ogr_XLS, Microsoft Office Excel(xls)
* ogr_MONGODBV3, MongoDB V3
* ogr_PARQUET, Parquet
* ogr_ARROW, Arrow
* ogr_OCI, Oracle OCI
* ogr_IDB, IDB
* ogr_OGDI, OGDI
* ogr_HANA, SAP HANA

# 没有找到以下可选功能的支持库，因此对应功能不能使用
-- The following OPTIONAL packages have not been found:

* Python (required version >= 3.8)
SWIG_PYTHON: Python binding
* ODBC_CPP
odbc-cpp library (external)
* MSSQL_NCLI
MSSQL Native Client to enable bulk copy
* MSSQL_ODBC
MSSQL ODBC driver to enable bulk copy

```

```

* MySQL
MySQL
* XercesC
Read and write XML formats (needed for GMLAS and ILI drivers)
* CryptoPP
Use crypto++ library for CPL.
* JSONC
json-c library (external)
* OpenCAD
libopencad (external, used by OpenCAD driver)
* BRUNSLI
Enable BRUNSLI for JPEG packing in MRF
* libQB3
Enable QB3 compression in MRF
* SPATIALITE (required version >= 4.1.2)
Enable spatialite support for sqlite3
* RASTERLITE2 (required version >= 1.1.0)
Enable RasterLite2 support for sqlite3
* LibKML
Use LIBKML library
* KEA
Enable KEA driver
* FreeXL
Enable XLS driver
* GTA
Enable GTA driver
* MRSID
MrSID raster SDK
* Armadillo
C++ library for linear algebra (used for TPS transformation)
* CFITSIO
C FITS I/O library
* HDF4
Enable HDF4 driver
* ECW
Enable ECW driver
* OGDI
Enable ogr_OGDI driver
* OpenCL
Enable OpenCL (may be used for warping)
* FYBA
enable ogr_SOSI driver
* JXL
JPEG-XL compression
* JXL_THREADS
JPEG-XL threading
* Crnlib
enable gdal_DDS driver
* basisu

```



```

Enable BASISU driver
* IDB
enable ogr_IDB driver
* rdb
enable RIEGL RDB library
* TileDB
enable TileDB driver
* OpenEXR
OpenEXR >=2.2
* MONGOCXX
Enable MongoDBV3 driver
* HEIF
HEIF >= 1.1
* OpenJPEG (required version >= 2.3.1)
Enable JPEG2000 support with OpenJPEG library
* HDF5
Enable Hadoop File System through native library
* Poppler (required version >= 0.86), A PDF rendering library, <http://poppler.freedesktop.org>
Enable PDF driver with Poppler (read side)
* PDFIUM
Enable PDF driver with Pdium (read side)
* Oracle
Enable Oracle OCI driver
* TEIGHA
Enable DWG and DGNv8 drivers
* FileGDB
Enable FileGDB (based on closed-source SDK) driver
* KDU
Enable KAKADU
* LURATECH
Enable JP2Lura driver
* Arrow
Apache Arrow C++ library
* Dotnet
* CSharp
SWIG_CSharp: CSharp binding
* BISON

# 没有找到以下建议功能的支持库，因此对应功能不能使用
-- The following RECOMMENDED packages have not been found:

* SWIG, Software development tool that connects programs written in C and C++ with a variety of high-
  level programming languages., <http://swig.org/>
* QHULL
Enable QHULL (external)

# 以下功能使用 gdal 自行实现的内部库
-- Internal libraries enabled:

```

```
* JSONC internal library enabled
* OPENCAD internal library enabled
* QHULL internal library enabled
```

继续构建 gdal:

```
cmake --build .
cmake --build . --target install
```

#### 4.4.7 安装 postgis

```
cd ~/software/sdb
curl -LJO https://download.osgeo.org/postgis/source/postgis-3.4.2.tar.gz
tar -zxvf postgis-3.4.2.tar.gz
cd postgis-3.4.2
./configure --prefix=$PGSQL
```

执行 configure 命令后, 会出现以下提示信息:

```
.....

PostGIS is now configured for x86_64-w64-mingw32

----- Compiler Info -----
C compiler:          gcc -std=gnu99 -g -O2 -fno-math-errno -fno-signed-zeros -Wall
C++ compiler (Wagyu): gcc -std=c++11 -x c++
C++ compiler (FlatGeobuf): gcc -std=c++11 -x c++
CPPFLAGS:            -ID:/msys64/usr/local/pgsql/include -ID:/msys64/ucrt64/include/webp -
                      DLIBDEFLATE_DLL -ID:/msys64/ucrt64/include/libxml2 -I/ucrt64/include -ID:/msys64/ucrt64/include/
                      json-c -DNDEBUG
LDFLAGS:              -lm
SQL preprocessor:    /ucrt64/bin/cpp -traditional-cpp -w -P -Upixel -Ubool
Archiver:            gcc-ar rs

----- Additional Info -----
Interrupt Tests: ENABLED

# 依赖 geos、gdal、sfcgal、proj4、libxml2 等
----- Dependencies -----
GEOS config:         /usr/local/pgsql/bin/geos-config
GEOS version:        3.12.2
GDAL config:         /usr/local/pgsql/bin/gdal-config
GDAL version:        3.9.2
SFCGAL config:       /ucrt64/bin/sfcgal-config
SFCGAL version:      1.5.2
PostgreSQL config:   /usr/local/pgsql/bin/pg_config
PostgreSQL version:  PostgreSQL 16.4
PROJ4 version:       94
Libxml2 config:      /ucrt64/bin/xml2-config
```

```

Libxml2 version: 2.12.9
JSON-C support: yes
protobuf support: yes
protobuf-c version: 1005000
PCRE support: Version 2
Perl: /usr/bin/perl

# 支持的扩展功能
----- Extensions -----
PostgreSQL EXTENSION support: enabled # 矢量数据, 处理地理要素
PostGIS Raster: enabled # 栅格数据, 处理遥感影像等
PostGIS Topology: enabled # 拓扑操作
SFCGAL support: enabled # 使用 cgal 进行空间分析, 特别是 3D 分析
Address Standardizer support: enabled # 地理编码, 地址解析

----- Documentation Generation -----
xsltproc:
xsl style sheets:
dblatex:
convert: /c/Windows/System32/convert
mathml2.dtd: http://www.w3.org/Math/DTD/mathml2/mathml2.dtd

```

postgis 使用到的 `bzero` 函数是 `bsd` 标准提供的, 在 `ucrt` 系统中并不包含此函数, 因此需要自行实现。修改 `postgis_config.h` 代码如下:

```

#include "postgis_revision.h"

// 此处为添加的bzero实现代码
#define bzero(buf,n) memset(buf,0,n)

```

编译安装:

```
make
```