

1.常用事件

生命周期相关的：



app常用事件

文档地址：<http://electronjs.org/docs/all>

- **ready**: 当 Electron 完成初始化时被触发。
- **window-all-closed**: 所有窗口被关闭
- **before-quit**: 在应用程序开始关闭窗口之前触发
- **will-quit**: 当所有窗口都已关闭并且应用程序将退出时发出。
- **quit**: 在应用程序退出时发出。

webContents常用事件

文档地址：<http://electronjs.org/docs/all>

- **did-finish-load**: 导航完成时触发，即选项卡的旋转器将停止旋转，并指派**onload**事件后。
- **dom-ready**: 一个框架中的文本加载完成后触发该事件。

案例测试：

```

13     height: 600,
14     webPreferences: {
15       preload: path.join(__dirname, 'preload.js')
16     }
17   })
18
19   mainWindow.webContents.on("did-finish-load", () => {
20     console.log("****did-finish-load");
21   })
22
23   mainWindow.webContents.on("dom-ready", () => {
24     console.log("****dom-ready");
25   })
26
27   // and load the index.html of the app.
28   mainWindow.loadFile('index.html');
29
30   // Open the DevTools.
31   // mainWindow.webContents.openDevTools()
32
33   // Emitted when the window is closed.
34   mainWindow.on('closed', function () {
35     // Dereference the window object, usually you would store windows
36     // in an array if your app supports multi windows, this is the time
37     // when you should delete the corresponding element.
38     mainWindow = null
39   })
40 }
41
42 // This method will be called when Electron has finished
43 // initialization and is ready to create browser windows.
44 // Some APIs can only be used after this event occurs.
45 app.on('ready', () => {
46   console.log("****ready");
47   createWindow();
48 })
49

```

```

30   mainWindow = null
31 }
32 }
33
34 // This method will be called when Electron has finished
35 // initialization and is ready to create browser windows.
36 // Some APIs can only be used after this event occurs.
37 app.on('ready', () => {
38   console.log("****ready");
39   createWindow();
40 })
41
42 // Quit when all windows are closed.
43 app.on('window-all-closed', function () {
44   console.log("****window-all-closed");
45   // On macOS it is common for applications and their menu bar
46   // to stay active until the user quits explicitly with Cmd + Q
47   if (process.platform !== 'darwin') app.quit()
48 })
49

```

debug启动查看

