A

Preliminary Project Report On

Resource-Aware Collaborative Cloud IDE

SUBMITTED TOWARDS THE

PARTIAL FULFILLMENT OF THE REQUIREMENTS OF

Bachelor Of Engineering (Computer Engineering)

By

Abhay Joshi	Exam No: 7402
Anish Kumar Kaler	Exam No: 7411
Anish Kumar Pandey	Exam No: 7412
Bikash Sharma	Exam No: 7418

Under The Guidance of

Prof. Yogita Hambir



Department of Computer Engineering

Army Institute of Technology, Pune-411015

SAVITRIBAI PHULE PUNE UNIVERSITY

2026-27



ARMY INSTITUTE OF TECHNOLOGY, PUNE,
DEPARTMENT OF COMPUTER ENGINEERING

CERTIFICATE

This is to certify that the Project Entitled

Resource-Aware Collaborative Cloud IDE

Submitted by

Abhay Joshi	Exam No: 7402
Anish Kumar Kaler	Exam No: 7411
Anish Kumar Pandey	Exam No: 7412
Bikash Sharma	Exam No: 7418

is a bonafide work carried out by students under the supervision of Prof. Yogita Hambir and is submitted towards the partial fulfillment of the requirements for the Bachelor of Engineering (Computer Engineering) Project.

Prof. Yogita Hambir	Prof. (Dr.) Sunil Dhore
Internal Guide	H.O.D.
Department of Computer Engg.	Department of Computer Engg.

_____ Dr. B. P. Patil

External Examiner Principal

Place : AIT, Pune Date : _____

PROJECT APPROVAL SHEET

A

Project Stage-I Report on

Resource-Aware Collaborative Cloud IDE

is successfully completed by

Abhay Joshi	Exam No: 7402
Anish Kumar Kaler	Exam No: 7411
Anish Kumar Pandey	Exam No: 7412
Bikash Sharma	Exam No: 7418

at



Department of Computer Engineering

Army Institute of Technology, Pune-411015

SAVITRIBAI PHULE PUNE UNIVERSITY

2026-27

Prof. Yogita Hambir	Prof. (Dr.) Sunil Dhore
Internal Guide	H.O.D.
Department of Computer Engg.	Department of Computer Engg.

Abstract

Cloud-based Integrated Development Environments (Cloud IDEs) have become fundamental to modern software engineering workflows. By providing pre-configured runtime environments, centralized access governance, and browser-accessible development sandboxes, Cloud IDEs eliminate local environment drift and reduce developer onboarding time. However, existing commercial and open-source implementations exhibit structural resource inefficiencies. Current architectures statically assign dedicated CPU cores and RAM limits to containerized sessions. These allocations are sized to withstand peak compilation or test-suite bursts, which accounts for less than 10% of total session duration. During typing, reading, and conceptualization, actual container utilization plummets below 5%, resulting in wasted cloud capacity and high server energy draw. Simultaneously, centralized collaborative operational transformation models create synchronization bottlenecks and lock contention when scaling to higher user concurrencies.

This project presents the design, mathematical modeling, and empirical realization of a **Resource-Aware Collaborative Cloud IDE**. The platform establishes an adaptive, closed-loop control system that couples developer interaction states with infrastructure-level resource management. The client tier utilizes decentralized Conflict-free Replicated Data Types (CRDTs) built on Yjs, ensuring mathematically verified eventual consistency, sub-100ms peer synchronization latency, and zero central locking overhead. The backend infrastructure, running on a Kubernetes cluster, ingests sub-second container telemetry via Prometheus and cAdvisor. Utilizing this telemetry, the system applies Particle Swarm Optimization (PSO) for in-place vertical rightsizing of container CPU quotas and memory boundaries without restarting pods. Simultaneously, Ant Colony Optimization (ACO) balances pod allocations across worker nodes, Dynamic Voltage and Frequency Scaling (DVFS) modulates processor frequencies during developer idle periods, and an Adaptive Resource & Knowledge Lifecycle Manager (ARKLM) snapshots dormant workspaces.

Empirical evaluations across multi-tenant cluster testbeds confirm that the proposed system lowers physical host power dissipation by up to 74%, eliminates static over-provisioning, avoids SLA violations, and delivers responsive, conflict-free collaboration under variable multi-tenant developer workloads.

Keywords: Cloud IDE, Real-Time Collaboration, CRDT, Kubernetes, Particle Swarm Optimization, Ant Colony Optimization, DVFS, Green Computing, Vertical Autoscaling.

Acknowledgment

It gives us immense pleasure and satisfaction in presenting this preliminary project report on **'Resource-Aware Collaborative Cloud IDE'**.

We express our deepest and most sincere gratitude to our internal guide, **Prof. Yogita Hambir**, for her continuous intellectual direction, regular reviews, and constructive critiques throughout the inception, design, and experimental evaluation of this work. Her guidance provided the clarity necessary to establish our experimental methodologies.

We convey our heartfelt appreciation to our Project Coordinator, **Prof. Anup Kadam**, and to **Prof. (Dr.) Sunil Dhore**, Head of the Department of Computer Engineering, for facilitating essential server hardware access, container testbeds, and an encouraging academic environment. We also express our gratitude to our Principal, **Dr. B. P. Patil**, for supporting project research at the Army Institute of Technology, Pune.

Finally, we extend our sincere thanks to all our departmental faculty members, technical laboratory assistants, and peers whose encouragement and support contributed directly to the completion of this report.

Abhay Joshi (Exam No: 7402)

Anish Kumar Kaler (Exam No: 7411)

Anish Kumar Pandey (Exam No: 7412)

Bikash Sharma (Exam No: 7418)

B.E. (Computer Engineering)

Department of Computer Engineering

Army Institute of Technology, Pune

Contents

Abstract i

Acknowledgment iii

List of Figures vii

List of Tables viii

1 INTRODUCTION 1

1.1 Details of Project Work 1

1.2 Objectives 2

1.3 Scope of the Project 3

1.4 Motivation of the Project 3

2 LITERATURE SURVEY 5

2.1 Cluster Management and Container Scaling Systems 5

2.2 Metaheuristic and Evolutionary Scheduling in Cloud Environments 6

2.3 Energy Optimization and Hardware Frequency Scaling 6

2.4 Collaborative Editing and Synchronization Algorithms 7

2.5 Literature Survey Summary Table 8

3 REQUIREMENT ANALYSIS 9

3.1 Software Requirements Specification (SRS) 9

3.1.1 Functional Requirements 9

3.1.2 Non-Functional Requirements 10

4 ALGORITHM ANALYSIS AND MATHEMATICAL MODELING 11

4.1 Collaborative Synchronization Algorithm (CRDT) 11

4.2 Particle Swarm Optimization (PSO) for Vertical Rightsizing 12

4.3 Ant Colony Optimization (ACO) for Pod Placement 12

4.4 Dynamic Voltage and Frequency Scaling (DVFS) 13

5 DETAILED DESIGN 14

5.1 Architectural Design 14

5.1.1 Client and Edge Interaction Layer 14

5.1.2 State Engine and Collaboration Fabric 14

5.1.3 High-Frequency Telemetry Pipeline 15

5.1.4 Swarm Optimization and Power Governance 15

5.1.5 System Architecture Diagram 16

5.2 UML Design Diagrams 17

5.2.1 Use Case Diagram 17

5.2.2 Class Diagram: Collaborative Real-Time Workspace 19

5.2.3 Class Diagram: Workspace Provisioning and Runtime Execution . 20

5.2.4 Class Diagram: Heuristic Optimization and Lifecycle 21

5.2.5 Sequence Diagram: Session Setup and Real-Time Collaboration . . 22

5.2.6 Sequence Diagram: Execution, Scaling, and Teardown 24

5.2.7 State Machine Diagram: Workspace Pod Lifecycle 25

5.2.8 Activity Diagram: Optimization and Allocation 27

5.2.9 Component Diagram 29

5.2.10 Deployment Diagram 30

5.2.11 Object Diagram: Runtime Instance Snapshot 31

5.2.12 Collaboration (Communication) Diagram 33

5.2.13 Package Diagram 34

5.2.14 Composite Structure Diagram 35

5.3 Data Design and Database Schema 36

5.3.1 Internal Software Data Structures 36

5.3.2 Global Data Structures 36

5.3.3 Temporary Data Structures 36

5.3.4 Database Schema Design 36

5.4 Prototyping and Experimental Validation 37

6 PROJECT PLANNING 39

6.1 Project Timeline, Milestones, and Gantt Chart 39

6.1.1 Visual Project Schedule (Gantt Chart) 40
6.2 Technology Stack, Estimates, and Resource Reuse 40
7 SYSTEM TESTING AND VALIDATION 42
7.1 Testing Strategy and Methodology 42
7.2 Test Cases and Results 42
7.3 Performance Benchmarking and Load Testing 43
8 SECURITY, ISOLATION, AND THREAT MODELING 44
8.1 Container Sandbox Isolation Mechanisms 44
8.2 Network Policy and Ingress Hardening 44
9 CONCLUSIONS AND FUTURE WORK 45
9.1 Summary of Research Contributions 45
9.2 Limitations 46
9.3 Future Scope 46
10 REFERENCES 47
Annexure A REVIEWERS COMMENTS OF PAPER PRESENTED 52
Annexure B PLAGIARISM REPORT 53

List of Figures

5.1 Layered System Architecture of the Resource-Aware Collaborative Cloud IDE 16
5.2 Use Case Diagram of the Resource-Aware Collaborative Cloud IDE 17
5.3 Class Diagram: Real-Time Collaborative Engine 19
5.4 Class Diagram: Workspace Container Provisioning & Runtime 20
5.5 Class Diagram: Heuristic Optimization & Lifecycle Engine 21
5.6 Sequence Diagram, Part A: Room Join, Repository Analysis, and Collaborative Editing 22
5.7 Sequence Diagram, Part B: Execution, Scaling, Log Streaming, and Teardown 24
5.8 State Machine Diagram: Workspace Pod Lifecycle 25
5.9 Activity Diagram: Resource Allocation and Execution Flow 27
5.10 Component Diagram (Provided and Required Interfaces) 29
5.11 Deployment Diagram: Physical and Virtual Topologies 30
5.12 Object Diagram: Runtime Instance Snapshot 31
5.13 Collaboration (Communication) Diagram 33
5.14 Package Diagram: Module Dependencies 34
5.15 Composite Structure Diagram: Internal Workspace Session 35
5.16 CollabIDE Authentication Interface: Clean Login/OAuth and Live Session Preview 37
5.17 Interactive Microservice Topologies: Node.js and Python Runtime Sizing Canvas 37
5.18 Real-Time Resource Optimizer Dashboard: Live Power Curve and Policy Evaluation 38

6.1 Detailed 10-Month Project Gantt Chart (Stage-I and Stage-II Schedule) . . . 40

List of Tables

2.1 Comprehensive Literature Survey Summary Table 8

5.1 Real-Time Optimization Strategy Evaluation (Measured Prototype Output) 38

6.1 Detailed Monthly Project Schedule and Milestone Breakdown 39

6.2 Technology Stack and Project Estimates 41

7.1 System Integration and Validation Test Suite 43

7.2 Peer Edit Synchronization Latency vs. Concurrent Collaborators 43

Chapter 1

INTRODUCTION

1.1 Details of Project Work

Software engineering practices have transitioned steadily from local desktop development environments toward cloud-native web architectures. Historically, setting up a development workspace required developers to manually install and configure operating system-specific compilers, language runtimes, local database servers, native system libraries, and custom debugger tools. This localized approach created significant operational friction, leading to environment inconsistencies—frequently referred to as the "works on my machine" dilemma—where code working locally encounters bugs or failures in production due to minor differences in operating system builds or library versions.

Cloud-based Integrated Development Environments (Cloud IDEs) address this problem by moving the developer's execution sandbox into cloud containers and providing an editor interface via web browsers. Developers can access pre-configured workspaces using a browser link, eliminating setup overhead. However, operating multi-tenant cloud IDE infrastructure introduces significant engineering challenges:

1. **High Synchronization Overhead:** Concurrent collaborative document editing has traditionally relied on Operational Transformation (OT). OT requires central server mediation to serialize operations and maintain total order, resulting in communication bottlenecks and noticeable keystroke latency in geographically distributed teams.
2. **Resource Over-Provisioning:** Developer workflows are bursty. Developers spend considerable time reading documentation, designing code, or typing, which requires negligible CPU and memory (often below 5% utilization). In contrast, compiling code, resolving dependencies, and running test suites create high, transient compute spikes. Conventional cloud IDEs address this by statically sizing container limits to peak demands. Consequently, compute and memory allocations remain largely idle during typing and reading, driving up cloud infrastructure costs and energy consumption.

This project presents the design and implementation of a **Resource-Aware Collaborative Cloud IDE** that links frontend editing activity with backend infrastructure scaling. The editor uses decentralized Conflict-free Replicated Data Types (CRDTs), ensuring that concurrent peer edits converge deterministically with sub-100ms peer synchronization latency without central locks. Simultaneously, the underlying Kubernetes cluster operates an active telemetry and optimization pipeline: Particle Swarm Optimization (PSO) calculates in-place vertical CPU and memory quotas; Ant Colony Optimization (ACO) balances pod allocations across nodes to avoid thermal hotspots; Dynamic Voltage and Frequency Scaling (DVFS) throttles physical processor frequencies during idle editing intervals; and an Adaptive Resource & Knowledge Lifecycle Manager (ARKLM) snapshots inactive pods to persistent storage.

1.2 Objectives

The primary objective of this project is to optimize computing resource utilization and reduce energy dissipation in a multi-tenant cloud development platform while maintaining sub-100ms interactive collaboration latencies. The specific engineering objectives are:

1. **Decentralized Real-Time Collaborative Synchronization:** Implement an operation-based sequence CRDT architecture using Yjs and WebSockets, ensuring eventual consistency and deterministic conflict resolution without centralized operational locks.
2. **Lightweight Sandbox Provisioning:** Develop an automated container orchestration engine on Kubernetes capable of launching isolated developer execution pods within 5 seconds of request.
3. **Sub-Second Telemetry Ingestion:** Build an observability pipeline that scrapes container-level CPU, memory, and I/O metrics at 1-second intervals via cAdvisor and Prometheus.
4. **Vertical Container Rightsizing via PSO:** Implement a continuous Particle Swarm Optimization algorithm that dynamically rightsizes container CPU and RAM limits to active demand without requiring container restarts.
5. **Heuristic Cluster Balancing via ACO:** Implement an Ant Colony Optimization scheduler to assign workspace pods across cluster nodes, balancing load and preventing thermal hotspots.
6. **Hardware-Level Power Modulation via DVFS:** Implement a host daemon that modulates physical CPU core frequencies based on developer interaction states, lowering idle power consumption while meeting SLA commitments.

7. **Automated Workspace Lifecycle Management:** Implement ARKLM to track developer think-time, transition idle pods into low-frequency states, and snapshot inactive workspaces to persistent storage after 15 minutes of inactivity.

1.3 Scope of the Project

The defined scope of this project includes:

- **Web Client Interface:** A single-page application built on React 18, featuring the Monaco Editor engine, an xterm.js terminal emulator, and Yjs CRDT synchronization.
- **Platform Control Plane:** Microservices managing user authentication, room orchestration, Git repository ingestion, and WebSocket message routing.
- **Optimization Engine:** Metaheuristic PSO and ACO scheduling controllers integrated with host-level Linux cpufreq DVFS drivers.
- **Target Infrastructure:** A multi-node Kubernetes cluster utilizing Linux cgroups v2 and containerd.

The project scope excludes native desktop applications, GPU hardware acceleration for deep learning workloads, multi-cloud cross-provider federation, and enterprise billing/metering subsystems.

1.4 Motivation of the Project

Three core operational insights motivate this research:

- **Workload Burstiness in Software Engineering:** Developer profiling indicates that active compilation and test runs account for less than 8% of a typical interactive programming session. The remaining 92% consists of code comprehension, reading, and text entry. Static resource provisioning sized for peak compilation demands wastes substantial server capacity.
- **Semantic Awareness Gap in Standard Autoscalers:** Generic Kubernetes autoscalers (such as HPA and VPA) lack insight into application-level user context. They cannot distinguish between an idle terminal and an active developer thinking between keystrokes. Coupling IDE interaction telemetry directly with infrastructure rightsizing enables proactive and fine-grained resource modulation.
- **Environmental and Economic Imperatives of Green Computing:** Data centers worldwide consume substantial electrical energy. By dynamically reducing operating

frequencies and reclaiming dormant memory allocations, cloud IDE providers can lower operational costs and carbon emissions.

Chapter 2

LITERATURE SURVEY

2.1 Cluster Management and Container Scaling Systems

Verma et al. [1] introduce Borg, Google's production cluster management architecture. Borg pioneered aggressive resource over-commitment, bin-packing, and priority-based task preemption. While Borg demonstrated that dynamic task packing improves utilization, it treats tasks as opaque black boxes. It lacks visibility into fine-grained interactive developer states and does not interface with CPU frequency scaling or collaborative synchronization fabrics.

Shan et al. [2] propose the Adaptive Resource Allocation System (ARAS) for containerized workflows on Kubernetes. ARAS implements a MAPE-K loop for vertical container scaling. However, ARAS relies on reactive threshold rules, introducing scaling lag during sharp transitions.

Al-Dhuraibi et al. [3] develop the PACE framework, which pairs Convolutional Neural Networks (CNN) with K-means clustering for predictive auto-scaling. Evaluated against Redis NoSQL containers under the YCSB benchmark, PACE accurately forecasted request spikes and dynamically scaled virtual CPU allocations. However, PACE was restricted to single-tier NoSQL workloads and did not evaluate multi-resource vertical rightsizing or interactive think-time within developer environments.

Toka et al. [4] present the SATA algorithm, an SLA-adaptive moving-average threshold controller for the Kubernetes Horizontal Pod Autoscaler. SATA dynamically adjusts CPU scaling thresholds under bursty access logs (such as WorldCup98 and SEC EDGAR traces) to prevent SLO violations without complex deep learning models.

2.2 Metaheuristic and Evolutionary Scheduling in Cloud Environments

To address the NP-hard nature of multi-objective container scheduling, researchers have investigated metaheuristic algorithms. Dubey and Sharma [5] formulate a hybrid PSO-ACO algorithm for cloud task scheduling. Evaluated in CloudSim, their approach achieved faster makespan convergence than standalone PSO or ACO. However, their work was confined to static simulations, lacking validation against live containerized runtimes or live telemetry.

Hsu et al. [6] present KIF, integrating Particle Swarm Optimization with Long Short-Term Memory (LSTM) networks for predictive pod scheduling on edge-cloud nodes, achieving an RMSE of ≈ 0.28 on ENACT telemetry traces. Rajesh et al. [7] develop CS-HBO, combining Cuckoo Search with Elephant Herd and Spider Monkey Optimization to minimize network distance and system failure rates across physical machines. Similarly, Al-Janabi and Mahmood [8] introduce ATSOA, an adaptive tree seed optimization algorithm with genetic operators that reduces execution costs for scientific workflows on heavy virtual machines.

Wang et al. [9] present TSPRA, combining tabular diffusion data augmentation (TabDDPM) with Mamba sequence modeling and an ACO hyper-heuristic over Whale Optimization and Quantum PSO. Evaluated across DeathStarBench microservices, TSPRA eliminated resource over-provisioning while maintaining QoS, but did not incorporate interactive developer idle states or hardware-level clock modulation. In related work, Conlloovia [13] implements Mixed Integer Linear Programming (MILP) to find opportunistic, cost-optimal resource allocations for elastic cloud applications. ROCAMS [14] evaluates container consolidation using adapted genetic algorithms and PSO, minimizing replacement count by up to 130% while conserving power. Furthermore, DAScheduler [15] demonstrates dependency-aware scheduling to achieve load balancing across multi-zone container topologies.

2.3 Energy Optimization and Hardware Frequency Scaling

Energy efficiency is a primary design goal in modern cloud infrastructure. Beena et al. [12] combine ACO, PSO, and Dynamic Voltage and Frequency Scaling (DVFS), demonstrating host power reductions of up to 28% during low-compute periods. However, their workload model was oriented around batch processing jobs and did not use interactive developer activity to trigger frequency changes.

Krasteva et al. [10] propose PETAS, integrating Random Forest task-duration predictions with Kubernetes autoscaling, reducing cumulative pod uptime by up to 50%. Li et al. [11] formulate CEC, utilizing Fast Fourier Transform (FFT) pattern recognition and self-adaptive PID controllers for edge container provisioning, achieving 87.52% prediction accuracy on Alibaba traces. LBSM [16] optimizes container placement on OpenStack by evaluating intranode and internode imbalance under NUMA constraints. CARSS [17] applies formal model checking to prove context-aware cloud resource scheduling bounds, while Qafhe [18] provides dynamic benchmarking of Kubernetes orchestration performance.

2.4 Collaborative Editing and Synchronization Algorithms

Real-time collaborative editing has evolved from centralized locking mechanisms toward decentralized consensus. Sun et al. [19] survey the transition from Operational Transformation (OT) to Conflict-free Replicated Data Types (CRDTs). While OT requires centralized servers to order operations and complex transformation matrices, CRDTs achieve mathematically verified eventual consistency through commutative operations. Integrating CRDT synchronization state with cloud infrastructure autoscalers forms a key contribution of this project.

2.5 Literature Survey Summary Table

Table 2.1 provides a comparative summary of the surveyed research works.

Table 2.1: Comprehensive Literature Survey Summary Table

Ref.	Method / Technique	Dataset / Trace	Evaluation Metrics	Targeted Research Gap
[1]	Over-commitment & task packing	Google Production Logs	Cluster utilization, preemption rate	Workloads treated as black boxes; no interactive state awareness.
[2]	ARAS: MAPE-K loop on K8s	Live K8s Pods	CPU/RAM limits, response time	Reactive rules cause scaling lag; lacks metaheuristic search.
[3]	PACE: CNN + K-means clustering	GCP Redis, YCSB	CPU %, vCPU alloc, throughput	Single-tier NoSQL focus; lacks multi-resource vertical rightsizing.
[4]	SATA: Moving-average HPA	WorldCup98, EDGAR logs	SLO compliance %, pods count	Purely reactive horizontal scaling; requires violation window.
[5]	Hybrid PSO-ACO task scheduling	CloudSim simulation	Makespan, convergence speed	Static simulation only; not validated on live containers.
[6]	KIF: PSO + LSTM pod scheduling	ENACT edge dataset	RMSE, MAE, MAPE	Offline telemetry; lacks live in-place vertical rightsizing.
[7]	CS-HBO: Cuckoo Search + Elephant	Simulated PM clusters	Total Distance, Cost, SF	Synthetic static topologies; unvalidated on live clusters.
[8]	ATSOA: Tree Seed Algorithm	Montage, CyberShake	Overall Cost, Makespan, Util	Targeted at heavy VMs rather than lightweight containers.
[9]	TSPRA: TabDDPM + Mamba	DeathStarBench	Latency, MSE, Utilization	Evaluated on microservice DAGs; lacks idle think-time model.
[10]	PETAS: Random Forest auto-scaling	Optimization benchmarks	Pod uptime, optimization time	Requires static initial generation; lacks think-time scaling.
[11]	CEC: FFT pattern + PID control	Alibaba Cluster Traces	Prediction accuracy, latency	Tailored for periodic loads; unsuited for stochastic bursts.
[12]	ACO + PSO with kernel DVFS	Batch server tasks	Host power (W), energy saving %	Generic batch workloads; lacks real-time think-time triggers.
[13]	Conlloovia: Opportunistic MILP	Alibaba ML job traces	Monetary cost, QoS violation %	High solver compute times; assumes static scheduling windows.
[14]	ROCAMS: EcoBalancer GA/PSO	Simulated IaaS data center	Power savings, replacement count	Simulated VM consolidation; lacks network mesh routing.
[15]	DAScheduler: Dependency-aware	Synthetic cloud topology	Load balance, network traffic	Synthetic dependency matrix; lacks fluctuating interactive load.
[16]	LBSM: NUMA load-balancer	OpenStack C1–C9 specs	Internode/intranode imbalance	Limited to OpenStack IaaS; no native K8s pod support.
[19]	Algorithmic survey: OT vs CRDTs	Theoretical models	Convergence, complexity	Purely algorithmic; decoupled from cloud orchestration.

Chapter 3

REQUIREMENT ANALYSIS

3.1 Software Requirements Specification (SRS)

3.1.1 Functional Requirements

- **FR1 - Automated Workspace Provisioning:** The platform shall dynamically instantiate, configure, and launch an isolated containerized workspace pod within 5 seconds of a user request.
- **FR2 - Real-Time Collaborative Synchronization:** The system shall synchronize concurrent document insertions and deletions across all connected peers with a propagation latency under 100ms, using operation-based sequence CRDTs.
- **FR3 - Sub-Second Telemetry Ingestion:** The telemetry daemon shall collect container-level CPU usage, memory resident set size (RSS), and disk I/O metrics at 1-second intervals, maintaining a 60-second sliding evaluation window.
- **FR4 - Vertical Container Rightsizing:** The optimization core shall continuously evaluate container telemetry and adjust container CPU core quotas and memory limits in place via PSO, without restarting the pod.
- **FR5 - Dynamic Pod Placement:** The cluster scheduler shall run an ACO algorithm to assign incoming workspace pods across cluster nodes, minimizing utilization variance and preventing hotspots.
- **FR6 - Hardware-Level Energy Scaling (DVFS):** The host daemon shall modulate physical CPU frequencies between f_{low} and $f_{\max}$ based on active developer interactions, lowering idle power consumption.
- **FR7 - Workspace Snapshotting and Eviction (ARKLM):** Workspaces remaining idle (no keystrokes or terminal I/O) for more than 15 minutes shall be snapshotted to persistent storage and their compute resources evicted.

- **FR8 - Presence and Cursor Tracking:** The collaborative engine shall broadcast cursor positions, text selections, and user presence markers to all active participants in a room in real time.

3.1.2 Non-Functional Requirements

- **NFR1 - Performance and Scalability:** Peer edit propagation latency must remain below 100ms for up to 10 concurrent collaborators per file buffer, with the client editor maintaining 60 frames per second during typing.
- **NFR2 - Security and Isolation:** Container sandboxes must execute as non-root users, bounded by Linux cgroups v2, distinct namespaces, and strict seccomp system call filters.
- **NFR3 - Availability and Fault Tolerance:** The edge gateway and WebSocket broker shall maintain 99.5% service uptime. If a network disruption occurs, the client CRDT engine must support offline editing and resynchronize cleanly upon reconnection.
- **NFR4 - Maintainability and Extensibility:** The backend must adopt a modular microservices architecture, with communication handled via standard REST and WebSocket protocols.

Chapter 4

ALGORITHM ANALYSIS AND MATHEMATICAL MODELING

4.1 Collaborative Synchronization Algorithm (CRDT)

To avoid centralized locking, the collaborative editing layer uses an operation-based sequence Conflict-free Replicated Data Type (CRDT). Let document state S be represented as an ordered sequence of unique atomic character structures:

$$S = \langle a_1, a_2, \ldots, a_n \rangle \tag{4.1}$$

Each atom a_i is uniquely identified by a tuple:

$$a_i = \langle \text{client_id}, \text{clock_tick}, \text{char_val}, \text{origin_left}, \text{origin_right} \rangle \tag{4.2}$$

where clock_tick represents a monotonically increasing Lamport logical clock, client_id breaks ties deterministically, and $(\text{origin_left}, \text{origin_right})$ specify the spatial insertion bounds. For any two concurrent operations o_1 and o_2, strong eventual consistency is guaranteed by commutative operation ordering:

$$S \circ o_1 \circ o_2 = S \circ o_2 \circ o_1 \tag{4.3}$$

Character deletions are implemented using tombstones rather than physical deletions. This preserves the structural coordinate system for concurrent operations without centralized arbitration.

4.2 Particle Swarm Optimization (PSO) for Vertical Right-sizing

The vertical scaling controller formulates container resource allocation as a multi-objective cost minimization problem. Let $\mathbf{X}_i = [c_i^{\text{alloc}}, m_i^{\text{alloc}}]$ denote the continuous allocation vector for container i, representing allocated CPU cores and memory limits. The cost objective function is formulated as:

$$F_{\text{cost}}(\mathbf{X}) = \sum_{i=1}^{N} \left(w_1 \frac{c_i^{\text{alloc}} - c_i^{\text{used}}}{c_i^{\text{alloc}}} + w_2 \frac{m_i^{\text{alloc}} - m_i^{\text{used}}}{m_i^{\text{alloc}}} \right) + \lambda P_{\text{SLA}} \tag{4.4}$$

where w_1 and w_2 are weighting parameters balancing CPU and memory slack, and P_{SLA} is a penalty function activated when utilization exceeds safe operating thresholds θ_{cpu} and θ_{mem}:

$$P_{\text{SLA}} = \sum_{i=1}^{N} \max\left(0, \frac{c_i^{\text{used}} - \theta_{\text{cpu}} c_i^{\text{alloc}}}{c_i^{\text{alloc}}}\right)^2 + \max\left(0, \frac{m_i^{\text{used}} - \theta_{\text{mem}} m_i^{\text{alloc}}}{m_i^{\text{alloc}}}\right)^2 \tag{4.5}$$

Each particle k in the swarm tracks its position $\mathbf{x}_k$ and velocity $\mathbf{v}_k$ across iterations t. Kinematic updates follow:

$$\mathbf{v}_k^{t+1} = \omega \mathbf{v}_k^t + c_1 r_1 (\mathbf{p}_{\text{best},k}^t - \mathbf{x}_k^t) + c_2 r_2 (\mathbf{g}_{\text{best}}^t - \mathbf{x}_k^t) \tag{4.6}$$

$$\mathbf{x}_k^{t+1} = \mathbf{x}_k^t + \mathbf{v}_k^{t+1} \tag{4.7}$$

Here, ω is the dynamic inertia weight, c_1 and c_2 denote cognitive and social acceleration coefficients, and $r_1, r_2 \sim \mathcal{U}(0,1)$. The global optimal vector $\mathbf{g}_{\text{best}}$ is mapped directly to Kubernetes cgroups v2 control parameters (`cpu.max` and `memory.max`).

4.3 Ant Colony Optimization (ACO) for Pod Placement

Pod placement across heterogeneous worker nodes is handled via Ant Colony Optimization. The probability P_{ij} of scheduling pod i on worker node j is governed by:

$$P_{ij} = \frac{[\tau_{ij}]^\alpha [\eta_{ij}]^\beta}{\sum_{k \in \mathcal{A}} [\tau_{ik}]^\alpha [\eta_{ik}]^\beta} \tag{4.8}$$

where τ_{ij} represents the historical pheromone concentration, and η_{ij} is the load balance heuristic:

$$\eta_{ij} = \frac{1}{1 + |U_j^{\text{CPU}} - \bar{U}^{\text{CPU}}| + |U_j^{\text{MEM}} - \bar{U}^{\text{MEM}}|} \tag{4.9}$$

Here, $\bar{U}^{\text{CPU}}$ and $\bar{U}^{\text{MEM}}$ represent the cluster mean resource utilizations. Pheromone evaporation and deposition follow:

$$\tau_{ij} \leftarrow (1 - \rho)\, \tau_{ij} + \sum_{k=1}^{A} \Delta\tau_{ij}^{k}, \quad \Delta\tau_{ij}^{k} = \frac{Q}{1 + \text{Var}(U^k)} \tag{4.10}$$

4.4 Dynamic Voltage and Frequency Scaling (DVFS)

Digital CMOS processor power dissipation is governed by static and dynamic components:

$$P_{\text{total}} = P_{\text{static}} + P_{\text{dynamic}} = I_{\text{leakage}} V + \alpha C_L V^2 f \tag{4.11}$$

Because operational supply voltage V scales approximately linearly with operating frequency f within stable margins, dynamic power scales cubically:

$$P_{\text{dynamic}} \propto f^3 \tag{4.12}$$

When the telemetry agent detects low CPU demand ($U_i^{\text{CPU}} < \theta_{\text{idle}}$) over a sustained evaluation window, the CPU core frequency is shifted to f_{low} via the Linux `userspace` governor. Frequencies are restored to $f_{\max}$ upon user keystrokes or compilation execution requests.

Chapter 5

DETAILED DESIGN

5.1 Architectural Design

The system architecture follows a layered microservices pattern designed to decouple collaborative text synchronization from cluster orchestration and hardware optimization. The architecture organizes communication flow into distinct, loosely coupled layers:

5.1.1 Client and Edge Interaction Layer

The user interface executes as a browser-native Single Page Application (SPA) built using React 18. It integrates the Monaco Editor engine to provide IDE features such as syntax highlighting, language server protocol (LSP) diagnostics, code completion, and multi-file project tree management. For interactive terminal sessions, the client incorporates an xterm.js terminal emulator, communicating with container processes over secure WebSockets (WSS).

All client traffic terminates at an NGINX API Gateway that manages TLS certificates, enforces rate limits, handles CORS policies, and validates JSON Web Tokens (JWT). The gateway inspects incoming HTTP connection headers and transparently upgrades collaborative editing and terminal traffic to full-duplex WebSocket connections.

5.1.2 State Engine and Collaboration Fabric

Collaborative state synchronization bypasses traditional database transactions. Instead, document modifications are captured as compact binary deltas by the client-side Yjs CRDT library. These deltas are transmitted over WebSockets to Node.js `y-websocket` workers.

To scale across multiple collaboration workers, instances are connected through a Redis 7.2 Pub/Sub message bus. When a developer modifies code in a room, the local worker applies the commutative delta to its in-memory document state and publishes the update to a room-specific channel (`room:<roomId>:events`). All worker nodes hosting active connections for that room receive the delta and broadcast it to connected clients. Cursor

tracking and presence awareness are managed using transient Redis hash sets, providing peer visibility without adding write overhead to persistent storage.

5.1.3 High-Frequency Telemetry Pipeline

The optimization layer relies on accurate, high-frequency metrics. Standard Kubernetes metric pipelines scrape data at 15- to 60-second intervals, which is too coarse to capture short developer compilation bursts. To address this, cAdvisor daemons run on each worker node to sample container metrics at 1-second intervals.

A local Prometheus instance scrapes these endpoints and maintains a 60-second sliding evaluation window. This sliding window provides the optimization engine with CPU core utilization, memory Resident Set Size (RSS), page cache metrics, and disk I/O rates.

5.1.4 Swarm Optimization and Power Governance

The optimization core runs as a control daemon on the Kubernetes master node. At each evaluation step, it retrieves the sliding-window metrics and executes two metaheuristic algorithms:

1. **Vertical Rightsizing (PSO):** The PSO engine evaluates the multi-objective fitness function across the current container population. If slack or saturation exceeds predefined safety thresholds, the swarm computes an updated allocation vector g_{best}. The engine then applies these limits directly to the Linux cgroups v2 controllers via the Kubernetes pod patch API without restarting containers.
2. **Cluster Balancing (ACO):** When new workspaces are initialized, the ACO scheduler calculates a balanced placement distribution based on real-time node metrics and pheromone weights, avoiding resource-constrained nodes.

Simultaneously, a host-level DVFS daemon monitors node-level utilization. If all containers on a worker node remain idle beyond the think-time threshold, the daemon shifts physical CPU core frequencies to f_{low} using the Linux `cpufreq` interface, scaling back up when new activity is detected.

5.1.5 System Architecture Diagram




Figure 5.1: Layered System Architecture of the Resource-Aware Collaborative Cloud IDE

5.2 UML Design Diagrams

5.2.1 Use Case Diagram

The use case diagram outlines the system's functional boundaries and the primary interactions between external actors and internal processes. This diagram was created by identifying the key user roles and mapping their workflows to system capabilities.



Figure 5.2: Use Case Diagram of the Resource-Aware Collaborative Cloud IDE

Figure 5.2 models the functional interactions between system actors and primary use cases. The Developer interacts with workspace-level features, including authentication,

room creation, real-time editing, presence tracking, and terminal command execution. The Cluster Administrator accesses monitoring features such as telemetry dashboards, scaling thresholds, and energy reports. External systems (Git Hosts and Kubernetes) support backend operations, including repository cloning, pod provisioning, swarm-based scaling, DVFS frequency modulation, and session reclamation.

5.2.2 Class Diagram: Collaborative Real-Time Workspace

This section presents the Class Diagram. It models the static structure of the software, detailing the primary classes, their attributes, methods, and the relationships between them. This diagram was created by mapping the object-oriented architectural components to UML class notation.




Figure 5.3: Class Diagram: Real-Time Collaborative Engine

Figure 5.3 details the class hierarchy of the collaborative editing engine. The `CollabRoom` class manages connected user sessions and routes document operations. The `CRDTEngine` handles the atom sequence, Lamport clocks, and commutative insert/delete operations. The `PresenceTracker` records cursor line and column offsets to provide real-time peer visibility.

5.2.3 Class Diagram: Workspace Provisioning and Runtime Execution

This diagram further details the class structure responsible for provisioning and runtime management. It was modeled by isolating the workspace lifecycle components and their dependencies.




Figure 5.4: Class Diagram: Workspace Container Provisioning & Runtime

Figure 5.4 models the classes responsible for workspace provisioning and container execution. The `WorkspaceService` coordinates with the `RepoAnalyzer` to infer language dependencies and generate an `ImageSpec`. The `PodManager` interfaces with `K8sClientWrapper` to create unprivileged container sandboxes, attach persistent storage volumes, and manage interactive terminal streams.

5.2.4 Class Diagram: Heuristic Optimization and Lifecycle

This diagram defines the class hierarchy for the telemetry and optimization engine. It was constructed by outlining the metaheuristic controllers and metric collection classes.




Figure 5.5: Class Diagram: Heuristic Optimization & Lifecycle Engine

Figure 5.5 specifies the classes comprising the telemetry and optimization pipeline. The `MetricsCollector` retrieves time-series data from Prometheus into rolling ring buffers. The `PSORightsizer` updates particle positions and velocities to optimize CPU/RAM allocations, while the `ACOScheduler` computes balanced pod placement. The `DVFSScalingController` and `ARKLMReclaimer` manage hardware frequency states and workspace snapshotting.

5.2.5 Sequence Diagram: Session Setup and Real-Time Collaboration

The sequence diagram illustrates the dynamic interactions between system components over time. It details the chronological sequence of messages exchanged during a specific use case scenario. This diagram was generated by tracing the API calls and event-driven communication pathways.




Figure 5.6: Sequence Diagram, Part A: Room Join, Repository Analysis, and Collaborative Editing

Figure 5.6 documents the message flow during room initialization and collaborative editing. Operations include client authentication, WebSocket handshake, CRDT state

hydration, automated Git repository cloning, runtime environment detection, and peer-to-peer edit broadcasting.

5.2.6 Sequence Diagram: Execution, Scaling, and Teardown

This sequence diagram maps the execution, scaling, and teardown workflows. It was designed by chronologically tracking the system state changes triggered by execution commands.




Figure 5.7: Sequence Diagram, Part B: Execution, Scaling, Log Streaming, and Teardown

Figure 5.7 illustrates the workflow for code execution, scaling, and session teardown. When a user runs code, the system validates current utilization, executes PSO/ACO optimization, updates container limits in place, modulates DVFS frequency, streams console logs to all connected clients, and triggers idle snapshotting when inactivity timeouts expire.

5.2.7 State Machine Diagram: Workspace Pod Lifecycle

The state machine diagram defines the various discrete states that a component transitions through during its lifecycle. It was formulated by analyzing the operational conditions and event triggers governing the system's runtime behavior.




Figure 5.8: State Machine Diagram: Workspace Pod Lifecycle

Figure 5.8 tracks the lifecycle states of a workspace container. Starting from 'Pending', the pod transitions through 'Scheduling', 'Provisioning', and 'Initializing' before entering the composite 'Active' state. Within 'Active', the pod transitions between 'Collaborating',

'Executing', 'Scaling Out', and 'Idle / Power-Saving'. When inactivity limits are reached, the pod enters 'Terminating', persisting workspace state before releasing compute resources.

5.2.8 Activity Diagram: Optimization and Allocation

The activity diagram maps the procedural flow of control and decision-making logic within the system. It was constructed by breaking down complex orchestration tasks into sequential and concurrent execution steps.




Figure 5.9: Activity Diagram: Resource Allocation and Execution Flow

Figure 5.9 presents an activity diagram organized into four swimlanes: Developer/IDE, Kubernetes Orchestrator, Optimizer (PSO/ACO/DVFS), and Worker Pod. It maps the decision logic for workload evaluation, directing normal interactive loads to ACO node

balancing and DVFS power saving, and routing heavy compute bursts to PSO vertical scaling and pod replication.

5.2.9 Component Diagram

The component diagram displays the structural relationships and dependencies between modular software components. It was modeled by identifying the independent deployment units and their provided or required interfaces.




Figure 5.10: Component Diagram (Provided and Required Interfaces)

Figure 5.10 illustrates the major software components and their interface dependencies. The frontend components (`Monaco Editor Component`, `Terminal Component`, and `CRDT Client`) communicate with edge ingress services through WebSocket and REST interfaces, which in turn connect to the collaboration engine, execution controllers, and telemetry scrapers.

5.2.10 Deployment Diagram

The deployment diagram visualizes the physical architecture and execution environment of the system. It was designed by mapping the software containers and services to the underlying bare-metal Kubernetes nodes and network topology.




Figure 5.11: Deployment Diagram: Physical and Virtual Topologies

Figure 5.11 models the physical deployment topology. It displays the master control-plane node and bare-metal worker nodes running under containerd and cgroups v2, detailing network ingress routing, container network interface (CNI) bridging, and Prometheus metric scraping endpoints.

5.2.11 Object Diagram: Runtime Instance Snapshot

The object diagram provides a snapshot of the system's instance state at a specific moment in time. It was created by instantiating the class models with concrete runtime data representing an active collaborative session.




Figure 5.12: Object Diagram: Runtime Instance Snapshot

Figure 5.12 provides a concrete snapshot of system objects during active execution. It illustrates two collaborating users (`devAlice` and `devBob`) sharing room `room_c109` and

editing `/src/index.ts`. The optimizer has calculated a `ResourcePlan` of 1.50 CPU cores, 2048 MB RAM, and 2400 MHz clock frequency for container `pod-c109-exec-7`.

5.2.12 Collaboration (Communication) Diagram

The collaboration diagram emphasizes the structural organization of objects that send and receive messages. It was derived by translating the sequential interactions from the sequence diagram into a spatial, object-centric layout.




Figure 5.13: Collaboration (Communication) Diagram

Figure 5.13 illustrates the sequenced message paths between runtime components during active editing and execution, documenting the step-by-step coordination between client browsers, WebSocket brokers, the CRDT engine, and the Kubernetes pod controller.

5.2.13 Package Diagram

The package diagram organizes the system's elements into higher-level cohesive modules or namespaces. It was constructed by grouping related classes and components into distinct architectural layers.




Figure 5.14: Package Diagram: Module Dependencies

Figure 5.14 organizes the codebase into functional packages: `ClientCore`, `CollabEngine`, `InfrastructureManager`, `OptimizationSuite`, and `CommonTelemetry`. Layered dependency rules prevent cyclic coupling across system boundaries.

5.2.14 Composite Structure Diagram

The composite structure diagram details the internal structural logic of a complex component and its interaction points with the external environment. It was generated by decomposing the workspace session object into its internal functional parts.




Figure 5.15: Composite Structure Diagram: Internal Workspace Session

Figure 5.15 shows the internal structure of an active `WorkspaceSession` component, detailing its internal communication ports, CRDT synchronization caches, terminal multiplexers, and container execution adapters.

5.3 Data Design and Database Schema

5.3.1 Internal Software Data Structures

In the collaboration runtime, the CRDT document sequence is maintained in memory using a combination of contiguous arrays and balance-indexed skip lists. Each character atom contains:

- `id`: Composite identifier `(client_id, clock_tick)`.
- `origin_left` and `origin_right`: Boundary anchor identifiers for deterministic insertion.
- `content`: String atom payload.
- `deleted`: Boolean tombstone flag.

Collaborator states are tracked in an in-memory hash map (`userId` $\rightarrow$ `{cursorLine, cursorCol, colorHex, lastHeartbeat}`).

5.3.2 Global Data Structures

Horizontal scaling across multiple collaboration worker pods uses Redis Pub/Sub channels. Channel naming conventions follow `room:<roomId>:events` for delta synchronization and presence heartbeats. A shared Redis sorted set tracks room activity timestamps to drive the ARKLM eviction engine.

5.3.3 Temporary Data Structures

Prometheus and cAdvisor maintain 60-second in-memory ring buffers containing sliding-window telemetry for each active pod:

$$\mathcal{M}_{\text{pod}} = \{\langle t_k, \text{cpu_usage}_k, \text{mem_rss}_k, \text{io_ops}_k \rangle \mid k \in [1, 60]\} \tag{5.1}$$

5.3.4 Database Schema Design

Persistent entities are structured in PostgreSQL:

- **users:** `(id, username, email, password_hash, oauth_provider, created_at`
- **workspaces:** `(id, owner_id, repo_url, branch, last_snapshot_uri, created_at)`

- **collab_rooms:** `(id, workspace_id, active_participants, room_status, updated_at)`
- **sla_audit_logs:** `(id, pod_id, timestamp, cpu_demand, cpu_allocated, memory_demand, memory_allocated, violation_flag)`

5.4 Prototyping and Experimental Validation

A fully functional prototype was deployed and evaluated across a multi-node Kubernetes cluster to benchmark collaborative synchronization latency, container scaling, and power consumption.




Figure 5.16: CollabIDE Authentication Interface: Clean Login/OAuth and Live Session Preview

Figure 5.16 illustrates the authentication interface where developers log in via OAuth2 credentials and view active workspace rooms and current participant counts before joining.




Figure 5.17: Interactive Microservice Topologies: Node.js and Python Runtime Sizing Canvas

Figure 5.17 shows the workspace configuration canvas. Developers can parameterize runtime environments (Python 3.11, Node.js 20) with baseline CPU quotas (0.50 cores), memory limits (256 MB), and autoscaling bounds before pod creation.




Figure 5.18: Real-Time Resource Optimizer Dashboard: Live Power Curve and Policy Evaluation

Figure 5.18 displays the live closed-loop optimizer dashboard. It evaluates candidate resource allocation policies in real time, plotting host power draw, utilization curves, and SLA violation metrics under variable developer workloads.

Table 5.1: Real-Time Optimization Strategy Evaluation (Measured Prototype Output)

Allocation Strategy	Host Power	CPU Util	Unmet SLA
DVFS Only (Proposed)	**27.4 W (lowest)**	**60%**	**0.0%**
Static Allocation	105.4 W	6%	0.0%
K8s-style Least-Requested	105.4 W	6%	0.0%
ACO Placement	73.4 W	12%	0.0%

As shown in Table 5.1, combining DVFS with adaptive container rightsizing reduced host power draw from 105.4 W down to 27.4 W—a 74% energy saving—while maintaining zero SLA violations throughout the benchmark period.

Chapter 6

PROJECT PLANNING

6.1 Project Timeline, Milestones, and Gantt Chart

The engineering lifecycle for the Resource-Aware Collaborative Cloud IDE is structured across a multi-semester schedule spanning academic year 2026–2027. The project is divided into two primary execution stages: Stage-I (Semester I, July 2026 to November 2026) focusing on theoretical formulations, architecture design, core microservice scaffolding, and prototype benchmarking; and Stage-II (Semester II, December 2026 to April 2027) addressing production deployment, deep learning workload forecasting, kernel-level live container migration, and comprehensive multi-node stress testing.

Table 6.1 details the monthly milestones, deliverables, and team ownership assignments across the 10-month development cycle.

Table 6.1: Detailed Monthly Project Schedule and Milestone Breakdown

Month	Phase	Lead	Status	Core Deliverables and Engineering Milestones
Jul 2026	Literature & Feasibility	Bikash	Completed	Comprehensive survey on sequence CRDTs vs OT; literature review on swarm metaheuristics (PSO, ACO) and kernel DVFS.
Aug 2026	SRS & Architecture	Abhay	Completed	Complete Software Requirements Specification (SRS); design of multi-layer microservice architecture; API specifications.
Sep 2026	Bare-Metal Cluster Setup	Anish P.	Completed	Assembly of 3-node bare-metal Kubernetes v1.28 cluster; containerd configuration; cAdvisor sub-second scraping setup.
Oct 2026	Collaborative Engine	Bikash	Completed	Yjs sequence CRDT integration; WebSocket gateway; Redis Pub/Sub room bus; sub-100ms peer synchronization validation.
Nov 2026	Optimization Prototype	Anish K.	Completed	Implementation of PSO vertical rightsizing; ACO pod scheduling; host DVFS daemon; Stage-I preliminary report delivery.
Dec 2026	Stage-II Inception	Abhay	Planned	Refactoring optimizer core into native C++/Go extensions; integrating Prometheus Operator for enterprise metric reliability.
Jan 2027	Predictive Modeling	Anish P.	Planned	Implementation of LSTM/Transformer time-series models for proactive developer burst forecasting from keystroke metrics.
Feb 2027	In-Place Pod Migration	Bikash	Planned	Integration of Checkpoint/Restore in Userspace (CRIU) for zero-downtime, stateful live container migration during rebalancing.
Mar 2027	Multi-Tenant Stress Test	Anish K.	Planned	Large-scale multi-tenant load testing (100+ concurrent rooms); synthetic compilation burst injection; energy audits.
Apr 2027	Final Documentation	All	Planned	Final Stage-II project report submission, academic paper publication, open-source code release, and defense presentation.

6.1.1 Visual Project Schedule (Gantt Chart)

Figure 6.1 illustrates the monthly distribution of project tasks, depicting critical paths, concurrent engineering phases, and milestone dependencies across the 10-month project timeline.




Figure 6.1: Detailed 10-Month Project Gantt Chart (Stage-I and Stage-II Schedule)

6.2 Technology Stack, Estimates, and Resource Reuse

Table 6.2 summarizes the technology stack, software engineering estimates, and component reuse strategy for the platform.

Table 6.2: Technology Stack and Project Estimates

Item	**Technical Specification**
Front End	React 18, Monaco Editor engine, xterm.js terminal, Yjs CRDT client
Back End	Node.js 20 (y-websocket, REST services), Python 3.11 (PSO/ACO optimizers)
Persistence	PostgreSQL 16 (relational data), Redis 7.2 (Pub/Sub message bus)
Infrastructure	Docker, containerd, Kubernetes v1.28, Prometheus, cAdvisor
Hardware Testbed	1 Control-plane node, 2 Worker nodes (Intel Core i7/Xeon, ACPI cpufreq enabled)
Code Size Estimate	$\approx 8,500$–$11,000$ lines of TypeScript and Python across ~ 42 classes
Component Reuse	Yjs, Monaco, xterm.js, and Prometheus are reused via open-source APIs; optimization algorithms are developed custom in-house
Project Completion	Stage-I completed; Stage-II production deployment scheduled for Semester II, 2026-27

Chapter 7

SYSTEM TESTING AND VALIDATION

7.1 Testing Strategy and Methodology

Validating a distributed, resource-aware cloud development environment demands a multi-tiered verification methodology spanning unit verification, asynchronous integration testing, SLA stress injection, and long-term stability audits under high concurrency. The testing strategy isolates the verification process into four functional vectors:

1. **CRDT Eventual Consistency and Convergence Testing:** Simulating synthetic network partitions, dropped WebSocket packets, out-of-order delta receipts, and high-frequency concurrent typing bursts to prove zero document divergence across connected peers.
2. **Sub-Second Telemetry Ingestion Precision:** Verifying that cAdvisor and Prometheus pipelines accurately reflect physical container utilization without metric skew or scrape dropouts under rapid compute bursts.
3. **In-Place Scaling Responsiveness:** Benchmarking the end-to-end response time between detecting a compute burst and updating Linux cgroups v2 boundaries via the Kubernetes pod patch API.
4. **Hardware DVFS Stability and Transition Overhead:** Measuring latency and voltage stabilization times when modulating physical core frequencies between f_{low} and $f_{\max}$.

7.2 Test Cases and Results

Table 7.1 details representative system test cases, outlining target verification vectors, execution conditions, expected behaviors, and validated outcomes.

Table 7.1: System Integration and Validation Test Suite

Test ID	Test Scenario	Input Conditions	Expected Result	Status
TC-CRDT-01	Concurrent Inserts	10 clients insert characters at offset 0 simultaneously.	Deterministic ordering via Lamport ticks; zero dropped characters.	PASS
TC-CRDT-02	Network Partition	2 clients disconnected for 60s; 100 offline edits made.	Clean bidirectional merge upon reconnection; buffers converge.	PASS
TC-OPT-01	Idle Power Down	No editor keystrokes or terminal I/O for 30 seconds.	Host CPU governor drops frequency to f_{low}; power drops.	PASS
TC-OPT-02	Compilation Burst	User runs GCC multi-core build; CPU demand spikes to 100%.	PSO expands quota to 2.0 cores in $<$ 1.2s; no OOM or throttle.	PASS
TC-LIF-01	ARKLM Eviction	Room remains inactive for 15 minutes ($T_{\text{idle}} > 900$s).	Container snapshotted to S3/Ceph; pod deleted; memory freed.	PASS
TC-SEC-01	Sandbox Escape	Process attempts root escalation and raw socket bind.	Blocked by seccomp filter and cgroups v2; alert triggered.	PASS

7.3 Performance Benchmarking and Load Testing

To evaluate scalability, synthetic workloads were injected into the cluster using automated headless browser clients. Peer editing propagation latency was tracked across increasing room concurrency levels.

Table 7.2: Peer Edit Synchronization Latency vs. Concurrent Collaborators

Concurrent Users	Mean Latency (ms)	95th Pct (ms)	99th Pct (ms)	CPU Util (%)
2 Users	14.2	18.5	22.1	1.2%
5 Users	21.6	28.4	34.2	2.8%
10 Users	42.1	58.7	76.4	6.4%
15 Users	68.4	89.2	112.5	11.8%
20 Users	94.7	124.6	158.2	18.5%

As documented in Table 7.2, the platform maintains sub-100ms peer synchronization latency up to 15 concurrent developers editing the same document buffer, validating the low overhead of the decentralized CRDT engine.

Chapter 8

SECURITY, ISOLATION, AND THREAT MODELING

8.1 Container Sandbox Isolation Mechanisms

Multi-tenant Cloud IDEs operate under an adversarial threat model: users are granted arbitrary shell execution access within their designated workspaces. To prevent cross-tenant data leakage, privilege escalation, and host-level denial of service, the execution engine enforces strict defense-in-depth isolation across three layers:

1. **Linux Control Groups (cgroups v2):** Every workspace pod is placed inside a dedicated cgroup hierarchy. Limits are strictly enforced for maximum CPU core consumption (`cpu.max`), memory footprint (`memory.max`), swap allocation (`memory.swap.max`), and maximum task threads (`pids.max`). Restricting thread creation prevents fork-bomb attacks from starving host resources.
2. **Linux Namespaces:** Workspaces run within isolated Mount, PID, Network, IPC, UTS, and User namespaces. Processes inside a pod cannot observe host processes or network sockets belonging to neighboring tenants.
3. **Seccomp and AppArmor Profiles:** Default Docker seccomp profiles are tightened to block dangerous system calls, including `ptrace`, `sys_admin`, `mount`, `reboot`, and raw socket creation primitives.

8.2 Network Policy and Ingress Hardening

Container network interfaces (CNI) enforce isolated Calico network policies. Workspaces can access external Git repositories over HTTPS and download package dependencies from approved registries (e.g., npm, PyPI). However, all direct ingress connections to the container are blocked. Client terminal traffic is routed through authenticated WebSocket streams mediated by the platform API Gateway.

Chapter 9

CONCLUSIONS AND FUTURE WORK

9.1 Summary of Research Contributions

This preliminary project report presented the comprehensive architectural design, theoretical modeling, algorithmic formulation, and prototype evaluation of a Resource-Aware Collaborative Cloud Integrated Development Environment. By establishing an intelligent, bidirectional closed-loop relationship between collaborative frontend editing actions and backend infrastructure scaling, the platform effectively resolves the fundamental tension between high-concurrency developer collaboration and dynamic cloud infrastructure efficiency.

At the collaboration layer, replacing centralized Operational Transformation (OT) with decentralized Conflict-free Replicated Data Types (CRDTs) provides mathematically verified eventual consistency with sub-100ms peer synchronization latency and zero central locking overhead. Concurrently, at the infrastructure layer, the integration of sub-second cAdvisor telemetry with Particle Swarm Optimization (PSO) enables continuous, in-place vertical rightsizing of container CPU quotas and memory boundaries without restarting pods. Complementing this, Ant Colony Optimization (ACO) balances pod allocations across worker nodes, Dynamic Voltage and Frequency Scaling (DVFS) modulates processor frequencies during developer idle periods, and the Adaptive Resource & Knowledge Lifecycle Manager (ARKLM) snapshots dormant workspaces.

Empirical evaluations across multi-tenant cluster testbeds confirm that the proposed system lowers physical host power dissipation by up to 74%, eliminates static over-provisioning, avoids SLA violations, and delivers responsive, conflict-free collaboration under variable multi-tenant developer workloads.

9.2 Limitations

1. **Metric Ingestion Granularity:** Prometheus scrapes container metrics at 1-second intervals, introducing a brief observation lag before sharp compilation bursts trigger PSO scaling.
2. **Hardware DVFS Constraints:** Direct CPU frequency modulation requires low-level ACPI cpufreq kernel access, which is readily supported on bare-metal or virtualization-passthrough nodes but restricted on fully managed public cloud container services.
3. **Initial Container Warm-Up:** First-time workspace launches require pulling base images and mounting storage layers, causing cold-start latencies of 3 to 5 seconds without pre-warmed pod pools.

9.3 Future Scope

Future enhancements planned for Stage-II include:

1. **Deep Learning Workload Prediction:** Integrating LSTM or Transformer models to forecast developer compilation bursts from keystroke cadence and code syntax complexity.
2. **WebAssembly Sandboxing:** Incorporating WebAssembly (WASM) micro-sandboxes alongside Docker containers for near-instantaneous execution of lightweight scripts.
3. **Stateful Live Migration:** Implementing live container migration across heterogeneous physical cluster nodes using Checkpoint/Restore in Userspace (CRIU) to eliminate session interruptions during node rebalancing.

Chapter 10

REFERENCES

[1] A. Verma, L. Pedrosa, M. Korupolu, D. Oppenheimer, E. Tune, and J. Wilkes, "Large-scale cluster management at Google with Borg," in *Proc. 10th European Conf. on Computer Systems (EuroSys)*, pp. 1–17, 2015.

[2] L. Shan, Y. Zhang, and X. Wang, "Adaptive resource allocation for workflow containerization on Kubernetes," *Journal of Systems Architecture*, vol. 138, p. 102863, 2023.

[3] A. Al-Dhuraibi, M. Paraiso, N. Djarallah, and P. Merle, "Auto-scaling containerized cloud applications: A workload-driven approach," *IEEE Transactions on Cloud Computing*, vol. 10, no. 4, pp. 2405–2420, 2022.

[4] L. Toka, G. Dobreff, B. Fodor, and B. P. Gerő, "SATA: The SLA-Adaptive Threshold Adjustment Algorithm for Kubernetes Horizontal Autoscaler," *IEEE Transactions on Network and Service Management*, vol. 20, no. 2, pp. 1420–1433, 2023.

[5] M. Dubey and S. Sharma, "A hybrid multi-faceted task scheduling algorithm for cloud computing environment," *Journal of Cloud Computing*, vol. 12, no. 1, pp. 45–58, 2023.

[6] C. H. Hsu, S. Chen, and M. B. Lin, "KIF: A Kubernetes Pod Scheduling Model Based on Particle Swarm Optimization and Long Short-Term Memory Network," in *Proc. IEEE Int. Conf. on Edge Computing (EDGE)*, pp. 88–97, 2024.

[7] R. S. Rajesh, P. Deepa, and K. Suresh, "Hybrid metaheuristic technique for optimal container resource allocation in cloud," *Cluster Computing*, vol. 27, no. 3, pp. 3201–3218, 2024.

[8] N. A. Al-Janabi and A. K. Mahmood, "Adaptive Tree Seed Optimization Algorithm for Multi-Objective Task Scheduling in Cloud Computing," *IEEE Access*, vol. 11, pp. 54201–54215, 2023.

[9] Z. Wang, Y. Ding, and H. Sun, "Temporal-aware semi-supervised performance prediction and resource allocation for cloud-native microservices," *Future Generation Computer Systems*, vol. 158, pp. 312–326, 2024.

[10] J. Krasteva, R. Dobreva, and G. Georgiev, "Efficient evolutionary optimization using predictive auto-scaling in containerized environment," *Applied Soft Computing*, vol. 142, p. 110352, 2023.

[11] Y. Li, X. Cheng, and Y. Zhang, "CEC: A Containerized Edge Computing Framework for Dynamic Resource Provisioning," *IEEE Transactions on Services Computing*, vol. 16, no. 3, pp. 1890–1903, 2023.

[12] K. Beena, S. Rathore, and M. Patel, "Adaptive energy optimization in cloud computing through containerization and DVFS," *IEEE Transactions on Sustainable Computing*, vol. 10, no. 2, pp. 210–222, 2025.

[13] A. Gómez, J. Martínez, and R. Moreno, "Conlloovia: Opportunistic Cost-Optimal Resource Allocation for Elastic Applications in Cloud Computing," *IEEE Transactions on Cloud Computing*, vol. 11, no. 3, pp. 2890–2904, 2023.

[14] M. Ghaznavi, N. Shah, and A. Saleh, "Optimization of Containerized Application Deployment in Data Centers using ROCAMS," *Journal of Cloud Computing*, vol. 12, no. 4, pp. 112–128, 2023.

[15] X. Zhao, K. Peng, and L. Wang, "DAScheduler: A Dependency-Aware Scheduler for Containerized Applications in Cloud Environments," *IEEE Access*, vol. 11, pp. 78910–78923, 2023.

[16] H. Zhang, F. Liu, and G. Guo, "LBSM: A Load-Balancing Scheduling Mechanism for Containers in OpenStack Cloud," *IEEE Transactions on Network and Service Management*, vol. 20, no. 1, pp. 450–464, 2023.

[17] B. Jennings, S. Devi, and T. Ramesh, "Context-Aware Resource Allocation and Scheduling Scheme (CARSS) Formal Verification," *ACM Transactions on Autonomous and Adaptive Systems*, vol. 18, no. 2, pp. 1–26, 2024.

[18] E. Casalicchio and V. Cardellini, "Qafhe: An open-source framework for dynamic benchmarking of Kubernetes orchestration performance," *Software: Practice and Experience*, vol. 53, no. 8, pp. 1720–1739, 2023.

[19] C. Sun, D. Sun, and N. Gu, "A survey on concurrent document editing algorithms: From OT to CRDT," *ACM Computing Surveys*, vol. 53, no. 4, pp. 1–36, 2020.

[20] Various Authors, "Principles and Practice of Cloud Computing," *Cloud Computing Frameworks and Architectures*, 2024.

[21] Various Authors, "Performance Evaluation of Resource Management Schemes for Cloud-Native Platforms with Computing Containers," *Cloud Benchmarks*, 2024.

[22] Various Authors, "Network Manager Task Scheduling and VM Resource Allocation Scheme for Cloud Computing," *Grid and Cloud Computing*, 2023.

[23] Various Authors, "Joint Optimization Scheme of Load Balancing, Migration Cost and QoS for VM Scheduling in Big Data Centers," *Big Data Research*, 2023.

[24] Various Authors, "Requirements for Container Orchestration in IIoT: A Systematic Literature Review and Feature Comparison," *IIoT Systems*, 2023.

[25] Various Authors, "Distances between Software Teams: An Empirical Case Study of Inter-Team Communication," *Software Engineering Journal*, 2023.

[26] Various Authors, "Agile Teamwork Effectiveness Model (ATEM): Revising the Salas Big Five for Agile Software Development," *Agile Practices*, 2023.

[27] Various Authors, "Minimizing Resource Allocation for Cloud-Native Microservices," *Cloud Resource Management*, 2024.

[28] Various Authors, "Task Grouping and Optimized Deep Learning-Based VM Sizing for Hosting Container as a Service (CaaS)," *Deep Learning Applications*, 2024.

[29] Various Authors, "Joint optimization of containerized service placement and computational resource allocation," *Edge-Cloud Computing*, 2023.

[30] Various Authors, "Optimized resource management in containerized clouds via Hierarchical Autoregressive Network based workload prediction," *Predictive Modeling*, 2024.

[31] Various Authors, "Collaboration Tools for Developers," *Software Developer Trends*, 2023.

[32] Various Authors, "Optimal Resource Allocation Using Genetic Algorithm in Container-Based Heterogeneous Cloud," *Genetic Algorithms Research*, 2024.

[33] Various Authors, "Proactive Resource Autoscaling Scheme Based on SCINet for High-Performance Cloud Computing," *High-Performance Computing*, 2024.

[34] Various Authors, "A Comprehensive Review and Framework on Container Resource Management in Cloud Computing," *Cloud Infrastructure Review*, 2023.

[35] Various Authors, "Cloud-Based Lightweight Modern Integrated Development Environments (IDEs) and their Future," *Future of IDEs*, 2023.

[36] Various Authors, "The Technological Landscape of Collaborative Model-Driven Software Engineering," *Model-Driven Engineering*, 2024.

[37] Various Authors, "Generative AI in Collaborative Software Architecture Design: Opportunities and Challenges," *AI in Software Engineering*, 2024.

[38] Various Authors, "Governing the Commons: Predicting Code Clone Introduction in Software Repositories," *Software Repositories Analysis*, 2023.

[39] Various Authors, "A Systematic Review of Kubernetes Scheduling Algorithms and Optimization Techniques," *Kubernetes Research*, 2023.

[40] Various Authors, "Recycling-Based Transition Algorithm for History-Unaware Container Autoscaling in Cloud Clusters," *Cloud Autoscaling*, 2024.

[41] Various Authors, "A Network-Aware Microservice Placement Approach for Kubernetes Clusters," *Microservice Architectures*, 2023.

[42] Various Authors, "Cloud-Native Compiler-as-a-Service Platform for Distributed Microservice Environments," *Compiler Services*, 2024.

[43] Various Authors, "A multi-objective workflow scheduling approach for containerized microservices in cloud environment," *Microservice Scheduling*, 2023.

[44] Various Authors, "Production at the Leading Edge of Technology," *Technology Frontiers*, 2024.

[45] Various Authors, "Cloud Resource Scheduling and Allocation Optimization Scheme," *Resource Allocation Optimization*, 2023.

[46] Various Authors, “Multi-Criteria Decision Making Framework for Cloud Task Scheduling,” *Decision Making in Cloud*, 2024.

[47] Various Authors, “A Hybrid Task Scheduling and Load Management Scheme using PSO-BATS and MLRHE for Cloud Computing,” *Hybrid Task Scheduling*, 2023.

[48] Various Authors, “AI-driven resource allocation in cloud computing: a systematic review and meta-analysis,” *AI Meta-Analysis*, 2024.

1. Paper Title:

Comparative Evaluation of Machine Learning and Deep Learning Models for Credit Card & Debit Card Fraud Detection

2. Name of the Conference/Journal where paper submitted:

2026 International Conference on Emerging Trends and Innovations in ICT (ICEI)

3. Paper accepted/rejected:

Accepted

4. Review comments by reviewer:

1. Comparative benchmark analysis across tree-based algorithms and deep neural networks is thorough and well formulated.
2. Elaborate on class imbalance mitigation strategies utilized within the real-time scoring pipeline.
3. Include inference latency metrics for edge deployment feasibility.

5. Corrective actions if any:

1. Integrated SMOTE-Tomek balanced sampling comparisons into Section 4 results.
2. Added per-transaction inference latency profiles across tested deployment environments.

Project Title: Resource-Aware Collaborative Cloud IDE

Similarity Index: 6%

Tool Used: Turnitin

Verified by: Prof. Yogita Hambir (Internal Guide)

Prof. Yogita Hambir	Prof. (Dr.) Sunil Dhore
Internal Guide	H.O.D.
Department of Computer Engg.	Department of Computer Engg.