

Common API Function Signature:

The following signature is common for most of all functions. If any other, then it mentioned in function description itself.

URL: [FQDN]:[PORT]/endpoint/

For ex: <https://myapi.com/api/>

URL	/methodName
Method	POST
Request	{ "param1": "value1", "param2": "value2" }
Response	{ "param1": "value1", "param2": "value2" }
HTTP Status	200 (Body is not empty)
Request/Response encoding	UTF-8
Validation Notes	Validation notes if any

SAY HELLO DEFINITION:

URL	/endpointurl
Method	POST
Request	{ "dvcSrNo": "string", "dvcTime": "yyyy-MM-ddHH:mm:ss +GMT" }
Response	{ "status": 0/1 }
HTTP Status	200 (Body is not empty)
Request/Response encoding	UTF-8
Validation Notes	Status is 0 if error and 1 if success

SAY HELLO EXAMPLE:

URL	/sayhello
Method	POST
Request	{ "dvcSrNo": "911573950381867", "dvcTime": "2018-02-27 09:00:00 +05:30:00" }
Response	{ "status": 1 }
HTTP Status	200 (Body is not empty)
Request/Response encoding	UTF-8
Validation Notes	Status is 0 if error and 1 if success

TRANSACTION DATA DEFINITION:

URL	/endpointurl
Method	POST
Request	<pre>{ "trans": [{ "txnId": "Big Integer", "dvclId": "integer", "dvclIP": "Device IPv4/IPv6 Address", "punchId": "integer", "txnDateTime": "yyyy-MM-dd HH:mm:ss", "mode": "IN/OUT/DEFAULT" }, { "txnId": "Big Integer", "dvclId": "integer", "dvclIP": "Device IPv4/IPv6 Address", "punchId": "integer", "txnDateTime": "yyyy-MM-dd HH:mm:ss", "mode": "IN/OUT/DEFAULT" }] }</pre>
Response	<pre>{ "transStatus": [{ "txnId": "Sameas 'txnId' of Request Transaction Part", "status": 0/1 }, { "txnId": "Sameas 'txnId' of Request Transaction Part", "status": 0/1 }] }</pre>
HTTP Status	200 (Body is not empty)
Request/Response encoding	UTF-8
Validation Notes	Status is 0 if error and 1 if success

TRANSACTION DATA EXAMPLE

URL	/transaction
Method	POST
Request	<pre>{ "trans": [{ "txnId":21, "dvclId":1, "dvclP":"192.168.1.1", "punchId":1000, "txnDateTime":"2018-05-11 18:05:36", "mode":"IN" }, { "txnId":22, "dvclId":1, "dvclP":"192.168.1.1", "punchId":1001, "txnDateTime":"2018-05-11 18:05:52", "mode":"IN" }] }</pre>
Response	<pre>{ "transStatus": [{ "txnId":21, "status":1 }, { "txnId":22, "status":1 }] }</pre>
HTTP Status	200 (Body is not empty)
Request/Response encoding	UTF-8
Validation Notes	Status is 0 if error and 1 if success