

Google Hotel Connectivity Flow

1. Push Hotel Listing

- Tujuan : untuk push data hotel general
- Trigger :
 - o Manual button di extranet
- Query :

```
SELECT
    th.`code` as "id",
    th.`name` as "name",
    th.street_address as "full address",
    th.region as "province",
    th.area as "city",
    th.zip_code as "postal code",
    th.latitude,
    th.longitude,
    th.phone as "phone type=main",
    th.wa_number as "phone type=mobile",
    mpc.category_name as "category",
    th.description as "listing description",
    th.web_link as "attributes > website",
    CONCAT(
        "https://fullbook-crm.s3.ap-southeast-1.amazonaws.com/public/",
        thi.filename
    ) as "image_url"
FROM
    tb_hotel th
    LEFT JOIN ms_brand mb on th.property_brand = mb.id
    LEFT JOIN ms_property_category mpc on th.property_category =
mpc.id
    LEFT JOIN tb_hotel_image thi on th.id = thi.hotel_id
    and thi.type = 1
    and thi.main_image = 1
```

```
WHERE  
    th.`status` = 1
```

2. Push Update ARI (Availability, Rate & Inventory)

a. Transaction

- Tujuan : untuk update data room type (id, name, capacity) dan rate plan (id, name, policy)
- Trigger :
 - o Manual button dari extranet
 - o Ketika ada perubahan data secara manual di extranet
- Query :

```
SELECT  
    th.code as "propertyID",  
    rt.id as "roomID",  
    rt.name as "room name",  
    rt.guest as "capacity",  
    CONCAT(  
        "https://fullbook-crm.s3.ap-southeast-1.amazonaws.com/public/",  
        thi.filename  
    ) as "image_url",  
    rp.id as "packageID",  
    rp.`name` as "package name",  
    rp.food as "food",  
    rp.food_desc as "food list",  
    rp.cancelation_policy as "policy"  
  
FROM tb_hotel_room_type rt  
LEFT JOIN tb_hotel th on rt.hotel_id = th.id  
LEFT JOIN tb_hotel_image thi on rt.id = thi.room_type_id AND type=1 AND  
main_image=1
```

LEFT JOIN tb_hotel_rate_plan rp on rp.room_type_id = rt.id;

b. ARI

1) Rate

- Tujuan : untuk update rate di rate plan di setiap date
- Trigger :
 - o Manual trigger dari extranet
 - o Ketika ada perubahan rate secara manual di extranet
 - o Ketika ada perubahan rate dari BNL yang berhasil di update di extranet
- Query :

```
WITH RECURSIVE date_range AS (  
    SELECT CURDATE() AS date  
    UNION ALL  
    SELECT DATE_ADD(date, INTERVAL 1 DAY)  
    FROM date_range  
    WHERE date < DATE_ADD(CURDATE(), INTERVAL 365 DAY)  
)
```

```
SELECT  
    th.code AS propertyID,  
    rt.id AS InvTypeCode,  
    rp.id AS RatePlanCode,  
        rt.guest AS capacity,  
    dr.date,  
    COALESCE(rc.rate, rp.rate) AS AmountAfterTax  
FROM tb_hotel_room_type rt  
LEFT JOIN tb_hotel th  
    ON rt.hotel_id = th.id  
LEFT JOIN tb_hotel_image thi
```

```

    ON rt.id = thi.room_type_id
    AND thi.type = 1
    AND thi.main_image = 1
LEFT JOIN tb_hotel_rate_plan rp
    ON rp.room_type_id = rt.id
CROSS JOIN date_range dr
LEFT JOIN tb_hotel_rate_custom rc
    ON rc.rate_plan_id = rp.id
    AND rc.date = dr.date
ORDER BY th.code, rt.id, rp.id, dr.date;

```

- o Rate plan dan date periode tertentu

```

WITH RECURSIVE date_range AS (
    SELECT DATE('2026-06-12') AS date
    UNION ALL
    SELECT DATE_ADD(date, INTERVAL 1 DAY)
    FROM date_range
    WHERE date < DATE('2026-12-31')
)

```

```

SELECT
    th.code AS propertyID,
    rt.id AS InvTypeCode,
    rp.id AS RatePlanCode,
    rt.guest AS capacity,
    dr.date,
    COALESCE(rc.rate, rp.rate) AS AmountAfterTax
FROM tb_hotel_room_type rt
LEFT JOIN tb_hotel th
    ON rt.hotel_id = th.id

```

```

LEFT JOIN tb_hotel_rate_plan rp
    ON rp.room_type_id = rt.id
CROSS JOIN date_range dr
LEFT JOIN tb_hotel_rate_custom rc
    ON rc.rate_plan_id = rp.id
    AND rc.date = dr.date
WHERE rp.id = 1
ORDER BY dr.date;

```

2) Inventory

- Tujuan : untuk update jumlah room yang tersedia di tanggal tertentu
- Trigger :
 - o Manual trigger dari extranet
 - o Ketika ada perubahan inventory (room qty) secara manual di extranet
 - o Ketika ada perubahan inventory (room qty) dari BNL yang berhasil di update di extranet
- Query :
 - o 1 tahun data

```

WITH RECURSIVE date_range AS (
    SELECT CURDATE() AS date
    UNION ALL
    SELECT DATE_ADD(date, INTERVAL 1 DAY)
    FROM date_range
    WHERE date < DATE_ADD(CURDATE(), INTERVAL 365 DAY)
)

```

```

SELECT
    th.code AS propertyID,
    rt.id AS InvTypeCode,
    rp.id AS RatePlanCode,

```

```

        rt.guest AS capacity,
    dr.date,
    -- COALESCE(rc.rate, rp.rate) AS AmountAfterTax,
        COALESCE(rc.room_qty, rt.room_qty) AS InvCount
FROM tb_hotel_room_type rt
LEFT JOIN tb_hotel th
    ON rt.hotel_id = th.id
LEFT JOIN tb_hotel_image thi
    ON rt.id = thi.room_type_id
    AND thi.type = 1
    AND thi.main_image = 1
LEFT JOIN tb_hotel_rate_plan rp
    ON rp.room_type_id = rt.id
CROSS JOIN date_range dr
LEFT JOIN tb_hotel_rate_custom rc
    ON rc.rate_plan_id = rp.id
    AND rc.date = dr.date
ORDER BY th.code, rt.id, rp.id, dr.date;

```

o Rate plan dan date periode tertentu

```

WITH RECURSIVE date_range AS (
    SELECT DATE('2026-06-12') AS date
    UNION ALL
    SELECT DATE_ADD(date, INTERVAL 1 DAY)
    FROM date_range
    WHERE date < DATE('2026-12-31')
)

SELECT
    th.code AS propertyID,

```

```

rt.id AS InvTypeCode,
rp.id AS RatePlanCode,
rt.guest AS capacity,
dr.date,
-- COALESCE(rc.rate, rp.rate) AS AmountAfterTax,
      COALESCE(rc.room_qty, rt.room_qty) AS InvCount
FROM tb_hotel_room_type rt
LEFT JOIN tb_hotel th
      ON rt.hotel_id = th.id
LEFT JOIN tb_hotel_rate_plan rp
      ON rp.room_type_id = rt.id
CROSS JOIN date_range dr
LEFT JOIN tb_hotel_rate_custom rc
      ON rc.rate_plan_id = rp.id
      AND rc.date = dr.date
WHERE rp.id = 1
ORDER BY dr.date;

```

3) Availability

- Tujuan :
- Trigger :
 - o Manual trigger dari extranet
 - o Ketika ada perubahan rate secara manual di extranet
 - o Ketika ada perubahan rate dari BNL yang berhasil di update di extranet
- Query :
 - o 1 tahun data

```

WITH RECURSIVE date_range AS (
  SELECT CURDATE() AS date
  UNION ALL
  SELECT DATE_ADD(date, INTERVAL 1 DAY)

```

```

FROM date_range
WHERE date < DATE_ADD(CURDATE(), INTERVAL 365 DAY)
)

SELECT
    th.code AS propertyID,
    rt.id AS InvTypeCode,
    rp.id AS RatePlanCode,
        rt.guest AS capacity,
    dr.date,
        IF(COALESCE(rc.stop_sell, 0)=0, "Open", "Close") as
RestrictionMaster,
        IF(COALESCE(rc.cta, 0)=0, "Open", "Close") as RestrictionArrival,
        IF(COALESCE(rc.ctd, 0)=0, "Open", "Close") as
RestrictionDeparture,
        COALESCE(rc.min_stay, rp.min_night) as SetMinLOS
FROM tb_hotel_room_type rt
LEFT JOIN tb_hotel th
    ON rt.hotel_id = th.id
LEFT JOIN tb_hotel_image thi
    ON rt.id = thi.room_type_id
    AND thi.type = 1
    AND thi.main_image = 1
LEFT JOIN tb_hotel_rate_plan rp
    ON rp.room_type_id = rt.id
CROSS JOIN date_range dr
LEFT JOIN tb_hotel_rate_custom rc
    ON rc.rate_plan_id = rp.id
    AND rc.date = dr.date

```


ORDER BY th.code, rt.id, rp.id, dr.date;

o Rate plan dan date periode tertentu

WITH RECURSIVE date_range AS (

SELECT DATE('2026-06-12') AS date

UNION ALL

SELECT DATE_ADD(date, INTERVAL 1 DAY)

FROM date_range

WHERE date < DATE('2026-12-31')

)

SELECT

th.code AS propertyID,

rt.id AS InvTypeCode,

rp.id AS RatePlanCode,

rt.guest AS capacity,

dr.date,

IF(COALESCE(rc.stop_sell, 0)=0, "Open", "Close") as

RestrictionMaster,

IF(COALESCE(rc.cta, 0)=0, "Open", "Close") as RestrictionArrival,

IF(COALESCE(rc.ctd, 0)=0, "Open", "Close") as

RestrictionDeparture,

COALESCE(rc.min_stay, rp.min_night) as SetMinLOS

FROM tb_hotel_room_type rt

LEFT JOIN tb_hotel th

ON rt.hotel_id = th.id

LEFT JOIN tb_hotel_rate_plan rp

ON rp.room_type_id = rt.id

CROSS JOIN date_range dr

LEFT JOIN tb_hotel_rate_custom rc

```

        ON rc.rate_plan_id = rp.id
        AND rc.date = dr.date
    WHERE rp.id = 1
    ORDER BY dr.date;

```

3. Logging

Log yang diperlukan :

- 1) Log Success
- 2) Log Failed

Data yang disimpan :

- 1) Timestamp
- 2) Endpoint
- 3) Metadata Request
- 4) Metadata Response

4. Database

- 1) tb_hotel

```

-- -----
-- Table structure for tb_hotel
-- -----
DROP TABLE IF EXISTS `tb_hotel`;
CREATE TABLE `tb_hotel` (
  `id` int NOT NULL AUTO_INCREMENT,
  `property_category` int NOT NULL,
  `property_brand` int NULL DEFAULT NULL,
  `role` int NOT NULL COMMENT '1 = operator ; 2 = hotel',
  `code` varchar(100) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT NULL,
  `name` varchar(100) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT NULL,
  `status` int NOT NULL DEFAULT 0 COMMENT '0 = Draft, 1 = Live',
  `be_comission` decimal(4, 2) NULL DEFAULT 0.00,
  `be_pay_at_hotel` int NOT NULL COMMENT '0=off/disable, 1=on/active',
  `region` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT NULL,
  `area` varchar(100) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT NULL,
  `street_address` text CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT NULL,
  `zip_code` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NULL
  DEFAULT NULL,
  `hotel_star` int NULL DEFAULT NULL,

```

```

`phone` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NULL
DEFAULT NULL,
`wa_number` bigint NULL DEFAULT NULL,
`email_hotel` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NULL
DEFAULT NULL,
`email_quota_month` int NOT NULL,
`email_send_month` int NOT NULL,
`precheckin_send_mail` int NOT NULL COMMENT '0 = not send mail, 1 = send mail',
`checkin_send_mail` int NOT NULL COMMENT '0 = not active , 1 = active',
`checkout_send_mail` int NOT NULL COMMENT '0 = not active , 1 = active',
`on_booking_send_email` int NULL DEFAULT NULL COMMENT '0 = not send mail, 1 =
send mail',
`on_payment_send_email` int NULL DEFAULT NULL COMMENT '0 = not send mail, 1 =
send mail',
`web_link` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NULL
DEFAULT NULL,
`fb_link` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NULL
DEFAULT NULL,
`ig_link` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NULL
DEFAULT NULL,
`tiktok_link` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NULL
DEFAULT NULL,
`yt_link` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NULL
DEFAULT NULL,
`twitter_link` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NULL
DEFAULT NULL,
`map_link` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NULL
DEFAULT NULL,
`title` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NULL
DEFAULT NULL,
`description` text CHARACTER SET latin1 COLLATE latin1_swedish_ci NULL,
`crm` int NOT NULL COMMENT '0=not user, 1=user',
`loyalty` int NOT NULL COMMENT '0=not user, 1=user',
`be` int NOT NULL COMMENT '0=not user, 1=user',
`create_user` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT
NULL,
`create_date` datetime(0) NOT NULL,
`update_user` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT
NULL,
`update_date` timestamp(0) NOT NULL DEFAULT CURRENT_TIMESTAMP(0) ON UPDATE
CURRENT_TIMESTAMP(0),
`bc_update_user` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci
NULL DEFAULT NULL COMMENT 'user update for be comission',
`bc_update_date` datetime(0) NULL DEFAULT NULL COMMENT 'date update for be
comission',
`bs_update_user` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci
NULL DEFAULT NULL COMMENT 'user update for be status',

```

```

    `bs_update_date` datetime(0) NULL DEFAULT NULL COMMENT 'date update for be
status',
    `cm_update_user` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci
NULL DEFAULT NULL COMMENT 'user update for cm connection',
    `cm_update_date` datetime(0) NULL DEFAULT NULL COMMENT 'date update for cm
connection',
    `timezone` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NULL
DEFAULT NULL,
    `gmt` int NULL DEFAULT NULL,
    `latitude` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NULL
DEFAULT NULL,
    `longitude` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NULL
DEFAULT NULL,
    PRIMARY KEY (`id`) USING BTREE,
    INDEX `code_hotel` (`code`) USING BTREE,
    INDEX `name_hotel` (`name`) USING BTREE,
    INDEX `area_hotel` (`area`) USING BTREE,
    INDEX `role_hotel` (`role`) USING BTREE,
    INDEX `category_hotel` (`property_category`) USING BTREE
) ENGINE = InnoDB AUTO_INCREMENT = 198 CHARACTER SET = latin1 COLLATE =
latin1_swedish_ci ROW_FORMAT = DYNAMIC;

```

2) ms_property_category

```

-- -----
-- Table structure for ms_property_category
-- -----
DROP TABLE IF EXISTS `ms_property_category`;
CREATE TABLE `ms_property_category` (
  `id` int NOT NULL AUTO_INCREMENT,
  `category_name` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT
NULL,
  `description` text CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT NULL,
  `create_user` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT
NULL,
  `create_date` datetime(0) NOT NULL,
  `update_user` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT
NULL,
  `update_date` timestamp(0) NOT NULL DEFAULT CURRENT_TIMESTAMP(0) ON UPDATE
CURRENT_TIMESTAMP(0),
  PRIMARY KEY (`id`) USING BTREE
) ENGINE = InnoDB AUTO_INCREMENT = 13 CHARACTER SET = latin1 COLLATE =
latin1_swedish_ci ROW_FORMAT = COMPACT;

```

3) ms_brand

```

-- -----
-- Table structure for ms_brand
-- -----
DROP TABLE IF EXISTS `ms_brand`;
CREATE TABLE `ms_brand` (
  `id` int NOT NULL AUTO_INCREMENT,
  `brand_name` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT NULL,
  `logo_image` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT NULL,
  `sort_order` int NULL DEFAULT NULL,
  `create_user` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT NULL,
  `create_date` datetime(0) NOT NULL,
  `update_user` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NULL DEFAULT NULL,
  `update_date` timestamp(0) NOT NULL DEFAULT CURRENT_TIMESTAMP(0) ON UPDATE CURRENT_TIMESTAMP(0),
  PRIMARY KEY (`id`) USING BTREE,
  UNIQUE INDEX `brand_name`(`brand_name`) USING BTREE
) ENGINE = InnoDB AUTO_INCREMENT = 11 CHARACTER SET = latin1 COLLATE = latin1_swedish_ci ROW_FORMAT = COMPACT;

```

4) tb_hotel_image

```

-- -----
-- Table structure for tb_hotel_image
-- -----
DROP TABLE IF EXISTS `tb_hotel_image`;
CREATE TABLE `tb_hotel_image` (
  `id` int NOT NULL AUTO_INCREMENT,
  `hotel_id` int NOT NULL,
  `room_type_id` int NULL DEFAULT NULL,
  `type` int NOT NULL COMMENT '0= Hotel Gallery, 1=Room Gallery',
  `main_image` int NOT NULL DEFAULT 0 COMMENT '0=not main image, 1=main image',
  `description` text CHARACTER SET latin1 COLLATE latin1_swedish_ci NULL,
  `filename` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NULL DEFAULT NULL,
  `sort_order` int NULL DEFAULT NULL,
  `create_user` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT NULL,
  `create_date` datetime(0) NOT NULL,
  `update_user` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT NULL,
  `update_date` timestamp(0) NOT NULL DEFAULT CURRENT_TIMESTAMP(0) ON UPDATE CURRENT_TIMESTAMP(0),

```

```

PRIMARY KEY (`id`) USING BTREE,
INDEX `hotel_id5` (`hotel_id`) USING BTREE,
INDEX `room_type` (`room_type_id`) USING BTREE,
CONSTRAINT `hotel_id5` FOREIGN KEY (`hotel_id`) REFERENCES `tb_hotel` (`id`) ON
DELETE CASCADE ON UPDATE CASCADE,
CONSTRAINT `room_type` FOREIGN KEY (`room_type_id`) REFERENCES
`tb_hotel_room_type` (`id`) ON DELETE CASCADE ON UPDATE CASCADE
) ENGINE = InnoDB AUTO_INCREMENT = 76 CHARACTER SET = latin1 COLLATE =
latin1_swedish_ci ROW_FORMAT = COMPACT;

```

5) tb_hotel_room_type

```

-----
-- Table structure for tb_hotel_room_type
-----
DROP TABLE IF EXISTS `tb_hotel_room_type`;
CREATE TABLE `tb_hotel_room_type` (
  `id` int NOT NULL AUTO_INCREMENT,
  `hotel_id` int NOT NULL,
  `hotel_code` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT
NULL,
  `name` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT NULL,
  `description` text CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT NULL,
  `room_qty` int NOT NULL,
  `room_available` int NOT NULL,
  `cut_off_day` int NOT NULL,
  `min_rate` float NOT NULL,
  `view` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT NULL
COMMENT 'e.g : street view, beach, pegunungan',
  `room_size` float NOT NULL COMMENT 'satuan m2',
  `smoking` int NOT NULL COMMENT '0=non smoking, 1=smoking, 2=both',
  `bathroom` int NOT NULL COMMENT '0=no-bathroom, 1=private-brathroom,
2=sharing-bathroom',
  `guest` int NOT NULL,
  `extra_guest` int NOT NULL,
  `bed_type` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NULL
DEFAULT NULL,
  `bed_qty` int NULL DEFAULT NULL,
  `status` int NOT NULL COMMENT '0=inactive(no-sell), 1=active(sell)',
  `create_user` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT
NULL,
  `create_date` datetime(0) NOT NULL,
  `update_user` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT
NULL,
  `update_date` timestamp(0) NOT NULL ON UPDATE CURRENT_TIMESTAMP(0),
PRIMARY KEY (`id`) USING BTREE,

```

```

INDEX `hotel_id8`(`hotel_id`) USING BTREE,
CONSTRAINT `hotel_id8` FOREIGN KEY (`hotel_id`) REFERENCES `tb_hotel` (`id`) ON
DELETE RESTRICT ON UPDATE CASCADE
) ENGINE = InnoDB AUTO_INCREMENT = 186 CHARACTER SET = latin1 COLLATE =
latin1_swedish_ci ROW_FORMAT = COMPACT;

```

6) tb_hotel_rate_plan

```

-- -----
-- Table structure for tb_hotel_rate_plan
-- -----
DROP TABLE IF EXISTS `tb_hotel_rate_plan`;
CREATE TABLE `tb_hotel_rate_plan` (
  `id` int NOT NULL AUTO_INCREMENT,
  `hotel_id` int NOT NULL,
  `room_type_id` int NOT NULL,
  `name` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT NULL,
  `description` text CHARACTER SET latin1 COLLATE latin1_swedish_ci NULL,
  `rate` float(11, 0) NOT NULL,
  `min_rate` float(11, 0) NOT NULL,
  `min_night` int NOT NULL,
  `extra_adult_charge` float(11, 0) NULL DEFAULT NULL,
  `food` int NOT NULL COMMENT '0 = unavailable, \r\n1 = all food (breakfast,
lunch, dinner), \r\n2 = breakfast only, \r\n3 = lunch only, \r\n4 = dinner only,
\r\n5 = breakfast & lunch, \r\n6 = breakfast & dinner, \r\n7 = lunch & dinner',
  `food_pack` int NULL DEFAULT NULL,
  `food_desc` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT
NULL,
  `cancelation_policy` int NOT NULL COMMENT '0=not refund, 1=refundable general,
2=refundable custom',
  `deposit_policy` int NOT NULL COMMENT '0=no deposit, 1=general deposit,
2=custom deposit',
  `status` int NOT NULL COMMENT '0=inactive, 1=active',
  `pay_at_hotel` int NOT NULL COMMENT '0=off (default), 1=on',
  `create_user` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT
NULL,
  `create_date` datetime(0) NOT NULL,
  `update_user` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT
NULL,
  `update_date` timestamp(0) NOT NULL DEFAULT CURRENT_TIMESTAMP(0) ON UPDATE
CURRENT_TIMESTAMP(0),
  PRIMARY KEY (`id`) USING BTREE,
  INDEX `hotel_id12`(`hotel_id`) USING BTREE,
  INDEX `room_type3`(`room_type_id`) USING BTREE,
  CONSTRAINT `hotel_id12` FOREIGN KEY (`hotel_id`) REFERENCES `tb_hotel` (`id`)
ON DELETE RESTRICT ON UPDATE CASCADE,

```

```

    CONSTRAINT `room_type3` FOREIGN KEY (`room_type_id`) REFERENCES
`tb_hotel_room_type` (`id`) ON DELETE RESTRICT ON UPDATE CASCADE
) ENGINE = InnoDB AUTO_INCREMENT = 307 CHARACTER SET = latin1 COLLATE =
latin1_swedish_ci ROW_FORMAT = COMPACT;

```

7) tb_hotel_rate_custom

```

-----
-- Table structure for tb_hotel_rate_custom
-----
DROP TABLE IF EXISTS `tb_hotel_rate_custom`;
CREATE TABLE `tb_hotel_rate_custom` (
  `date` date NOT NULL DEFAULT '0000-00-00',
  `rate_plan_id` int NOT NULL DEFAULT 0,
  `room_qty` int NULL DEFAULT NULL,
  `rate` float NULL DEFAULT NULL,
  `stop_sell` int NULL DEFAULT 0 COMMENT '0=sell, 1=stop sell',
  `cta` int NULL DEFAULT 0 COMMENT '0=open, 1=close to arrival',
  `ctd` int NULL DEFAULT 0 COMMENT '0=open, 1=close to departure',
  `min_stay` int NULL DEFAULT NULL,
  `pay_at_hotel` int NULL DEFAULT NULL COMMENT '0=off, 1=on',
  `create_user` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT
NULL,
  `create_date` datetime(0) NOT NULL,
  `update_user` varchar(255) CHARACTER SET latin1 COLLATE latin1_swedish_ci NOT
NULL,
  `update_date` timestamp(0) NOT NULL DEFAULT CURRENT_TIMESTAMP(0) ON UPDATE
CURRENT_TIMESTAMP(0),
  PRIMARY KEY (`date`, `rate_plan_id`) USING BTREE,
  INDEX `rate_plan` (`rate_plan_id`) USING BTREE,
  CONSTRAINT `rate_plan` FOREIGN KEY (`rate_plan_id`) REFERENCES
`tb_hotel_rate_plan` (`id`) ON DELETE CASCADE ON UPDATE CASCADE
) ENGINE = InnoDB CHARACTER SET = latin1 COLLATE = latin1_swedish_ci ROW_FORMAT =
COMPACT;

```