

VARIATION IN NORMS OF QUANTUM INPUT MODELS[†]

HYEONMIN ROH*, TAEWON KIM**

ABSTRACT. The main goal of this paper is to formulate a quantum data structure that prevents efficient classical counterparts of Quantum machine learning algorithms. Since such prevention have been an open problem in quantum machine learning theory, we provide some general properties regarding the problem, focusing on norm variation.

AMS Mathematics Subject Classification : 65H05, 65F10.

Key words and phrases :

1. Introcution

Quantum machine learning (QML) is a field of study after the HHL algorithm [2] that approximately solves a system of linear equations in a logarithmic time. However, there have been critiques [3] on input model assumptions or quantum data structures utilized in QML algorithms. Furthermore, Tang [8] introduced *dequantization*, a method that provides efficient classical counterparts on classical data for QML algorithms by randomized-linear algebraic exploitations of quantum-advantageous assumptions. Currently, preventing dequantization is one of the open problems [11] in QML theory.

Input data for QML algorithms are mostly classical as ML. For compatiblility of classical data with QML algorithms, such data get efficiently transformed into quantum states. A simple solution is to assume a quantum counterpart to classical RAM. That is *quantum random access memory* (QRAM) storing n bits of data and capable of querying these data in superposition within a time complexity of $\text{polylog}(n)$. For a fair comparison between quantum and classical machine

Received , . Revised , . Accepted , . *Corresponding author.

[†]Please add: “This research received no external funding” or “This research was funded by NAME OF FUNDER grant number XXX.” and and “The APC was funded by XXX”. Check carefully that the details given are accurate and use the standard spelling of funding agency names, any errors may affect your future funding. Example: This work was supported by the research grant of the University

© 2023 KSCAM.

learning methodologies, dequantization assumes an input model of *sampling and query access* to a vector.

The outcomes of dequantization establish a boundary for our comprehension of QML algorithms and their constraints. Consequently, a significant unresolved issue in QML pertains to identifying alternative methods for constructing data structures that prevent dequantization. The objective is to provide general exposition to the question of what properties allow or prevent dequantization of QML algorithms.

2. Nomenclature

3. Quantum accesible classical data structure

Most data given for QML are classical. So we use the term QRAM to denote notions such as Quantum accessible classical memory or Quantum Read-Only Memory (QROM [5]).

Definition 3.1 ([10] Definition 1). Let a table of data $T \in \{0, 1\}^N$. QRAM is a collection of unitaries $U_Q(T)$ such that for all states $|i\rangle$ in the computational basis with $0 \leq i \leq N - 1$,

$$U_Q(T) |i\rangle |0\rangle = |i\rangle |T_i\rangle.$$

Or by mapping, query of the form $|i\rangle |0\rangle \rightarrow |i\rangle |T_i\rangle$ requires $\mathcal{O}(\text{polylog})$ time.

An *input model* or a *data structure* for the quantum recommendation algorithm uses such QRAM.

Theorem 3.2 ([4] Theorem 15). Let $A \in \mathbb{R}^{m \times n}$ be a matrix. Let (i, j, A_{ij}) be entries arriving in the system in an arbitrary order with w as the number of entries already in the system. Then, there exists a data structure to store the matrix A with the following properties:

- (1) The size of the data structure is $\mathcal{O}(w \log^2(mn))$.
- (2) The time to store a new entry (i, j, A_{ij}) is $\mathcal{O}(\log^2(mn))$.
- (3) Corresponding to the rows of the matrix currently stored, a quantum algorithm that has quantum access to the data structure can perform the mapping

$$\tilde{U} : |i\rangle |0\rangle \rightarrow |i\rangle |A_i\rangle,$$

and for $\tilde{A} \in \mathbb{R}^m$ with entries $\tilde{A}_i = \|A_i\|$ and $j \in [n]$,

$$\tilde{V} : |0\rangle |j\rangle \rightarrow |\tilde{A}\rangle |j\rangle.$$

This quantum algorithm takes $\text{polylog}(mn)$ time.

This data structure is an array of m binary trees. The value stored at the root is $\|A_i\|^2$ for $i \in [m]$, and depth of each tree is at most $\lceil \log n \rceil$. Here, dequantization questions the assumption of ‘*quantum access* to the data structure that can efficiently handle classical inputs’ and provides a fair comparison. Goal is to classically construct identical tree with only a polynomial slowdown.

Definition 3.3 ([11] Definition 4.1). For all $i \in [n]$, if we can query for $v(i)$, we have *query access* to a vector $v \in \mathbb{C}^n$, denoted by $Q(v)$. For all $(i, j) \in [m] \times [n]$, if we can query for A_{ij} , we have $Q(A)$ to a matrix $A \in \mathbb{C}^{m \times n}$. Time cost of such query is denoted by $q(v)$ and $q(A)$, respectively.

Definition 3.4 ([11] Definition 4.2). For a vector $v \in \mathbb{C}^n$, we have *sampling and query access* to v , denoted by $SQ(v)$, if we can:

- (1) have query access to v ;
- (2) obtain independent samples $i \in [n]$ following the distribution $\mathcal{D}_v \in \mathbb{R}^n$ with $\mathcal{D}_v(i) := |v(i)|^2 / \|v\|^2$;
- (3) have query access to $\|v\|$.

Cost of entry querying, index sampling, norm querying, are denoted as $q(v)$, $s(v)$, and $n(v)$, respectively. Also, let $sq(v) := \max(q(v), s(v), n(v))$.

Samples obtained from sampling and query access are analogue to the quantum state $|v\rangle := 1/\|v\| \sum v_i |i\rangle$ in the computational basis. Such sampling and query access may be generalized by some oversampling rate.

Definition 3.5. For $v \in \mathbb{C}^n$ and $\phi \geq 1$, we have $\tilde{v} \in \mathbb{C}^n$ if $\|\tilde{v}\|^2 = \phi\|v\|^2$ and $|\tilde{v}_i|^2 \geq |v_i|^2$ for all $i \in [n]$.

Definition 3.6 ([11] Definition 4.3). For $v \in \mathbb{C}^n$ and $\phi \geq 1$, if $Q(v)$ and $SQ(\tilde{v})$ for $\tilde{v} \in \mathbb{C}^n$, we have ϕ -oversampling and query access to v or $SQ_\phi(v)$. Also,

$$s_\phi(v) := s(\tilde{v}), \quad q_\phi(v) := q(\tilde{v}), \quad n_\phi(v) := n(\tilde{v}), \quad sq_\phi(v) := \max(s_\phi(v), q_\phi(v), n_\phi(v)).$$




FIGURE 1. example of a ϕ -sampling and query access data structure

Note that $SQ_\phi(v)$ constructs an identical tree structure to the one from QRAM. So, we can dequantize whenever QML algorithm relies on QRAM based data structure.

4. Alternative Data Structures

However, there have been variations for such definitions of QRAM, which might prevent dequantization. We first present such variant with general approach, then with more concrete form of presentation by *block-encoding*. Theorem below constructs a more efficient variant of QRAM, where the memory requirement [9] is $\tilde{O}(mn)$ and time cost of update, insertion, or deletion for a single entry is $\mathcal{O}(\text{polylog}(n))$.

Theorem 4.1 ([9] Theorem IV.2). *Let $M = \max_{i \in [m]} \|a_i\|^2$ and $A \in \mathbb{R}^{m \times n}$. There exists an efficient QRAM data structure for storing matrix entries (i, j, a_{ij}) such that access to this data structure allows a quantum algorithm to implement following unitary in time $\tilde{O}(\log(mn))$.*

$$U |i, 0^{\lceil \log(n+1) \rceil}\rangle = |i\rangle \frac{1}{\sqrt{M}} \left(\sum_{j \in [n]} a_{ij} |j\rangle + (M - \|a_i\|^2)^{1/2} |n+1\rangle \right).$$

Before heading to the proof, it is helpful to understand utility of M .

Definition 4.2. The normalized vector state corresponding to vector $x \in \mathbb{R}^n$ and $M \in \mathbb{R}$ such that $\|x\|^2 \leq M$ is the quantum state

$$|\bar{x}\rangle = \frac{1}{\sqrt{M}} \left(\sum_{i \in [n]} x_i |i\rangle + (M - \|x\|^2)^{1/2} |n+1\rangle \right).$$

So the key variation is the norm in the input state.

Proof. m binary trees $B_i \longrightarrow$ use **rotation**

•
•
•

□

Now we define the notion of block-encoding to clarify the prevention of result above. Block-encoding was devised during a optimal solution of Hamiltonian simulation problem, [6] originally termed as ‘qubitization’. Simply put, block-encoding is a technique of representing Hermitian or subnormalized matrix as the top-left block of a unitary matrix, that is;

$$U = \begin{bmatrix} A/\alpha & \cdot \\ \cdot & \cdot \end{bmatrix}$$

where \cdot denotes arbitrary elements of U .

Definition 4.3 (Gilyén 2019). For $A \in \mathbb{C}^{n \times m}$, $\alpha, \epsilon \in \mathbb{R}_+$ and $a \in \mathbb{N}$, $(s+a)$ -qubit unitary U is an (α, a, ϵ) -block-encoding of A if

$$\|A - \alpha(\langle 0|^{\otimes a} \otimes I)U(|0\rangle^{\otimes a} \otimes I)\| \leq \epsilon.$$

For $n, m \leq 2^s$ we may define an embedding matrix $A_e \in \mathbb{C}^{2^s \times 2^s}$ such that the top-left block of A_e is A and all other entries are 0.

Theorem 4.4 (Chakraborty, 2019, Lemma 25). *Let $A \in \mathbb{C}^{m \times n}$.*

- (1) *Fix $p \in [0, 1]$. If $A^{(p)}$ and $(A^{(1-p)})^\dagger$ are both stored in quantum-accessible data structures, then there exist unitaries U_R and U_L that can be implemented in time $\mathcal{O}(\text{polylog}(mn/\epsilon))$ such that $U_R^\dagger U_L$ is a $(\mu_p(A), \lceil \log(n + m + 1) \rceil, \epsilon)$ -block-encoding of \tilde{A} .*
- (2) *On the other hand, if A is stored in a quantum-accessible data structure, then there exist unitaries U_R and U_L that can be implemented in time $\mathcal{O}(\text{polylog}(mn/\epsilon))$ such that $U_R^\dagger U_L$ is a $(\|A\|_F, \lceil \log(m + n) \rceil, \epsilon)$ -block-encoding of \tilde{A} .*

Theorem 4.5. *Chakraborty2019*

Theorem 4.6. *main result*

5. Examples and Applications

Conflicts of interest : Declare conflicts of interest or state “The authors declare no conflict of interest.” Authors must identify and declare any personal circumstances or interest that may be perceived as inappropriately influencing the representation or interpretation of reported research results.

Data availability : In this section, please provide details regarding where data supporting reported results can be found, including links to publicly archived datasets analyzed or generated during the study. If the study did not report any data, you might add “Not applicable” here.

Acknowledgments : In this section you can acknowledge any support given which is not covered by the author contribution or funding sections.

REFERENCES

1. C. Baiocchi and A. Capelo, *Variational and Quasi Variational Inequalities*, J. Wiley and Sons, New York, 1984.
2. A. W. Harrow, A. Hassidim and S. Lloyd, *Quantum algorithm for linear Systems of equations*, Phys. Rev. Lett **103** (2009), 150502.
3. S. Aaronson, *Read the fine print*, Nature Phys **11** (2015), 291-293.
4. I. Kerenidis and A. Prakash, *Quantum Recommendation Systems*, ITCS **67** (2017), 49:1–49:21.
5. R. Babbush, C. Gidney, B. Dominic, N. Weibe, J. McClean, A. Paler, A. Fowler and H. Neven, *Encoding Electronic Spectra in Quantum Circuits with Linear T Complexity* Phys. Rev. **8** (2018), 041015.
6. H. Low and I. Chuang, *Hamiltonian Simulation by Qubitization*, Quantum **3** (2019), 163.
7. Chakraborty, Gilyén and Jeffery. *The Power of Block-Encoded Matrix Powers*, ICALP **132** (2019), 33:1-33:14.

8. E. Tang, *A Quantum-Inspired Classical Algorithm for Recommendation Systems*, Proceedings of the 51st Annual ACM SIGACT Symposium on Theory of Computing (2019), 217–228.
9. Kerenidis, Iordanis and Prakash, Anupam, *Quantum gradient descent for linear systems and least squares*, Phys.Rev.A **2** (2020), 022316.
10. S. Jaques and A. Rattew, *QRAM: A Survey and Critique*, arXiv: 2305.10310 [quant-ph] (2023).
11. E. Tang, *Quantum Machine Learning Without Any Quantum*, Ph.D. diss, University of Washington (2023).
12. D. Chan and J.S. Pang, *The generalized quasi variational inequality problems*, Math. Oper. Research **7** (1982), 211-222.
13. C. Belly, *Variational and Quasi Variational Inequalities*, J. Appl. Math. and Computing **6** (1999), 234-266.
14. D. Pang, *The generalized quasi variational inequality problems*, J. Appl. Math. and Computing **8** (2002), 123-245.

1st Author name received M.Sc. from Seoul National University and Ph.D. at University of Minnesota. Since 1992 he has been at Chungnam National University. His research interests include numerical optimization and biological computation.

Department of Mathematics, Chungnam National University, Daejeon 305-764, Korea.
 e-mail: `soh@cnu.ac.kr`

2nd Author name received M.Sc. from Kyungpook National University, and Ph.D. from Iowa State University. He is currently a professor at Chungbuk National University since 1991. His research interests are computational mathematics, iterative method and parallel computation.

Department of Mathematics, College of Natural Sciences, Chungbuk National University, Cheongju 361-763, Korea.
 e-mail: `gmjae@chungbuk.ac.kr`