

The Ultimatest Monad Tutorial

Panicz Maciej Godek

`godek.maciek@gmail.com`

15.12.2023

Agenda

- the concept of monads
- problems with Haskell
- pyramid of doom (with sugar coating)
- rants

Agenda

- the concept of monads
- problems with Haskell
- pyramid of doom (with sugar coating)
- rants

Agenda

- the concept of monads
- problems with Haskell
- pyramid of doom (with sugar coating)
- rants

Agenda

- the concept of monads
- problems with Haskell
- pyramid of doom (with sugar coating)
- rants

Agenda

- the concept of monads
- problems with Haskell
- pyramid of doom (with sugar coating)
- rants

Point-free programming

Inverse of a square root

```
isqrt x = 1/(sqrt x)
```

point-free style:

```
isqrt = (1/) . sqrt
```

```
where (f . g) x = f (g x)
```

in JS:

```
function compose(f, g) {  
  return function(x) {  
    return f(g(x));  
  };  
}
```

Point-free programming

Inverse of a square root

```
isqrt x = 1/(sqrt x)
```

point-free style:

```
isqrt = (1/) . sqrt
```

```
where (f . g) x = f (g x)
```

in JS:

```
function compose(f, g) {  
  return function(x) {  
    return f(g(x));  
  };  
}
```


Point-free programming

Inverse of a square root

```
isqrt x = 1/(sqrt x)
```

point-free style:

```
isqrt = (1/) . sqrt  
where (f . g) x = f (g x)
```

in JS:

```
function compose(f, g) {  
  return function(x) {  
    return f(g(x));  
  };  
}
```

Point-free programming

Inverse of a square root

```
isqrt x = 1/(sqrt x)
```

point-free style:

```
isqrt = (1/) . sqrt
```

```
where (f . g) x = f (g x)
```

in JS:

```
function compose(f, g) {  
  return function(x) {  
    return f(g(x));  
  };  
}
```

Point-free programming

Inverse of a square root

```
isqrt x = 1/(sqrt x)
```

point-free style:

```
isqrt = (1/) . sqrt
```

where $(f \cdot g) \ x = f \ (g \ x)$

in JS:

```
function compose(f, g) {  
  return function(x) {  
    return f(g(x));  
  };  
}
```

Point-free programming

Inverse of a square root

```
isqrt x = 1/(sqrt x)
```

point-free style:

```
isqrt = (1/) . sqrt
```

where $(f \cdot g) \ x = f \ (g \ x)$

in JS:

```
function compose(f, g) {  
  return function(x) {  
    return f(g(x));  
  };  
}
```

Function composition operator

Type of the function composition operator:

$(.) :: (b \rightarrow c) \rightarrow (a \rightarrow b) \rightarrow (a \rightarrow c)$

looks a bit awkward, but if we define

$(g \mid f) \ x = f \ (g \ x)$

the type of the “swapped composition” is

$(\mid) :: (a \rightarrow b) \rightarrow (b \rightarrow c) \rightarrow (a \rightarrow c)$

vide UNIX pipes

or “the uncle of the friend of my brother” vs. “my brother's friend's uncle”

or $f(g(x))$ vs. $x \rightarrow getG() \rightarrow getF()$

Function composition operator

Type of the function composition operator:

$(.) :: (b \rightarrow c) \rightarrow (a \rightarrow b) \rightarrow (a \rightarrow c)$

looks a bit awkward, but if we define

$(g \mid f) \ x = f \ (g \ x)$

the type of the “swapped composition” is

$(\mid) :: (a \rightarrow b) \rightarrow (b \rightarrow c) \rightarrow (a \rightarrow c)$

vide UNIX pipes

or “the uncle of the friend of my brother” vs. “my brother's friend's uncle”

or $f(g(x))$ vs. $x \rightarrow \text{getG}() \rightarrow \text{getF}()$

Function composition operator

Type of the function composition operator:

$(.) :: (b \rightarrow c) \rightarrow (a \rightarrow b) \rightarrow (a \rightarrow c)$

looks a bit awkward, but if we define

$(g \mid f) \ x = f \ (g \ x)$

the type of the “swapped composition” is

$(\mid) :: (a \rightarrow b) \rightarrow (b \rightarrow c) \rightarrow (a \rightarrow c)$

vide UNIX pipes

or “the uncle of the friend of my brother” vs. “my brother's friend's uncle”

or $f(g(x))$ vs. $x \rightarrow getG() \rightarrow getF()$

Function composition operator

Type of the function composition operator:

$(.) :: (b \rightarrow c) \rightarrow (a \rightarrow b) \rightarrow (a \rightarrow c)$

looks a bit awkward, but if we define

$(g \mid f) \ x = f \ (g \ x)$

the type of the “swapped composition” is

$(\mid) :: (a \rightarrow b) \rightarrow (b \rightarrow c) \rightarrow (a \rightarrow c)$

vide UNIX pipes

or “the uncle of the friend of my brother” vs. “my brother's friend's uncle”

or $f(g(x))$ vs. $x \rightarrow getG() \rightarrow getF()$

Function composition operator

Type of the function composition operator:

$(.) :: (b \rightarrow c) \rightarrow (a \rightarrow b) \rightarrow (a \rightarrow c)$

looks a bit awkward, but if we define

$(g \mid f) \ x = f \ (g \ x)$

the type of the “swapped composition” is

$(\mid) :: (a \rightarrow b) \rightarrow (b \rightarrow c) \rightarrow (a \rightarrow c)$

vide UNIX pipes

or “the uncle of the friend of my brother” vs. “my brother's friend's uncle”

or $f(g(x))$ vs. $x \rightarrow getG() \rightarrow getF()$

Function composition operator

Type of the function composition operator:

$(.) :: (b \rightarrow c) \rightarrow (a \rightarrow b) \rightarrow (a \rightarrow c)$

looks a bit awkward, but if we define

$(g \mid f) \ x = f \ (g \ x)$

the type of the “swapped composition” is

$(\mid) :: (a \rightarrow b) \rightarrow (b \rightarrow c) \rightarrow (a \rightarrow c)$

vide UNIX pipes

or “the uncle of the friend of my brother” vs. “my brother's friend's uncle”

or $f(g(x))$ vs. $x \rightarrow getG() \rightarrow getF()$

Function composition operator

Type of the function composition operator:

$(.) :: (b \rightarrow c) \rightarrow (a \rightarrow b) \rightarrow (a \rightarrow c)$

looks a bit awkward, but if we define

$(g \mid f) \ x = f \ (g \ x)$

the type of the “swapped composition” is

$(\mid) :: (a \rightarrow b) \rightarrow (b \rightarrow c) \rightarrow (a \rightarrow c)$

vide UNIX pipes

or “the uncle of the friend of my brother” vs. “my brother's friend's uncle”

or $f(g(x))$ vs. $x \rightarrow \text{getG}() \rightarrow \text{getF}()$

Function composition operator

Type of the function composition operator:

$(.) :: (b \rightarrow c) \rightarrow (a \rightarrow b) \rightarrow (a \rightarrow c)$

looks a bit awkward, but if we define

$(g \mid f) \ x = f \ (g \ x)$

the type of the “swapped composition” is

$(\mid) :: (a \rightarrow b) \rightarrow (b \rightarrow c) \rightarrow (a \rightarrow c)$

vide UNIX pipes

or “the uncle of the friend of my brother” vs. “my brother's friend's uncle”

or $f(g(x))$ vs. $x \rightarrow \text{getG}() \rightarrow \text{getF}()$

Function composition operator

Properties of function composition:

- **associative:** $f \cdot (g \cdot h) = (f \cdot g) \cdot h$
like: $x + (y + z) = (x + y) + z$
or: $x * (y * z) = (x * y) * z$
- **has a neutral element `id`:**
 $f \cdot id = id \cdot f = f$
like: $x + 0 = 0 + x = x$
or: $x * 1 = 1 * x = x$

where the `id` function is defined as

```
id x = x
```

```
function id(x) { return x; }
```

Function composition operator

Properties of function composition:

- **associative:** $f \cdot (g \cdot h) = (f \cdot g) \cdot h$

like: $x + (y + z) = (x + y) + z$

or: $x * (y * z) = (x * y) * z$

- has a neutral element `id`:

$f \cdot \text{id} = \text{id} \cdot f = f$

like: $x + 0 = 0 + x = x$

or: $x * 1 = 1 * x = x$

where the `id` function is defined as

```
id x = x
```

```
function id(x) { return x; }
```

Function composition operator

Properties of function composition:

- **associative:** $f \cdot (g \cdot h) = (f \cdot g) \cdot h$
like: $x + (y + z) = (x + y) + z$
or: $x * (y * z) = (x * y) * z$
- has a neutral element `id`:
 $f \cdot \text{id} = \text{id} \cdot f = f$
like: $x + 0 = 0 + x = x$
or: $x * 1 = 1 * x = x$

where the `id` function is defined as

```
id x = x
```

```
function id(x) { return x; }
```

Function composition operator

Properties of function composition:

- **associative:** $f \cdot (g \cdot h) = (f \cdot g) \cdot h$
like: $x + (y + z) = (x + y) + z$
or: $x * (y * z) = (x * y) * z$
- has a neutral element `id`:
 $f \cdot \text{id} = \text{id} \cdot f = f$
like: $x + 0 = 0 + x = x$
or: $x * 1 = 1 * x = x$

where the `id` function is defined as

```
id x = x
```

```
function id(x) { return x; }
```


Function composition operator

Properties of function composition:

- **associative:** $f \cdot (g \cdot h) = (f \cdot g) \cdot h$

like: $x + (y + z) = (x + y) + z$

or: $x * (y * z) = (x * y) * z$

- **has a neutral element `id`:**

$f \cdot id = id \cdot f = f$

like: $x + 0 = 0 + x = x$

or: $x * 1 = 1 * x = x$

where the `id` function is defined as

```
id x = x
```

```
function id(x) { return x; }
```

Function composition operator

Properties of function composition:

- **associative:** $f \cdot (g \cdot h) = (f \cdot g) \cdot h$
like: $x + (y + z) = (x + y) + z$
or: $x * (y * z) = (x * y) * z$
- **has a neutral element `id`:**
 $f \cdot id = id \cdot f = f$
like: $x + 0 = 0 + x = x$
or: $x * 1 = 1 * x = x$

where the `id` function is defined as

```
id x = x
```

```
function id(x) { return x; }
```

Function composition operator

Properties of function composition:

- **associative:** $f \cdot (g \cdot h) = (f \cdot g) \cdot h$
like: $x + (y + z) = (x + y) + z$
or: $x * (y * z) = (x * y) * z$
- **has a neutral element `id`:**
 $f \cdot id = id \cdot f = f$
like: $x + 0 = 0 + x = x$
or: $x * 1 = 1 * x = x$

where the `id` function is defined as

```
id x = x
```

```
function id(x) { return x; }
```

Function composition operator

Properties of function composition:

- **associative:** $f \cdot (g \cdot h) = (f \cdot g) \cdot h$
like: $x + (y + z) = (x + y) + z$
or: $x * (y * z) = (x * y) * z$
- **has a neutral element `id`:**
 $f \cdot id = id \cdot f = f$
like: $x + 0 = 0 + x = x$
or: $x * 1 = 1 * x = x$

where the `id` function is defined as

```
id x = x
```

```
function id(x) { return x; }
```

Function composition operator

Properties of function composition:

- **associative:** $f \cdot (g \cdot h) = (f \cdot g) \cdot h$
like: $x + (y + z) = (x + y) + z$
or: $x * (y * z) = (x * y) * z$
- **has a neutral element `id`:**
 $f \cdot id = id \cdot f = f$
like: $x + 0 = 0 + x = x$
or: $x * 1 = 1 * x = x$

where the `id` function is defined as

`id x = x`

```
function id(x) { return x; }
```

Function composition operator

Properties of function composition:

- **associative:** $f \cdot (g \cdot h) = (f \cdot g) \cdot h$
like: $x + (y + z) = (x + y) + z$
or: $x * (y * z) = (x * y) * z$
- **has a neutral element `id`:**
 $f \cdot id = id \cdot f = f$
like: $x + 0 = 0 + x = x$
or: $x * 1 = 1 * x = x$

where the `id` function is defined as

```
id x = x
```

```
function id(x) { return x; }
```

All that math

In mathematics, an associative operator with neutral element is called *a monoid* (or *semigroup with identity*).

Now imagine the following *generalization* of the composition operator:

$$<|_m :: (b \rightarrow m\ c) \rightarrow (a \rightarrow m\ b) \rightarrow (a \rightarrow m\ c)$$

For example:

```
class WithLog<T> {  
    public T value;  
    public String log;  
}  
  
(f <|_WithLog g) a =  
    WithLog b = g(a);  
    WithLog c = f(b.value);  
    return WithLog(value = c.value, log = b.log  
+ c.log);
```

All that math

In mathematics, an associative operator with neutral element is called *a monoid* (or *semigroup with identity*).

Now imagine the following *generalization* of the composition operator:

$\langle |_m :: (b \rightarrow m\ c) \rightarrow (a \rightarrow m\ b) \rightarrow (a \rightarrow m\ c)$

For example:

```
class WithLog<T> {  
    public T value;  
    public String log;  
}  
  
(f <|_withLog g) a =  
    WithLog b = g(a);  
    WithLog c = f(b.value);  
    return WithLog(value = c.value, log = b.log  
+ c.log);
```


All that math

In mathematics, an associative operator with neutral element is called *a monoid* (or *semigroup with identity*).

Now imagine the following *generalization* of the composition operator:

$$<|_m :: (b \rightarrow m \ c) \rightarrow (a \rightarrow m \ b) \rightarrow (a \rightarrow m \ c)$$

For example:

```
class WithLog<T> {  
    public T value;  
    public String log;  
}  
  
(f <|_WithLog g) a =  
    WithLog b = g(a);  
    WithLog c = f(b.value);  
    return WithLog(value = c.value, log = b.log  
+ c.log);
```

All that math

In mathematics, an associative operator with neutral element is called *a monoid* (or *semigroup with identity*).

Now imagine the following *generalization* of the composition operator:

$$<|_m :: (b \rightarrow m \ c) \rightarrow (a \rightarrow m \ b) \rightarrow (a \rightarrow m \ c)$$

For example:

```
class WithLog<T> {  
    public T value;  
    public String log;  
}  
  
(f <|_withLog g) a =  
    WithLog b = g(a);  
    WithLog c = f(b.value);  
    return WithLog(value = c.value, log = b.log  
+ c.log);
```

All that math

In mathematics, an associative operator with neutral element is called *a monoid* (or *semigroup with identity*).

Now imagine the following *generalization* of the composition operator:

$$<|_m :: (b \rightarrow m \ c) \rightarrow (a \rightarrow m \ b) \rightarrow (a \rightarrow m \ c)$$

For example:

```
class WithLog<T> {  
    public T value;  
    public String log;  
}  
  
(f <|_WithLog g) a =  
    WithLog b = g(a);  
    WithLog c = f(b.value);  
    return WithLog(value = c.value, log = b.log  
+ c.log);
```

Generalization of identity

```
idWithLog x = WithLog(value = x, log = "")
```

The triple (m, \leq_m, id_m) is called *a monad*.

For example, $(\text{WithLog}, \leq_{\text{WithLog}}, \text{id}_{\text{WithLog}})$ is a monad.

Other popular examples: `Optional`, `List`.

Generalization of identity

```
idWithLog x = WithLog(value = x, log = "")
```

The triple $(m, <|_m, id_m)$ is called *a monad*.

For example, $(WithLog, <|_{WithLog}, id_{WithLog})$ is a monad.

Other popular examples: `Optional`, `List`.

Generalization of identity

```
idWithLog x = WithLog(value = x, log = "")
```

The triple (m, \leq_m, id_m) is called *a monad*.

For example, $(WithLog, \leq_{WithLog}, id_{WithLog})$ is a monad.

Other popular examples: `Optional`, `List`.

Generalization of identity

```
idWithLog x = WithLog(value = x, log = "")
```

The triple $(m, <|_m, id_m)$ is called *a monad*.

For example, $(WithLog, <|_{WithLog}, id_{WithLog})$ is a monad.

Other popular examples: `Optional`, `List`.

But why?

Problem with Haskell: lazy evaluation.

Solution: “input/output system based on monads”

But what does it mean?

But why?

Problem with Haskell: lazy evaluation.

Solution: “input/output system based on monads”

But what does it mean?

But why?

Problem with Haskell: lazy evaluation.

Solution: “input/output system based on monads”

But what does it mean?

But why?

Problem with Haskell: lazy evaluation.

Solution: “input/output system based on monads”

But what does it mean?

Evaluation strategies

```
square x = x * x
```

The “applicative” order (evaluate arguments before expanding function):

```
square (2*3) = square 6 =def 6 * 6 = 36
```

The “normal” order (evaluate arguments as late as possible):

```
square (2*3) =def (2*3) * (2*3) = 6 * 6 = 36
```

Evaluation strategies

```
square x = x * x
```

The “applicative” order (evaluate arguments before expanding function):

```
square (2*3) = square 6 =def 6 * 6 = 36
```

The “normal” order (evaluate arguments as late as possible):

```
square (2*3) =def (2*3) * (2*3) = 6 * 6 = 36
```

Evaluation strategies

```
square x = x * x
```

The “applicative” order (evaluate arguments before expanding function):

```
square (2*3) = square 6 =def 6 * 6 = 36
```

The “normal” order (evaluate arguments as late as possible):

```
square (2*3) =def (2*3) * (2*3) = 6 * 6 = 36
```

Evaluation strategies

```
square x = x * x
```

The “applicative” order (evaluate arguments before expanding function):

```
square (2*3) = square 6 =def 6 * 6 = 36
```

The “normal” order (evaluate arguments as late as possible):

```
square (2*3) =def (2*3) * (2*3) = 6 * 6 = 36
```

Evaluation strategies

```
square x = x * x
```

The “applicative” order (evaluate arguments before expanding function):

```
square (2*3) = square 6 =def 6 * 6 = 36
```

The “normal” order (evaluate arguments as late as possible):

```
square (2*3) =def (2*3) * (2*3) = 6 * 6 = 36
```


Evaluation strategies

```
square x = x * x
```

The “applicative” order (evaluate arguments before expanding function):

```
square (2*3) = square 6 =def 6 * 6 = 36
```

The “normal” order (evaluate arguments as late as possible):

```
square (2*3) =def (2*3) * (2*3) = 6 * 6 = 36
```

Evaluation strategies

```
square x = x * x
```

The “applicative” order (evaluate arguments before expanding function):

```
square (2*3) = square 6 =def 6 * 6 = 36
```

The “normal” order (evaluate arguments as late as possible):

```
square (2*3) =def (2*3) * (2*3) = 6 * 6 = 36
```

Evaluation strategies

```
square x = x * x
```

The “applicative” order (evaluate arguments before expanding function):

```
square (2*3) = square 6 =def 6 * 6 = 36
```

The “normal” order (evaluate arguments as late as possible):

```
square (2*3) =def (2*3) * (2*3) = 6 * 6 = 36
```

Evaluation strategies

```
square x = x * x
```

The “applicative” order (evaluate arguments before expanding function):

```
square (2*3) = square 6 =def 6 * 6 = 36
```

The “normal” order (evaluate arguments as late as possible):

```
square (2*3) =def (2*3) * (2*3) = 6 * 6 = 36
```

Evaluation strategies

```
square x = x * x
```

The “applicative” order (evaluate arguments before expanding function):

```
square (2*3) = square 6 =def 6 * 6 = 36
```

The “normal” order (evaluate arguments as late as possible):

```
square (2*3) =def (2*3) * (2*3) = 6 * 6 = 36
```

Evaluation strategies

```
square x = x * x
```

The “applicative” order (evaluate arguments before expanding function):

```
square (2*3) = square 6 =def 6 * 6 = 36
```

The “normal” order (evaluate arguments as late as possible):

```
square (2*3) =def (2*3) * (2*3) = 6 * 6 = 36
```

The problem with Haskell: lazy evaluation

```
readNumber()*3 + 2*readNumber()
```

```
< 1
```

```
< 0
```

The problem with Haskell: lazy evaluation

```
readNumber()*3 + 2*readNumber()  
< 1  
< 0
```


The problem with Haskell: lazy evaluation

```
readNumber()*3 + 2*readNumber()  
< 1  
< 0
```

Idea for a solution

```
let  a      = readNumber( ) in
  let  b      = readNumber( ) in
    a*2 + 3*b
```

gdzie

```
let name = value in expression
( $\lambda$  name  $\rightarrow$  expression) value
```

Idea for a solution

```
let  a      = readNumber( ) in
  let  b      = readNumber( ) in
    a*2 + 3*b
```

gdzie

```
let name = value in expression
(λ name -> expression) value
```

Idea for a solution

```
let  a      = readNumber( ) in
  let  b      = readNumber( ) in
    a*2 + 3*b
```

gdzie

```
let name = value in expression
( $\lambda$  name  $\rightarrow$  expression) value
```

Idea for a solution

```
let  a      = readNumber( ) in
  let  b      = readNumber( ) in
    a*2 + 3*b
```

gdzie

```
let name = value in expression
(λ name -> expression) value
```

A working solution

```
let (a,w1) = readNumber(w0) in
  let (b,w2) = readNumber(w1) in
    a*2 + 3*b
```

A better solution

```
let (a,w1) = readNumber(w0) in
  let (b,w2) = readNumber(w1) in
    (a*2 + 3*b, w2)
```

Extracting a function

```
myOperation :: RealWorld -> (Int, RealWorld)
myOperation w0 =
  let (a,w1) = readNumber(w0) in
    let (b,w2) = readNumber(w1) in
      (a*2 + 3*b, w2)
```

https://wiki.haskell.org/IO_inside

Problems

- we need to pass additional argument
- error-prone (e.g. `w0` zamiast `w1`)
- indentation level increases

Problems

- we need to pass additional argument
- error-prone (e.g. `w0` zamiast `w1`)
- indentation level increases

Problems

- we need to pass additional argument
- error-prone (e.g. w_0 zamiast w_1)
- indentation level increases

Problems

- we need to pass additional argument
- error-prone (e.g. `w0` zamiast `w1`)
- indentation level increases

Sweeping w_n under the rug

```
pass readNumber
  (λ a -> pass readNumber
    (λ b -> return a*2 + 3*b))

return value = λ world -> (value, world)

pass value continuation = λ w0 ->
  let (result, w1) = value w0 in
    continuation result w1
```

Sweeping w_n under the rug

```
pass readNumber
  (λ a -> pass readNumber
    (λ b -> return a*2 + 3*b))

return value = λ world -> (value, world)

pass value continuation = λ w0 ->
  let (result, w1) = value w0 in
    continuation result w1
```

Sweeping w_n under the rug

```
pass readNumber
  (λ a -> pass readNumber
    (λ b -> return a*2 + 3*b))

return value = λ world -> (value, world)

pass value continuation = λ w0 ->
  let (result, w1) = value w0 in
    continuation result w1
```

Sweeping w_n under the rug

```
pass readNumber
  (λ a -> pass readNumber
    (λ b -> return a*2 + 3*b))

return value = λ world -> (value, world)

pass value continuation = λ w0 ->
  let (result, w1) = value w0 in
    continuation result w1
```


Sweeping w_n under the rug

```
pass readNumber
  (λ a -> pass readNumber
    (λ b -> return a*2 + 3*b))

return value = λ world -> (value, world)

pass value continuation = λ w0 ->
  let (result, w1) = value w0 in
    continuation result w1
```

But does it work?

```
pass readNumber  
  (λ a -> pass readNumber  
           (λ b -> return a*2 + 3*b))
```

```
return value = λ world -> (value, world)
```

```
pass value continuation = λ w0 ->  
  let (result, w1) = value w0 in  
    continuation result w1
```

But does it work?

```
pass readNumber
  (λ a -> pass readNumber
    (λ b -> λ w -> (a*2 + 3*b, w)))
```

```
return value = λ world -> (value, world)
```

```
pass value continuation = λ w0 ->
  let (result, w1) = value w0 in
    continuation result w1
```

But does it work?

```
pass readNumber  
  (λ a -> pass readNumber  
        (λ b -> λ w -> (a*2 + 3*b, w)))
```

```
return value = λ world -> (value, world)
```

```
pass value continuation = λ w0 ->  
  let (result, w1) = value w0 in  
    continuation result w1
```

But does it work?

```
pass readNumber (λ a -> λ w1 ->
  let (y, w2) = readNumber(w1) in
    (λ b -> λ w -> (a*2 + 3*b, w)) y w2)
```

```
return value = λ world -> (value, world)
```

```
pass value continuation = λ w0 ->
  let (result, w1) = value w0 in
    continuation result w1
```

But does it work?

```
pass readNumber (λ a -> λ w1 ->
  let (y, w2) = readNumber(w1) in
    (λ b -> λ w -> (a*2 + 3*b, w)) y w2)
```

```
return value = λ world -> (value, world)
```

```
pass value continuation = λ w0 ->
  let (result, w1) = value w0 in
    continuation result w1
```

But does it work?

```
pass readNumber (λ a -> λ w1 ->
  let (y, w2) = readNumber(w1) in
    (λ w -> (a*2 + 3*y, w)) w2)

return value = λ world -> (value, world)

pass value continuation = λ w0 ->
  let (result, w1) = value w0 in
    continuation result w1
```

But does it work?

```
pass readNumber (λ a -> λ w1 ->  
  let (y, w2) = readNumber(w1) in  
    (a*2 + 3*y, w2))
```

```
return value = λ world -> (value, world)
```

```
pass value continuation = λ w0 ->  
  let (result, w1) = value w0 in  
    continuation result w1
```


But does it work?

```
pass readNumber ( $\lambda$  a ->  $\lambda$  w1 ->  
  let (y, w2) = readNumber(w1) in  
    (a*2 + 3*y, w2))
```

```
return value =  $\lambda$  world -> (value, world)
```

```
pass value continuation =  $\lambda$  w0 ->  
  let (result, w1) = value w0 in  
    continuation result w1
```

But does it work?

```
λ w0 -> let (x,w3) = readNumber(w0) in  
  (λ a -> λ w1 -> let (y, w2) = readNumber(w1)  
    in (a*2 + 3*y, w2)) x w3
```

```
return value = λ world -> (value, world)
```

```
pass value continuation = λ w0 ->  
  let (result, w1) = value w0 in  
    continuation result w1
```

But does it work?

```
λ w0 -> let (x,w3) = readNumber(w0) in  
  (λ a -> λ w1 -> let (y, w2) = readNumber(w1)  
    in (a*2 + 3*y, w2)) x w3
```

```
return value = λ world -> (value, world)
```

```
pass value continuation = λ w0 ->  
  let (result, w1) = value w0 in  
    continuation result w1
```

But does it work?

```
λ w0 -> let (x,w3) = readNumber(w0) in  
  (λ w1 -> let (y, w2) = readNumber(w1) in  
    (x*2 + 3*y, w2)) w3
```

```
return value = λ world -> (value, world)
```

```
pass value continuation = λ w0 ->  
  let (result, w1) = value w0 in  
    continuation result w1
```

But does it work?

```
λ w0 -> let (x,w3) = readNumber(w0) in  
    let (y, w2) = readNumber(w3) in  
        (x*2 + 3*y, w2)
```

```
return value = λ world -> (value, world)
```

```
pass value continuation = λ w0 ->  
    let (result, w1) = value w0 in  
        continuation result w1
```

But does it work?

```
λ w0 -> let (x,w3) = readNumber(w0) in  
    let (y, w2) = readNumber(w3) in  
        (x*2 + 3*y, w2)
```

```
let (a,w1) = readNumber(w0) in  
    let (b,w2) = readNumber(w1) in  
        (a*2 + 3*b, w2)
```

It works!

```
pass readNumber
  (λ a -> pass readNumber
    (λ b -> return a*2 + 3*b))
```

But typing λ and the increasing indentation level are annoying!

```
pass readNumber (λ a
-> pass readNumber (λ b
-> return a*2 + 3*b))
```

It works!

```
pass readNumber
  (λ a -> pass readNumber
    (λ b -> return a*2 + 3*b))
```

But typing λ and the increasing indentation level are annoying!

```
pass readNumber (λ a
-> pass readNumber (λ b
-> return a*2 + 3*b))
```


It works!

```
pass readNumber
  (λ a -> pass readNumber
    (λ b -> return a*2 + 3*b))
```

But typing λ and the increasing indentation level are annoying!

```
pass readNumber (λ a
-> pass readNumber (λ b
-> return a*2 + 3*b))
```

"The pyramid of doom"

```
empty = 0;
if ($_POST['user_name']) {
    if ($_POST['user_password_new']) {
        if ($_POST['user_password_new'] == $_POST['user_password_repeat']) {
            if (strlen($_POST['user_password_new']) > 5) {
                if (strlen($_POST['user_name']) < 65 && strlen($_POST['user_name']) > 1) {
                    if (preg_match('/^[a-z\d]{2,64}$/i', $_POST['user_name'])) {
                        $user = read_user($_POST['user_name']);
                        if (!isset($user['user_name'])) {
                            if ($_POST['user_email']) {
                                if (strlen($_POST['user_email']) < 65) {
                                    if (filter_var($_POST['user_email'], FILTER_VALIDATE_EMAIL)) {
                                        create_user();
                                        $_SESSION['msg'] = 'You are now registered so please login';
                                        header('Location: ' . $_SERVER['PHP_SELF']);
                                        exit();
                                    } else $msg = 'You must provide a valid email address';
                                } else $msg = 'Email must be less than 64 characters';
                            } else $msg = 'Email cannot be empty';
                        } else $msg = 'Username already exists';
                    } else $msg = 'Username must be only a-z, A-Z, 0-9';
                } else $msg = 'Username must be between 2 and 64 characters';
            } else $msg = 'Password must be at least 6 characters';
        } else $msg = 'Passwords do not match';
    } else $msg = 'Empty Password';
} else $msg = 'Empty Username';
$_SESSION['msg'] = $msg;
```



Syntactic sugar (do-notation):

```
do result <- action
  actions ...
```

is transformed to:

```
pass action (\ result -> do actions ...)
```

Note: In Haskell, `pass` is written down as `>=` and pronounced “bind”.

Syntactic sugar (do-notation):

```
do result <- action  
  actions ...
```

is transformed to:

```
pass action (\ result -> do actions ...)
```

Note: In Haskell, `pass` is written down as `>=` and pronounced “bind”.

Syntactic sugar (do-notation):

```
do result <- action  
  actions ...
```

is transformed to:

```
pass action (\ result -> do actions ...)
```

Note: In Haskell, `pass` is written down as `>>=` and pronounced “bind”.

Syntactic sugar (do-notation):

```
do result <- action  
  actions ...
```

is transformed to:

```
pass action (\ result -> do actions ...)
```

Note: In Haskell, `pass` is written down as `>>=` and pronounced “bind”.

Relation between `pass` and `<|`

```
passm :: m a -> (a -> m b)
<|m :: (b -> m c) -> (a -> m b) -> (a -> m c)
pass value function = (function <| id) value
(f <| g) x = pass (g x) f
returnm :: (a -> m a)
returnm = idm
```

Relation between `pass` and `<|`

```
passm :: m a -> (a -> m b)
<|m :: (b -> m c) -> (a -> m b) -> (a -> m c)
pass value function = (function <| id) value
(f <| g) x = pass (g x) f
returnm :: (a -> m a)
returnm = idm
```


Relation between `pass` and `<|`

```
passm :: m a -> (a -> m b)
<|m :: (b -> m c) -> (a -> m b) -> (a -> m c)
pass value function = (function <| id) value
(f <| g) x = pass (g x) f
returnm :: (a -> m a)
returnm = idm
```

Relation between `pass` and `<|`

```
passm :: m a -> (a -> m b)
<|m :: (b -> m c) -> (a -> m b) -> (a -> m c)
pass value function = (function <| id) value
(f <| g) x = pass (g x) f
returnm :: (a -> m a)
returnm = idm
```

Relation between `pass` and `<|`

```
passm :: m a -> (a -> m b)
<|m :: (b -> m c) -> (a -> m b) -> (a -> m c)
pass value function = (function <| id) value
(f <| g) x = pass (g x) f
returnm :: (a -> m a)
returnm = idm
```

Relation between `pass` and `<|`

```
passm :: m a -> (a -> m b)
<|m :: (b -> m c) -> (a -> m b) -> (a -> m c)
pass value function = (function <| id) value
(f <| g) x = pass (g x) f
returnm :: (a -> m a)
returnm = idm
```

Relation between `pass` and `<|`

```
passm :: m a -> (a -> m b)
<|m :: (b -> m c) -> (a -> m b) -> (a -> m c)
pass value function = (function <| id) value
(f <| g) x = pass (g x) f
returnm :: (a -> m a)
returnm = idm
```