



Scan Here For More Info



**Ultravent 7000 Series
- Safety Helmet**

STANDARD : IS 2925:1984, EN 397, CE

INDUSTRY

Iron & steel
Cement
Automotive
Power & utilities
Metals & mining

IDEAL APPLICATIONS

Construction & projects works
Material handling
Shop floor
Packaging
Maintenance

SPECIAL FEATURES



LIGHT WEIGHT



RECYCLABLE



STRONG & DURABLE



TEMPERATURE RESISTANT



RATCHET FIT

COLOURS:



COMPONENT	MATERIAL	ADVANTAGES
Shell	HDPE (High density poly ethylene)	Resistant to high level impact
Peak	HDPE	22 mm, peak protects eye & face from falling objects
Brim	HDPE	Rim around the shell, drains rain water
Cradle	LDPE / Textile	6-point adjustment, perfect load distribution
Head band	LDPE	Universal fit, dia. 53 cm – 60 cm
Sweat band	Brushed cloth on foam	Sweat absorbent, long time use
Chin strap	PP	Holds the shell, universal fit
Chin strap clip	Nylon	Attachment between shell and chin strap
Ratchet	Nylon	Fully adjustable, smooth & universal fit
Slot	Universal slots on the both sides	Compatible with head & face PPE accessories
Ventilation	Both side of the crown ventilated	4 point ventilation on each side for air circulation

FEATURES

Shell proprietary injection-moulded HDPE compound

Aesthetic look with smooth finish – solid colour resin for a permanent, no-chip, no-peel finish

Unique crown ventilation system provides air circulation & comfort

Greater impact resistance and crack resistance

6-point plastic / textile suspension with slip fit or ratchet fit adjustment

Adjustable chin strap for customized fit and comfort

High quality sweat band provides comfort

Radiant heat resistivity higher than ABS helmets yet light weight

Designed for use in industries where there is a hazard, which can damage skull

APPLICATION

Protects head from falling objects

Protects splashes, spatters etc.

STORAGE

Can be stored and transported in their original cartons at ambient temperature (0°C to + 30°C)

Shell may be stored in the dark for up to 5 years

Do not store in direct / high heat or sunlight as this may distort the shell

CLEANING	WEIGHT	PACKING
Clean using warm soapy water and soft cloth	Slip fit - 390 grams, Ratchet fit - 420 grams	50 pieces per carton
Do not use solvents or abrasives		

Udyogi

294, B. B. Ganguly Street,
2nd Floor, Kolkata - 700 012

E-mail : info@udyogi.net
Website : www.udyogisafety.com

Tel. : +91 33 2225 1470/71/72