Assignment 2

Satvik Chauhan (Y9521), Pankaj More (Y9402)

Simulation

The Simulation part of the assignment was written in **Haskell** (pure functional programming language). Some of the implementation details are given below:

- We have used **State Monads** to simulate the machine.
- A virtual machine is implemented which requires a scheduler to run.
- The scheduler function requires the readyQueue and returns the pair (selected process,Alloted Burst time).
- The Alloted burst time is same as the next CPU burst for all the schedulers except round robin.
- The time quanta taken for round robin in 6 by default. It can be varied on users choice.
- The parameters to generate the initial data are varied like heavy CPU bound processes or IO bound processes .
- An assumption is made that the process starts with a CPU burst and ends with a CPU burst . So the number of CPU bursts is one more than the number of IO bursts.

We have written a python script to generate the distributions for inter arrival times , priority , IO and CPU bursts

- The most popular and fast python library called NumPy was used to generate these distributions.
- The value of λ for exponential and poisson distributions is taken to be 10. IO Bursts are taken from uniform distribution in the range 0 to 9. Besides, the uniform distribution for generating priorities is from the range 0 to 9. Number of processes is N = 20. Number of cpu bursts is 500 and io burst is 499.

We have drawn charts also using the **haskell chart library**. We have shown the Bar graph comparison of average response, turnaround and waiting times for all the standard algorithms. To run use the following steps.

- python $seed_data.py$
- runhaskell process.hs

- \bullet runhaskell drawBar.hs
- \bullet runhaskell drawBarP.hs
- runhaskell drawChart.hs

Then we have shown the comparison of average response .waiting and turnaround times for three priority categories

NACH OS

- Our system can run up to 16 threads at the same time without crashing. Thereafter the behaviour is erratic as documented in the source code.
- The kernel is made preemptive by using timer interrupts every 100 ticks. Every 100 ticks , Alarm::CallBack(), our timer interrupt handler is called.
- The main thread must have a response time of 0. There after the minimum response time is 10 ms due to context switching. Process with priority 9 is guaranteed to have a response time of 10 ms.
- \bullet Our implementation consists of multi level queues , highQueue for priority 9 process , midQueue for process between priority 5 and 8 , and the lower priority processes are put in lowQueue.
- Excluding the time spent in servicing priority 9 processes, the cpu spends 80 percent time in mid queue and 20 percent time in low queue.
- This and rr scheduling guarantees that mid queue processes will have a finite response time.
- The idea of cpu time division between mid and low queues makes the scheduler realistic and saves the low priority processes from starvation.

STATS

- Thread Name: child TotalTicks: 261 PID: 4 Priority: 7 Burst Time: 38 Arrival Time: 213 Response Time: 10 Waiting Time: 10 Turnaround Time: 48
 - Thread Name : main TotalTicks : 310 PID : 0 Priority : -1 Burst Time : 138 Arrival Time : 0 Response Time : 0 Waiting Time : 172 Turnaround Time : 310
 - Thread Name : child TotalTicks : 586 PID : 2 Priority : 9 Burst Time : 170 Arrival Time : 35 Response Time : 10 Waiting Time : 10 Turnaround Time : 551
 - Thread Name : child Total Ticks : 728 PID : 3 Priority : 4 Burst Time : 116 Arrival Time : 68 Response Time : 61 Waiting Time : 113 Turnaround Time : 660
 - Thread Name : child Total Ticks : 951 PID : 5 Priority : 7 Burst Time : 96 Arrival Time : 548 Response Time : 38 Waiting Time : 258 Turnaround Time : 403
 - Thread Name : child TotalTicks : 1051 PID : 6 Priority : 4 Burst Time : 96 Arrival Time : 638 Response Time : 41 Waiting Time : 79 Turnaround Time : 413
- Thread Name : child TotalTicks : 261 PID : 4 Priority : 9 Burst Time : 38 Arrival Time : 213 Response Time : 10 Waiting Time : 10 Turnaround Time : 48
 - Thread Name : main Total Ticks : 310 PID : 0 Priority : -1 Burst Time : 138 Arrival Time : 0 Response Time : 0 Waiting Time : 172 Turnaround Time : 310

Thread Name : child TotalTicks : 731 PID : 2 Priority : 1 Burst Time : 170 Arrival Time : 35 Response Time : 10 Waiting Time : 167 Turnaround Time : 696

Thread Name : child TotalTicks : 752 PID : 3 Priority : 6 Burst Time : 136 Arrival Time : 68 Response Time : 10 Waiting Time : 114 Turnaround Time : 684

Thread Name : child TotalTicks : 854 PID : 5 Priority : 2 Burst Time : 86 Arrival Time : 548 Response Time : 10 Waiting Time : 182 Turnaround Time : 306

Thread Name: child TotalTicks: 954 PID: 6 Priority: 7 Burst Time: 86 Arrival Time: 641 Response Time: 10 Waiting Time: 10 Turnaround Time: 313

• Thread Name : child TotalTicks : 261 PID : 4 Priority : 6 Burst Time : 38 Arrival Time : 213 Response Time : 10 Waiting Time : 10 Turnaround Time : 48

Thread Name : main Total Ticks : 310 PID : 0 Priority : -1 Burst Time : 138 Arrival Time : 0 Response Time : 0 Waiting Time : 172 Turnaround Time : 310

Thread Name : child TotalTicks : 731 PID : 2 Priority : 0 Burst Time : 170 Arrival Time : 35 Response Time : 10 Waiting Time : 167 Turnaround Time : 696

Thread Name: child TotalTicks: 752 PID: 3 Priority: 3 Burst Time: 136 Arrival Time: 68 Response Time: 10 Waiting Time: 114 Turnaround Time: 684

Thread Name : child TotalTicks : 854 PID : 5 Priority : 7 Burst Time : 86 Arrival Time : 548 Response Time : 10 Waiting Time : 182 Turnaround Time : 306

Thread Name : child TotalTicks : 954 PID : 6 Priority : 9 Burst Time : 86 Arrival Time : 641 Response Time : 10 Waiting Time : 10 Turnaround Time : 313




Figure 1: Averages . Preemptive sjf clearly perform better than others . Round robin has a good response time




Figure 2: Average Response time . It can be clearly seen that the average response time for priority 9 is zero for preemptive priority scheduling




Figure 3: Average turnaround time. Again preemptive priority scheduling for priority 9 beats other




Figure 4: Average waiting time