
When Can Language Models Join Without Lexical Cues?

Unique-Path Traversal versus End-to-End Accuracy under Path Ambiguity

Pankaj Pandey
Independent researcher, India
mightypn.nits@gmail.com
<https://github.com/pankajnits/oir>

Abstract

We ask whether multi-hop answering over knowledge graphs needs readable predicates, or only equality among identifiers. **Opaque isomorphic reasoning (OIR)** is a measurement protocol: a renaming σ of entities and relations that we verify to be injective on each instance’s finite atom set, with no legend in the prompt. HMAC-SHA256 is one generator of σ , not a cryptographic or privacy primitive.

Finding. Unique sealed routes still join. Competing sealed routes typically yield UNKNOWN, not the decoy. With the start entity already named in the question, OpenAI opaque unique is 32/32; both-opaque unique is 32/32 for Composer 2.5, OpenAI gpt-5.6-sol, and Grok 4.5. On the 26 city-valued WIKI-H5 items, unique English, unique opaque, and English two-path are 26/26; named-arm opaque two-path is 5/26, 2/26, 2/26 across three draws of the unpinned alias (August: UNKNOWN 21, decoy 0, selective accuracy 5/5). The $n=32$ lock is 6/32: one extra gold on a non-city P159 HQ; both decoys fall on items whose gold is one of those six, so the city slice has decoy 0. A city-typed OpenAI freeze at $n=200$ (every HQ is Wikidata P31 city-like; QIDs re-checked live) repeats the pattern: unique English/opaque 200/200, English two-path 199/200, named-arm opaque two-path 38/200 (Wilson [0.14, 0.25]; UNKNOWN 151, decoy 11), plan 200/200. Exact-match under two sealed routes is strongly sensitive to prompt surface form (Sclar et al., 2024). The largest OpenAI move at 512 tokens on cyclic decoys is case-id wording (same-date 11 September: named-arm 5/32 vs. hashed ids 20/32; ARM line kept). Later same-day draws are +18 and +19 items; August vs. September +14 mixes dates. The ARM line at 4096/medium is non-monotonic and interacts with decoy type (cyclic/constant: no ARM 25/27, H5 20/10, K2 30/26). English relation names restore OpenAI even with anonymous entities (OE two-path 32/32 vs. both-opaque 1/32). We score the answer node, not an emitted (r_1, r_2) . Seals remove lexical cues; they are not a confidentiality proof.

1 Introduction

The scored Wikidata question is *What city is the headquarters of the company led by Michael Eisner?* English unique-path context walks `works_at` then `headquartered_in` to Burbank; that success may use English predicates, or only equality among identifiers. The two-path decoy is a second `person`→`company`→`city` route (`partner_of/located_in`) to Kansas City. Opaque two-path keeps the English question and entity names; those predicates become HMAC tokens (`works_at` $\mapsto$ E334675310f05 on the scored Eisner item). Figure 1 is the OpenAI named-arm relation-only




Figure 1: OpenAI WIKI-H5 on Wikidata ($n=32$, start in q ; relation-only). Stacked bars are gold / decoy / UNKNOWN; whiskers are Wilson 95% intervals on exact match (item-level, one August draw). English unique/two-path 31/32; opaque unique 32/32; named-arm opaque two-path 6/32 (mostly UNKNOWN). City-valued subset: unique-path 26/26, opaque two-path 5/26 (decoy 0). Prompt-surface ablations of the same graphs are Section 5.2, not plotted.

2×2 . On 26 city-valued items the unique-path cells are 26/26 and named-arm opaque two-path is 5/26 (all misses UNKNOWN). The $n=32$ bar is 6/32: one extra gold on a non-city P159 HQ; both decoys fall on items whose gold is one of those six. A city-typed OpenAI $n=200$ freeze (Appendix A) is unique-path 200/200 and named-arm opaque two-path 38/200. Prompt-surface packing of the same graphs is Section 5.2 and Appendix B.

OIR measures whether a model can join after English predicate strings are replaced by keyed opaque tokens. We write a 2-hop as two inferred maps (only the answer node is scored): selection $q \mapsto (r_1, r_2)$ and traversal $(v_0, r_1, r_2, G) \mapsto v_2$. Opacity does not, by itself, block traversal. The question is when the prompt no longer maps query semantics onto one of two sealed relation sequences. Putting the start entity in q as the same atom as in V (**start in q**) separates that question from start-entity identification.

Each instance uses a keyed injective σ on that instance’s atom set (HMAC-SHA256, 48-bit tokens; Section 4). The model emits the answer node in the graph’s namespace or UNKNOWN; recovering σ^{-1} is not scored. A written hop is an execution control. Matched versus novel demonstrations test in-prompt reuse of shown seals.

OIR is a measurement protocol. HMAC renaming is the same family as PrivGemo’s entity map ϕ_Q (Tan et al., 2026); we apply it to relation strings, which that paper leaves as original or clustered schema labels. “Lexical cues” on the primary 2×2 means relation strings (entities stay English); both-opaque is a separate ablation. English multi-hop scores should not be read as evidence that the same join succeeds once predicates are sealed and two same-type routes compete.

This paper reports: (i) unique-route sealed execution with the start in q and no written hop; (ii) under two competing sealed routes the usual reply is UNKNOWN, not the decoy, and exact-match moves with prompt surface form (case-id wording; ARM line non-monotonic; Section 5.2); (iii) matched demonstrations restore shown seals, while novel seals do not. What is new is the interaction of opacity with path ambiguity, not opacity alone, and how large a prompt-surface move can be on the same sealed graph. Cited privacy KGQA keeps relation strings as readable words (Ning et al., 2026; Tan et al., 2026; Liu et al., 2026). We seal *relation* strings, keep entities English, and cross that with path ambiguity. Unique routes succeed; two competing same-type routes are underspecified and packaging-sensitive (Table 2).

Work	Hidden	Remote task	Join under opacity
ICL	substitution text	ICL task accuracy (bijection inferred)	ICL tasks
CIPHERS			
ARoG	entities; relations readable; topic names in q	retrieve + generate (relations, concepts)	privacy KG-RAG
PrivGemo	entities (HMAC); relations original or clustered schema words	rank retrieved paths; local plaintext answer	privacy KG-RAG
CoR	opaque entity IDs; relations readable	relation-centric exploration	KGQA
OIR	relations (primary 2×2); entities too (ablation); one join or none	emit graph-namespaces answer (no local decode)	selection vs. traversal

Table 1: Related protocols. PrivGemo HMAC-seals entities; relations remain original or clustered schema labels. OIR sends one graph and scores the answer token from the same model.

2 Related Work

Think-on-Graph and Reasoning-on-Graphs select the next readable relation (Sun et al., 2024; Luo et al., 2024). Ciphred ICL is not path ambiguity on a labeled graph (Fang et al., 2025; Guo et al., 2026). GSM-Symbolic swaps entity names in English math (Mirzadeh et al., 2025); 2WikiMultihopQA is a readable multi-hop control (Ho et al., 2020).

ARoG anonymizes *entities* while relations stay the retrieval language (Ning et al., 2026). PrivGemo HMAC-seals entities (ϕ_Q , e.g. `ent_17`); relations stay original labels or clustered schema words, not keyed opaque tokens, and a local Hand answers on the raw graph after a remote Brain ranks retrieved paths (CWQ 67% $\rightarrow$ 59%; WebQSP 75%) (Tan et al., 2026). CoR explores readable relations because entities often have no semantics beyond opaque IDs — the OE hide-set, not relation-only WIKI-H5 (Liu et al., 2026). Tang et al. (2023) find LLMs fail when relation names are replaced by symbols (`r1`) and rules must carry deduction; OpenAI unique-path opaque 32/32 is the complementary case: sealed relations still traverse when topology fixes the route. Guo et al. (2025) report collapse to random guessing among end entities when distractor two-hops have other sources. Named-arm Wiki-H5 opaque two-path, with UNKNOWN allowed, is abstention rather than guessing (OpenAI decoy 2/32, UNKNOWN 24/32). Section 5.2 shows that this is a named-arm fact for at least Grok: no-ARM opaque commits are near chance. A forced-choice arm is not in this evaluation (Section 7) and would put those protocols on the same scale. OIR withholds retrieved paths on the free arms (Table 1). The primary cell seals relations while entities stay English; both-opaque is a separate ablation.

Chain-of-thought and Text-to-SQL externalize plans over English (Wei et al., 2022; Yu et al., 2018). We ask a behavioral question: can a pretrained model join when the relation vocabulary is freshly randomized and no plan is given? A sealed plan is then an execution upper bound. NLGraph and Talk like a Graph encode graphs without readable typed predicates (Wang et al., 2023; Fatemi et al., 2024); OIR starts from a labeled KG and removes only the relation lexicon. ARM headers are a prompt-surface feature (Sclar et al., 2024). Symbol tuning, binding-ID analyses, and compositional-limit studies change the labels or the task (Wei et al., 2023; Feng and Steinhardt, 2024; Dziri et al., 2023). OIR holds the join, hop length, graph size, and question template fixed and replaces relation strings; OpenAI unique-path opaque traversal stays at 32/32, so that removal withdraws the cue that would otherwise select between routes rather than blocking execution.

3 Problem Formulation

Let $G = (V, R, T)$ be a labeled multi-relational graph ($T \subseteq V \times R \times V$) and q a natural-language or programmatic query with answer $a \in V$. A **seal** σ is a keyed map from entity and relation strings to opaque tokens that we verify to be injective on the finite normalized atom set of each

evaluation instance. We reject any instance where two distinct raw atoms normalize to the same string. Truncated HMAC-SHA256 is not injective over $\{0, 1\}^*$; we use 48-bit truncation because that width is injective on our small per-instance atom sets, not as a cryptographic bound. On the scored Wikidata 2×2 instances, no HMAC collision was observed. HMAC is computed from the normalized atom string; entity and relation types are not domain-separated, so identical plaintext yields the same token regardless of type. On each scored evaluation instance the normalized entity strings and relation strings are disjoint, so no entity is identified with a relation. The model receives G or $\sigma(G)$ and a query form built from σ (or from English, depending on the arm) and must return the answer node in that namespace; recovering σ^{-1} is not scored. Sealing is deterministic *given the instance key*; the same plaintext need not map to the same token across prompts.

A 2-hop join factors as two maps we measure separately:

$$\text{selection: } (q, G, \mathcal{C}) \mapsto (r_1, r_2), \quad (1)$$

$$\text{traversal: } (v_0, r_1, r_2, G) \mapsto v_2. \quad (2)$$

In general, traversal is set-valued ($\tau_G: V \times R \times R \rightarrow 2^V$); we evaluate only instances for which $|\tau_G(v_0, r_1, r_2)| = 1$ for the gold plan (and, on two-path items, for the decoy plan as well), so each scored route has a unique tail. Uniqueness is per plan, not “one answer in G .” We write $q \mapsto (r_1, r_2)$ when G and prompt context $\mathcal{C}$ are held fixed. A sealed join plan supplies (r_1, r_2) and tests (2). Unique-path items with v_0 already in q also test (2) when topology leaves only one route. Free sealed English tests (1) then (2) together. Dual-path items hold G fixed, give two complete routes from v_0 , and vary whether demonstrations expose the gold seals. The CEO free-English arm does *not* put v_0 in q as a single graph atom (the question is hashed piecewise), so it is not a pure test of (1).

A 2-hop is *structurally executable* when (r_1, r_2) is given, or when topology leaves only one 2-hop from a start already in q . The prompt *explicitly maps* query semantics onto one relation sequence when it contains English predicates, a legend, or demonstrated seals. When two complete routes exist and relation tokens are arbitrary HMAC strings with no such mapping supplied, selection is *unsupported by explicit cues* under this construction. Residual statistical structure can remain (token form, order, HMAC vs. permutation rates); we do not claim mathematical unidentifiability. Without an external semantic-to-symbol map, the gold route is not explicitly identifiable from the sealed two-path graph alone; any successful selection must rely on residual statistical cues or information supplied elsewhere in the prompt. Low exact-match is therefore unsurprising when the prompt provides no explicit mapping; it is not evidence that traversal failed. Dual-path separates those cases: in-prompt reuse of demonstrated relation-seal correspondences restores end-to-end accuracy; novel seals receive no such mapping. Models may abstain (UNKNOWN) rather than guess. That is selective prediction (El-Yaniv and Wiener, 2010; Geifman and El-Yaniv, 2017), studied in language models as calibration and abstention (Kadavath et al., 2022; Wen et al., 2025): coverage is the fraction of items with a non-UNKNOWN parse, and selective accuracy is exact match among those items, not a forced-choice among the two routes.

After sealing, the Eisner unique-path CONTEXT is Michael_Eisner | E334675310f05 | The_Walt_Disney_Company then The_Walt_Disney_Company | Eac04fab538ca | Burbank (12-hex tokens; entities remain English on the primary 2×2).

We use five measurement arms. **Readable English** is the baseline (start in q ; names and predicates unsealed). **Unique opaque** has one 2-hop and no plan: execution when topology uniquely determines the route. **Two-path opaque** has two same-type 2-hops and no plan: end-to-end behavior when two complete routes compete and the prompt supplies no semantic-to-symbol map; the scored output is the answer node or UNKNOWN, not (r_1, r_2) . **Sealed join plan** writes (r_1, r_2) over σ -atoms (execution control); a non-LLM router saturates on the same sequence. **Free sealed English** seals the question and graph with no plan and no legend. On CEO, the question is hashed piecewise, so the full person atom in G typically does not appear in q (confounded; not the matched factorial). Additional scaffolds (name/key legends, sealed demonstrations) appear as ablations.

The scored output on every free arm is that answer node (plaintext city when entities stay English; $\sigma(a)$ when entities are sealed) or UNKNOWN. We infer whether selection was supported from those end-to-end outcomes and from controls (unique topology, written hop, matched vs. novel seals); we do not score an emitted (r_1, r_2) . Throughout, “selection failure” names that inference about the latent (r_1, r_2) stage; we do not observe the pair.

4 Method

Seal recipe. Normalize each atom: strip; collapse whitespace to `_`; map other non-alphanumeric characters (except underscore, period, hyphen) to `_` using the ASCII class `[A-Za-z0-9_.-]` (so `Zürich`→`Z_rich`; pure CJK keeps Unicode); truncate to 64; empty maps to `EMPTY`. The CEO JSON already deleted diacritics upstream. Distinct raw atoms must normalize to distinct strings. Tokens are HMAC-SHA256 over UTF-8 bytes with a per-item 16-byte key; the token is `E` plus the first 6 digest bytes as 12 hex digits. HMAC is keyed renaming, not a security mechanism: 48-bit truncation is instance-wise injective on our small atom sets. On the scored Wikidata 2×2 graphs, normalization and HMAC produced no collisions among prompt atoms. The intervention removes lexical semantics and also changes token-level surface statistics; permutation and alphanumeric generators assess robustness to that latter variation (Table 8). The atom `Michael Eisner` normalizes to `Michael_Eisner`, so those two strings receive the same seal. Hashing the question token-by-token does not reconstruct that graph atom, which is the missing-start failure a name-binding wrapper is designed to prevent. Reported opaque cells are performance under this keyed HMAC construction, not a claim that every opaque identifier distribution yields the same rate.

Matched 2×2 (start in q). The $n=32$ suite is a seeded random sample of 32 of 73 Wikidata-derived CEO records (`random.Random(20260821).sample`; Vrandečić and Krötzsch, 2014), not a published CEO benchmark and not a hand-picked subset. Each instance is 4 triples (unique-path: 6 entities with a disconnected decoy island; two-path: 5 entities sharing the start). The gold two-hop uses `works_at` then the headquarters relation; the question says “led by”. The competing two-path route is synthetic (`ambig_edges` attaches record $i+1$ ’s company/HQ under `partner_of/located_in`; not a Wikidata fact; decoy HQ pool = gold HQ pool). To isolate relation selection from start-entity identification we keep the start string in the question and hold hop length, template, and graph size fixed. Two factors vary: relation labels (English vs. HMAC) and topology (one 2-hop from the start vs. two). Tails are intended as the same type; Wikidata P159 was not filtered (buildings/stations/a street among gold HQs; both OpenAI opaque two-path decoys sit on city/non-city pairs; Appendix A). On Wikidata two-path graphs both intermediates are companies (`works_at/headquartered_in` vs. `partner_of/located_in`). In the primary run the gold 2-hop is listed before the decoy 2-hop in `CONTEXT`; that order is the same in the English and opaque arms. A shuffled listing of the same 32 graphs and HMAC keys (16 gold-first, 16 decoy-first) is a robustness check on a later endpoint snapshot (Appendix A): English two-path 29/32, opaque two-path 5/32 (UNKNOWN 25/32, decoy 1/32, other 1/32=`LOD`). Opaque gold-first is 3/16 vs. decoy-first 2/16 (decoy 0/16 vs. 1/16): putting the decoy route first does not raise the decoy rate.

The primary two-path prompt is a single user message:

```
MODEL UNDER TEST. Read ONLY this file. Use CONTEXT only.
No other files.
Format: ANSWER_PLAIN[...]: <city_or_UNKNOWN>
ARM OPAQUE_AMBIG: opaque relations, English entities;
two 2-hops from start.
```

It does *not* contain the equality-recipe line (Appendix J). The format token is `<city_or_UNKNOWN>`, but six gold HQs are not cities (Appendix A). A model that obeys the format on those items must emit `UNKNOWN`. The 26 city-valued items are the primary report in Section 5.1; the $n=32$ hash-pinned cell is the robustness note and the lockfile. OpenAI English two-path is 31/32 under that `CONTEXT`-only instruction, so the line does not by itself force abstention. Readable names (Eisner, Burbank) still leave OpenAI at `UNKNOWN` 24/32 on opaque two-path: either parametric HQ is treated as inadmissible, or the verb does not map onto one seal. We cannot separate those readings here (Section 7). The CEO three-arm decoy 2-hop begins at a different person; it is not the matched two-path factorial.

Further constructions. The relation-only factorial keeps entities English. A second isolation suite on the same 32 CEO records seals entities, relations, or both, always with the start token in q . Opaque-entity / English-relation (OE) is the ARoG-like cell: readable predicates, anonymous nodes. Both-opaque (Wiki-OO) seals entities *and* relations; it is a complementary ablation, not the primary relation-only 2×2 . Readable entity names therefore leave residual pretrained world knowledge as a possible cue; both-opaque is not a substitute for synthetic identifiers.

WikiMovies facts are sampled from the public MetaQA movie KB (Miller et al., 2016; Zhang et al., 2018). MOVIE-A32 and MOVIE-A100 leave English verbs such as *directed* in q ; MOVIE-B hashes question atoms except the bracketed start entity. We exclude a genre-vs-language variant because object type would bypass relation selection. This is not an evaluation on the official MetaQA 14K test split. Dual-path holds G fixed with two complete 2-hop routes and varies whether demonstrations expose the gold seals (Appendix D).

Scoring. The format asks for one answer token in the graph’s namespace or UNKNOWN. Primary metric: exact match (UNKNOWN is a miss). Scored UNKNOWN on Wiki-H5/Wiki-OO is an explicit UNKNOWN line. Dual and some no-hop OpenAI cells stored empty completions as UNKNOWN. On two-path arms we also report decoy and UNKNOWN rates (Table 3). Wilson 95% intervals use $z=1.96$ (Wilson, 1927) ($0/32 \Rightarrow [0.00, 0.11]$; $6/32 \Rightarrow [0.09, 0.35]$; $32/32 \Rightarrow [0.89, 1.00]$). Those intervals treat the 32 items as Bernoulli trials on a single draw; they are not a generation-variance interval. OpenAI WIKI-H5 $k=3$ (August lock plus two later draws) is Section 5.1. On the OpenAI Wikidata 2×2 , English two-path is correct and opaque two-path is not on 25 of 32 paired items, and the reverse never occurs (McNemar exact two-sided complete-case $p=5.96 \times 10^{-8}$; McNemar, 1947). That is the two-path paired contrast, not an interaction test, and it largely measures removing the cue that made one sealed route identifiable. The empirical content is the response mode (UNKNOWN vs. decoy) and prompt-surface packing (Section 5.2). That p clears 0.001 (confirmatory McNemar only). **Isolation** means one quiz per file with gold answers stored outside the model-visible prompt (stricter than multi-quiz **batch** files). Isolation $n=32$ uses one quiz per file and a per-item HMAC. Cells marked **n.r.** were not evaluated; we never impute them as zeros. *Mid-hop error* means the model emits the sealed mid-hop company token instead of the headquarters answer.

Models. The primary family is OpenAI `gpt-5.6-sol` (hereafter OpenAI). Composer 2.5 and Grok 4.5 are a robustness note on the same quiz files, not a ranking (Table 3). Secondary packaging probes additionally use an unversioned Claude endpoint (Anthropic model id not stored; Appendix F). `gpt-5.6-sol` is the GPT-5.6 Sol Chat Completions endpoint (Sol is the flagship-equivalent tier of the GPT-5.6 family; <https://developers.openai.com/api/docs/models/gpt-5.6-sol>). OpenAI cells use that API with no tools, temperature omitted because that family rejects temperature 0 (`max_completion_tokens` 512). The runner does not pass `reasoning_effort` and used the unpinned alias `gpt-5.6-sol`; the August lock stores the parsed answer, not the API model string. $k=3$ OpenAI draws (August lock plus two 15 September 2026 draws with JSON sidecars that *do* store `returned_model`) are reported in Section 5.1. Composer 2.5 and Grok 4.5 ran through Cursor’s agent SDK on the same quiz files, with a reply-only preamble OpenAI never received. Tools, retry, and empty-reply handling are not equated (OpenAI locked empty completions as UNKNOWN). Unique-path opaque stays high on all three (Composer 27/32, OpenAI 32/32, Grok 30/32): those SDK cells still execute unique-path joins. Named-arm difference-in-differences (DiD) is most readable for OpenAI (Grok English two-path 4/32 vs. English, no ARM, hashed ids 24/32; Section 5.2). Unique both-opaque 32/32 is the three-family traversal cell. Isolation quizzes (`runs/`) and locked exact-match scores (`results/`) are at <https://github.com/pankajmits/oir>. Inference settings are Appendix A.

5 Results

Table 2 names the cells. WIKI-H5 is the Wikidata CEO relation-only 2×2 with the start already in q (OpenAI primary; Composer/Grok are a different harness). WIKI-OO seals entities *and* relations on the same graphs; OE seals entities only. MOVIE-A32 is WikiMovies $n=32$ with English verbs still in q ; MOVIE-A100 is the $n=100$ version; MOVIE-B hashes those verbs except the start. Header $\times$ decoy is the same 32 people with hashed case ids, crossing the ARM line with cyclic vs. constant decoys (Section 5.2). MOVIE-B is a cross-dataset check, not a resampling of WIKI-H5. Packaging probes ($n \leq 16$) are Appendix G and do not bear on the 2×2 .

5.1 Opacity $\times$ path ambiguity

WIKI-H5 holds the start string in q and varies only relation lexicality (English vs. HMAC) and the number of 2-hops from that start (one vs. two). OpenAI is the primary family. Composer 2.5 and

ID	Dataset	Condition	n	Models	Scored
WIKI-H5	Wikidata CEO	rel-only 2×2 , start in q	32	OpenAI (primary)	node
WIKI-H5-200	Wikidata CEO, city P31	same 2×2 , QID freeze	200	OpenAI	node
Header $\times$ decoy	same 32 people	ARM line $\times$ decoy, hashed ids	32	3 families	node
Header $\times$ decoy-200	same 200 people	ARM $\times$ decoy, hashed ids	200	OpenAI	node
WIKI-OO	same graphs	both-opaque	32	3 families	$\sigma(a)$
WIKI-OO-200	$n=200$ freeze	both-opaque	200	OpenAI	$\sigma(a)$
WIKI-SHUF	same two-path	listing order	32	OpenAI	city
MOVIE-A32	WikiMovies	actor $\rightarrow$ movie $\rightarrow$ dir vs writer	32	3 models	person
MOVIE-A100	WikiMovies	same hops; verbs in q	100	OpenAI	person
MOVIE-A200	WikiMovies	$n=100$ prefix + 100 new actors	200	OpenAI	person
MOVIE-B	WikiMovies	same hops; verbs hashed	100	OpenAI	person
MOVIE-B200	WikiMovies	Condition B on $n=200$ freeze	200	OpenAI	person
DUAL	WikiMovies/synth	matched vs. novel demos	32	3 models	$\sigma(a)$
DUAL-200	WikiMovies $n=200$	matched vs. novel	200	OpenAI	$\sigma(a)$
CEO-NL	Wikidata CEO	piecewise q , no plan	32	3 models	$\sigma(a)$
CEO-NL-200	$n=200$ freeze	piecewise q , no plan	200	OpenAI	$\sigma(a)$

Table 2: Cell inventory, listed before results. WIKI-H5 is the OpenAI discovery (Composer/Grok in Table 3, not a ranking). Header $\times$ decoy and the case-id contrast are Section 5.2. Scored output is the answer node; six P159 golds are not cities, so the city-valued $n=26$ slice is the $n=32$ headline (Appendix A). WIKI-H5-200 is a separate city-typed QID freeze (OpenAI). A32/A100/B share the actor $\rightarrow$ movie $\rightarrow$ director vs. writer template; A100 Condition A uses a thinner ARM than A32. Isolation cells use per-item HMAC; batch three-arm $n=12/n=24$ share one key per file.

Grok 4.5 are Table 3 robustness, not a ranking: they used Cursor’s agent SDK with a preamble OpenAI never received.

Lead with the response mode, then the rate. On unique sealed routes OpenAI executes (opaque unique 32/32; plan on the two-path graph 32/32). On competing sealed routes the usual named-arm reply is UNKNOWN, not the decoy. The headline cell is the 26 city-valued items, where the format token `<city_or_UNKNOWN>` is well-posed: unique English, unique opaque, and English two-path are 26/26; named-arm opaque two-path is 5/26, 2/26, 2/26 across three draws of the unpinned alias ($k=3$ below). August (draw 1): UNKNOWN 21, decoy 0, selective accuracy 5/5; McNemar 21 vs. 0, $p=9.54 \times 10^{-7}$; McNemar, 1947. Unique-path Δ_{opq} is 0/26.

The hash-pinned $n=32$ lock is the robustness note, not the headline. English unique 31/32, English two-path 31/32, opaque unique 32/32, named-arm opaque two-path 6/32 (UNKNOWN 24, decoy 2). Both decoys fall on items whose gold is one of the six non-city P159 HQs (items 27 and 31; Appendix A); a model that obeys the city format on those items is forced toward UNKNOWN or a type error. Wilson 95% on the August $n=32$ lock (item-level, one draw): 32/32 $\Rightarrow$ [0.89, 1.00], 31/32 $\Rightarrow$ [0.84, 0.99], 6/32 $\Rightarrow$ [0.09, 0.35]. On the city slice of that same draw, 5/26 $\Rightarrow$ [0.09, 0.38]. Figure 1 plots the $n=32$ OpenAI 2×2 .

City-typed $n=200$ (OpenAI). The $n=32$ source file has 73 CEO rows and six non-city P159 golds. WIKI-H5-200 is a new freeze: 200 unique people and companies, HQ frequency capped at 3, every HQ an instance of a city-like Wikidata class, person/company/HQ QIDs stored, and all 200 P169+P159+P31 triples re-checked live against the Query Service (`wikidata_ceo_hops_n200.json`). It does not overwrite the $n=32$ lock. OpenAI named-arm: unique English and unique opaque 200/200, English two-path 199/200, opaque two-path 38/200 (UNKNOWN 151, decoy 11; Wilson [0.14, 0.25]), plan 200/200. The 38/200 rate sits inside the $n=32$ Wilson band for 6/32. Same-date hashed-id H5-cyclic at 512 tokens is 134/200 vs. named-arm 38/200 (ARM line kept): the case-id gap is not an $n=32$ artifact. Header $\times$ decoy at 4096/medium on the same 200 people (Table 5): cyclic/constant no ARM 174/151, H5 129/44, K2 179/144; English no ARM cyclic 197/200. H5 cyclic vs. constant McNemar 95 vs. 10, $p=1.6 \times 10^{-18}$; no-ARM 30 vs. 7, $p=1.9 \times 10^{-4}$. Both-opaque two-path is 12/200 (unique 200/200; OE two-path 200/200). Listing-order shuffle: opaque two-path 59/200 (gold-first 25/100, decoy-first 34/100). CEO-NL free sealed English 0/200 with plan 200/200. WikiMovies Condition A 122/200 two-path (unique 200/200); Condition B 7/200; Dual novel 2/200 vs. matched 200/200. Condition A $n=200$ uses the Wiki-H5 topology ARM line, not the A100 banner ARM

OPAQUE_AMBIG $n=100$, so 122/200 is not a resample of 96/100. $n=200$ is OpenAI-only; three-family cells stay at $n=32$.

Let Δ_{opq} be opaque minus English exact-match on $n=32$. Unique path: $\Delta_{\text{opq}} = +1/32$ (32/32 vs. 31/32), one non-city miss. Two-path: $\Delta_{\text{opq}} = -25/32$ (6/32 vs. 31/32). The descriptive difference-in-differences is $-26/32$. Section 4 already notes that the gold route is not explicitly identifiable from the sealed two-path graph, so that DiD substantially measures removing the disambiguating cue. The paired count remains: 25 items English-correct and opaque-wrong, 0 reverse (McNemar exact two-sided $p=5.96 \times 10^{-8}$; McNemar, 1947). Opacity is not a randomized within-item treatment. Wilson intervals treat items as independent Bernoulli trials, which the cyclic decoy construction slightly violates (Appendix A). An optional sign-flip of the per-item interaction contrast is Appendix I (same numerical p , different test).

OpenAI $k=3$. Every August cell is one sample; temperature is omitted. The $k=3$ protocol reuses that August lock as draw 1 and adds two 15 September 2026 draws on the same quiz files, same alias, 512 completion tokens, sidecars storing returned_model (factorial_2x2_iso_gpt56k3r2.json, factorial_2x2_iso_gpt56k3r3.json). Those later draws are a new snapshot of the unpinned alias, not a resample of a pinned checkpoint, so they do not deliver a generation-variance interval.

Named-arm opaque two-path is 6/32, 3/32, 3/32 (city-valued 5/26, 2/26, 2/26). Draws 2 and 3 are the same day and give identical counts. The same shape appears in Composer (10, 7, 6) and Grok (1, 0, 0): August is highest in all three families. Within a snapshot the counts barely move; the August-to-September gap looks like drift in the served alias and moves all three families the same direction on this cell. The later draws stay well below the hashed-id H5-cyclic rate (20–22/32). Unique opaque is 32/32, 31/32, 32/32; English two-path is 31/32, 30/32, 30/32; plan is 32/32 on every draw. A separate 11 September snapshot of named-arm opaque two-path only (gpt56sep) is 5/32 (one NO_OUTPUT) and is not one of the three draws; with hashed-id H5-cyclic 20/32 that day it is the same-date case-id pair in Section 5.2.

This pattern is *not* a universal three-family exact-match rate. Unique-path opaque stays high on all three. On named-arm opaque two-path the usual reply is UNKNOWN, not the decoy. Named-arm English two-path is OpenAI 31/32, Composer 26/32, Grok 4/32 (UNKNOWN 28; English, no ARM, hashed ids 24/32): a packaging $\times$ family effect, not a ranking (Section 5.2). Opaque unique remains high (Composer 27/32, Grok 30/32); named-arm opaque two-path drops (10/32, 1/32); a written hop recovers (28/32, 32/32). Exact-match alone hides the behavior: opaque two-path is mostly UNKNOWN, not decoy. Coverage is the fraction of items with a non-UNKNOWN parse; selective accuracy is exact match among those items (El-Yaniv and Wiener, 2010; Geifman and El-Yaniv, 2017). Two-path coverage / selective accuracy (named-arm): OpenAI English 31/32, 31/31 and opaque 8/32, 6/8; Composer English 26/32, 26/26 and opaque 10/32, 10/10; Grok English 4/32, 4/4 and opaque 1/32, 1/1. A forced uniform guess among two routes would be 1/2; that is not the relevant null once UNKNOWN is allowed. Composer English two-path 26/32 is 26/26 on cities (all six misses are those P159 golds). Grok named-arm English two-path is 4/26: that named-arm abstention is not a format artifact. Composer named-arm opaque two-path, same Cursor preamble as the August lock: 10/32, 7/32, 6/32. Grok: 1/32, 0/32, 0/32. Unique-path cells were not resampled for those families.

On the same graphs under two other opaque generators, unique-path accuracy exceeds two-path accuracy (permutation 31/32 vs. 15/32; alphanumeric 29/32 vs. 12/32; Table 8). Direction agrees across three generators; the two-path *rate* is not invariant.

5.2 Prompt surface as a factor

The named-arm WIKI-H5 prompt contains this line:

```
ARM OPAQUE_AMBIG: opaque relations, English entities;
two 2-hops from start.
```

That sentence tells the model in English that two 2-hops exist. It is an uncontrolled treatment if abstention is attributed only to opacity-meets-ambiguity. Prompt-surface packing is a factor (Sclar et al., 2024). Two manipulations must not be collapsed.

Wikidata named-arm (iso. $n=32$)	OpenAI	Composer 2.5	Grok 4.5
English, unique	31/0/1/0	29/0/2/1	32/0/0/0
English, two paths	31/0/1/0	26/0/6/0	4/0/28/0
Opaque, unique	32/0/0/0	27/0/3/2	30/0/2/0
Opaque, two paths	6/2/24/0	10/0/22/0	1/0/31/0
Opaque two paths + plan	32/0/0/0	28/0/3/1	32/0/0/0

Table 3: Four-way outcomes: gold / decoy / UNKNOWN / other wrong token. OpenAI is the primary family (August lock; $k=3$ in the surrounding text). Composer 2.5 and Grok 4.5 used Cursor’s agent SDK with a reply-only preamble OpenAI never received; this table is not a ranking. On this table UNKNOWN is an explicit UNKNOWN line (missing/unparsed 0; both-named 0). Composer “other” is truncated gold `Lod` (English unique, opaque unique, and plan) plus one wrong city (`Fox_Plaza`→`Los Angeles`). OpenAI’s two decoys are P159 type-asymmetric pairs. Coverage and selective accuracy for every two-path row are in the surrounding text. Grok named-arm English two-path is mostly UNKNOWN.

Case-id wording, ARM line held fixed. The case id appears twice: in `Format: ANSWER_PLAIN[id]` and in the ID line. Named-arm uses `F22_OPAQUE_AMBIG_i; OPQ_H5_CYC` substitutes hashes `HDA_*`. ARM line and CONTEXT are identical on all 32 items. The clean 512-token pair is same-date 11 September: named-arm `gpt56sep 5/32` vs. hashed-id H5-cyclic `gpt56abl512 20/32` (one `NO_OUTPUT` each). That is +15 items, not a test of whether the prompt announces ambiguity: both prompts keep the ARM line. $k=3$ hashed-id gold is 20, 21, 22. Against named-arm 6/3/3 the gaps are +14, +18, +19. Only +18 and +19 are same-day (15 September); +14 is the August lock against the 11 September hashed-id cell and mixes dates.

ARM line, case ids held hashed. Header×decoy at 4096 tokens with medium reasoning effort (`header_decoy_ablation_iso_gpt56abl.json`) varies the ARM line on hashed ids (Table 4). K2 is a shorter ARM that still names two hops (ARM K2: `opaque relations; 2 same-type 2-hop(s) from start.`). Cyclic gold ranges over 10 items (H5 20 to K2 30); constant over 17 (H5 10 to no ARM 27). Decoy type moves the Wiki-H5 header (cyclic 20 vs. constant 10; McNemar 14 vs. 4, $p=0.031$) and not no-ARM (25 vs. 27, $p=0.625$). That header×decoy interaction is why the ablation is named as it is. Those cells are not at the Wiki-H5 512-token budget; K2 and no-ARM were not run at 512.

ARM line (OpenAI, hashed ids, 4096/medium)	Cyclic	Constant
no ARM	25/32	27/32
H5	20/32	10/32
K2	30/32	26/32

Table 4: Header×decoy gold counts on the same 32 people. English, no ARM, cyclic is 29/32. Composer/Grok: Appendix B.

ARM line (OpenAI, hashed ids, 4096/medium, $n=200$)	Cyclic	Constant
no ARM	174/200	151/200
H5	129/200	44/200
K2	179/200	144/200

Table 5: Header×decoy on the city-typed $n=200$ freeze (same people as `Wiki-H5-200`). English, no ARM, cyclic is 197/200. H5 cyclic vs. constant McNemar 95 vs. 10 ($p=1.6\times 10^{-18}$). Same-date 512-token hashed-id H5-cyclic is 134/200.

English Grok. Named-arm English two-path is Grok 4/32 (UNKNOWN 28). The English header×decoy cell (`ENG_NONE_CYC`) is 24/32. That cell has *no* ARM line and hashed ids, so two things differ from the 4/32 named-arm English prompt. Call it English, no ARM, hashed ids—not “arm-neutral English.” A prompt-verbatim Grok rerun of the named-arm English files (`grok45pn`) stays 4/32, so the Cursor preamble is not that gap. OpenAI named-arm English is 31/32 vs. English,

Arm	Ent.	Rel.	OpenAI	Composer	Grok
Unique path	opaque	Eng.	32/32	32/32	32/32
Two paths	opaque	Eng.	32/32	28/32	3/32
Unique path	opaque	opaque	32/32	32/32	32/32
Two paths	opaque	opaque	1/32	0/32	0/32
Two paths + plan	opaque	opaque	32/32	28/32	32/32

Table 6: WIKI-OO and OE on the same 32 graphs (start in q). OpenAI OE two-path 32/32; both-opaque two-path 1/32. Plan is a control.

no ARM, hashed ids 29/32: OpenAI English does not abstain either way. MOVIE-B topology-only two-path is 3/100; an archived banner that names the two routes is 25/100 (a different surface, not the Wiki-H5 case-id contrast).

What the data support: exact-match under competing sealed routes is strongly sensitive to prompt surface form. The largest OpenAI move at the 512-token budget on cyclic decoys is case-id wording (same-date 5/32 vs. 20/32). The ARM line at 4096/medium is non-monotonic and interacts with decoy type; it is not uniformly smaller than the case-id gaps. That is narrower than “whether the prompt flags the ambiguity,” and it is still worth reporting.

A consequence for the contrast with Guo et al. (2025). That work reports collapse to guessing among end entities when distractor two-hops have other sources. Our named-arm OpenAI cell is abstention (UNKNOWN 24/32, decoy 2/32), not a coin-flip onto the decoy. That “UNKNOWN rather than decoy” pattern is not a three-family law. Grok no-ARM opaque commits are 6 gold / 3 decoy cyclic and 1 / 5 constant (7 vs. 8 pooled): chance. For Grok, preferring UNKNOWN over the decoy is a named-arm phenomenon.

Composer/Grok hashed-id H5-cyclic cells used `--preamble none` and score 6/32 and 0/32; the named-arm locks used the Cursor preamble and score 10/32 and 1/32. Both families go *down* with hashed ids, a sign reversal relative to OpenAI. We did not re-query Composer named-arm with the prompt file verbatim, so that reversal mixes case-id wording with preamble deletion and is not interpretable. Grok is at floor on both opaque two-path cells.

5.3 Both-opaque and readable relations

Table 6 is a second isolation suite on the same 32 records (ANSWER_SEALED; start seal in q). Unique-path both-opaque is 32/32 for all three families. Composer/Grok relation-only unique (27/32, 30/32 in Table 3) is a different file, not evidence that hiding entities helps. Two-path both-opaque is OpenAI 1/32 (Wilson [0.01, 0.16]), Composer 0/32, Grok 0/32. A written hop recovers (32/32, 28/32, 32/32). OpenAI OE two-path (opaque entities, English relations) is 32/32: readable predicates restore end-to-end accuracy with anonymous nodes under this construction. Grok OE two-path remains 3/32.

WikiMovies unique-path with English verbs in q (MOVIE-A32) is 32/32 for all three families; opaque two-path is 17/32, 17/32, 0/32, with plan 32/32. MOVIE-A32 and MOVIE-A100 are the same actor→movie→director vs. writer template (person tails). A32’s ARM names two 2-hops; A100’s is OPAQUE_AMBIG $n=100$. On 32 A32 items matched by gold name (31 unique names) OpenAI is 17/32 vs. 29/32 under A100’s thinner ARM. The extra 68 items are 67/68, which is why the $n=100$ cell is 96/100. Keys differ; they cannot explain an English-name lookup. Director is always the first person-tail, so parametric knowledge and a listing-slot heuristic are not separated. Movie-B keeps those names, hashes the verbs, and is 3/100. The contrast is not a same-prompt Wiki-H5 replication; it remains a header-width comparison on WikiMovies (Section 5.2). Verbs in q can cue seals; we do not treat Condition A as a selection result.

5.4 WikiMovies: hashed verbs

Table 7 uses the same actor→movie→director vs. writer template as MOVIE-A32 (person-valued tails). Condition A leaves *directed/starred* in q (not a selection result). Condition B hashes those verbs: OpenAI unique 100/100, two-path 3/100 (UNKNOWN 87, decoy 0, both-named 10; Wilson [0.01, 0.08]). Coverage is 13/100 and selective accuracy 3/13. A written hop is 100/100. Com-

WikiMovies people (OpenAI, $n=100$)	Unique	Two-path
English relations, Condition A (verb in q)	100/100	100/100
Opaque relations, Condition A (verb in q)	100/100	96/100
Opaque relations, Condition B (verbs hashed)	100/100	3/100
Opaque two-path + plan, Condition B	—	100/100

Table 7: MOVIE-A100/MOVIE-B: same actor→movie→director vs. writer template as MOVIE-A32 (Miller et al., 2016; Zhang et al., 2018) (OpenAI $n=100$, start in q). Condition B: unique 100/100, two-path 3/100 (UNKNOWN 87, decoy 0, both-named 10; coverage 13/100, selective accuracy 3/13).

poser/Grok Condition A two-path: 62/100, 36/100; Condition B $n=100$ is OpenAI-only. Movie-B’s ARM names two 2-hops (Wiki-H5-style); A100 Condition A does not. The $n=32$ MetaQA-style template cell (Appendix H) is not MOVIE-B.

5.5 In-prompt seal reuse

Sealed demonstrations enable the corresponding joins when the relevant relation seals appear in the demos. Dual-path probes hold G fixed with two complete 2-hop routes (gold vs. decoy) and vary whether those gold seals appeared in the demonstrations. Matched-relation demos expose the gold relation seals; novel-relation demos teach seals that do not appear on the gold route. An explicit join plan is the execution upper bound on the same graphs. “Asymmetric” noise makes the decoy look cleaner; “balanced” noise is symmetric on both mids. Matched-relation is in-prompt reuse of demonstrated correspondences; it is not induction of a general cipher.

Isolation $n=32$ (Figure 2, Appendix D): OpenAI saturates matched-relation under both noise regimes (32/32, decoy 0). Novel-relation balanced is exact match 0/32: all 32 replies are UNKNOWN (24 empty completions). Novel-relation asymmetric is also 0/32 (UNKNOWN 24, of which 17 empty, decoy 8). An explicit dual-path plan scores 32/32. WikiMovies director/writer Dual is 32/32 vs. 0/32 for all three families (dualpath_wikimovies_iso_*; Composer novel decoy 2/32), with plan 32/32. On the synthetic Dual suite, Composer isolation-tag novel-relation UNKNOWN (composer25) is a sealed-demo helper; free-form composer25ff is decoy 32/32. Grok free-form (grok45ff) novel-relation asymmetric is UNKNOWN on all 32 items. Last-demo answer-token copy is 0/32 on every arm.

On a two-path graph a forced uniform guess among the two complete routes is 1/2; that null does not apply once UNKNOWN is a third action. The pattern is consistent with prompt-local reuse of demonstrated seals and provides no evidence of systematic transfer to unseen relation tokens. We do not interpret this as a variable-binding mechanism. Arm definitions: Appendix D.

5.6 Missing-start control

The CEO isolation three-arm is an execution upper bound plus a missing-start cell, not the isolation of selection. Join plans score 32/32 on both plaintext and sealed atoms; SealRouter given the gold sealed relation sequence is 32/32; free sealed English scores 0/32 (all UNKNOWN) for Composer 2.5, OpenAI, and Grok 4.5 (Table 11). We exclude a batched free-sealed cell that can succeed by returning a unique neighbor without using q .

6 Discussion

A join is structurally executable when the route is unique or (r_1, r_2) is given (OpenAI unique opaque 32/32; both-opaque unique 32/32 on three families; written hop OpenAI/Grok 32/32, Composer 28/32). The prompt explicitly maps query semantics onto one relation sequence when English predicates, a legend, or demonstrated seals are present. When two complete routes exist and that mapping is absent, the usual named-arm reply is UNKNOWN rather than the decoy (Table 3); we do not claim mathematical unidentifiability. Exact-match under two routes also moves with prompt surface form (Section 5.2): the largest OpenAI move at 512 tokens on cyclic decoys is case-id wording (same-date 5/32 vs. 20/32); the ARM line at 4096/medium is non-monotonic and interacts with decoy type (Table 4).

On city-valued items unique-path cells are 26/26 and named-arm opaque two-path is 5/26, 2/26, 2/26 (unique-path $\Delta_{\text{opq}} = 0/26$, so that two-path gap equals the descriptive DiD). English relations restore OpenAI end-to-end accuracy with anonymous entities (32/32); Grok still abstains (3/32). Dual-path reuses demonstrated seals; novel seals do not transfer. Unique topology with the start in q , English predicates, matched demonstrations, or a same- σ equality recipe restore execution; a bare schema list does not (Table 13). A high English two-path rate does not imply the same join once relations are opaque. OIR diagnoses residual join ability after readable relations and retrieved paths are withheld; PrivGemo keeps those paths and answers locally (Tan et al., 2026).

7 Limitations

OpenAI is the primary family. Composer/Grok used a different harness (Appendix A); Table 3 is not a ranking. The format token `<city_or_UNKNOWN>` makes six P159 golds ill-posed; the 26 city items (26/26 vs. 5/26, 2/26, 2/26) are the headline, $n=32$ the lockfile. The suite is $n=32$ of 73 records, one template, one seed; later Wiki suites reuse those records. Decoys are cyclic, so Wilson intervals are slightly optimistic (McNemar is not). Wilson intervals are item-level on a single draw; they are not generation variance. OpenAI WIKI-H5 $k=3$ mixes the August lock with two later draws of the unpinned `gpt-5.6-sol` alias (Section 5.1): same-day draws 2 and 3 match, and August is the high cell in all three families, so the useful reading is alias drift, not a generation-variance CI. Composer/Grok $k=3$ covers only the named-arm opaque two-path drop cell. English entities leave parametric cues; HMAC two-path rates vary by generator (6/32, 15/32, 12/32); short pronounceable symbols are not run. Selection is inferred from the answer node. Named-arm selective accuracy stays high (6/8, 10/10, 1/1); Grok no-ARM opaque commits are near chance when pooled (Section 5.2). Header $\times$ decoy at 4096/medium is Table 4: non-monotonic in the ARM line, with a header $\times$ decoy interaction (H5 20 vs. 10; no-ARM 25 vs. 27). At the Wiki-H5 512-token budget the same-date case-id pair is named-arm 5/32 vs. hashed-id H5-cyclic 20/32; August named-arm 6/32 vs. that 20/32 mixes dates. K2 and no-ARM were not run at 512. MOVIE-A32 vs. MOVIE-A100 (17/32 vs. 29/32) is a thinner ARM on WikiMovies, not that band. Dual novel OpenAI UNKNOWN includes empty completions (24/32 balanced, 17/32 asymmetric). Forced-choice, scored (r_1, r_2) , and an HQ-city swap are not in this evaluation. MOVIE-B and WIKI-SHUF are OpenAI-only. The ARM line was not randomized independently of case-id wording on the original lock. Composer hashed-id H5-cyclic used `--preamble none`; the named-arm Composer lock used the Cursor preamble, so that sign reversal is uninterpretable.

Ethical considerations

Instances use public Wikidata CEO records (CC0; Vrandečić and Krötzsch, 2014) and the MetaQA/WikiMovies movie graph as publicly released with WikiMovies (Miller et al., 2016) and MetaQA (Zhang et al., 2018) (upstream papers do not name a license string). Appendix cells additionally use 2WikiMultihopQA (Apache-2.0; Ho et al., 2020) and Spider (CC-BY-SA-4.0; Yu et al., 2018). No personally sensitive information is used. Per-item replies are hash-pinned in the repository, not released as a training corpus. OIR is a diagnostic, not a deployed anonymizer: treating HMAC seals as a confidentiality mechanism would over-trust prompts that still contain English names on the primary 2×2 .

8 Conclusion

Unique-route sealed execution succeeds with the start in q (opaque unique OpenAI 32/32; both-opaque unique 32/32 on three families). On the 26 city-valued items, unique-path cells are 26/26 and named-arm opaque two-path is 5/26, 2/26, 2/26 across three draws of the unpinned alias (August: UNKNOWN 21, decoy 0). The $n=32$ lock is 6/32 (UNKNOWN 24, decoy 2). City-typed OpenAI $n=200$: unique-path 200/200, named-arm opaque two-path 38/200 (UNKNOWN 151, decoy 11), hashed-id H5-cyclic at 512 tokens 134/200, both-opaque two-path 12/200, CEO-NL 0/200. Same-day September draws match each other; August is highest on this cell in all three families. Within-snapshot variance looks small relative to alias drift, and $k=3$ is not a generation-variance interval. Exact-match under two sealed routes is strongly sensitive to prompt surface form: the largest OpenAI move at 512 tokens on cyclic decoys is case-id wording (same-date 5/32 vs. 20/32); the

ARM line at 4096/medium is non-monotonic and interacts with decoy type (H5 20/10 vs. no ARM 25/27). OpenAI both-opaque two-path is 1/32. Grok no-ARM opaque commits are near chance, so “UNKNOWN rather than decoy” is not a three-family law.

References

- Zhiyu Chen, Wenhui Chen, Charese Smiley, Sameena Shah, Iana Borova, Dylan Langdon, Reema Moussa, Matt Beane, Ting-Hao Huang, Bryan Routledge, and William Yang Wang. FinQA: A Dataset of Numerical Reasoning over Financial Data. *EMNLP*, 2021.
- Nouha Dziri, Ximing Lu, Melanie Sclar, Xiang Lorraine Li, Liwei Jiang, Bill Yuchen Lin, Peter West, Chandra Bhagavatula, Ronan Le Bras, Jena D. Hwang, Soumya Sanyal, Sean Welleck, Xiang Ren, Allyson Ettinger, Zaid Harchaoui, and Yejin Choi. Faith and Fate: Limits of Transformers on Compositionality. *NeurIPS*, 2023.
- Ran El-Yaniv and Yair Wiener. On the Foundations of Noise-free Selective Classification. *JMLR*, 11:1605–1641, 2010.
- Zhouxiang Fang, Aayush Mishra, Muhan Gao, Anqi Liu, and Daniel Khashabi. ICL CIPHERS: Quantifying “Learning” in In-Context Learning via Substitution Ciphers. *EMNLP*, 2025.
- Bahare Fatemi, Jonathan Halcrow, and Bryan Perozzi. Talk like a Graph: Encoding Graphs for Large Language Models. *ICLR*, 2024.
- Jiahai Feng and Jacob Steinhardt. How do Language Models Bind Entities in Context? *ICLR*, 2024.
- Yonatan Geifman and Ran El-Yaniv. Selective Classification for Deep Neural Networks. *NeurIPS*, 2017.
- Shiyuan Guo, Henry Sleight, and Fabien Roger. All Code, No Thought: Current Language Models Struggle to Reason in Ciphred Language. *ICLR*, 2026.
- Tianyu Guo, Hanlin Zhu, Ruiqi Zhang, Jiantao Jiao, Song Mei, Michael I. Jordan, and Stuart Russell. How Do LLMs Perform Two-Hop Reasoning in Context? *arXiv:2502.13913*, 2025.
- Xanh Ho, Anh-Khoa Duong Nguyen, Saku Sugawara, and Akiko Aizawa. Constructing A Multi-hop QA Dataset for Comprehensive Evaluation of Reasoning Steps (2WikiMultihopQA). *COLING*, 2020.
- Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DasSarma, Eli Tran-Johnson, Scott Johnston, Sheer El-Showk, Andy Jones, Nelson Elhage, Tristan Hume, Anna Chen, Yuntao Bai, Sam Bowman, Stanislav Fort, Deep Ganguli, Danny Hernandez, Josh Jacobson, Jackson Kernion, Shauna Kravec, Liane Lovitt, Kamal Ndousse, Catherine Olsson, Sam Ringer, Dario Amodei, Tom Brown, Jack Clark, Nicholas Joseph, Ben Mann, Sam McCandlish, Chris Olah, and Jared Kaplan. Language Models (Mostly) Know What They Know. *arXiv:2207.05221*, 2022.
- Chenhui Liu, Jianpeng Zhou, and Jiahai Wang. Chain-of-Relations: Faithful and Efficient LLM Reasoning over Knowledge Graphs via Relation-Centric Exploration. *Findings of ACL*, 2026. <https://aclanthology.org/2026.findings-acl.2138/>.
- Linhao Luo, Yuan-Fang Li, Gholamreza Haffari, and Shirui Pan. Reasoning on Graphs: Faithful and Interpretable Large Language Model Reasoning. *ICLR*, 2024.
- Quinn McNemar. Note on the Sampling Error of the Difference Between Correlated Proportions or Percentages. *Psychometrika*, 12(2):153–157, 1947.
- Alexander Miller, Adam Fisch, Jesse Dodge, Amir-Hossein Karimi, Antoine Bordes, and Jason Weston. Key-Value Memory Networks for Directly Reading Documents (WikiMovies). *EMNLP*, 2016.
- Iman Mirzadeh, Keivan Alizadeh, Hooman Shahrokhi, Oncel Tuzel, Samy Bengio, and Mehrdad Farajtabar. GSM-Symbolic: Understanding the Limitations of Mathematical Reasoning in Large Language Models. *ICLR*, 2025.

- Yunfeng Ning, Mayi Xu, Jintao Wen, Qiankun Pi, Yuanyuan Zhu, Ming Zhong, Jiawei Jiang, and Tiejun Qian. Privacy-protected Retrieval-Augmented Generation for Knowledge Graph Question Answering (ARoG). *AAAI*, 2026.
- Panupong Pasupat and Percy Liang. Compositional Semantic Parsing on Semi-Structured Tables. *ACL*, 2015.
- Melanie Sclar, Yejin Choi, Yulia Tsvetkov, and Alane Suhr. Quantifying Language Models’ Sensitivity to Spurious Features in Prompt Design. *ICLR*, 2024.
- Jiashuo Sun, Chengjin Xu, Luminyuan Tang, Saizhuo Wang, Chen Lin, Yeyun Gong, Lionel Ni, Heung-Yeung Shum, and Jian Guo. Think-on-Graph: Deep and Responsible Reasoning of Large Language Model on Knowledge Graph. *ICLR*, 2024.
- Xingyu Tan, Xiaoyang Wang, Qing Liu, Xiwei Xu, Xin Yuan, Liming Zhu, and Wenjie Zhang. PrivGemo: Privacy-Preserving Dual-Tower Graph Retrieval for Empowering LLM Reasoning with Memory Augmentation. arXiv:2601.08739, 2026.
- Xiaojuan Tang, Zilong Zheng, Jiaqi Li, Fanxu Meng, Song-Chun Zhu, Yitao Liang, and Muhan Zhang. Large Language Models are In-Context Semantic Reasoners rather than Symbolic Reasoners. arXiv:2305.14825, 2023.
- Denny Vrandečić and Markus Krötzsch. Wikidata: A Free Collaborative Knowledgebase. *CACM*, 2014.
- Heng Wang, Shangbin Feng, Tianxing He, Zhaoxuan Tan, Xiaochuang Han, and Yulia Tsvetkov. Can Language Models Solve Graph Problems in Natural Language? *NeurIPS*, 2023.
- Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed H. Chi, Quoc V. Le, and Denny Zhou. Chain-of-Thought Prompting Elicits Reasoning in Large Language Models. *NeurIPS*, 2022.
- Jerry Wei, Le Hou, Andrew Lampinen, Xiangning Chen, Da Huang, Yi Tay, Xinyun Chen, Yifeng Lu, Denny Zhou, Tengyu Ma, and Quoc Le. Symbol tuning improves in-context learning in language models. *EMNLP*, 2023.
- Bingbing Wen, Jihan Yao, Shangbin Feng, Chenjun Xu, Yulia Tsvetkov, Bill Howe, and Lucy Lu Wang. Know Your Limits: A Survey of Abstention in Large Language Models. *TACL*, 13:529–556, 2025.
- Edwin B. Wilson. Probable Inference, the Law of Succession, and Statistical Inference. *JASA*, 22(158):209–212, 1927.
- Tao Yu, Rui Zhang, Kai Yang, Michihiro Yasunaga, Dongxu Wang, Zifan Li, James Ma, Irene Li, Qingning Yao, Shanelle Roman, Zilin Zhang, and Dragomir Radev. Spider: A Large-Scale Human-Labeled Dataset for Complex and Cross-Domain Semantic Parsing and Text-to-SQL. *EMNLP*, 2018.
- Yuyu Zhang, Hanjun Dai, Zornitsa Kozareva, Alexander J. Smola, and Le Song. Variational Reasoning for Question Answering with Knowledge Graph. *AAAI*, 2018.

A Protocol, scoring, and models

Isolation quizzes (runs/) and locked scores (results/) are at <https://github.com/pankajmits/oir/releases/tag/v1.0.6> (Python ≥ 3.10). OpenAI cells: gpt-5.6-sol, no tools, August 2026 lock plus two 15 September 2026 $k=3$ draws on the same alias, temperature omitted, max_completion_tokens 512; reasoning_effort was omitted. The August runner stores the parsed answer, not the API model string or usage (including reasoning-token counts); $k=3$ sidecars store returned_model. WIKI-SHUF is a 7 September 2026 snapshot on the same 32 keys. Composer 2.5 and Grok 4.5 used the same quiz files through Cursor’s agent SDK with a reply-only preamble OpenAI never received; settings are not equated. Composer Wiki-OO unique/two-path, Composer/Grok CEO, Dual *ff and some Dual isolation-tag

arms are answer-line locks (cite *ff; Grok Wiki-OO is a one-line tail). A later Composer Wiki-OO unique transcript rerun (composer25tx) is 32/32; it does not replace the August lock. Two-path stays 0/32 (one decoy vs. lock UNKNOWN 32). Some Dual and no-hop OpenAI cells store empty completions as UNKNOWN; Wiki-H5/Wiki-OO do not. Wiki-H5 uses seed 20260821 and a per-item 16-byte key derived from oir-fact-2x2-iso-v1 and the item index. The 32 records are random.Random(20260821).sample from the 73-row CEO file; two-path decoys attach record $i+1 \bmod 32$, so each item’s decoy company/HQ is the next item’s gold. Wilson intervals in the body treat items as i.i.d.; that is slightly optimistic under this cycle. Wiki-H5-200 is a separate freeze (data/real/wikidata_ceo_hops_n200.json, seed 20260915): company P169 person, company P159 HQ, HQ P31 a city-like class (not station/building/state), unique people and companies, at most three rows per HQ city, cyclic decoys arranged so consecutive items do not share HQ or person. Each row stores Wikidata QIDs. Live SPARQL re-check of all 200 P169+P159 pairs and city P31 is results/wikidata_ceo_hops_n200_verify.json (200/200). HMAC keys are oir-fact-2x2-iso-n200-v1; $n=32$ prompts are not rewritten. Header×decoy, Wiki-OO, shuffle, and CEO-NL $n=200$ use that freeze. WikiMovies $n=200$ keeps the $n=100$ people prefix and adds 100 new unique actors from wiki_entities_kb.txt. OpenAI $n=200$ tag is gpt56n200 (header 4096/medium: gpt56n200abl; 512-token H5-cyclic: gpt56n200h512). A SHA-256 lockfile over git-tracked JSON summaries and per-item reply files in results/ is results/SHA256SUMS (regenerate with harness/write_sha256sums.py; ignored packs such as longctx_lm* are omitted). That file is a hash pin, not a timestamped preregistration. Verify with shasum -c results/SHA256SUMS. Cite GitHub release tag v1.0.6 rather than branch HEAD. No models were trained. OpenAI cells used Chat Completions on CPU-side API calls (max_completion_tokens 512; header×decoy 4096). Wiki-H5 isolation is 32 items × five named arms; header×decoy is 224 queries per family. Composer 2.5 and Grok 4.5 used Cursor’s hosted agent API on the same quiz files. Wall-clock is API latency, not local GPU-hours. Wiki-OO is a second suite on those records (oir-entrel-2x2-iso-v1 and index). MOVIE-A32/MOVIE-A100/MOVIE-B and Dual isolation items are per-item keys; Dual demonstrations reuse that item’s key. CEO-NL isolation $n=32$ uses seed 20260820 and per-item keys. The $n=12$ three-arm is **batch** with one shared key (oir-ceiling-three-arm-v1, seed 20260728) for Composer 2.5, OpenAI, and Grok 4.5; $n=24$ is the same protocol at a larger n . We never impute n.r. as zeros.

P159 gold HQs that are not cities: Broadway, NRK_Marienlyst, Fox_Plaza, CNN_Center, Lod_Railway_Station; New_Jersey is a state. OpenAI opaque two-path decoys are items 27 and 31 (CNN_Center vs. Swindon; Lod_Railway_Station vs. Burbank). Both decoys are on the non-city subset; city-valued OpenAI opaque two-path is gold 5/26, decoy 0, UNKNOWN 21. Every non-two-path miss in Table 3 for all three families falls on those six golds. Composer “other” on that table is truncated Lod (item 31) plus Fox_Plaza→Los Angeles. Source slice: Kansas_City 10/73, Burbank 6/73; Disney three times in the 32. An archived Movie-B ARM banner naming director vs. writer is OpenAI two-path 25/100; the locked topology-only Condition B header is 3/100.

The CEO three-arm graphs add extra edges on the gold company (owned-by, partner-of, meta-of). One question template is used. Free English hashes the question piecewise, so the full person atom typically does not appear in q .

B Generator robustness

Opaque generator (OpenAI, start in q)	Unique	Two-path
Keyed HMAC (E+12hex)	32/32	6/32
Random permutation (E+12hex)	31/32	15/32
Random alphanumeric (not HMAC-shaped)	29/32	12/32

Table 8: Generator robustness on the same 32 Wikidata graphs and question template. Unique-path accuracy exceeds two-path accuracy under three independently generated opaque relation maps; the two-path *rate* is not invariant. Wilson: 29/32 $\Rightarrow$ [0.76, 0.97], 12/32 $\Rightarrow$ [0.23, 0.55], 15/32 $\Rightarrow$ [0.31, 0.64]. Alphanumeric two-path is all abstention or gold (decoy 0).

A random permutation of relation labels (HMAC-shaped tokens, not keyed HMAC) on the same Wiki-data 2×2 preserves unique-path accuracy exceeding two-path accuracy: OpenAI 31/32 vs. 15/32 (plan 30/32); Composer 28/32 vs. 2/32 (plan 28/32); Grok 31/32 vs. 0/32 (plan 32/32).

An English-entity ambiguity sweep $k=1..5$ still seals relations (HMAC key `oir-ambig-curve-iso-v1`) and, for every item, reuses one constant decoy route (Cogent Communications $\rightarrow$ Washington, DC). OpenAI stays high (29/32, 29/32, 28/32, 27/32, 28/32; plan 32/32); Composer declines (27/32 to 11/32; plan 29/32); Grok is 29/32 at $k=1$ then 0/32 for $k \geq 2$ (plan 32/32). K2 on the ambig-curve suite (curve HMAC key, constant decoy, named K2 header) is OpenAI 29/32 vs. Wiki-H5 6/32; that is not the header $\times$ decoy K2 cells (30/32 cyclic, 26/32 constant). Names such as Disney remain, so k is not isolated from entity semantics; neither curve is a replication of both-opaque 1/32.

Header $\times$ decoy uses arm-neutral case ids on the same 32 people (`header_decoy_ablation_iso_*.json`; body Section 5.2). Cells are named by header and decoy: H5 keeps the Wiki-H5 ARM line, K2 keeps a shorter two-hop ARM, and “no ARM” deletes the line; cyclic decoys attach record $i+1$, constant decoys reuse Cogent Communications $\rightarrow$ Washington, DC. Composer/Grok slash pairs below are cyclic / constant gold counts. OpenAI 4096/medium gold counts are Table 4. Composer and Grok the same day, Cursor SDK, prompt file verbatim (`--preamble none`), 224/224 finished: H5 6/2 and 0/0; K2 20/13 and 0/0; no ARM 21/18 and 6/1; English 26 and 24 (markdown wrappers on four Composer answers stripped at score time). A named-arm English Grok rerun with the prompt file verbatim (no Cursor preamble; tag `grok45pn`) stays 4/32 (rate, not item identity): the Cursor preamble is not that 4/32 cell. The 24/32 English cell (`ENG_NONE_CYC`) has no ARM line *and* hashed ids, so two things differ from named-arm English 4/32; do not read it as a pure case-id contrast. English, no ARM, hashed ids vs. no-ARM cyclic opaque is Grok 24/32 vs. 6/32 (McNemar 18 vs. 0, $p=7.63 \times 10^{-6}$); OpenAI 29 vs. 25 and Composer 26 vs. 21 are underpowered at $n=32$. Grok no-ARM opaque commits are 6 gold / 3 decoy cyclic and 1 / 5 constant (7 vs. 8 pooled). Named-arm OpenAI snapshot 5/32 (512 tokens, one `NO_OUTPUT`) vs. H5 cyclic at the same budget 20/32 (also one `NO_OUTPUT`) is the same-date case-id pair in Section 5.2. Constant decoy does not raise the Wiki-H5-header cell on any family.

C Hypothesis status and maps

Arm	Input to the model	Maps tested	Score
English, unique	readable q , start in q	e2e: (1)+(2)	26/26
English, two paths	readable q , start in q	e2e: (1)+(2)	26/26
Opaque, unique	start in q ; one route; no plan	traversal (2) (e2e)	26/26
Opaque, two paths	start in q ; two routes; no map	e2e (selection unobserved)	5/26
Plan (control)	opaque q plus (r_1, r_2)	traversal (2)	26/26
Binding fail ($n=32$)	piecewise q ; start usually absent	start-ID (confounded)	0/32

Table 9: WIKI-H5 maps on city-valued items (OpenAI unless noted). Exact match on the answer node, not (r_1, r_2) . City-valued $n=26$ is the headline (August opaque two-path 5/26); the lockfile $n=32$ opaque two-path is 6/32 (Section 5.1). Plan is 26/26 on this slice (32/32 on $n=32$). Last row is CEO-NL ($n=32$).

Hypothesis	Test	Status
H1. Opacity alone blocks traversal	unique-path, start in q	not supported (32/32)
H2. Written hop restores e2e (control)	two-path + plan; SealRouter	control (32/32)
H3. Input-binding control (CEO piecewise q)	CEO isolation NL	control (0/32); not selection
H4. Matched demos restore shown seals	dual-path matched vs. novel	OpenAI 32/32 vs. 0/32
H5. End-to-end accuracy degrades when opaque relations meet path ambiguity	matched 2×2 , start in q	named-arm 25 vs. 0 (city 21 vs. 0); Sec. 5.1
H6. Movie KB, hashed verbs (check)	WikiMovies Cond. B $n=100$	OpenAI two-path 3/100
H7. Readable relations with opaque entities	Wikidata OE vs. OO	supported for OpenAI here
H8. Prompt surface moves two-path exact match	case-id at 512 cyclic; ARM $\times$ decoy at 4096	same-date case-id +15; H5 decoy 20 vs. 10; Sec. 5.2

Table 10: Hypothesis status. H4 exact-match is OpenAI Dual; Composer free-form novel is decoy 32/32 (composer25ff). H5 is named-arm WIKI-H5 (OpenAI). H6 is MOVIE-B. H7 is OpenAI-specific (OE vs. WIKI-OO). H8 is prompt surface on the same graphs (Section 5.2).

CEO-NL isolation $n=32$	Composer 2.5	OpenAI	Grok 4.5
Sealed plan / SealRouter	32/32	32/32	32/32
Free sealed English (piecewise q)	0/32	0/32	0/32

Table 11: Missing-start control, not WIKI-H5. Batch $n=12/n=24$ and packaging rows: Appendix G.

Cell (iso. $n=32$)	OpenAI	Composer 2.5	Grok 4.5
MOVIE-A32 opaque unique	32/32	32/32	32/32
MOVIE-A32 opaque two-path	17/32	17/32	0/32
MOVIE-A32 two-path + plan	32/32	32/32	32/32
Both-opaque unique	32/32	32/32	32/32
Both-opaque two-path	1/32	0/32	0/32
Both-opaque two-path + plan	32/32	28/32	32/32

Table 12: Three-family isolation beyond Table 3. MOVIE-A32 leaves verbs in q (not a selection result). Both-opaque is Table 6 compactly.

D Dual-path arms

We name the arms by what the demos teach. **Matched-relation** (asymmetric or balanced noise): demos expose the gold relation seals; the decoy path uses different seals. **Novel-relation** (asymmetric or balanced noise): demos teach seals that do not appear on the gold route; both routes are novel at quiz time. **Explicit join plan**: gold relation sequence is written in the prompt.




Figure 2: DUAL (synthetic, OpenAI $n=32$): matched 32/32; novel 0/32 (asymmetric decoy 8); explicit plan 32/32.

An $n=8$ cell is zero demos 2/8; one or more demos 8/8. Isolation $n=32$ is the reported dual-path measurement. Local mistral/qwen35 runs are not in the roster (matched-asymmetric 0/32; Qwen matched-balanced 7/32; plan n.r.). Composer isolation-tag novel-relation UNKNOWN is `adv_induction_n32_iso_composer25.json` (helper `run_induce_mut_n32_iso.py`); the free-form lock is `composer25ff` (decoy 32/32). Grok free-form is `grok45ff`.

E No-hop binding (JSON)

Arm (no written hop)	OpenAI	Composer 2.5	Grok 4.5
Schema list only	0/32	0/32	0/32
English protocol (no hop)	32/32	32/32	32/32
Same σ , silent	6/32	19/32	31/32
Same σ + equality recipe	32/32	32/32	32/32
JSONKEY : match broken	0/32	0/32	0/32
Sealed Q, two routes, recipe	31/32	25/32	32/32
Sealed Q, two routes, vague hints*	13/32	23/32	31/32

Table 13: Selection support without a written hop (Wikidata CEO JSON; city or mentor country is the distractor; isolation; per-item HMAC). Schema-only and broken token overlap fail for all three. An English protocol or an equality recipe that does not name the field saturates. Silent same- σ overlap and vague hints are family-dependent, not a three-family restore. OpenAI silent 6/32 and vague-hint 13/32 include 24 and 15 empty completions stored as UNKNOWN. *Composer vague-hint distractor 1/32. JOIN was not evaluated at $n=32$. Wilson: 32/32 $\Rightarrow$ [0.89, 1.00], 0/32 $\Rightarrow$ [0.00, 0.11], 6/32 $\Rightarrow$ [0.09, 0.35], 31/32 $\Rightarrow$ [0.84, 0.99]. Silent same- σ OpenAI 6/32 is a JSON-binding cell, distinct from WIKI-H5. NS_SILENT ARM lines say “Match impossible”; those 0/32 rows are not a sealed-join collapse.




Figure 3: No-hop binding (Wikidata JSON, OpenAI $n=32$). Bars are exact match; the 6/32 silent bar is gold hits, not a decoy rate.

Figure 3 is the OpenAI row of Table 13. The Table 13 prompts are fixed English blocks (same wording for all three families). We use *equality* rather than similarity: exact identity of sealed tokens, not a continuous metric. Schema list only is a bilingual KEY_SCHEMA (English name = sealed JSON key) plus “Use the schema to read CONTEXT. No JOIN is given.” The English protocol adds that QUESTION and CONTEXT are encoded, that identical tokens are the same entity or field (equality, not decryption), and that schema names plus token equality walk CONTEXT; it also names the asked field as country rather than city. The same- σ equality recipe (Appendix J) does not name country or city in English. It is not the WIKI-H5 prompt. The suite uses the same 32 Wikidata people (per-item keys; seed 20260826–20260829). The OpenAI $n=6$ cell with an English question template and English JSON keys (1/6) is not plaintext Wiki-H5: the start token and all values are sealed, city is a nested distractor under $h\sigma$, and the prompt forbids world knowledge and allows UNKNOWN. English keys alone do not restore the walk.

F Sealing middleware

The necessary step is binding a typed full name to one graph atom: spaced tokens otherwise miss V . The layer then seals entities, relations, and sensitive values. When the relation sequence is already specified, the join can be executed by a deterministic non-LLM router. If the hop is not compiled, the layer may attach one sealed join as an execution control (not a list of candidate paths). The model, when used, returns $\sigma(a)$; the layer unseals. Isolation on the CEO vault without start-entity binding is 0/6 vs. full layer 6/6 for Composer 2.5, OpenAI, and an unversioned Claude endpoint (Anthropic model id not stored; plaintext names in the packed prompt: 0). On complex 3-hop and real 2Wiki, Composer 2.5 without binding is 0/6 vs. layer 6/6; OpenAI layer 6/6 (without binding: complex 4/6, 2Wiki 0/6). Those isolation files also attach a join: that is the execution control, not the reason to call a model. The model never receives a retrieved path list and never answers in plaintext (Table 1). The 6/6 scores are this binding-and-join control, not the free WIKI-H5 6/32 cell.

G Packaging probes

These cells test serialization and application packaging. They are *not* the matched 2×2 , not a second discovery, and not required to restate the body claim. Sample sizes are $n=6$ –16 except a counterfactual 2Wiki sanity check and the public Spider identifier-in- q cell ($n=100$). We keep one paragraph per family so a reader who wants the packaging inventory can find it; a reader of WIKI-H5 can skip this appendix.

Tables / JSON / SQL / Excel / FinQA / WTQ. Same CEO join as markdown tables, nested JSON, or a value store: free sealed English 0/12, join plan 12/12 (Composer 2.5 and OpenAI). JSON keys without a legend: 0/6; a key legend yields 6/6 for OpenAI only; a join plan yields 6/6 for both. Token overlap vs. `SQLCOL`: break on public Spider is Table 14 (OpenAI; identifier-in- q slice $n=100$: 51/100 vs. 0/100). Excel NL already names both join predicates (batched $n=16$): Composer 0/16 (mid-hop error 16/16) vs. plan 16/16; OpenAI 16/16 on both. FinQA / WTQ (Chen et al., 2021; Pasupat and Liang, 2015) on shared sealed context: FinQA NL 0/8 vs. gold programs 8/8; WTQ NL 0/6 vs. LOOKUP DSL 6/6 (Composer). OpenAI matches FinQA and WTQ DSL; WTQ NL is 1/6. Not a leaderboard.

Counterfactual 2Wiki sanity check. Composer 2.5 plain NL 200/200 (Wikipedia leak 0); OpenAI batched 150/200 with overlap leak 50/200. We do not treat this as a standard 2Wiki evaluation. Spider: sealed-cell NL 4/12; model SQL executed locally 29/32; gold-SQL engine 191/200 (Appendix K).

English q	Find the number of papers published by the institution “University of Pennsylvania”.
Sealed q (A)	Find the number of E41f626311a9f published by the institution “University of Pennsylvania”.
EQ	q token equals sqlite identifier $\rightarrow$ execute; first-cell gold on this item
NS	same q ; identifiers are HMAC(<code>SQLCOL:name</code>) $\rightarrow$ UNKNOWN
A (name in q)	$n=100$ (45 DBs). EQ 51/100; NS 0/100 (UNKNOWN 100/100)
B (no name in q)	$n=26$. EQ 18/26; NS 20/26 (English q ; legend can still bind)

Table 14: Spider identifier overlap vs. namespace break (OpenAI; Yu et al., 2018). Slice A $n=100$: EQ 51/100, NS 0/100. Not official exact-match. n.r. for Composer/Grok.

Long context / rename. At $\sim 128k$ and $\sim 1.14M$ sealed tokens, free sealed NL remains 0/8; plans 8/8. Paired sealed plans under a second HMAC key: 12/12 with differing golds (Figure 4).




Figure 4: Sealed-plan rename equivariance ($n=12$): plans remain correct under a second HMAC key with a different gold on every pair.




Figure 5: Non-LLM and packaging controls. Panel A is Composer $n=12$; panels B–C are frozen $n=200$ baselines. Left: plain NL 12/12, opaque-rel NL 0/12, plan/legend 12/12 (Composer 2.5, $n=12$). Middle: 2Wiki-CF BM25 6/200, Wikipedia-string leak 75/200, SealRouter 200/200. Right: Spider sqlite 200/200, gold-SQL engine 191/200, BM25 1/200. CEO/2Wiki opacity $\times$ prompt-form scores are in the surrounding prose.

H Extended scores

MetaQA-style 2-hop templates on the same public movie graph are a question-form control, not an evaluation on the official MetaQA 14K test split. Plaintext is 32/32 for all three families. Condition A (English question over opaque relations) is OpenAI 32/32, Composer 19/32, Grok 15/32. Condition B hashes those verbs except `[start]`: OpenAI 25/32, Composer 27/32, Grok 14/32 (plans 32/32, 31/32, 32/32). That $n=32$ template cell is not MOVIE-B. Packaging cells with $n \leq 16$ are Appendix G, not a second 2×2 .

I Sign-flip of the H5 interaction

Let $d_i = \mathbf{1}[\text{opaque correct}] - \mathbf{1}[\text{English correct}]$ and $c_i = d_i^{\text{two}} - d_i^{\text{unique}}$. Of 32 WIKI-H5 items, 24 have $c_i = -1$, one has $c_i = -2$, 7 have $c_i = 0$; $T = -26$. Under exchangeability of unique-path and two-path opacity effects, $p = 2^{-24} = 5.96 \times 10^{-8}$. That p coincides numerically with the two-path McNemar p (25 vs. 0; McNemar, 1947); the tests are not the same. Opacity is not a randomized within-item treatment. The body reports Wilson intervals and the paired counts.

J Equality recipe (JSON cell)

Verbatim protocol used in Table 13, *not* in WIKI-H5: “QUESTION and CONTEXT use the same encoding. Identical tokens are the same entity or the same field (equality, not English). START is a QUESTION token that also appears as an id value in CONTEXT. The asked field is a QUESTION token that also appears as a JSON key. Walk CONTEXT by token equality. If more than one reading is possible, UNKNOWN.”

The $n=32$ JSON cells are Table 13. Sample sizes $n \leq 16$ (vault, Excel, FinQA, WTQ, middleware) are packaging probes (Appendix G), not WIKI-H5.

K Symbolic execution controls

SealRouter executes a gold sealed path with no LLM. The gold-SQL engine executes gold Spider SQL locally. Figure 5 summarizes those controls.

NeurIPS Paper Checklist

1. Claims

Question: Do the main claims made in the abstract and introduction accurately reflect the paper’s contributions and scope?

Answer: [\[Yes\]](#)

Justification: The abstract and introduction state a measurement protocol, unique-path sealed traversal, and packaging-sensitive abstention under two competing routes. They report named-arm Wiki-H5 and family×packaging exact-match rates, not a ranking of families, and do not claim a confidentiality proof or a scored (r_1, r_2) .

Guidelines:

- The answer [\[N/A\]](#) means that the abstract and introduction do not include the claims made in the paper.
- The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations.
- The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
- It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. Limitations

Question: Does the paper discuss the limitations of the work performed by the authors?

Answer: [\[Yes\]](#)

Justification: Section 7 states that named-arm Wiki-H5 DiD is most readable for OpenAI, $n=32$ on one template (reused on later suites), cyclic decoys, 512 vs. 4096/medium packaging, harness mismatch, Dual empty completions, inferred rather than scored (r_1, r_2) , OpenAI-only MOVIE-B/WIKI-SHUF, and controls not evaluated here (forced-choice, short symbols, second seed).

Guidelines:

- The answer [\[N/A\]](#) means that the paper has no limitation while the answer [\[No\]](#) means that the paper has limitations, but those are not discussed in the paper.
- The authors are encouraged to create a separate “Limitations” section in their paper.
- Reviewers are specifically instructed not to penalize honesty concerning limitations.

3. Theory assumptions and proofs

Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: [\[N/A\]](#)

Justification: The paper is a measurement protocol. Section 3 defines selection and traversal maps; it does not state theorems.

Guidelines:

- The answer [\[N/A\]](#) means that the paper does not include theoretical results.

4. Experimental result reproducibility

Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

Answer: [\[Yes\]](#)

Justification: Section 4 and Appendix A give seeds, HMAC width, isolation vs. batch, scoring (Wiki-H5/Wiki-OO: explicit UNKNOWN; Dual/no-hop OpenAI: empty completions stored as UNKNOWN; new runner: NO_OUTPUT), model endpoints, and which cells are answer-line locks. Quizzes are in `runs/`; locked scores in `results/`.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility.

5. Open access to data and code

Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

Answer: [Yes]

Justification: Isolation quizzes, locked JSON, reply trees, and `results/SHA256SUMS` are in the public repository named on the title page. Composer 2.5 and Grok 4.5 used a vendor agent SDK that is not the OpenAI API; Appendix A records that mismatch.

Guidelines:

- The answer [N/A] means that the paper does not include experiments requiring code.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).

6. Experimental setting/details

Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

Answer: [Yes]

Justification: No models are trained. Sampling seed, HMAC keys, n , temperature omission, token budgets, and ARM text are in Section 4 and Appendix A.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results.

7. Experiment statistical significance

Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer: [Yes]

Justification: Wilson 95% intervals ($z=1.96$) and McNemar exact two-sided complete-case tests are reported for the primary OpenAI 2×2 . Appendix A notes that cyclic decoys slightly violate the i.i.d. assumption of the Wilson intervals.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The authors should answer [Yes] if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.

8. Experiments compute resources

Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

Answer: [Yes]

Justification: Appendix A records that no models were trained; OpenAI cells used Chat Completions; Composer/Grok used a hosted agent API; query counts for Wiki-H5 and header $\times$ decoy are stated.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.

9. Code of ethics

Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics <https://neurips.cc/public/EthicsGuidelines>?

Answer: [Yes]

Justification: Instances use licensed public graphs. No human subjects, no crowdwork. Per-item replies are hash-pinned, not a training dump. HMAC is not treated as a privacy mechanism (Ethical considerations).

Guidelines:

- The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.

10. Broader impacts

Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

Answer: [Yes]

Justification: Ethical considerations states the diagnostic use and the misuse of reading HMAC seals as confidentiality. The protocol is not a deployed anonymizer.

Guidelines:

- The answer [N/A] means that there is no societal impact of the work performed.

11. Safeguards

Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

Answer: [N/A]

Justification: The release is quizzes, scores, and hashing code over public KG slices. We do not release pretrained generators or scraped image/text corpora.

Guidelines:

- The answer [N/A] means that the paper poses no such risks.

12. Licenses for existing assets

Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

Answer: [Yes]

Justification: Wikidata CEO records (CC0), WikiMovies/MetaQA as publicly released (upstream papers do not name a license string), 2WikiMultihopQA (Apache-2.0), and Spider (CC-BY-SA-4.0) are cited in Ethical considerations.

Guidelines:

- The answer [N/A] means that the paper does not use existing assets.
- The name of the license (e.g., CC-BY 4.0) should be included for each asset.

13. New assets

Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

Answer: [Yes]

Justification: Isolation quizzes, locked scores, SHA-256 pins, and per-item reply files are documented in Appendix A and the repository README. Replies are not released as a training corpus.

Guidelines:

- The answer [N/A] means that the paper does not release new assets.
- At submission time, remember to anonymize your assets (if applicable).

14. Crowdsourcing and research with human subjects

Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

Answer: [N/A]

Justification: The study evaluates language-model APIs on public graphs. There are no human participants.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.

15. Institutional review board (IRB) approvals or equivalent for research with human subjects

Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

Answer: [N/A]

Justification: No human-subjects research.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.

16. Declaration of LLM usage

Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does not impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

Answer: [N/A]

Justification: HMAC sealing and the quiz files are the method. Language models are evaluated systems (Section 4), not a component of the protocol.

Guidelines:

- The answer [N/A] means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.