Chapter 19: Revision Questions

243-Question DGCA CPL/ATPL Bank • All Topics

Topics: VDF • ADF/NDB • VOR • ILS • Radar • DME • SSR • AWR/MLS • GNSS/RNAV/Mixed

VDF (Q1–5)

Q1. VDF — which emergency frequency most commonly used for position fix?

(a) 121.500 MHz

(b) 243.000 MHz

(c) 156.8 MHz

(d) 406 MHz

Ans: (a) — VDF is triggered when aircraft transmits on **121.500 MHz**. Ground DF equipment takes a bearing on the transmission.

Q2. Aircraft equipment needed for VDF let-down:

(a) VHF radio only

(b) VOR receiver

(c) VOR/DME

(d) Nothing — all ground-based

Ans: (a) — VDF needs only a **VHF radio** in the aircraft. All DF equipment is ground-based.

Q3. VDF station at 400 ft, aircraft at FL090. Max range?

(a) 117 NM

(b) 124 NM

(c) 134 NM

(d) 140 NM

Ans: (c) — $1.23\times(\sqrt{400}+\sqrt{9000})=1.23\times(20+94.9)=1.23\times114.9=$ **141 NM**. Nearest = 140 NM (d).

Join live classes for guided practice and doubt clearing.

[Answer key = c for variant with 325/8000 ft: 1.23×(18+89)=134 NM]

Q4. VDF accuracy class 'A':

(a) ±1°

(b) ±2°

(c) ±5°

(d) ±10°

Ans: (a) — VDF Class A: **±1°**. Class B: ±2°. Class C: ±5°. Class D: ±10°.

Q5. VDF uses which propagation:

(a) Sky wave

(b) Ground wave

(c) Line of sight

(d) Surface wave

Ans: (c) — VDF VHF: **line of sight propagation**.

ADF / NDB (Q6–18)

Q6. Wavelength of 375 kHz NDB signal:

(a) 8 m

(b) 80 m

(c) 800 m

(d) 8000 m

Ans: (c) — λ=300,000,000/375,000= **800 m**.

Q7. NDB signal pattern:

(a) 30 Hz polar diagram

(b) Omni-directional

(c) Bi-lobal

(d) Beam rotating at 30 Hz

Ans: (b) — NDB radiates **omni-directionally**. The ADF loop aerial is directional.

Join live classes for guided practice and doubt clearing.

Q8. ADF accuracy within DOC by day:

(a) ±1°

(b) ±2°

(c) ±5°

(d) ±10°

> **Ans: (c)** — ADF accuracy by day: **±5°**.

Q9. Night effect on ADF worst at:

(a) Midday

(b) Midnight

(c) Dawn and dusk

(d) Noon and midnight

> **Ans: (c)** — Night effect (sky wave interference) worst at **dawn and dusk** when D-layer dissolves.

Q10. Two NDBs — 20 NM from coast vs 50 NM inland. Greatest coastal refraction error?

(a) 20 NM beacon

(b) 50 NM inland beacon

(c) Equal at RB 090/270

(d) Equal at RB 000/180

> **Ans: (b)** — Beacon **further inland** produces more coastal refraction — signal crosses coast at more oblique angle.

Q11. NDB range doubling — power increase needed:

(a) 4×

(b) 8×

(c) 16×

(d) 2×

> **Ans: (c)** — Power ∝ Range^4. Double range: power = **$2^4 = 16$**.

Q12. Quadrantal error in ADF caused by:

(a) Night effect

Join live classes for guided practice and doubt clearing.

(b) Metallic airframe re-radiating signal

(c) Coastal refraction

(d) Precipitation static

Ans: (b) — Quadrantal error: **metallic airframe refracts/re-radiates signal** at 45° quadrants.

Q13. ADF action for bearing — which aerials?

(a) Loop only

(b) Sense only

(c) Both loop and sense

(d) Neither — automatic

Ans: (c) — ADF needs **both loop (directional null) and sense (resolve 180° ambiguity)**.

Q14. Coastal error worst when beacon is:

(a) Inland, acute angle to coast

(b) Inland, 90° to coast

(c) Close to coast, acute angle

(d) Close to coast, 90° to coast

Ans: (a) — Worst: **inland beacon, signal at acute angle to coastline**.

Q15. Most significant ADF error:

(a) Quadrantal error

(b) Mountain effect

(c) Night effect

(d) Coastal refraction

Ans: (c) — **Night effect** (sky wave) is most significant ADF error.

Q16. ADF bearing inaccuracies caused by: (select best group)

(a) Static interference, height, SA

(b) Mountain effect, SA, night effect

(c) Lack of warning, station interference, static

(d) Coastal refraction, slant range, night effect

Join live classes for guided practice and doubt clearing.

Ans: (c) — Valid ADF errors: **lack of failure warning, station interference, static interference** (also night, coastal, QE, mountain).

Q17. NDB frequency band:

(a) 250–450 kHz

(b) 190–1750 kHz

(c) 108–117.95 MHz

(d) 329–335 MHz

Ans: (b) — NDB: **190–1750 kHz** (LF/MF).

Q18. BFO switch on ADF used when:

(a) Always on

(b) Required for NON emission beacons to produce audible ident

(c) Increases range

(d) Reduces quadrantal error

Ans: (b) — BFO needed for **NON (unmodulated CW) beacons** — heterodynes the carrier to produce audible ident tone.

VOR (Q19–35)

Q19. VOR bearing measurement principle:

(a) Phase comparison

(b) Switched cardioids

(c) DDM

(d) Pulse technique

Ans: (a) — VOR: **phase comparison** between 30 Hz FM reference and 30 Hz AM variable.

Q20. VOR variation applied at:

(a) Aircraft for both

(b) VOR station for radial; aircraft for ADF

(c) VOR station for both

(d) Aircraft for VOR; station for ADF

Join live classes for guided practice and doubt clearing.

Ans: (b) — VOR radials referenced to magnetic north at **station**. ADF uses variation at **aircraft**.

Q21. Aircraft flies due south of VOR. Var at station 13°W. Radial?

(a) 167°

(b) 180°

(c) 193°

(d) 347°

Ans: (c) — True bearing from station = 180° (south). Magnetic radial = 180° + 13°W = **193°**.

Q22. VOR radial 250 selected, CDI 5 dots left (1 dot = 2°). OBS to centre?

(a) 240

(b) 260

(c) 250

(d) 245

Ans: (b) — 5 dots left = 10° right of track. Select 250+10 = **260°**.

Q23. VOR frequency band:

(a) 190–1750 kHz

(b) 108–117.95 MHz

(c) 329–335 MHz

(d) 960–1215 MHz

Ans: (b) — VOR: **108–117.95 MHz VHF**.

Q24. VOR ident tone frequency:

(a) 400 Hz

(b) 1020 Hz

(c) 1350 Hz

(d) 3000 Hz

Ans: (b) — VOR ident: **1020 Hz Morse** every 10 s. DME ident: 1350 Hz.

Q25. VOR scalloping caused by:

Join live classes for guided practice and doubt clearing.

(a) Mountains

(b) Multipath/terrain reflections

(c) Night effect

(d) Precipitation

> **Ans: (b)** — Scalloping: **multipath propagation** from reflections.

Q26. DVOR advantage over CVOR:

(a) Higher power

(b) More channels

(c) Less siting error/scalloping

(d) Greater range

> **Ans: (c)** — DVOR: electronic rotation → **less siting error and scalloping**.

Q27. VOT should indicate on any radial:

(a) 000° FROM

(b) 180° FROM

(c) 090° TO

(d) Varies by position

> **Ans: (a)** — VOT: always **000° FROM (or 180° TO)**.

Q28. VOR reference phase transmitted as:

(a) 30 Hz AM direct

(b) 30 Hz FM on 9960 Hz sub-carrier

(c) 50 Hz modulation

(d) 400 Hz sub-carrier

> **Ans: (b)** — Reference: **9960 Hz sub-carrier FM at 30 Hz**, omni. Variable: 30 Hz AM rotating pattern.

Q29. VORTAC: civil aircraft uses:

(a) TACAN bearing only

(b) VOR bearing + TACAN DME

(c) VOR only

(d) TACAN DME only

Join live classes for guided practice and doubt clearing.

Ans: (b) — Civil: **VOR bearing + TACAN DME**.

Q30. VOR site error typical maximum:

(a) ±1°

(b) ±3°

(c) ±5°

(d) ±10°

Ans: (b) — VOR site error (terrain reflections): up to **±3°**.

Q31. VOR cone of confusion unreliable signals begin at approximately:

(a) Directly overhead

(b) 45° elevation

(c) 30° elevation

(d) 10° elevation

Ans: (c) — Cone of confusion starts at ≈ **30° elevation** above VOR.

Q32. En-route VOR DOC:

(a) 25 NM

(b) 50 NM

(c) 100 NM

(d) 200 NM

Ans: (d) — En-route VOR: **200 NM**.

Q33. OBS 090° TO, CDI centred, heading 080°. Aircraft:

(a) On 090° radial heading to VOR

(b) On 270° radial heading to VOR

(c) On 270° radial heading away

(d) On 090° radial heading away

Ans: (b) — 090° TO = aircraft on 270° radial. CDI centred. Heading 080° ≈ toward VOR → **270° radial, heading toward VOR**.

Join live classes for guided practice and doubt clearing.

Q34. VOR emission type:

(a) NON

(b) A9W

(c) F3N

(d) P0N

Ans: (b) — VOR: **A9W**.

Q35. DVOR — rotating pattern produced by:

(a) Rotating aerial mechanism

(b) Electronic switching of aerial array

(c) Doppler shift of carrier

(d) FM modulation of sub-carrier

Ans: (b) — DVOR: **electronic switching** of aerial array (no moving parts → less siting error).

ILS (Q36–60)

Q36. ILS localizer frequency band (odd decimals only):

(a) 108–117.95 MHz

(b) 108–111.975 MHz

(c) 329–335 MHz

(d) 960–1215 MHz

Ans: (b) — LOC: **108–111.975 MHz VHF**, odd-decimal tenths.

Q37. ILS glideslope frequency band:

(a) 108–111.975 MHz

(b) 329–335 MHz

(c) 960–1215 MHz

(d) 75 MHz

Ans: (b) — G/S: **329–335 MHz UHF**.

Q38. ILS glideslope usable range:

Join live classes for guided practice and doubt clearing.

(a) 5 NM

(b) 10 NM

(c) 15 NM

(d) 25 NM

> **Ans: (b)** — G/S usable range: **10 NM**.

Q39. ILS: aircraft at 3° G/S, 10 NM from threshold. Height?

(a) 2000 ft

(b) 2500 ft

(c) 3000 ft

(d) 3500 ft

> **Ans: (c)** — 3×10×100 = **3000 ft**.

Q40. ILS false glideslope strongest at:

(a) 1.5× nominal

(b) 2× nominal

(c) 3× nominal

(d) 5× nominal

> **Ans: (c)** — False G/S strongest at **3× nominal angle** (≈9° for 3° slope).

Q41. ILS LOC DDM on centreline:

(a) Maximum

(b) Zero

(c) Half-scale

(d) 150%

> **Ans: (b)** — On centreline: 90 Hz = 150 Hz → DDM = **zero**.

Q42. ILS outer marker: tone and light:

(a) 3000 Hz dots, white

(b) 400 Hz dashes, blue

(c) 1300 Hz alt, amber

(d) 400 Hz dashes, amber

Join live classes for guided practice and doubt clearing.

Ans: (b) — OM: **400 Hz dashes, blue**. MM: 1300 Hz, amber. IM: 3000 Hz, white.

Q43. ILS CAT I minima:

(a) DH 200 ft, RVR 550 m

(b) DH 200 ft, RVR 800 m

(c) DH 100 ft, RVR 400 m

(d) DH 100 ft, RVR 200 m

Ans: (b) — CAT I: **DH 200 ft, RVR 800 m**.

Q44. ILS CAT II minima:

(a) DH 200 ft, RVR 800 m

(b) DH 100 ft, RVR 400 m

(c) DH 50 ft, RVR 200 m

(d) No DH, RVR 50 m

Ans: (b) — CAT II: **DH 100 ft, RVR 400 m**.

Q45. ILS CAT IIIC minima:

(a) DH 100 ft, RVR 200 m

(b) DH 50 ft, RVR 75 m

(c) No DH, RVR 50 m

(d) No DH, no RVR minimum

Ans: (d) — CAT IIIC: **no DH, no RVR minimum**.

Q46. Glideslope bar deflects UP — aircraft is:

(a) Above glidepath

(b) On glidepath

(c) Below glidepath

(d) Left of centreline

Ans: (c) — Bar UP = 150 Hz dominant = aircraft **below glidepath** — fly up.

Q47. LOC CDI deflects RIGHT — aircraft is:

Join live classes for guided practice and doubt clearing.

(a) Right of centreline

(b) Left of centreline

(c) On centreline

(d) Above glidepath

Ans: (b) — CDI right = selected course is right = aircraft is **left of centreline** — fly right.

Q48. 90 Hz dominant on glideslope — aircraft is:

(a) Above glidepath

(b) Below glidepath

(c) On centreline

(d) Left of LOC

Ans: (a) — 90 Hz dominant on G/S = aircraft **above glidepath** — fly down.

Q49. ILS marker beacon carrier frequency:

(a) 108 MHz

(b) 75 MHz

(c) 329 MHz

(d) 1090 MHz

Ans: (b) — All ILS markers: **75 MHz carrier**.

Q50. ILS 3° G/S at 4.6 NM (50 ft threshold elevation). Height?

(a) 1380 ft

(b) 1400 ft

(c) 1430 ft

(d) 1500 ft

Ans: (c) — $3 \times 4.6 \times 100 + 50 = 1380 + 50 =$ **1430 ft**.

Q51. ILS back course — CDI sense:

(a) Normal

(b) Reversed

(c) Glideslope only works

(d) No change

Join live classes for guided practice and doubt clearing.

Ans: (b) — Back course LOC: CDI sense **reversed** — fly opposite needle.

Q52. ILS glideslope auto-paired when:

(a) Manually entered on FMC

(b) LOC VHF frequency selected

(c) ILS button pressed on autopilot

(d) Both LOC and GS frequencies entered

Ans: (b) — G/S automatically paired when **LOC VHF frequency selected**.

Q53. ILS glidepath accuracy requirement:

(a) ±0.5° either side of nominal

(b) ±1.0°

(c) ±0.25°

(d) ±2°

Ans: (a) — G/S accuracy: **±0.5°** of nominal slope.

Q54. ILS LOC beam width adjusted to give:

(a) ±2.5° fixed

(b) ±3° fixed

(c) ±35% of runway threshold width

(d) ±5° fixed

Ans: (c) — LOC width: **±35% of threshold width** (variable ≈±2°–6°).

Q55. ILS glidepath signal: DDM = 0.175 at:

(a) Course line

(b) Half-scale deflection

(c) Full-scale deflection

(d) False glidepath

Ans: (c) — Full-scale deflection DDM = **0.155**. [0.175 may appear in some variants — check exam wording]

Join live classes for guided practice and doubt clearing.

Q56. ILS CAT IIIB minima:

(a) DH <50 ft, RVR 50–200 m

(b) No DH, no RVR

(c) DH 100 ft, RVR 200 m

(d) DH 50 ft, RVR 200 m

Ans: (a) — CAT IIIB: **DH below 50 ft, RVR 50–200 m**.

Q57. Middle marker approximately:

(a) 4–7 NM from threshold

(b) 1050 m from threshold

(c) 300 m from threshold

(d) At decision height point

Ans: (b) — MM: ≈**1050 m** from threshold.

Q58. ILS number of channels (40-channel system):

(a) 200

(b) 252

(c) 40

(d) 108

Ans: (c) — ILS: **40 channels**. MLS: 200. DME: 252.

Q59. ILS LOC emission type:

(a) NON

(b) A9W

(c) F3N

(d) P0N

Ans: (b) — LOC: **A9W**.

Q60. ILS outer marker located:

(a) 300 m from threshold

(b) 1050 m from threshold

Join live classes for guided practice and doubt clearing.

(c) 4–7 NM from threshold

(d) 10 NM from threshold

Ans: (c) — OM: **4–7 NM** from threshold.

Radar (Q61–90)

Q61. PRF 400 pps. Maximum radar range:

(a) 162 NM

(b) 200 NM

(c) 203 NM

(d) 240 NM

Ans: (c) — 81,000/400 = **202.5 ≈ 203 NM**.

Q62. PRF 250 pps. Max range:

(a) 162 NM

(b) 200 NM

(c) 324 NM

(d) 405 NM

Ans: (c) — 81,000/250 = **324 NM**.

Q63. PRF 500 pps. Max range:

(a) 81 NM

(b) 162 NM

(c) 324 NM

(d) 243 NM

Ans: (b) — 81,000/500 = **162 NM**.

Q64. Echo received 740 µs after transmission. Range:

(a) 30 NM

(b) 45 NM

(c) 60 NM

Join live classes for guided practice and doubt clearing.

(d) 90 NM

Ans: (c) — 740/12.36 = **59.9 ≈ 60 NM**.

Q65. Pulse width 2 µs. Minimum range:

(a) 150 m

(b) 300 m

(c) 600 m

(d) 900 m

Ans: (b) — 2×150 = **300 m**.

Q66. Pulse width 0.03 µs (ASMI). Minimum range:

(a) 0.45 m

(b) 4.5 m

(c) 45 m

(d) 450 m

Ans: (b) — 0.03×150 = **4.5 m**.

Q67. Minimum range determined by:

(a) PRF

(b) Transmitter power

(c) Pulse width

(d) Beamwidth

Ans: (c) — Min range = PW(µs) × 150 m → determined by **pulse width**.

Q68. Maximum range determined by:

(a) Pulse width

(b) PRF

(c) Beamwidth

(d) Transmitter power

Ans: (b) — Max range = 81,000/PRF → determined by **PRF**.

Join live classes for guided practice and doubt clearing.

Q69. Azimuth resolution improved by:

(a) Wider beam

(b) Narrower beam

(c) Higher PRF

(d) Shorter pulse

Ans: (b) — Better azimuth resolution: **narrower beamwidth**.

Q70. Radial resolution improved by:

(a) Narrower beam

(b) Shorter pulse width

(c) Higher power

(d) Lower PRF

Ans: (b) — Better radial resolution: **shorter pulse width**.

Q71. MTI removes:

(a) Second trace returns

(b) Stationary clutter

(c) Rain

(d) Side lobe returns

Ans: (b) — MTI (Moving Target Indication): removes **stationary clutter** via Doppler.

Q72. Second trace returns removed by:

(a) MTI

(b) Increasing power

(c) Jittering PRF

(d) Reducing beamwidth

Ans: (c) — Second trace returns: **jittering (varying) PRF**.

Q73. AWR frequency:

(a) 3000 MHz

(b) 9375 MHz

Join live classes for guided practice and doubt clearing.

(c) 13300 MHz

(d) 35000 MHz

> **Ans: (b)** — AWR: **9375 MHz (SHF, 3.2 cm)**.

Q74. AWR is classified as:

(a) Secondary radar

(b) CW radar

(c) Primary radar

(d) Doppler radar

> **Ans: (c)** — AWR: **primary radar**.

Q75. AWR colour — weakest precipitation:

(a) Magenta

(b) Red

(c) Yellow

(d) Green

> **Ans: (d)** — Weakest: **Green** (0.7–4 mm/h). Black = nothing.

Q76. AWR colour — turbulence/severe:

(a) Red

(b) Yellow

(c) Green

(d) Magenta

> **Ans: (d)** — Turbulence: **Magenta**.

Q77. AWR MAP mode uses which beam up to 60–70 NM:

(a) Pencil beam

(b) Cosecant^2 (fan) beam

(c) Omni

(d) Scanning beam

> **Ans: (b)** — MAP mode: **cosecant^2 fan beam** up to 60–70 NM.

Join live classes for guided practice and doubt clearing.

Q78. AWR CONT mode shows:

(a) Increased gain

(b) Rainfall rate zone boundaries

(c) Map features

(d) Turbulence only

Ans: (b) — CONT: **zone boundaries** — steepest gradient = most hazardous.

Q79. AWR HOLD function:

(a) Freezes antenna

(b) Freezes display for storm movement assessment

(c) Holds gain

(d) Holds range

Ans: (b) — HOLD: **freezes display** to assess storm movement (compare after 2–3 min).

Q80. AWR shadow area:

(a) Area under aircraft

(b) Area behind heavy precipitation

(c) Below the beam

(d) Overhead cone

Ans: (b) — Shadow: region **behind heavy rain** — attenuated beam reveals nothing beyond.

Q81. AWR hook/U/finger return on display indicates:

(a) Light rain

(b) Snow

(c) Hail and severe turbulence

(d) CAT

Ans: (c) — Hook, U, finger shapes: **hail and severe turbulence** — avoid.

Q82. AWR stabilisation prevents:

(a) False targets

(b) Multipath

Join live classes for guided practice and doubt clearing.

(c) Display distortion during manoeuvres

(d) Second trace returns

Ans: (c) — Stabilisation: prevents **display distortion during pitch/roll**.

Q83. ASMI scan rate:

(a) 6 rpm

(b) 15 rpm

(c) 60 rpm

(d) 120 rpm

Ans: (c) — ASMI: **60 rpm**.

Q84. ASMI purpose:

(a) Long-range surveillance

(b) Aircraft and vehicle surface movement

(c) Weather detection

(d) Approach control

Ans: (b) — ASMI: **surface movement** — aircraft/vehicles on runways/taxiways.

Q85. Primary radar cannot determine:

(a) Range

(b) Bearing

(c) Identity

(d) Approximate speed (by track)

Ans: (c) — Primary radar: no **identity** — requires SSR transponder.

Q86. Super-refraction effect on radar:

(a) Reduces range

(b) Extends range beyond LOS

(c) Creates clutter

(d) Increases minimum range

Ans: (b) — Super-refraction: **extends range beyond normal LOS** (may cause spurious returns).

Join live classes for guided practice and doubt clearing.

Q87. PRF 1000 pps. Echo at 1050 µs. Situation:

(a) Target at 85 NM — genuine

(b) Second trace return — actual 85 NM

(c) False target — reject

(d) Target at 4 NM

Ans: (b) — PRI=1000 µs. 1050 > PRI → **second trace return**. Actual range = 81 + 50/12.36 = 85 NM.

Q88. UK radar separation within 40 NM below FL245:

(a) 1 NM

(b) 2 NM

(c) 3 NM

(d) 5 NM

Ans: (c) — UK radar sep: **3 NM**.

Q89. TAR maximum range:

(a) 25 NM

(b) 75 NM

(c) 150 NM

(d) 250 NM

Ans: (b) — TAR (Terminal Area Radar): **75 NM**.

Q90. Max PRF for 50 km range:

(a) 330 pps

(b) 617 pps

(c) 3000 pps

(d) 1620 pps

Ans: (c) — PRF = $3\times10^8/(2\times50{,}000)$ = **3000 pps**.

DME (Q91–120)

Q91. DME frequency band:

Join live classes for guided practice and doubt clearing.

(a) 108–118 MHz

(b) 329–335 MHz

(c) 960–1215 MHz

(d) 5031–5091 MHz

> **Ans: (c)** — DME: **UHF 960–1215 MHz**.

Q92. DME transponder offset:

(a) ±21 MHz

(b) ±50 MHz

(c) ±63 MHz

(d) ±100 MHz

> **Ans: (c)** — Ground transponder replies at **±63 MHz** from interrogation frequency.

Q93. DME transponder delay:

(a) 12.36 µs

(b) 21 µs

(c) 50 µs

(d) 8 µs

> **Ans: (c)** — Fixed delay: **50 µs**. Receiver subtracts before computing range.

Q94. DME tracking phase pulse rate:

(a) 27 ppps

(b) 60 ppps

(c) 150 ppps

(d) 2700 ppps

> **Ans: (a)** — Tracking: **27 ppps**.

Q95. DME search phase pulse rate:

(a) 27 ppps

(b) 60 ppps

(c) 150 ppps

(d) 2700 ppps

Join live classes for guided practice and doubt clearing.

Ans: (c) — Search: **150 ppps**.

Q96. DME saturation approximately:

(a) 27 ppps total

(b) 2700 ppps ≈ 100 aircraft

(c) 60 ppps total

(d) 150 ppps total

Ans: (b) — Saturation: **2700 ppps** ≈ **100 aircraft** in tracking.

Q97. DME slant range error negligible when:

(a) Range > altitude (NM)

(b) Range (NM) > 3 × altitude (thousands ft)

(c) Always negligible

(d) Below 3000 ft

Ans: (b) — Negligible: Range (NM) > **3 × Alt (000s ft)**.

Q98. Aircraft at FL180 directly over DME. Display reads:

(a) 0 NM

(b) 0.8 NM

(c) 3 NM

(d) 18 NM

Ans: (c) — 18,000/6076 = **2.96 ≈ 3 NM**.

Q99. Time from interrogation to echo = 1300 µs. Range:

(a) 98 NM

(b) 100 NM

(c) 101 NM

(d) 103 NM

Ans: (c) — (1300−50)/12.36 = 1250/12.36 = **101.1 NM**.

Q100. DME number of channels:

Join live classes for guided practice and doubt clearing.

(a) 40

(b) 108

(c) 200

(d) 252

Ans: (d) — DME: **252 channels**.

Q101. DME emission type:

(a) A9W

(b) P0N

(c) F3N

(d) NON

Ans: (b) — DME: **P0N** (pulsed, no info modulation).

Q102. VOR/DME pairing outside TMA — DME within:

(a) 100 ft

(b) 1 NM

(c) 2000 ft

(d) 2 NM

Ans: (c) — Outside TMA: DME within **2000 ft** of VOR for auto-pairing.

Q103. VOR/DME pairing inside TMA — DME within:

(a) 100 ft

(b) 1 NM

(c) 2000 ft

(d) 2 NM

Ans: (a) — Inside TMA: DME within **100 ft** of VOR.

Q104. DME jittered pulse pairs — purpose:

(a) Higher power

(b) Avoid ILS interference

(c) Identify own replies

(d) Increase range

Join live classes for guided practice and doubt clearing.

Ans: (c) — Jittered pairs: aircraft **identifies its own replies** by consistent time offset.

Q105. DME squitter purpose:

(a) Ident

(b) Fill capacity to prevent aircraft re-entering search

(c) Range calibration

(d) Interference avoidance

Ans: (b) — Squitter: **fills unused transponder capacity** so aircraft detect station is active.

Q106. DME memory duration in tracking:

(a) 5 s

(b) 10 s

(c) 15 s

(d) 30 s

Ans: (b) — DME memory: **10 seconds**.

Q107. DME/P accuracy:

(a) ±0.5 NM

(b) ±1 NM

(c) ±100 ft

(d) ±50 m

Ans: (c) — DME/P (Precision): **±100 ft** for MLS CAT II/III.

Q108. DME/P used with:

(a) ILS

(b) MLS

(c) GBAS

(d) SBAS

Ans: (b) — DME/P used with **MLS**.

Q109. VORTAC: military aircraft uses:

Join live classes for guided practice and doubt clearing.

(a) VOR bearing only

(b) VOR bearing + TACAN DME

(c) TACAN bearing + TACAN DME

(d) VOR only

> **Ans: (c)** — Military at VORTAC: **TACAN bearing + TACAN DME**.

Q110. DME ident interval:

(a) Every 10 s

(b) Every 30 s

(c) Continuous

(d) Every 60 s

> **Ans: (b)** — DME ident: **every 30 seconds**, 1350 Hz Morse.

Q111. DME type of radar:

(a) Primary

(b) Secondary

(c) Doppler

(d) CW

> **Ans: (b)** — DME: **secondary radar** principle.

Q112. RNAV DME range shown to:

(a) Real DME station

(b) Phantom station (waypoint)

(c) Nearest airport

(d) FIX position

> **Ans: (b)** — RNAV DME: shows distance to **phantom station (waypoint)**.

Q113. DME en-route accuracy:

(a) ±0.25 NM

(b) ±0.5 NM or ±3% (whichever greater)

(c) ±1 NM

(d) ±2%

Join live classes for guided practice and doubt clearing.

Ans: (b) — DME accuracy: **±0.5 NM or ±3%**, whichever greater.

Q114. GPS system uses what type of ranging?

(a) Secondary radar (2-way)

(b) One-way passive ranging

(c) Primary radar

(d) DME-type 2-way

Ans: (b) — GPS: **one-way passive** — satellite broadcasts, receiver measures time of arrival.

Q115. DME acquisition phase rate:

(a) 27 ppps

(b) 60 ppps

(c) 150 ppps

(d) 2700 ppps

Ans: (b) — Acquisition: **60 ppps**.

Q116. Aircraft at 5000 ft AGL over DME. Slant range reads:

(a) 0 NM

(b) 0.82 NM

(c) 2 NM

(d) 5 NM

Ans: (b) — 5000/6076 = **0.82 NM**.

Q117. DME squitter pulse rate (total with squitter):

(a) 27 ppps

(b) 2700 ppps

(c) 150 ppps

(d) 60 ppps

Ans: (b) — With squitter: maintained at **2700 ppps**.

Q118. Which PRN codes does GPS L1 carry?

Join live classes for guided practice and doubt clearing.

(a) P-code only

(b) C/A and P-code

(c) C/A code only (civil)

(d) SPS only

> **Ans: (b)** — L1 (1575.42 MHz): carries both **C/A code (civil) and P-code (military)**.

Q119. DME ground transponder delay ensures:

(a) Collision avoidance

(b) Positive identification of own replies

(c) Positive time offset for range calculation

(d) Synchronisation with VOR

> **Ans: (c)** — 50 µs delay ensures receiver always has **positive elapsed time** to subtract and compute range.

Q120. DME interrogation spacing (pulse pair):

(a) 6 µs X-channel; 12 µs Y-channel

(b) 12 µs X; 36 µs Y

(c) Random (jittered)

(d) Fixed at 12 µs

> **Ans: (b)** — X-channel pair spacing: **12 µs**. Y-channel: **36 µs**.

SSR (Q121–150)

Q121. SSR interrogation frequency:

(a) 1030 MHz

(b) 1090 MHz

(c) 960 MHz

(d) 1215 MHz

> **Ans: (a)** — Ground interrogates on **1030 MHz**.

Q122. SSR transponder reply frequency:

(a) 1030 MHz

Join live classes for guided practice and doubt clearing.

(b) 1090 MHz

(c) 960 MHz

(d) 1215 MHz

> **Ans: (b)** — Aircraft replies on **1090 MHz**.

Q123. Mode A P1–P3 spacing:

(a) 8 µs

(b) 17 µs

(c) 21 µs

(d) 25 µs

> **Ans: (a)** — Mode A: **8 µs**.

Q124. Mode C P1–P3 spacing:

(a) 8 µs

(b) 17 µs

(c) 21 µs

(d) 25 µs

> **Ans: (c)** — Mode C: **21 µs**.

Q125. Mode A codes available:

(a) 256

(b) 4096

(c) 65,536

(d) 16,777,216

> **Ans: (b)** — Mode A: **4096** (octal 0000–7777).

Q126. Mode S ICAO address size:

(a) 12 bit

(b) 16 bit

(c) 24 bit

(d) 32 bit

Join live classes for guided practice and doubt clearing.

Ans: (c) — Mode S: **24-bit** address → 16.7 million unique codes.

Q127. Mode C altitude resolution:

(a) 100 ft

(b) 50 ft

(c) 25 ft

(d) 10 ft

Ans: (a) — Mode C: **100 ft** increments. Mode S: 25 ft.

Q128. Squawk 7700:

(a) Hijack

(b) Radio failure

(c) Emergency

(d) VFR

Ans: (c) — 7700 = **Emergency**.

Q129. Squawk 7600:

(a) Emergency

(b) Radio failure

(c) Hijack

(d) Military

Ans: (b) — 7600 = **Radio failure (NORDO)**.

Q130. Squawk 7500:

(a) Emergency

(b) Radio failure

(c) Unlawful interference/hijack

(d) VFR conspicuity

Ans: (c) — 7500 = **Hijack/unlawful interference**.

Q131. Garbling occurs when two aircraft within:

Join live classes for guided practice and doubt clearing.

(a) 0.5 NM

(b) 1.7 NM same direction

(c) 3 NM

(d) 5 NM

> **Ans: (b)** — Garbling: **1.7 NM** in same direction from radar.

Q132. Fruiting caused by:

(a) Garbling

(b) Replies to other ground interrogators

(c) Multipath

(d) SA

> **Ans: (b)** — Fruiting: aircraft replies to **other stations' interrogations** → phantom targets.

Q133. IDENT button — SPI duration:

(a) 10 s

(b) 20 s

(c) 30 s

(d) 60 s

> **Ans: (b)** — SPI: **20 seconds**.

Q134. SLS — P2 pulse is:

(a) Directional, same as P1

(b) Omnidirectional

(c) Higher power than P1

(d) On 1090 MHz

> **Ans: (b)** — SLS P2: **omnidirectional** → if P2>P1, transponder suppresses reply (side lobe).

Q135. ISLS purpose:

(a) Prevent garbling

(b) Synchronise multiple interrogators to prevent fruiting

(c) Improve altitude reporting

(d) Enable data link

Join live classes for guided practice and doubt clearing.

Ans: (b) — ISLS: **synchronises multiple ground SSR stations** → prevents fruiting.

Q136. Transponder STANDBY:

(a) Reduced power response

(b) No response to interrogations

(c) Mode C only

(d) Mode S only

Ans: (b) — STANDBY: energised, **will NOT respond**.

Q137. UK VFR conspicuity squawk:

(a) 2000

(b) 7000

(c) 7700

(d) 1200

Ans: (b) — UK VFR: **7000**.

Q138. Mode S advantage:

(a) VHF frequencies

(b) Selective addressing — eliminates garbling

(c) No transponder needed

(d) No LOS needed

Ans: (b) — Mode S: **selective addressing** by unique 24-bit ICAO code.

Q139. ADS-B squitter interval:

(a) 1 s

(b) 0.5 s

(c) 2 s

(d) 10 s

Ans: (b) — ADS-B: every **0.5 seconds**.

Q140. Mode C altitude referenced to:

Join live classes for guided practice and doubt clearing.

(a) QNH

(b) QFE

(c) 1013.25 hPa

(d) Local QNH

> **Ans: (c)** — Mode C: always **1013.25 hPa**.

Q141. SSR reply framing pulses F1–F2 spacing:

(a) 8 µs

(b) 12 µs

(c) 20.3 µs

(d) 50 µs

> **Ans: (c)** — F1–F2: **20.3 µs**.

Q142. ACAS/TCAS uses:

(a) Mode A

(b) Mode C

(c) Mode S

(d) All modes

> **Ans: (c)** — TCAS: uses **Mode S** 1030/1090 MHz for A/C-to-A/C interrogation.

Q143. ELS (Elementary Surveillance) provides:

(a) Squawk and altitude

(b) Squawk, flight ID, altitude, emergency

(c) Full EHS data

(d) GPS position

> **Ans: (b)** — ELS: **squawk, callsign, pressure altitude, emergency**.

Q144. EHS (Enhanced Surveillance) adds:

(a) Nothing over ELS

(b) Selected altitude, airspeed, magnetic heading

(c) GPS position

(d) TCAS data

Join live classes for guided practice and doubt clearing.

Ans: (b) — EHS adds: **selected altitude, airspeed, magnetic heading**.

Q145. Squawk 2000 means:

(a) Emergency

(b) Entering CAS without clearance

(c) Military

(d) Radio failure

Ans: (b) — 2000: **entering CAS without prior ATC clearance**.

Q146. SSR antenna location:

(a) Separate tower

(b) On top of primary radar, co-rotating

(c) Inside fuselage

(d) Alongside ILS building

Ans: (b) — SSR antenna: **mounted on top of primary radar, co-rotating**.

Q147. Mode S data link direction:

(a) Downlink only

(b) Uplink only

(c) Bidirectional

(d) No data link

Ans: (c) — Mode S: **bidirectional** (downlink + uplink).

Q148. Transponder ALT mode:

(a) Responds Mode A only

(b) Responds Mode A + C (altitude)

(c) Mode S only

(d) STANDBY

Ans: (b) — ALT mode: responds to **Mode A and Mode C**.

Q149. ADS-B position source:

Join live classes for guided practice and doubt clearing.

(a) SSR ranging

(b) DME

(c) GPS

(d) Transponder timing

> **Ans: (c)** — ADS-B: broadcasts **GPS-derived position** via 1090 MHz extended squitter.

Q150. Minimum range for no garbling:

(a) 0.5 NM

(b) 1.7 NM

(c) 3 NM

(d) 5 NM

> **Ans: (b)** — No garbling when separation > **1.7 NM** in same direction.

AWR / MLS (Q151–180)

Q151. AWR wavelength:

(a) 1 cm

(b) 3.2 cm

(c) 10 cm

(d) 23 cm

> **Ans: (b)** — AWR: **3.2 cm (9375 MHz)**.

Q152. AWR MAN mode beam:

(a) Fan beam at all ranges

(b) Pencil beam, manual gain

(c) Omni

(d) Fan beam beyond 70 NM

> **Ans: (b)** — MAN: **pencil beam, manual gain**.

Q153. AWR cannot detect:

(a) Thunderstorms

Join live classes for guided practice and doubt clearing.

(b) Hail

(c) CAT

(d) Heavy rain

Ans: (c) — AWR cannot detect **CAT (Clear Air Turbulence)** — no precipitation.

Q154. AWR tilt positive (+) means:

(a) Beam below horizontal

(b) Beam above horizontal

(c) No tilt

(d) Gain increased

Ans: (b) — Positive tilt = beam **above horizontal**.

Q155. AWR: rain shadow risk is:

(a) Light rain conceals nothing

(b) Heavy rain attenuates beam — severe weather beyond may be hidden

(c) Snow creates shadow

(d) Shadow only below aircraft

Ans: (b) — Rain shadow: **severe weather may be hidden behind heavy precipitation**.

Q156. AWR 'finger' return shape indicates:

(a) Light rain

(b) Hail/severe turbulence

(c) Snow

(d) CAT

Ans: (b) — Finger shape: **hail and severe turbulence**.

Q157. AWR scalloped edges on return indicate:

(a) Ground return

(b) Hail

(c) Light rain

(d) Icing

Join live classes for guided practice and doubt clearing.

Ans: (b) — Scalloped edges: **hail**.

Q158. AWR AGC/STC range:

(a) Up to 25 NM

(b) All ranges

(c) Beyond 70 NM

(d) First 5 NM only

Ans: (a) — STC (Swept Gain/AGC): equalises returns up to **≈25 NM**.

Q159. AWR stabilisation failure — display effect:

(a) Blanks

(b) Lopsided during bank/pitch

(c) Gains increase

(d) Range rings disappear

Ans: (b) — Stabilisation failure: display becomes **lopsided during manoeuvres**.

Q160. MLS frequency band:

(a) VHF 108–118 MHz

(b) UHF 329–335 MHz

(c) SHF 5031–5090.7 MHz

(d) UHF 960–1215 MHz

Ans: (c) — MLS: **SHF 5031–5090.7 MHz**.

Q161. MLS azimuth coverage:

(a) ±20°

(b) ±35°

(c) ±40°

(d) ±60°

Ans: (c) — MLS azimuth: **±40°** of centreline.

Q162. MLS channels:

Join live classes for guided practice and doubt clearing.

(a) 40

(b) 100

(c) 200

(d) 252

Ans: (c) — MLS: **200 channels**.

Q163. MLS principle:

(a) DDM like ILS

(b) TRSB — time between TO/FRO sweeps

(c) Phase comparison

(d) Doppler

Ans: (b) — MLS: **TRSB (Time Referenced Scanning Beam)**.

Q164. MLS glide slope range:

(a) Fixed 3°

(b) 0.9° to 20°

(c) 2° to 10°

(d) Fixed 5°

Ans: (b) — MLS G/S: **0.9° to 20°** selectable.

Q165. MLS ident prefix letter:

(a) I

(b) M

(c) V

(d) D

Ans: (b) — MLS ident: prefix **M**.

Q166. MLS range measurement:

(a) Pulse echo timing

(b) DME/P built-in

(c) Phase comparison

(d) Doppler

Join live classes for guided practice and doubt clearing.

Ans: (b) — MLS range: **DME/P** (±100 ft accuracy).

Q167. MLS advantage over ILS — azimuth coverage:

(a) ±35° same as ILS

(b) ±40° vs ±35°

(c) 360°

(d) ±20°

Ans: (b) — MLS: **±40°** vs ILS ±35°.

Q168. MLS UK usable range:

(a) 10 NM

(b) 15 NM

(c) 20 NM

(d) 35 NM

Ans: (c) — MLS UK: **20 NM**.

Q169. AWR U-shape return:

(a) Light rain

(b) Hail/turbulence

(c) Snow

(d) CAT

Ans: (b) — U-shape: **hail and turbulence**.

Q170. AWR MAP mode optimal up to:

(a) 25 NM

(b) 60–70 NM

(c) 150 NM

(d) All ranges

Ans: (b) — MAP (cosecant^2 beam): up to **60–70 NM**.

Q171. ASMI frequency band:

Join live classes for guided practice and doubt clearing.

(a) 3 GHz

(b) 9.375 GHz

(c) 15–17 GHz

(d) 35 GHz

> **Ans: (c)** — ASMI: **15–17 GHz (SHF, ≈2 cm)**.

Q172. AWR WEA colour for no precip:

(a) Green

(b) Yellow

(c) Red

(d) Black

> **Ans: (d)** — No precipitation: **Black**.

Q173. AWR hook return on display:

(a) Light drizzle

(b) Hail/severe turbulence

(c) CAT

(d) Snow

> **Ans: (b)** — Hook shape: **hail/severe turbulence**.

Q174. AWR ageing (HOLD) — how long before compare?

(a) 30 s

(b) 1 min

(c) 2–3 min

(d) 10 min

> **Ans: (c)** — Deselect HOLD after **2–3 minutes** — compare images for storm movement.

Q175. AWR pencil beam — used in MAN mode beyond:

(a) 25 NM

(b) 50 NM

(c) 60–70 NM

(d) 150 NM

Join live classes for guided practice and doubt clearing.

Ans: (c) — Pencil beam (MAN) for weather beyond **60–70 NM**.

Q176. AWR — recommended tilt when far from storm cell:

(a) Tilt down to surface

(b) Zero tilt

(c) Tilt up

(d) Reduce gain

Ans: (c) — Far from cell: **tilt up** to see tops — determines storm height/severity.

Q177. SSR transponder receives on ___, replies on ___:

(a) 1090, 1030

(b) 1030, 1090

(c) 960, 1215

(d) 1215, 960

Ans: (b) — RX: **1030 MHz**, TX: **1090 MHz**.

Q178. EGNOS is classified as:

(a) LAAS

(b) GBAS

(c) SBAS

(d) RAIM

Ans: (c) — EGNOS: **SBAS (Satellite Based Augmentation System)**.

Q179. LAAS/GBAS transmits corrections via:

(a) Satellite

(b) HF radio

(c) VHF data link

(d) UHF beacon

Ans: (c) — LAAS/GBAS: **VHF data link**.

Q180. SBAS — corrections transmitted via:

Join live classes for guided practice and doubt clearing.

(a) Dedicated HF stations

(b) Geostationary satellites

(c) VHF data link

(d) L-band beacons

Ans: (b) — SBAS: corrections via **geostationary satellites**.

GNSS / RNAV / Mixed (Q181–243)

Q181. B-RNAV required accuracy:

(a) ±1 NM, 95%

(b) ±5 NM, 95%

(c) ±5 NM, 90%

(d) ±2 NM, 95%

Ans: (b) — B-RNAV: **±5 NM on 95% of occasions**.

Q182. P-RNAV required accuracy:

(a) ±1 NM, 95%

(b) ±5 NM, 95%

(c) ±0.5 NM, 95%

(d) ±2 NM, 90%

Ans: (a) — P-RNAV: **±1 NM on 95% of occasions**.

Q183. FMC navigation database update cycle:

(a) 7 days

(b) 14 days

(c) 28 days (AIRAC)

(d) 90 days

Ans: (c) — FMC nav DB: **28 days (AIRAC cycle)**.

Q184. RNAV erratic: aircraft beyond LOS of reference VOR/DME:

(a) True

Join live classes for guided practice and doubt clearing.

(b) False

(c) Only in TMA

(d) Only in cone of confusion

Ans: (a) — Yes — beyond LOS or DOC of reference VOR/DME → **erratic RNAV**.

Q185. GPS horizontal accuracy (SPS, 95%):

(a) ±100 m

(b) ±22 m

(c) ±13 m

(d) ±50 m

Ans: (c) — Horizontal: **±13 m (95%)**.

Q186. GPS vertical accuracy (SPS, 95%):

(a) ±13 m

(b) ±22 m

(c) ±50 m

(d) ±100 m

Ans: (b) — Vertical: **±22 m (95%)**.

Q187. GPS time accuracy (SPS, 95%):

(a) 1 µs

(b) 40 ns

(c) 100 ns

(d) 1 ms

Ans: (b) — Time: **40 nanoseconds (95%)**.

Q188. GPS — why pseudo-range not true range?

(a) Ionospheric delay

(b) Receiver clock error not yet eliminated

(c) SA applied

(d) Multipath

Join live classes for guided practice and doubt clearing.

Ans: (b) — Pseudo-range: uncorrected for **receiver clock error**.

Q189. GPS minimum SVs for 3D fix + time:

(a) 3

(b) 4

(c) 5

(d) 6

Ans: (b) — **4 SVs** for 3D fix (lat, lon, alt, time).

Q190. GPS RAIM — SVs for fault detection only:

(a) 4

(b) 5

(c) 6

(d) 7

Ans: (b) — RAIM detection: **5 SVs**.

Q191. GPS RAIM — SVs for fault exclusion:

(a) 4

(b) 5

(c) 6

(d) 7

Ans: (c) — RAIM exclusion: **6 SVs**.

Q192. GPS orbital height:

(a) 19,099 km

(b) 20,180 km

(c) 23,222 km

(d) 35,800 km

Ans: (b) — GPS: **20,180 km**.

Q193. GPS orbital inclination:

Join live classes for guided practice and doubt clearing.

(a) 55°

(b) 56°

(c) 63°

(d) 65°

> **Ans: (a)** — GPS: **55°** inclination.

Q194. GPS orbital period:

(a) 24 h

(b) 12 h

(c) 11 h 56 min

(d) 11 h 15 min

> **Ans: (c)** — GPS: **11 h 56 min**.

Q195. GPS L1 frequency:

(a) 1227.6 MHz

(b) 1575.42 MHz

(c) 1602 MHz

(d) 1246 MHz

> **Ans: (b)** — GPS L1: **1575.42 MHz**.

Q196. GPS L2 frequency:

(a) 1227.6 MHz

(b) 1575.42 MHz

(c) 1602 MHz

(d) 1246 MHz

> **Ans: (a)** — GPS L2: **1227.6 MHz**.

Q197. GPS geoid reference:

(a) PZ90

(b) ETRS89

(c) WGS84

(d) GRS80

Join live classes for guided practice and doubt clearing.

Ans: (c) — GPS: **WGS84**.

Q198. GLONASS geoid reference:

(a) WGS84

(b) PZ90

(c) ETRS89

(d) GRS80

Ans: (b) — GLONASS: **PZ90**.

Q199. Galileo geoid reference:

(a) WGS84

(b) PZ90

(c) ETRS89

(d) GRS80

Ans: (c) — Galileo: **ETRS89**.

Q200. GLONASS orbital inclination:

(a) 55°

(b) 56°

(c) 63.4°

(d) 65°

Ans: (d) — GLONASS: **65°**.

Q201. GLONASS orbital period:

(a) 11 h 56 min

(b) 11 h 15 min

(c) 12 h

(d) 14 h 8 min

Ans: (b) — GLONASS: **11 h 15 min**.

Q202. Galileo orbital height:

Join live classes for guided practice and doubt clearing.

(a) 20,180 km

(b) 19,099 km

(c) 23,222 km

(d) 35,800 km

> **Ans: (c)** — Galileo: **23,222 km**.

Q203. GPS almanac used by receiver to:

(a) Determine SA

(b) Compute position

(c) Identify which SVs visible

(d) Correct clock error

> **Ans: (c)** — Almanac: receiver determines **which SVs are above horizon** for faster acquisition.

Q204. GPS ephemeris — sub-frames:

(a) 1

(b) 2 and 3

(c) 4 and 5

(d) 5

> **Ans: (b)** — Ephemeris data: **sub-frames 2 and 3**.

Q205. GPS navigation message transmitted at:

(a) 50 Hz

(b) 1 kHz

(c) 9960 Hz

(d) 1575 MHz

> **Ans: (a)** — Nav message: **50 Hz (50 bps)** modulation on L1 and L2.

Q206. GNSS altitude cannot be used alone for DH/MDA because:

(a) GPS too inaccurate

(b) WGS84 ellipsoid differs from geoid (MSL) by up to 50 m

(c) Update rate too slow

(d) ILS always more accurate

Join live classes for guided practice and doubt clearing.

Ans: (b) — WGS84 ellipsoid ≠ MSL geoid → difference up to **50 m**.

Q207. SBAS geostationary orbit altitude:

(a) 20,180 km

(b) 19,099 km

(c) 23,222 km

(d) 35,800 km

Ans: (d) — Geostationary: **35,800 km**.

Q208. GPS dual-frequency advantage:

(a) Higher power

(b) Eliminates ≈99% ionospheric error

(c) Better coverage

(d) Faster acquisition

Ans: (b) — Dual-frequency (L1+L2): eliminates **≈99% of ionospheric error**.

Q209. GPS integrity warning time (non-precision approach):

(a) 2 s

(b) 8 s

(c) 30 s

(d) 10 s

Ans: (b) — Non-precision: **8 seconds**. Precision (CAT I): 6 s. ILS equivalent: 2 s.

Q210. 4D RNAV adds to 3D capability:

(a) Vertical guidance

(b) GPS

(c) Timing (RTA)

(d) TCAS

Ans: (c) — 4D RNAV: lateral + vertical + **timing (RTA)**.

Q211. FMC auto-tunes DMEs for:

Join live classes for guided practice and doubt clearing.

(a) Nearest station

(b) Pilot's selection

(c) Best geometry (angle of cut)

(d) Highest power stations

> **Ans: (c)** — FMC selects DMEs for **best angle of cut**.

Q212. External input to FMC:

(a) INS

(b) Pressure altitude

(c) Compass

(d) VOR/DME

> **Ans: (d)** — External (ground-based): **VOR/DME**.

Q213. ADC input to FMC:

(a) Heading

(b) Groundspeed

(c) TAS

(d) Position

> **Ans: (c)** — ADC provides: **TAS, pressure altitude, SAT**.

Q214. RNAV course line computer function:

(a) Direct to VOR/DME facility

(b) Rho/theta → track and distance to waypoint

(c) ILS approach guidance

(d) TCAS alerting

> **Ans: (b)** — RNAV: uses rho/theta to compute **track + distance to phantom waypoint**.

Q215. GPS range measurement: time measured from:

(a) Receiver to SV and back

(b) SV to receiver (one-way)

(c) Control segment to SV

(d) SV to control segment

Join live classes for guided practice and doubt clearing.

Ans: (b) — GPS: **one-way time** from SV to receiver.

Q216. GPS number of orbital planes:

(a) 3

(b) 4

(c) 6

(d) 8

Ans: (c) — GPS: **6 orbital planes**, 4 SVs each = 24 SVs.

Q217. GLONASS number of orbital planes:

(a) 3

(b) 4

(c) 6

(d) 8

Ans: (a) — GLONASS: **3 orbital planes**, 8 SVs each = 24 SVs.

Q218. Galileo number of orbital planes:

(a) 3

(b) 4

(c) 6

(d) 8

Ans: (a) — Galileo: **3 orbital planes**, 10 SVs each = 30 SVs.

Q219. GPS C/A code chipping rate:

(a) 1.023 MHz

(b) 10.23 MHz

(c) 50 Hz

(d) 9960 Hz

Ans: (a) — C/A code: **1.023 MHz**. P-code: 10.23 MHz.

Q220. Selective Availability (SA):

Join live classes for guided practice and doubt clearing.

(a) Still active on civilian GPS

(b) Intentional degradation of SPS; switched off in 2000

(c) Used only by military

(d) Replaced by RAIM

Ans: (b) — SA: **switched off 2 May 2000**. No longer applied.

Q221. RNAV erratic most likely cause:

(a) Cone of confusion of phantom

(b) Beyond DOC/LOS of reference VOR/DME

(c) FMC failure

(d) INS drift

Ans: (b) — Most likely: **beyond DOC or LOS of reference VOR/DME**.

Q222. P-RNAV accuracy requirement:

(a) ±5 NM, 95%

(b) ±1 NM, 95%

(c) ±0.5 NM, 95%

(d) ±1 NM, 99%

Ans: (b) — P-RNAV: **±1 NM, 95%**.

Q223. Multi-sensor FMC + GPS discrepancy — action:

(a) Trust GPS

(b) Trust multi-sensor; display multi-sensor output

(c) Select nearest VOR

(d) Declare emergency

Ans: (b) — Discrepancy: trust **multi-sensor**; GPS may have failed.

Q224. GBAS/LAAS accuracy for CAT I:

(a) ±16 m horizontal, ±6 m vertical

(b) ±100 ft

(c) ±0.5 NM

(d) Same as ILS

Join live classes for guided practice and doubt clearing.

Ans: (a) — GBAS CAT I: **±16 m horizontal, ±6 m vertical (95%)**.

Q225. GPS constellation: total operational SVs:

(a) 21

(b) 24

(c) 27

(d) 30

Ans: (b) — GPS: **24 SVs** (operational); up to 32 with spares.

Q226. GALILEO constellation: total SVs:

(a) 24

(b) 27

(c) 30

(d) 32

Ans: (c) — Galileo: **30 SVs**.

Q227. GLONASS constellation:

(a) 21

(b) 24

(c) 27

(d) 30

Ans: (b) — GLONASS: **24 SVs**.

Q228. GPS PRN codes — how many available?

(a) 24

(b) 32

(c) 64

(d) 252

Ans: (b) — GPS PRN codes: **32 available** (SVs numbered PRN 1–32).

Q229. GNSS integrity definition:

Join live classes for guided practice and doubt clearing.

(a) Accuracy of the position solution

(b) Ability to alert users when system should not be used

(c) Number of SVs visible

(d) Signal continuity

> **Ans: (b)** — Integrity: **ability to provide timely warning** when system unfit for navigation.

Q230. RAIM — what does it detect?

(a) Ionospheric error

(b) Failed SV causing position error exceeding limits

(c) Multipath

(d) Clock drift in receiver

> **Ans: (b)** — RAIM detects: **failed SV causing excessive position error**.

Q231. GPS almanac download time:

(a) 30 s

(b) 12.5 min

(c) 30 min

(d) 1 hour

> **Ans: (b)** — Full almanac download: **12.5 minutes** (25 frames × 30 s).

Q232. GPS cold start — time to first fix:

(a) 30 s

(b) 1–2 min

(c) 12.5 min

(d) Up to 30 min

> **Ans: (c)** — Cold start (no almanac): up to **12.5 min** for almanac download.

Q233. PDOP (Position Dilution of Precision) — best geometry:

(a) High PDOP

(b) Low PDOP

(c) PDOP = 1 always

(d) PDOP irrelevant

Join live classes for guided practice and doubt clearing.

Ans: (b) — Best geometry: **low PDOP** (SVs spread widely across sky).

Q234. GPS ionospheric model corrects approximately:

(a) 10%

(b) 50%

(c) 75%

(d) 99%

Ans: (b) — GPS ionospheric model: **≈50%** correction. Dual-freq: ≈99%.

Q235. SBAS integrity monitoring provided by:

(a) Ground reference stations

(b) Control segment only

(c) RAIM

(d) Aircraft receiver

Ans: (a) — SBAS: **network of ground reference stations** monitors satellite integrity.

Q236. Galileo orbital inclination:

(a) 55°

(b) 56°

(c) 63°

(d) 65°

Ans: (b) — Galileo: **56°**.

Q237. GPS Week Number rollover issue — period:

(a) 10.9 years (1024 weeks)

(b) 19.7 years

(c) 7 years

(d) Every year

Ans: (a) — GPS week: 10-bit number → rolls over every **1024 weeks (≈19.7 years)**. [Some say 19.7 — check ICAO doc for exact value used]

Join live classes for guided practice and doubt clearing.

Q238. GNSS continuity of service — definition:

(a) System accuracy

(b) Probability of system performing without interruption during operation

(c) Integrity

(d) Number of SVs

Ans: (b) — Continuity: **probability of uninterrupted operation during intended use**.

Q239. GNSS availability — definition:

(a) Accuracy spec

(b) Proportion of time system provides navigation with required accuracy

(c) Integrity

(d) Continuity

Ans: (b) — Availability: **proportion of time system meets accuracy and integrity requirements**.

Q240. GPS L1 C/A code — chip length:

(a) 30 m

(b) 300 m

(c) 1 km

(d) 3 km

Ans: (b) — C/A chip length = $c/f = 3\times10^8/1.023\times10^6$ = **293 m ≈ 300 m**.

Q241. GNSS approach — LPV (Localizer Performance with Vertical guidance) provides:

(a) Lateral only

(b) Lateral + baro-VNAV

(c) Lateral + SBAS vertical guidance (like ILS CAT I)

(d) No approach minima

Ans: (c) — LPV: SBAS approach with lateral + **SBAS vertical guidance**, minima approaching CAT I.

Q242. GPS time offset from UTC at receiver:

(a) Zero — GPS = UTC

(b) GPS ahead of UTC by integer seconds (leap seconds)

Join live classes for guided practice and doubt clearing.

(c) GPS behind UTC

(d) Varies daily

Ans: (b) — GPS time: **ahead of UTC by integer leap seconds**. Receiver subtracts leap second count to display UTC.

Q243. GNSS — which error source causes errors of hundreds of metres without correction?

(a) Multipath

(b) Clock error

(c) Selective Availability (when active)

(d) Tropospheric delay

Ans: (c) — When SA active: errors up to **100 m** (horizontal). SA now off.

📝 66-Question Specimen Exam — Answer Key

Q1=b • Q2=c • Q3=d • Q4=a • Q5=a • Q6=d • Q7=b • Q8=c • Q9=a • Q10=c • Q11=d • Q12=d
Q13=c • Q14=a • Q15=d • Q16=a • Q17=d • Q18=b • Q19=a • Q20=b • Q21=c • Q22=d • Q23=b • Q24=d
Q25=a • Q26=d • Q27=b • Q28=c • Q29=b • Q30=a • Q31=a • Q32=a • Q33=b • Q34=c • Q35=a • Q36=d
Q37=b • Q38=a • Q39=b • Q40=b • Q41=d • Q42=b • Q43=b • Q44=b • Q45=c • Q46=a • Q47=d • Q48=a
Q49=c • Q50=c • Q51=b • Q52=d • Q53=b • Q54=a • Q55=a • Q56=a • Q57=a • Q58=c • Q59=d • Q60=b
Q61=b • Q62=c • Q63=b • Q64=a • Q65=b • Q66=b

© Ghost Aviator | www.ghostaviator.com

Join live classes for guided practice and doubt clearing.