

```
In [15]: import matplotlib.pyplot as plt
import pandas as pd
import numpy as np
```

```
In [16]: def kernel(point, xmat, k):
    m,n = np.shape(xmat)
    weights = np.mat(np.eye((m)))
    for j in range(m):
        diff = point - X[j]
        weights[j,j] = np.exp(diff*diff.T/(-2.0*k**2))
    return weights

def localWeight(point, xmat, ymat, k):
    wei = kernel(point,xmat,k)
    W = (X.T*(wei*X)).I*(X.T*(wei*ymat.T))
    return W

def localWeightRegression(xmat, ymat, k):
    m,n = np.shape(xmat)
    ypred = np.zeros(m)
    for i in range(m):
        ypred[i] = xmat[i]*localWeight(xmat[i],xmat,ymat,k)
    return ypred
```


```
In [17]: # load data points
data = pd.read_csv('restaurant_bill.csv')
bill = np.array(data.total_bill)
tip = np.array(data.tip)
```

```
In [18]: #preparing and add 1 in bill
mbill = np.mat(bill)
mtip = np.mat(tip)
```

```
In [19]: m= np.shape(mbill)[1]
one = np.mat(np.ones(m))
X = np.hstack((one.T,mbill.T))
```

```
In [20]: #set k here
ypred = localWeightRegression(X,mtip,0.5)
SortIndex = X[:,1].argsort(0)
xsort = X[SortIndex][:,0]
```

```
In [21]: fig = plt.figure()
ax = fig.add_subplot(1,1,1)
ax.scatter(bill,tip, color='green')
ax.plot(xsort[:,1],ypred[SortIndex], color = 'red', linewidth=5)
plt.xlabel('Total bill')
plt.ylabel('Tip')
plt.show();
```



In []: