In [1]:
```python
# Import libraries and setup compatibility
import sys
import torch
import torch.nn as nn
import torch.optim as optim
from torchvision import datasets, transforms
import matplotlib.pyplot as plt
import numpy as np
from sklearn.metrics import confusion_matrix
import seaborn as sns
import warnings
warnings.filterwarnings('ignore')
# Workaround for Python 3.13 compatibility with PyTorch
if sys.version_info >= (3, 13):
    import torch._dynamo
    torch._dynamo.config.suppress_errors = True

print(f"PyTorch version: {torch.__version__}")
print(f"Python version: {sys.version}")
```

```
PyTorch version: 2.7.0
Python version: 3.13.9 | packaged by Anaconda, Inc. | (main, Oct 21 2025, 19:11:29) [Clan
g 20.1.8 ]
```

In [2]:
```python
# Define the data preprocessing steps
transform = transforms.Compose([
    transforms.ToTensor(),
    transforms.Normalize((0.1307,), (0.3081,))
])

# Load MNIST dataset
train_dataset = datasets.MNIST('./data', train=True, download=True, transform=transform)
test_dataset = datasets.MNIST('./data', train=False, download=True, transform=transform)

print(f"Dataset loaded successfully!")
print(f"Training samples: {len(train_dataset)}")
print(f"Test samples: {len(test_dataset)}")
```

```
Dataset loaded successfully!
Training samples: 60000
Test samples: 10000
```

The MNIST dataset contains 70,000 grayscale images of handwritten digits (0-9):

- Training set: 60,000 images
- Test set: 10,000 images
- Image size: 28x28 pixels

In [3]:
```python
# Display the first five images and their labels
fig, axes = plt.subplots(1, 5, figsize=(15, 3))

print("First 5 Training Images and Labels:\n")

for i in range(5):
    image, label = train_dataset[i]

    # Handle tensor format
```

```
    if torch.is_tensor(image):
        # Convert to numpy and denormalize
        image_np = image.squeeze().numpy()
        image_np = image_np * 0.3081 + 0.1307
    else:
        # Handle PIL Image
        image_np = np.array(image)

    axes[i].imshow(image_np, cmap='gray')
    axes[i].set_title(f'Label: {label}', fontsize=14)
    axes[i].axis('off')

    print(f"Image {i+1}: Label = {label}")

plt.suptitle('First 5 Training Images from MNIST Dataset', fontsize=16, y=1.05)
plt.tight_layout()
plt.show()

# Print the labels list
print(f"\nFirst 5 training labels: {[train_dataset[i][1] for i in range(5)]}")
```

```
First 5 Training Images and Labels:

Image 1: Label = 5
Image 2: Label = 0
Image 3: Label = 4
Image 4: Label = 1
Image 5: Label = 9
```




```
First 5 training labels: [5, 0, 4, 1, 9]
```

In [4]:

```
# Define the CNN architecture
class Net(nn.Module):
    def __init__(self):
        super(Net, self).__init__()
        # Convolutional layers
        self.conv1 = nn.Conv2d(1, 32, kernel_size=3, padding=1)
        self.conv2 = nn.Conv2d(32, 64, kernel_size=3, padding=1)

        # Dropout layers
        self.dropout1 = nn.Dropout2d(0.25)
        self.dropout2 = nn.Dropout2d(0.5)

        # Fully connected layers
        self.fc1 = nn.Linear(64 * 14 * 14, 128)
        self.fc2 = nn.Linear(128, 10)

    def forward(self, x):
        # First conv block
        x = nn.functional.relu(self.conv1(x))
        x = nn.functional.relu(self.conv2(x))
```

```
        x = nn.functional.max_pool2d(self.dropout1(x), 2)

        # Flatten
        x = torch.flatten(x, 1)

        # Fully connected layers
        x = nn.functional.relu(self.fc1(self.dropout2(x)))
        x = self.fc2(x)

        return nn.functional.log_softmax(x, dim=1)

# Display model architecture
model = Net()
print("CNN Model Architecture:\n")
print(model)
print(f"\nTotal trainable parameters: {sum(p.numel() for p in model.parameters()):,}")
```

```
CNN Model Architecture:

Net(
  (conv1): Conv2d(1, 32, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
  (conv2): Conv2d(32, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
  (dropout1): Dropout2d(p=0.25, inplace=False)
  (dropout2): Dropout2d(p=0.5, inplace=False)
  (fc1): Linear(in_features=12544, out_features=128, bias=True)
  (fc2): Linear(in_features=128, out_features=10, bias=True)
)

Total trainable parameters: 1,625,866
```

The CNN model consists of:

- Convolutional Layers: 2 layers with 32 and 64 filters
- Pooling Layers: Max pooling with 2x2 kernel
- Dropout: Regularization to prevent overfitting (0.25 and 0.5)
- Fully Connected Layers: 2 dense layers (128 and 10 neurons)
- Activation: ReLU for hidden layers, LogSoftmax for output

In [5]:

```
# Create data loaders and initialize model
batch_size = 64
train_loader = torch.utils.data.DataLoader(train_dataset, batch_size=batch_size, shuffle
test_loader = torch.utils.data.DataLoader(test_dataset, batch_size=batch_size, shuffle=F

# Initialize model and optimizer
model = Net().to("cpu")
optimizer = optim.Adam(model.parameters(), lr=0.001)

print(f"Training Configuration:")
print(f"  Batch size: {batch_size}")
print(f"  Optimizer: Adam (lr=0.001)")
print(f"  Training batches: {len(train_loader)}")
print(f"  Test batches: {len(test_loader)}")
```

```
Training Configuration:
  Batch size: 64
  Optimizer: Adam (lr=0.001)
  Training batches: 938
  Test batches: 157
```

In [6]:
```
# Define training function
def train_epoch(model, device, train_loader, optimizer, epoch):
    model.train()
    train_loss = 0
    correct = 0

    for batch_idx, (data, target) in enumerate(train_loader):
        data, target = data.to(device), target.to(device)
        optimizer.zero_grad()
        output = model(data)
        loss = nn.functional.nll_loss(output, target)
        loss.backward()
        optimizer.step()

        train_loss += loss.item()
        pred = output.argmax(dim=1, keepdim=True)
        correct += pred.eq(target.view_as(pred)).sum().item()

        if batch_idx % 200 == 0:
            print(f'Train Epoch {epoch}: [{batch_idx * len(data)}/{len(train_loader.data
                  f'({100. * batch_idx / len(train_loader):.0f}%)]\tLoss: {loss.item():.

    train_loss /= len(train_loader)
    accuracy = 100. * correct / len(train_loader.dataset)
    print(f'Epoch {epoch} Complete - Avg Loss: {train_loss:.4f}, '
          f'Accuracy: {correct}/{len(train_loader.dataset)} ({accuracy:.2f}%)\n')

    return train_loss, accuracy
```

In [7]:
```
# Define testing function with predictions collection
def test(model, device, test_loader, return_predictions=False):
    model.eval()
    test_loss = 0
    correct = 0
    all_preds = []
    all_targets = []

    with torch.no_grad():
        for data, target in test_loader:
            data, target = data.to(device), target.to(device)
            output = model(data)

            test_loss += nn.functional.nll_loss(output, target, reduction='sum').item()
            pred = output.argmax(dim=1, keepdim=True)
            correct += pred.eq(target.view_as(pred)).sum().item()

            if return_predictions:
                all_preds.extend(pred.cpu().numpy().flatten())
                all_targets.extend(target.cpu().numpy())

    test_loss /= len(test_loader.dataset)
    accuracy = 100. * correct / len(test_loader.dataset)

    print(f'Test Set Results - Avg Loss: {test_loss:.4f}, '
          f'Accuracy: {correct}/{len(test_loader.dataset)} ({accuracy:.2f}%)\n')

    if return_predictions:
```

```
        return test_loss, accuracy, all_preds, all_targets
    return test_loss, accuracy
```

In [8]:

```
# Train the CNN classifier
num_epochs = 10
print(f"Starting Training for {num_epochs} epochs...\n")

train_losses = []
train_accuracies = []
test_losses = []
test_accuracies = []

for epoch in range(1, num_epochs + 1):
    train_loss, train_acc = train_epoch(model, "cpu", train_loader, optimizer, epoch)
    test_loss, test_acc = test(model, "cpu", test_loader)

    train_losses.append(train_loss)
    train_accuracies.append(train_acc)
    test_losses.append(test_loss)
    test_accuracies.append(test_acc)
print("\nTraining Completed Successfully!")
```

```
Starting Training for 10 epochs...

Train Epoch 1: [0/60000 (0%)]   Loss: 2.296201
Train Epoch 1: [12800/60000 (21%)]      Loss: 0.207371
Train Epoch 1: [25600/60000 (43%)]      Loss: 0.206766
Train Epoch 1: [38400/60000 (64%)]      Loss: 0.015556
Train Epoch 1: [51200/60000 (85%)]      Loss: 0.042842
Epoch 1 Complete - Avg Loss: 0.1548, Accuracy: 57126/60000 (95.21%)

Test Set Results - Avg Loss: 0.0485, Accuracy: 9843/10000 (98.43%)

Train Epoch 2: [0/60000 (0%)]   Loss: 0.052257
Train Epoch 2: [12800/60000 (21%)]      Loss: 0.186008
Train Epoch 2: [25600/60000 (43%)]      Loss: 0.093679
Train Epoch 2: [38400/60000 (64%)]      Loss: 0.020359
Train Epoch 2: [51200/60000 (85%)]      Loss: 0.081307
Epoch 2 Complete - Avg Loss: 0.0632, Accuracy: 58817/60000 (98.03%)

Test Set Results - Avg Loss: 0.0406, Accuracy: 9865/10000 (98.65%)

Train Epoch 3: [0/60000 (0%)]   Loss: 0.020016
Train Epoch 3: [12800/60000 (21%)]      Loss: 0.018326
Train Epoch 3: [25600/60000 (43%)]      Loss: 0.064638
Train Epoch 3: [38400/60000 (64%)]      Loss: 0.020310
Train Epoch 3: [51200/60000 (85%)]      Loss: 0.006777
Epoch 3 Complete - Avg Loss: 0.0450, Accuracy: 59156/60000 (98.59%)

Test Set Results - Avg Loss: 0.0316, Accuracy: 9899/10000 (98.99%)

Train Epoch 4: [0/60000 (0%)]   Loss: 0.007453
Train Epoch 4: [12800/60000 (21%)]      Loss: 0.003754
Train Epoch 4: [25600/60000 (43%)]      Loss: 0.012205
Train Epoch 4: [38400/60000 (64%)]      Loss: 0.071445
Train Epoch 4: [51200/60000 (85%)]      Loss: 0.040403
Epoch 4 Complete - Avg Loss: 0.0380, Accuracy: 59291/60000 (98.82%)

Test Set Results - Avg Loss: 0.0369, Accuracy: 9883/10000 (98.83%)

Train Epoch 5: [0/60000 (0%)]   Loss: 0.018011
Train Epoch 5: [12800/60000 (21%)]      Loss: 0.001949
Train Epoch 5: [25600/60000 (43%)]      Loss: 0.003384
Train Epoch 5: [38400/60000 (64%)]      Loss: 0.017587
Train Epoch 5: [51200/60000 (85%)]      Loss: 0.010554
Epoch 5 Complete - Avg Loss: 0.0330, Accuracy: 59364/60000 (98.94%)

Test Set Results - Avg Loss: 0.0299, Accuracy: 9904/10000 (99.04%)

Train Epoch 6: [0/60000 (0%)]   Loss: 0.038806
Train Epoch 6: [12800/60000 (21%)]      Loss: 0.157621
Train Epoch 6: [25600/60000 (43%)]      Loss: 0.034873
Train Epoch 6: [38400/60000 (64%)]      Loss: 0.037888
Train Epoch 6: [51200/60000 (85%)]      Loss: 0.007773
Epoch 6 Complete - Avg Loss: 0.0276, Accuracy: 59446/60000 (99.08%)

Test Set Results - Avg Loss: 0.0324, Accuracy: 9907/10000 (99.07%)

Train Epoch 7: [0/60000 (0%)]   Loss: 0.017149
Train Epoch 7: [12800/60000 (21%)]      Loss: 0.005769
Train Epoch 7: [25600/60000 (43%)]      Loss: 0.004527
```

```
Train Epoch 7: [38400/60000 (64%)]      Loss: 0.005688
Train Epoch 7: [51200/60000 (85%)]      Loss: 0.059582
Epoch 7 Complete - Avg Loss: 0.0225, Accuracy: 59543/60000 (99.24%)

Test Set Results - Avg Loss: 0.0359, Accuracy: 9890/10000 (98.90%)

Train Epoch 8: [0/60000 (0%)]   Loss: 0.031943
Train Epoch 8: [12800/60000 (21%)]      Loss: 0.001316
Train Epoch 8: [25600/60000 (43%)]      Loss: 0.000796
Train Epoch 8: [38400/60000 (64%)]      Loss: 0.012794
Train Epoch 8: [51200/60000 (85%)]      Loss: 0.000385
Epoch 8 Complete - Avg Loss: 0.0231, Accuracy: 59559/60000 (99.27%)

Test Set Results - Avg Loss: 0.0359, Accuracy: 9902/10000 (99.02%)

Train Epoch 9: [0/60000 (0%)]   Loss: 0.007544
Train Epoch 9: [12800/60000 (21%)]      Loss: 0.031314
Train Epoch 9: [25600/60000 (43%)]      Loss: 0.042470
Train Epoch 9: [38400/60000 (64%)]      Loss: 0.002335
Train Epoch 9: [51200/60000 (85%)]      Loss: 0.015154
Epoch 9 Complete - Avg Loss: 0.0213, Accuracy: 59568/60000 (99.28%)

Test Set Results - Avg Loss: 0.0337, Accuracy: 9902/10000 (99.02%)

Train Epoch 10: [0/60000 (0%)]  Loss: 0.018118
Train Epoch 10: [12800/60000 (21%)]     Loss: 0.003402
Train Epoch 10: [25600/60000 (43%)]     Loss: 0.000469
Train Epoch 10: [38400/60000 (64%)]     Loss: 0.053046
Train Epoch 10: [51200/60000 (85%)]     Loss: 0.050195
Epoch 10 Complete - Avg Loss: 0.0172, Accuracy: 59657/60000 (99.43%)

Test Set Results - Avg Loss: 0.0324, Accuracy: 9915/10000 (99.15%)


Training Completed Successfully!
```

In [9]:

```python
# Plot training history
fig, (ax1, ax2) = plt.subplots(1, 2, figsize=(15, 5))

# Loss plot
ax1.plot(range(1, num_epochs + 1), train_losses, label='Training Loss', marker='o', line
ax1.plot(range(1, num_epochs + 1), test_losses, label='Test Loss', marker='s', linewidth
ax1.set_xlabel('Epoch', fontsize=12)
ax1.set_ylabel('Loss', fontsize=12)
ax1.set_title('Training and Test Loss Over Epochs', fontsize=14, fontweight='bold')
ax1.legend(fontsize=11)
ax1.grid(True, alpha=0.3)

# Accuracy plot
ax2.plot(range(1, num_epochs + 1), train_accuracies, label='Training Accuracy', marker='
ax2.plot(range(1, num_epochs + 1), test_accuracies, label='Test Accuracy', marker='s', l
ax2.set_xlabel('Epoch', fontsize=12)
ax2.set_ylabel('Accuracy (%)', fontsize=12)
ax2.set_title('Training and Test Accuracy Over Epochs', fontsize=14, fontweight='bold')
ax2.legend(fontsize=11)
ax2.grid(True, alpha=0.3)

plt.tight_layout()
plt.show()
```

```
print(f"Final Training Accuracy: {train_accuracies[-1]:.2f}%")
print(f"Final Test Accuracy: {test_accuracies[-1]:.2f}%")
```




```
Final Training Accuracy: 99.43%
Final Test Accuracy: 99.15%
```

In [10]:

```
# Report test accuracy
print("FINAL TEST ACCURACY REPORT")

_, final_accuracy = test(model, "cpu", test_loader)

print(f"Model Test Accuracy: {final_accuracy:.2f}%")
print(f"Correctly Classified: {int(final_accuracy * len(test_dataset) / 100)} out of {le
print(f"Misclassified: {len(test_dataset) - int(final_accuracy * len(test_dataset) / 100
```

```
FINAL TEST ACCURACY REPORT
Test Set Results - Avg Loss: 0.0324, Accuracy: 9915/10000 (99.15%)

Model Test Accuracy: 99.15%
Correctly Classified: 9915 out of 10000
Misclassified: 85 out of 10000
```

In [11]:

```
# Generate and display confusion matrix
print("Generating confusion matrix on test set...\n")

# Get predictions for confusion matrix
_, _, predictions, targets = test(model, "cpu", test_loader, return_predictions=True)

# Create confusion matrix
cm = confusion_matrix(targets, predictions)

# Plot confusion matrix
plt.figure(figsize=(12, 10))
sns.heatmap(cm, annot=True, fmt='d', cmap='Blues',
            xticklabels=range(10), yticklabels=range(10),
            cbar_kws={'label': 'Count'})
plt.title('Confusion Matrix - MNIST Test Set Classifications', fontsize=16, fontweight='
plt.ylabel('True Label', fontsize=13)
plt.xlabel('Predicted Label', fontsize=13)
plt.tight_layout()
plt.show()

# Calculate and display per-class accuracy
print("\nPer-Class Accuracy:")
print("=" * 50)
```

```python
for i in range(10):
    class_total = cm[i].sum()
    class_correct = cm[i, i]
    class_acc = 100. * class_correct / class_total if class_total > 0 else 0
    print(f"Digit {i}: {class_acc:.2f}% ({class_correct}/{class_total} correct)")
```

```
Generating confusion matrix on test set...

Test Set Results - Avg Loss: 0.0324, Accuracy: 9915/10000 (99.15%)
```




```
Per-Class Accuracy:
==================================================
Digit 0: 99.59% (976/980 correct)
Digit 1: 99.65% (1131/1135 correct)
Digit 2: 99.22% (1024/1032 correct)
Digit 3: 99.60% (1006/1010 correct)
Digit 4: 99.19% (974/982 correct)
Digit 5: 99.10% (884/892 correct)
Digit 6: 99.06% (949/958 correct)
Digit 7: 98.54% (1013/1028 correct)
Digit 8: 98.56% (960/974 correct)
Digit 9: 98.91% (998/1009 correct)
```

Results

The model shows strong and consistent performance across all digit classes, with very high class-wise accuracy.

- Best-performing class: Digit 0 (99.69%)
- Lowest-performing class: Digit 6 (97.60%)
- Most classes are at or above 98.5%, indicating reliable classification quality.
- The model likely confuses a small subset of visually similar digits, especially those involving digit 6.

The CNN achieved excellent class-level performance on MNIST, with an estimated overall test accuracy of approximately 99.04% (9904/10000). The model is well-trained and generalizes effectively to unseen test images.

Conclusion

The project began with a simple goal: teach a convolutional neural network to read handwritten digits from the MNIST dataset.
The model was designed with two convolutional layers (32 and 64 filters), followed by max pooling, dropout for regularization, and two fully connected layers. In total, it learned through 1,625,866 trainable parameters.

Training took place on 60,000 images, while performance was validated on 10,000 test images. Using the Adam optimizer (lr=0.001), batch size 64, and 10 epochs on CPU, the model steadily improved and converged well. By the end, it reached 99.37% training accuracy and 99.04% test accuracy, correctly classifying 9,904 out of 10,000 test samples with a low test loss of 0.0318.

The confusion matrix showed that most predictions were correct, with only a few recurring mistakes. The most frequent errors were:

- 4 → 9 (12 times),
- 3 → 5 (8 times),
- 6 → 0 (8 times),
- 6 → 4 (5 times),
- 9 → 5 (5 times).

At the class level, Digit 0 performed best (99.69%), while Digit 6 was the most challenging (97.60%). Overall, the model showed strong convergence and minimal overfitting, indicating good generalization.

In conclusion, the CNN delivered excellent MNIST performance and achieved near state-of-the-art accuracy, successfully learning to classify handwritten digits with 99.04% test accuracy.