

Paste HTML element by inspecting here!

es/74tdo0adae1d049a4410e9076ee9ee4b55242" class="notecardImageClass"
d="74tdo0adae1d049a4410e9076ee9ee4b55242"></div>
</div><div>
</div></div><div>
</div>
</div><div>
</div></div> </div> </div> </div>


Download as PDF

Thread Pools and ThreadPoolExecutor

"Concept && Coding" YT Video Notes

What is ThreadPool:

- It's a collection of threads (aka workers), which are available to perform the submitted tasks.
- Once task completed, worker thread get back to Thread Pool and wait for new task to assigned.
- Means threads can be reused.



What's the Advantage of Thread Pool?

- Thread Creation time can be saved:

- When each thread created, space is allocated to it (stack, heap, program counter etc..) and this takes time.
- With thread, this can be avoided by reusing the thread.


- Overhead of managing the Thread lifecycle can be removed:

- Thread has different state like Running, Waiting, terminate etc. And managing thread state includes complexity.
- Thread pool abstract away this management.

- Increased the performance:

- More threads means, more **Context Switching** time, using control over thread creation, excess context switching can be avoided.

package java.util.concurrent;



ThreadPoolExecutor:

It's helps to create a customizable ThreadPool.

```
public ThreadPoolExecutor  
    ( int corePoolSize  
      int maximumPoolSize,  
      long keepAliveTime,  
      TimeUnit unit,  
      BlockingQueue<Runnable> workQueue,  
      ThreadFactory threadFactory,  
      RejectedExecutionHandler handler)
```

- **corePoolSize:**

Number of threads are initially created and keep in the pool, even if they are idle.

- **allowCoreThreadTimeOut:**

If this property is set to TRUE (by default its FALSE), idle thread kept Alive till time specified by 'KeepAliveTime'.

- **KeepAliveTime:**

Thread, which are idle get terminated after this time.

- **maxPoolSize:**

Maximum number of thread allowed in a pool.

If no. of thread are == corePoolSize and queue is also full, then new threads are created (till its less than 'maxPoolSize').


Excess thread, will remain in pool, this pool is not shutdown or if **allowCoreThreadTimeOut** is set to true, then excess thread get terminated after remain idle for **KeepAliveTime**.

- **TimeUnit:**

TimeUnit for the keepAliveTime, whether **Millisecond** or **Second** or **Hours** etc.

- **BlockingQueue:**

Queue used to hold task, before they got picked by the worker thread.



- **ThreadFactory:**


Factory for creating new thread. `ThreadPoolExecutor` use this to create new thread, this Factory provide us an interface to:

- To give custom Thread name
- To give custom Thread priority
- To set Thread Daemon flag etc.

- **RejectedExecutionHandler:**

Handler for tasks that can not be accepted by thread pool.

Generally logging logic can be put here. For debugging purpose.



Example:

```
public class Main {

    public static void main(String args[]) {

        ThreadPoolExecutor poolExecutor = new ThreadPoolExecutor( corePoolSize: 2, maximumPoolSize: 5, keepAliveTime: 1,
            TimeUnit.HOURS, new ArrayBlockingQueue<>( capacity: 10), new CustomThreadFactor(),
            new CustomRejectedHandler());

        poolExecutor.allowCoreThreadTimeOut( value: true);

        //submit task
        for(int i=0; i< 25 ; i++){
            poolExecutor.submit(() -> {
                try {
                    Thread.sleep( millis: 5000);
                    System.out.println("Thread name:" + Thread.currentThread().getName());
                }catch (Exception e) {
                }
            });
        }

        poolExecutor.shutdown();
    }
}

class CustomRejectedHandler implements RejectedExecutionHandler{

    @Override
    public void rejectedExecution(Runnable r, ThreadPoolExecutor executor) {
        //logging
        System.out.println("Task denied:" + r.toString());
    }
}

class CustomThreadFactor implements ThreadFactory{

    @Override
    public Thread newThread(Runnable r) {

        Thread th = new Thread(r);
        return th;
    }
}
```

Interview question:

Why you have taken corePoolSize as 2, why not 10 or 15 or another number, what's the logic?

My Answer:

Generally, the ThreadPool min and max size are depend on various factors like:

- CPU Cores
- JVM Memory
- Task Nature (CPU Intensive or I/O Intensive)
- Concurrency Requirement (Want high or medium or low concurrency)
- Memory Required to process a request
- Throughput etc.

And its an iterative process to update the min and max values based on monitoring.

Formula to find the no. of thread:

Max No of thread = No. of CUP Core * (1 + Request waiting time/processing time)

No. of CUP Core = 4

Request waiting time = 10ms

Processing time = 100ms

But this formula, do not consider Memory yet, which need to be consider...