

ALGORITHM:

10. Create a New Android Project:

- Click New in the toolbar.
- In the window that appears, open the Android folder, select Android Application Project, and click next.
- Provide the application name and the project name and then finally give the desired package name.
- Choose a launcher icon for your application and then select Blank Activity and then click Next
- Provide the desired Activity name for your project and then click Finish.

11. Create a New AVD (Android Virtual Device):

- click Android Virtual Device Manager from the toolbar.
- In the Android Virtual Device Manager panel, click New.
- Fill in the details for the AVD. Give it a name, a platform target, an SD card size, and a skin (HVGA is default).
- Click Create AVD and Select the new AVD from the Android Virtual Device Manager and click Start.

12. Design the graphical layout using buttons, text and ImageView.

13. Run the application.

14. Fetch the details from the URL.

15. Display the output by clicking the result button.

16. Close the Android project.

MainActivity.java

```
package com.example.admin.myapplication;
```

```
import android.app.ListActivity;
import android.content.Intent;
import android.net.Uri;
import android.os.AsyncTask;
import android.os.Bundle;
import android.view.View;
import android.widget.AdapterView;
import android.widget.AdapterView.OnItemClickListener;
import android.widget.ListView;
```

```
import org.xmlpull.v1.XmlPullParser;
import org.xmlpull.v1.XmlPullParserException;
import org.xmlpull.v1.XmlPullParserFactory;
```

```
import java.io.IOException;
import java.io.InputStream;
import java.net.MalformedURLException;
import java.net.URL;
```

```

import java.util.ArrayList;
import java.util.List;

public class MainActivity extends ListActivity {
    List<String> headlines;
    List<String> links;

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        new MyAsyncTask().execute();
    }

    class MyAsyncTask extends AsyncTask<Object, Void, ArrayAdapter<String>> {
        @Override
        protected ArrayAdapter<String> doInBackground(Object[] params) {
            headlines = new ArrayList<>();
            links = new ArrayList<>();

            try {
                URL url = new URL("https://codingconnect.net/feed");
                XmlPullParserFactory factory = XmlPullParserFactory.newInstance();
                factory.setNamespaceAware(false);
                XmlPullParser xpp = factory.newPullParser();

                // We will get the XML from an input stream
                xpp.setInput(getInputStream(url), "UTF_8");
                boolean insideltem = false;

                // Returns the type of current event: START_TAG, END_TAG, etc..
                int eventType = xpp.getEventType();
                while (eventType != XmlPullParser.END_DOCUMENT) {
                    if (eventType == XmlPullParser.START_TAG) {
                        if (xpp.getName().equalsIgnoreCase("item")) {
                            insideltem = true;
                        } else if (xpp.getName().equalsIgnoreCase("title")) {
                            if (insideltem) {
                                headlines.add(xpp.nextText()); // extract the headline
                            }
                        } else if (xpp.getName().equalsIgnoreCase("link")) {
                            if (insideltem) {
                                links.add(xpp.nextText()); // extract the link of article
                            }
                        }
                    } else if (eventType == XmlPullParser.END_TAG &&
xpp.getName().equalsIgnoreCase("item")) {
                        insideltem = false;
                    }
                }
            }
        }
    }
}

```

```

        eventType = xpp.next(); // move to next element
    }
} catch (MalformedURLException e) {
    e.printStackTrace();
} catch (XmlPullParserException e) {
    e.printStackTrace();
} catch (IOException e) {
    e.printStackTrace();
}
return null;
}

@Override
protected void onPostExecute(ArrayAdapter<String> adapter) {
    adapter = new ArrayAdapter<>(MainActivity.this,
    android.R.layout.simple_list_item_1, headlines);
    setListAdapter(adapter);
}

@Override
protected void onItemClick(ListView l, View v, int position, long id) {
    Uri uri = Uri.parse((links.get(position)).toString());
    Intent intent = new Intent(Intent.ACTION_VIEW, uri);
    startActivity(intent);
}

public InputStream getInputStream(URL url) {
    try {
        return url.openConnection().getInputStream();
    } catch (IOException e) {
        return null;
    }
}
}

```

AndroidManifest.xml

```

<?xml version="1.0" encoding="utf-8"?>
<manifest xmlns:android="http://schemas.android.com/apk/res/android"
    package="com.example.exno10" >

    <uses-permission android:name="android.permission.INTERNET"/>

    <application
        android:allowBackup="true"
        android:icon="@mipmap/ic_launcher"

```

```

        android:label="@string/app_name"
        android:supportsRtl="true"
        android:theme="@style/AppTheme" >

        <activity android:name="com.example.admin.myapplication.MainActivity" >
            <intent-filter>
                <action android:name="android.intent.action.MAIN" />
                <category android:name="android.intent.category.LAUNCHER" />
            </intent-filter>
        </activity>

    </application>

</manifest>

```

activity_main.xml

```

<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="fill_parent"
    android:layout_height="fill_parent"
    android:orientation="vertical" >

    <ListView
        android:id="@+id/listView"
        android:layout_width="match_parent"
        android:layout_height="wrap_content" />

</LinearLayout>

```

11.

ALGORITHM:

1. Create a New Android Project:

- Click New in the toolbar.
- In the window that appears, open the Android folder, select Android Application Project, and click next.
- Provide the application name and the project name and then finally give the desired package name.
- Choose a launcher icon for your application and then select Blank Activity and then click Next

- Provide the desired Activity name for your project and then click Finish.
2. Create a New AVD (Android Virtual Device):
 - click Android Virtual Device Manager from the toolbar.
 - In the Android Virtual Device Manager panel, click New.
 - Fill in the details for the AVD. Give it a name, a platform target, an SD card size, and a skin (HVGA is default).
 - Click Create AVD and Select the new AVD from the Android Virtual Device Manager and click Start.
 3. Design the graphical layout.
 4. Run the application.
 5. When the application starts alarm sound will be invoked.
 6. Stop alarm button is clicked to stop the alarm.
 7. Close the Android project.

MainActivity.java

```
package com.example.admin.myapplication;

import android.content.Intent;
import android.net.Uri;
import android.os.Bundle;
import android.support.v7.app.AppCompatActivity;
import android.util.Log;
import android.view.View;
import android.widget.Button;
import android.widget.Toast;

public class MainActivity extends AppCompatActivity {

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);

        Button startBtn = (Button) findViewById(R.id.sendbtn);
        startBtn.setOnClickListener(new View.OnClickListener() {
            public void onClick(View view) {
                sendEmail();
            }
        });
    }
}
```

```

protected void sendEmail() {
    Log.i("Send email", "");
    String[] TO = {"muthuramalingam566@gmail.com"};
    String[] CC = {"ramdurai25@gmail.com"};

    Intent emailIntent = new Intent(Intent.ACTION_SEND);
    emailIntent.setData(Uri.parse("mailto:"));
    emailIntent.setType("text/plain");
    emailIntent.putExtra(Intent.EXTRA_EMAIL, TO);
    emailIntent.putExtra(Intent.EXTRA_CC, CC);
    emailIntent.putExtra(Intent.EXTRA_SUBJECT, "Your subject");
    emailIntent.putExtra(Intent.EXTRA_TEXT, "Email message goes here");

    try {
        startActivity(Intent.createChooser(emailIntent, "Send mail..."));
        finish();
        Log.i("Finished sending email...", "");
    } catch (android.content.ActivityNotFoundException ex) {
        Toast.makeText(MainActivity.this, "There is no email client installed.",
        Toast.LENGTH_SHORT).show();
    }
}
}

```

activity_main.xml

```

<?xml version="1.0" encoding="utf-8"?>
<RelativeLayout xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:tools="http://schemas.android.com/tools"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:paddingBottom="@dimen/activity_vertical_margin"
    android:paddingLeft="@dimen/activity_horizontal_margin"
    android:paddingRight="@dimen/activity_horizontal_margin"
    android:paddingTop="@dimen/activity_vertical_margin"
    tools:context="com.example.admin.myapplication.MainActivity">

    <EditText
        android:id="@+id/editText"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:inputType="textEmailAddress"
        android:ems="10"
        android:layout_alignParentTop="true"

```

```
android:layout_alignParentRight="true"  
android:layout_alignParentEnd="true" />
```

```
<EditText  
    android:id="@+id/editText2"  
    android:layout_width="wrap_content"  
    android:layout_height="wrap_content"  
    android:inputType="textEmailAddress"  
    android:ems="10"  
    android:layout_below="@+id/editText"  
    android:layout_alignRight="@+id/editText"  
    android:layout_alignEnd="@+id/editText" />
```

```
<EditText  
    android:id="@+id/editText3"  
    android:layout_width="wrap_content"  
    android:layout_height="wrap_content"  
    android:inputType="textEmailAddress"  
    android:ems="10"  
    android:layout_below="@+id/editText2"  
    android:layout_alignRight="@+id/editText2"  
    android:layout_alignEnd="@+id/editText2" />
```

```
<Button  
    android:id="@+id/sendbtn"  
    android:layout_width="wrap_content"  
    android:layout_height="wrap_content"  
    android:text="SEND MAIL"  
    android:layout_centerVertical="true"  
    android:layout_alignLeft="@+id/editText3"  
    android:layout_alignStart="@+id/editText3" />
```

```
<TextView  
    android:id="@+id/textView"  
    android:layout_width="wrap_content"  
    android:layout_height="wrap_content"  
    android:text="Recipient"  
    android:layout_alignBottom="@+id/editText"  
    android:layout_alignParentLeft="true"  
    android:layout_alignParentStart="true" />
```

```
<TextView  
    android:id="@+id/textView2"  
    android:layout_width="wrap_content"
```

```
android:layout_height="wrap_content"  
android:text="subject"  
android:layout_alignBottom="@+id/editText2"  
android:layout_alignParentLeft="true"  
android:layout_alignParentStart="true" />
```

```
<TextView  
    android:id="@+id/textView3"  
    android:layout_width="wrap_content"  
    android:layout_height="wrap_content"  
    android:text="Message Body"  
    android:layout_alignBottom="@+id/editText3"  
    android:layout_alignParentLeft="true"  
    android:layout_alignParentStart="true" />
```

```
</RelativeLayout>
```