

Safety Data Sheet

Atlas HydraSeal AH-220 — Bearing Housing Lubricant

SDS No: SDS-AH220-REV-3 | Revision Date: January 2026 | Format: GHS-aligned (illustrative)

Section 1: Identification

Product name: Atlas HydraSeal AH-220

Product code: AH-220

Recommended use: Bearing housing lubricant for AF-series pumps

Manufacturer: Atlas Fluid Systems B.V., Waalhaven Oz 45, 3087 Rotterdam, Netherlands

Emergency telephone: +31 10 555 0199 (24-hour)

Section 2: Hazard(s) Identification

Signal word: Warning

Hazard statements:

- H304 — May be fatal if swallowed and enters airways (aspiration hazard).
- H411 — Toxic to aquatic life with long-lasting effects.

Precautionary statements: Avoid release to the environment. Do not induce vomiting if swallowed. Wear protective gloves and eye protection.

Section 3: Composition / Information on Ingredients

Component	Reference ID	Concentration (%)
Mineral oil base stock	ATL-REF-0110	70 – 90
Anti-wear additive package (proprietary)	ATL-REF-0231	5 – 15
Corrosion inhibitor	ATL-REF-0344	1 – 5

Section 4: First-Aid Measures

Eye contact: Flush with water for at least 15 minutes; seek medical attention if irritation persists.

Skin contact: Remove contaminated clothing; wash skin thoroughly with soap and water.

Inhalation: Move to fresh air; seek medical attention if breathing difficulty occurs.

Ingestion: Do not induce vomiting. Seek immediate medical attention.

Section 5: Fire-Fighting Measures

Flash point (closed cup): 220°C

Suitable extinguishing media: Foam, dry chemical, carbon dioxide. Do not use a direct water jet.

Section 6: Accidental Release Measures

Contain spill with absorbent material; prevent entry into drains or waterways; dispose of per local regulations. Notify Atlas EHS at ehs@atlasfluidsystems-example.com for spills exceeding 20 L.

Section 7: Handling and Storage

Store in original sealed containers between 5°C and 40°C, away from oxidizing agents and direct sunlight. Keep containers closed when not in use.

Section 8: Exposure Controls / Personal Protection

- Gloves: Nitrile rubber, minimum 0.4 mm thickness.
- Eye protection: Safety glasses with side shields.
- Ventilation: Use in well-ventilated areas; local exhaust not normally required for routine handling.

Section 9: Physical and Chemical Properties

Property	Value
Appearance	Amber liquid
Odor	Mild, characteristic
Flash point	220°C (closed cup)
Viscosity @ 40°C	46 cSt
Density @ 15°C	0.87 g/cm³
Pour point	-24°C

Section 10: Stability and Reactivity

Stable under normal storage and handling conditions. Avoid contact with strong oxidizing agents.

Section 11: Toxicological Information

No significant acute toxicity expected via dermal contact under normal handling. Repeated inhalation of mist should be avoided.

Section 15: Regulatory Information

Classified per illustrative GHS criteria for this demonstration document only; does not reflect an actual regulatory filing.

Section 16: Other Information

Revision date: January 2026. Supersedes SDS-AH220-REV-2. Prepared by Atlas Fluid Systems EHS team. This SDS is provided for illustrative use in a fictional dataset.