

=====

SAFETY DATA SHEET (SDS) - GHS / OSHA HAZCOM STANDARD

Document Code: SDS_108-95-2 | Revision: R1

Chemical Name: Phenol (Carbolic Acid, CAS 108-95-2) & Acetone (CAS 67-64-1) Cleavage Product

Applicable Process Streams: Unit 2300 Streams S379, S380, S384 (D-2304, E-2307, D-2310)

1. HAZARD IDENTIFICATION & SYSTEMIC TOXICITY

- Rapid Dermal Absorption Hazard: Liquid Phenol penetrates intact skin rapidly, causing local anesthesia (masking
- Occupational Exposure Limits: OSHA PEL / ACGIH TWA = 5.0 ppm (19 mg/m3) Skin Notation; IDLH = 250 ppm.

=====

SDS_108-95-2 PAGE 2 OF 3 - PHYSICAL & CHEMICAL PROPERTIES

- Pure Phenol Freezing Point: 40.9 degC | Normal Boiling Point: 181.7 degC | Flash Point: 79.0 degC (Closed Cup)
- Acetone Normal Boiling Point: 56.1 degC | Flash Point: -20.0 degC (Extremely Flammable Liquid Category 2)

=====

SDS_108-95-2 PAGE 3 OF 3 - MANDATORY FIRST AID & PEG-300 DECONTAMINATION

- Immediate Dermal First Aid Protocol: Irrigate immediately with Polyethylene Glycol 300/400 (PEG-300) swabbing s