

=====

SAFETY DATA SHEET (SDS) - GHS / OSHA HAZCOM STANDARD

Document Code: SDS\_80-15-9 | Revision: R1

Chemical Name: Cumene Hydroperoxide (alpha,alpha-Dimethylbenzyl Hydroperoxide, 80-82 wt% in Cumene)

CAS Number: 80-15-9 | UN Number: UN 3109 (Organic Peroxide Type F, Liquid)

1. HAZARD IDENTIFICATION & REACTIVE THERMAL HAZARDS

- GHS Classifications:

\* Organic Peroxide Type F (H242: Heating may cause a fire or explosion)

\* Acute Toxicity Oral/Dermal Category 3, Inhalation Category 2

\* Skin Corrosion Category 1B (Causes severe skin burns and eye damage)

- Self-Accelerating Decomposition Temperature (SADT): 75.0 degC (for prolonged unstirred storage); maximum contin

- Exothermic Decomposition Energy: -1580 kJ/kg CHP (liberates non-condensable methane, oxygen, acetone, and aceto

=====

SDS\_80-15-9 PAGE 2 OF 4 - INCOMPATIBLE MATERIALS & CONTAMINATION HAZARDS

- Strictly Incompatible Substances: Strong mineral acids (H<sub>2</sub>SO<sub>4</sub> above controlled 180 ppmw catalytic setpoint), tr
- Material Compatibility Rule: Only passivated 316L Stainless Steel (SA-240 316L) or glass-lined equipment is per

=====

SDS\_80-15-9 PAGE 3 OF 4 - EMERGENCY RUNAWAY QUENCH & SPILL RESPONSE

- Process Runaway Mitigation: If temperature in D-2304 exceeds 92.0 degC (TAH-1301) and approaches 115.0 degC (TX
- Fire Fighting Media: Water spray/deluge from safe distance, alcohol-resistant foam. Never use dry chemical ager

=====

SDS\_80-15-9 PAGE 4 OF 4 - PERSONAL PROTECTIVE EQUIPMENT & EXPOSURE CONTROLS

- Short-Term Exposure Limit (STEL): 1.0 ppm ceiling
- Required PPE: Full chemical splash suit (Viton/Butyl), SCBA for any line-breaking or sampling on Stream S210 /