


Meshes



Ottawa Convention Center




Some Slides/Images adapted from Marschner and Shirley and David Levin

Agenda

- Types of Surfaces
- Data Structures for Triangle Meshes
- Normals for Meshes
- Texture Mapping
- Subdivision Surfaces

Surface Representations in Graphics

Implicit Surface




Parametric Surface

$$x = r \cos \phi \sin \theta,$$

$$y = r \sin \phi \sin \theta,$$

$$z = r \cos \theta.$$




Triangles

p_2

p_1

p_0




Triangles


$\mathbf{p}_2$

$\mathbf{p}_0$


$\mathbf{p}_1$



Triangles




Triangles



Barycentric Coordinates

$$\mathbf{p}(\alpha, \beta) = \mathbf{p}_0 + \alpha(\mathbf{p}_1 - \mathbf{p}_0) + \beta(\mathbf{p}_2 - \mathbf{p}_0)$$

$$\mathbf{p}(\alpha, \beta) = \alpha\mathbf{p}_1 + \beta\mathbf{p}_2 + (1 - \alpha - \beta)\mathbf{p}_0$$



Barycentric Coordinates

$\mathbf{p}_2$

$$\mathbf{p}(\alpha, \beta) = \alpha \mathbf{p}_1 + \beta \mathbf{p}_2 + (1 - \alpha - \beta) \mathbf{p}_0$$

$$\alpha \geq 0$$


$$\beta \geq 0$$

$$\alpha + \beta \leq 1$$


$$\gamma = 1 - \alpha - \beta$$

$\mathbf{p}_0$


$\mathbf{p}_1$




Triangle Soup



Triangle Mesh



Soup




Mesh

Topology


Topology is concerned with the connectivity of a mesh

We are going to assume that our meshes are *2-manifolds*




Manifold

A *2-manifold* is a surface for which the neighbourhood around any point can be flattened onto the plane




Manifold

A *2-manifold* is a surface for which the neighbourhood around any point can be flattened onto the plane



Watertight

Watertight meshes have no holes





Geometry

Geometrically, a mesh is a **piecewise planar** surface


- almost everywhere, it is planar
- exceptions are at the edges where triangles join

Often, it's a piecewise planar approximation of a smooth surface

$$\begin{aligned}x &= r \cos \phi \sin \theta, \\y &= r \sin \phi \sin \theta, \\z &= r \cos \theta.\end{aligned}$$



Examples of Meshes



12 triangles, 8 vertices

Examples of Meshes



10 million triangles from a high-resolution 3D scan



About a trillion triangles from automatically processed satellite and aerial photography.

Google earth

42°26'48.20" N 79°02'16.00" W elev 720.5 m alt 1438 ft

Storing Triangle Meshes

What do we care about ?

Storing Triangle Meshes

What do we care about?


1. Compactness
2. Efficiency of queries
 - all vertices of a triangle
 - all triangles around a vertex
 - neighboring triangles of a triangle

Data Structures for Triangle Meshes

- Separate Triangles (soup)
- Indexed Triangle Set
- Triangle-Neighbour Data Structure
- Winged-Edge Data Structure
- Half-Edge Data Structure

Separate triangles


	[0]	[1]	[2]
tris[0]	x_0, y_0, z_0	x_2, y_2, z_2	x_1, y_1, z_1
tris[1]	x_0, y_0, z_0	x_3, y_3, z_3	x_2, y_2, z_2
	$\vdots$	$\vdots$	$\vdots$



Indexed triangle set

verts[0]	x_0, y_0, z_0
verts[1]	x_1, y_1, z_1
	x_2, y_2, z_2
	x_3, y_3, z_3
	$\vdots$

tInd[0]	0, 2, 1
tInd[1]	0, 3, 2
	$\vdots$




Indexed Triangle set

$$V = \begin{pmatrix} 0 & 0 & 0 \\ 1 & 0 & 0 \\ 1 & 1 & 1 \\ 2 & 1 & 0 \end{pmatrix}$$

$$F = \begin{pmatrix} 0 & 1 & 2 \\ 1 & 3 & 2 \end{pmatrix}$$



vertices adjacent to a given triangle



Triangle-Neighbour Data Structure

verts[0]	x_0, y_0, z_0
verts[1]	x_1, y_1, z_1
	x_2, y_2, z_2
	x_3, y_3, z_3
	$\vdots$

tInd[0]	0, 2, 1
tInd[1]	0, 3, 2
	$\vdots$



triangles adjacent to a given triangle




triangles adjacent to a given vertex




Triangle-Neighbour Data Structure

```
Mesh {  
    float3 verts[nv];    // 3D vertex positions  
    int vTri[nv];         // index of any adjacent triangle  
  
    int tInd[nt][3];     // vertex indices  
    int tNbr[nt][3];     // indices of neighbor triangles  
}
```




Triangle-Neighbour Data Structure

$vTri[0]$	0	$tNbr[0]$	1, 6, 7
$vTri[1]$	6	$tNbr[1]$	10, 2, 0
$vTri[2]$	1	$tNbr[2]$	3, 1, 12
$vTri[3]$	1	$tNbr[3]$	2, 13, 4
	$\vdots$		$\vdots$
		$tInd[0]$	0, 2, 1
		$tInd[1]$	0, 3, 2
		$tInd[2]$	10, 2, 3
		$tInd[3]$	2, 10, 7
			$\vdots$




Triangle-Neighbour Data Structure





The k th entry of tNbr points to the neighboring triangle that shares vertices k and $k+1$

Quadrilateral (Quad) Meshes



[A. Bærentzen, J. Frisvad, and K. Singh. 2019. Signifier-Based Immersive and Interactive 3D Modeling. ACM VRST '19].

Winged-Edge Data Structure




Edge	Vertex 1	Vertex 2	Face left	Face right	Pred left	Succ left	Pred right	Succ right
a	A	D	3	0	f	e	c	b
b	A	B	0	2	a	c	d	f
c	B	D	0	1	b	a	e	d
d	B	C	1	2	c	e	f	b
e	C	D	1	3	d	c	a	f
f	C	A	3	2	e	e	b	d

Vertex	Edge
A	a
B	d
C	d
D	e

Face	Edge
0	a
1	c
2	d
3	a

Winged-Edge Data Structure



Edge {

Edge hl, hr, tl, tr;

Vertex h, t;

Face l, r;

}

Face { // per-face data

Edge e; // any adjacent edge


}

Vertex { // per-vertex data

Edge e; // any incident edge

}


Winged-Edge Data Structure



EdgesOfFace(f)

```
{  
    e = f.e;  
    do {  
        if (e.l == f) e = e.hl;  
        else e = e.tr;  
    } while (e != f.e);  
}
```


Winged-Edge Data Structure



EdgesOfVertex(v)

```
{  
     $e = v.e$ ;  
    do {  
        if ( $e.t == v$ )  $e = e.tl$ ;  
        else  $e = e.hr$ ;  
    } while ( $e != v.e$ );  
}
```

Winged-Edge Data Structure





EdgesOfVertex(v)

```
{  
    e = v.e;  
    do {  
        if (e.t == v) e = e.tl;  
        else e = e.hr;  
    } while (e != v.e);  
}
```

FacesOfVertex(v)

```
{  
    e = v.e;  
    do {  
        if (e.t == v) {  
            f=e.l;  
            e = e.tl; }  
        else {  
            f=e.r;  
            e = e.hr;}  
    } while (e != v.e);  
}
```

Half-Edge Data Structure



```
HEdge {
  Edge hl, hr, tl, tr;      Hedge pair, next;
  Vertex h, t;             Vertex v;
  Face l, r;               Face f;
}
```

```
Face { // per-face data
  HEdge e; // any adjacent edge
}
```


```
Vertex { // per-vertex data
  HEdge e; // any incident edge
}
```

```
EdgesOfVertex(v) {
  h = v.h;
  do { h = h.next.pair; }
  while (h != v.h);
}
```


Relationships between primitive Types

What is the relationship between the number of vertices, the number of edges and the number of triangles in a mesh?


Euler's Formula: $V + F - E = 2$
(closed manifold mesh)



$$\begin{aligned} V &= 8 \\ E &= 12 \\ F &= 6 \end{aligned}$$




$$\begin{aligned} V &= 5 \\ E &= 8 \\ F &= 5 \end{aligned}$$




$$\begin{aligned} V &= 6 \\ E &= 12 \\ F &= 8 \end{aligned}$$

Relationships between primitive Types


Number of half edges = $2E = 3F$
(closed triangle mesh)
 $V + F - 3F/2 = 2 \Rightarrow F = 2V - 4$



$V = 8$
 $E = 12$
 $F = 6$



$V = 5$
 $E = 8$
 $F = 5$



$V = 6$
 $E = 12$
 $F = 8$

Data on meshes

Often need to store additional information besides just the geometry

Can store additional data at faces, vertices, or edges


Examples

- colours stored on faces, for faceted objects
- information about sharp creases stored at edges
- any quantity that varies continuously (without sudden changes, or discontinuities) gets stored at vertices

Key types of vertex data


- Positions
 - at some level this is just another piece of data
 - position varies continuously between vertices
- Surface normals
 - when a mesh is approximating a curved surface, store normals at vertices
- Texture coordinates
 - 2D coordinates that tell you how to paste images or 2D data on the surface

Normal Vectors




Computing Per-vertex Normals


Per-Face Normals




Per-Vertex Normals




Per-Corner Normals





Per-Face Normals



Per-Vertex Normals




Meshes representing smooth surfaces




Per-Corner Normals


Per-Face Normals




Per-Vertex Normals




Per-Corner Normals




Per-Corner Normals



Texture coordinates




$$\begin{aligned}\phi : S &\rightarrow T \\ &: (x, y, z) \mapsto (u, v)\end{aligned}$$



What makes a good function?

- Bijectivity
- Size distortion
- Shape distortion
- Continuity

$$\begin{aligned}\phi : S &\rightarrow T \\ &: (x, y, z) \mapsto (u, v)\end{aligned}$$




<https://github.com/alecjacobson/geometry-processing-csc2520/blob/master/lecture-notes/parameterization-ryan-schmidt.pdf>

https://members.loria.fr/Bruno.Levy/papers/LSCM_SIGGRAPH_2002.pdf

<https://arxiv.org/pdf/1704.06873.pdf>

Planar Texture Map




$$\phi(x, y, z) = (u, v)$$


where

$$\begin{bmatrix} u \\ v \\ * \\ 1 \end{bmatrix} = M_t \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix}$$

Planar Texture Map



09	19	29	39	49	59	69	79	89	99
08	18	28	38	48	58	68	78	88	98
07	17	27	37	47	57	67	77	87	97
06	16	26	36	46	56	66	76	86	96
05	15	25	35	45	55	65	75	85	95
04	14	24	34	44	54	64	74	84	94
03	13	23	33	43	53	63	73	83	93
02	12	22	32	42	52	62	72	82	92
01	11	21	31	41	51	61	71	81	91
00	10	20	30	40	50	60	70	80	90



Spherical Texture Map






Image space




Surface S in world space





Texture space, T

$$\phi(x, y, z) = ([\pi + \text{atan2}(y, x)]/2\pi, [\pi - \text{acos}(z/\|x\|)]/\pi)$$

Spherical Texture Map Distortion




Cube Texture Map




$$(x, y, z) \mapsto \left(\frac{x}{z}, \frac{y}{z} \right).$$

Cube Texture Map


3D Vertex Positions




2D Parameterization Positions





3D Normal Vectors



Interpolated Texture Coordinates




Meshes representing smooth surfaces



Subdivision Surfaces


Recursive refinement of polygonal mesh

Results in a smooth “limit surface”




Catmull-Clark Subdivision

Particular type of subdivision scheme.




Catmull-Clark Subdivision

Step 1: Set the face point for each facet to be the average of its vertices




Catmull-Clark Subdivision

Step 2: Add edge points – average of two neighbouring face points and edge end points



Catmull-Clark Subdivision


Step 3: Add edges between face points and edge points



Catmull-Clark Subdivision

Step 4: Move each original vertex according to new position given by:

$$\frac{F + 2R + (n - 3)P}{n}$$




F : Average of all n created
face points adjacent to P

R : Average of all original edge
midpoints touching P

Catmull-Clark Subdivision

Step 4: Move each original vertex according to new position given by:

$$\frac{F + 2R + (n - 3)P}{n}$$




F : Average of all n created
face points adjacent to P

R : Average of all original edge
midpoints touching P

Catmull-Clark Subdivision

Step 4: Move each original vertex according to new position given by:

$$\frac{F + 2R + (n - 3)P}{n}$$




F : Average of all n created
face points adjacent to P

R : Average of all original edge
midpoints touching P

Catmull-Clark Subdivision

Step 4: Move each original vertex according to new position given by:

$$\frac{F + 2R + (n - 3)P}{n}$$




F : Average of all n created
face points adjacent to P

R : Average of all original edge
midpoints touching P


Catmull-Clark Subdivision

Step 5: Connect up original points to make facets



Catmull-Clark Subdivision

Particular type of subdivision scheme.



Subdivision Surfaces in Action



©Disney/Pixar

<http://graphics.pixar.com/opensubdiv/>

Subdivision Surfaces in Action



Figure 5: Geri's hand as a piecewise smooth Catmull-Clark surface. Infinitely sharp creases are used between the skin and the fingernails.

<https://www.youtube.com/watch?v=9IYRC7g2ICg>
<https://graphics.pixar.com/library/Geri/paper.pdf>

Where to find meshes?

Make your own!

<https://www.blender.org/>

<https://www.autodesk.ca/en/products/maya/overview>



MAYA

Download them!

<https://www.cs.cmu.edu/~kmcrane/Projects/ModelRepository/>

<https://www.turbosquid.com/>

<https://poly.google.com/>

<https://www.thingiverse.com/>

<https://ten-thousand-models.appspot.com/>

Assignment #4: Tasks

Part 1 Tasks

File	Marks	What it does
<code>src/write_obj.py</code>	8	Write a tri/quad mesh to a 1-indexed <code>.obj</code> .
<code>src/cube.py</code>	8	The 8-vertex / 6-quad unit cube.
<code>src/sphere.py</code>	8	A <code>num_u × num_v</code> lat-long quad sphere.
<code>src/triangle_area_normal.py</code>	7	$0.5 \cdot (b-a) \times (c-a)$ (area-weighted normal).
<code>src/per_face_normals.py</code>	7	Unit normal per triangle.
<code>src/per_vertex_normals.py</code>	6	Area-weighted per-vertex normals.
<code>src/vertex_triangle_adjacency.py</code>	6	Faces incident on each vertex.
<code>src/per_corner_normals.py</code>	5	Crease-aware per-corner normals.
<code>src/catmull_clark.py</code>	5	Catmull-Clark quad subdivision.

Next: Transformations and Shaders

