

The screenshot displays a database design tool interface with a complex ER diagram. The diagram consists of several tables, each with its attributes and primary/foreign keys. The tables and their attributes are as follows:

- roles**:
  - id\_rol (PK, int)
  - codigo (varchar(50))
  - nombre (varchar(80))
  - descripcion (varchar(255))
  - estado (varchar)
  - creado\_en (timestamp)
  - actualizado\_en (timestamp)
- user**:
  - id\_user (PK, int)
  - nombres (varchar(100))
  - apellidos (varchar(100))
  - documento\_identidad (varchar(30))
  - correo (varchar(150))
  - telefono (varchar(30))
  - password\_hash (varchar(255))
  - foto\_perfil\_url (varchar(255))
  - estado (varchar)
  - correo\_verificado\_en (datetime)
  - ultimo\_acceso\_en (datetime)
  - creado\_en (timestamp)
  - actualizado\_en (timestamp)
- tokens\_recuperacion**:
  - id\_token (PK, int)
  - id\_user (FK, int)
  - token (varchar(255))
  - usado (tinyint(1))
  - expira\_en (datetime)
  - creado\_en (timestamp)
- planes**:
  - id\_plan (PK, int)
  - nombre (varchar(150))
  - slug (varchar(170))
  - descripcion (text)
  - precio (decimal(12,2))
  - duracion\_dias (int)
  - modalidad (varchar)
  - tipo\_cliente (varchar)
- clientes**:
  - id\_cliente (PK, int)
  - id\_user (FK, int)
  - id\_coach (FK, int)
  - id\_institucion (FK, int)
  - fecha\_nacimiento (date)
  - genero (varchar)
  - direccion (varchar(180))
  - ciudad (varchar(100))
  - objetivo\_principal (varchar(100))
  - peso\_inicial\_kg (decimal(5,2))
  - estatura\_cm (decimal(5,2))
  - estado\_cliente (varchar)
  - fecha\_alta (date)
  - creado\_en (timestamp)
  - actualizado\_en (timestamp)
- plan\_modulos**:
  - id\_plan\_modulo (PK, int)
  - id\_plan (FK, int)
- solicitudes\_compra**:
  - id\_solicitud (PK, int)
  - codigo\_solicitud (FK, varchar(40))
  - id\_plan (FK, int)
  - id\_institucion (FK, int)
  - nombres (varchar(100))
  - apellidos (varchar(100))
  - documento\_identidad (varchar(30))
  - correo (varchar(150))
  - telefono (varchar(30))
  - ciudad (varchar(100))
  - tipo\_cliente (varchar)
  - observacion\_usuario (text)
  - estado\_solicitud (varchar)
  - revisado\_por (FK, int)
  - fecha\_revision (datetime)
- coaches**:
  - id\_coach (PK, int)

The relationships between the tables are indicated by lines connecting primary keys to foreign keys. For example, 'user' has foreign keys to 'roles', 'tokens\_recuperacion', 'clientes', and 'planes'. 'planes' has foreign keys to 'plan\_modulos' and 'solicitudes\_compra'. 'clientes' has foreign keys to 'tokens\_recuperacion', 'planes', and 'plan\_modulos'. 'solicitudes\_compra' has foreign keys to 'planes', 'plan\_modulos', and 'coaches'.













