

# Wavelet-based visualization of time-varying data on graphs

**Paola Llerena Valdivia**

**Advisor: Prof. Dr. Luis Gustavo Nonato**

*Instituto de Ciências Matemáticas e de Computação  
USP São Carlos*





Moens et al., *Mining user generated content*, 2014.

## Machine

Statistical analysis

Data mining

Machine learning

Compression & filtering

**Keim et al.**, *Visual analytics: Definition, process, and challenges*, 2008.

# Visual Analytics

## Machine

Statistical analysis

Data mining

Machine learning

Compression & filtering

## Human

Human cognition


Perception

Visual intelligence

Decision making theory


Keim et al., *Visual analytics: Definition, process, and challenges*, 2008.

# Visual Analytics




Keim et al., *Visual analytics: Definition, process, and challenges*, 2008.


# Spatiotemporal data




# Spatial time series



# Spatial time series



# Spatial time series



- Take advantage of many graph techniques.
- Particularly, Wavelet theory on graphs, that allows the analysis of local variations .

# Aim

Investigate novel visual analytic methodologies for the analysis of spatial time series that relies on the recent developments of graph Wavelet theory.

Investigate novel visual analytic methodologies for the analysis of spatial time series that relies on the recent developments of graph Wavelet theory.

The intended methodology will combine graph wavelets, computational tools and visual elements in order to allow for the analysis of local and global data variation.


## Expected contributions

- An efficient and scalable methodology that will guide users in the exploration of spatial time series towards the discovery of hidden patterns.
- An interactive visual framework tailored for the proposed methodology.
- Application in real scenarios such as urban data.



# Visualization of spatial time-series


# Integrated views



Bak et al., "Spatiotemporal analysis of sensor logs using growth ring maps", 2009.


Andrienko et al., "A conceptual framework and taxonomy of techniques for analyzing movement", 2011.

# Integrated views



Shrestha et al., “Storygraph: Extracting Patterns from Spatio-temporal Data”, 2013.

# Integrated views in 3D



Thakur and Rhyne, "Data Vases: 2D and 3D Plots for Visualizing Multiple Time Series", 2009.

# Multiple views




Small multiples.


Park and Quealy, *Drought's Footprint, 2012*.

New York Times, <http://www.nytimes.com/interactive/2012/07/20/us/drought-footprint.htm>. Accessed May, 2015.

# Multiple views



A)



B)

Coordinated multiple views.


A) Ferreira et al., “Visualization and Computer Graphics, IEEE Transact”, 2013.

B) Jern and Franzén, “GeoAnalytics - Exploring spatio-temporal and multivariate data”, 2006.



# Visual analytics of time series


# Geographically weighted regression



Regression parameters.

Demšar et al., “Exploring the spatio-temporal dynamics of geographical processes with geographically weighted regression and geovisual analytics”, 2008.


# Geographically weighted regression



geoMap





SOM



Temporal PCP

Demšar et al., “Exploring the spatio-temporal dynamics of geographical processes with geographically weighted regression and geovisual analytics”, 2008.



# Space-in-time SOMs



Temporal patterns


Andrienko et al., “Space-in-Time and Time-in-Space Self-Organizing Maps for Exploring Spatiotemporal Patterns”, 2010.

# Time-in-space SOMs



Andrienko et al., "Space-in-Time and Time-in-Space Self-Organizing Maps for Exploring Spatiotemporal Patterns", 2010.

# Event-guided exploration



Doraiswamy et al., “Using Topological Analysis to Support Event-Guided Exploration in Urban Data”, 2014.

# Graph Basics

## Weighted graph

$$\mathcal{G}^w = \{\mathcal{V}, \mathcal{E}, \mathbf{W}\}$$

## Weighted graph

$$\mathcal{G}^w = \{\mathcal{V}, \mathcal{E}, \mathbf{W}\}$$

$\mathcal{V} = \{\tau_1, \tau_2, \dots, \tau_N\}$	node set
$\mathcal{E}$	link set
$\mathbf{W}$	weight matrix
$w_{ij} \neq 0$ if $\tau_i \sim \tau_j$	weight matrix entry
$d^w(\tau_i) = \sum_{\tau_j \sim \tau_i} w_{ij}$	node degree

# Graph function

$$f : \mathcal{V} \rightarrow \mathbb{R}$$


$$\mathbf{f} \in \mathbb{R}^N$$

# Graph function

$$f : \mathcal{V} \rightarrow \mathbb{R}$$

$$\mathbf{f} \in \mathbb{R}^N$$

$f(i)$  is the scalar value  
in the node  $\tau_i$ .



$$\mathbf{f} = \begin{bmatrix} 10 \\ 8 \\ 6 \\ 4 \\ 2 \\ -2 \\ -4 \\ -6 \\ -8 \\ -10 \end{bmatrix}$$

Function defined on the Petersen graph.

# Unnormalized Laplacian matrix

$$\mathbf{L} := \mathbf{D} - \mathbf{W}$$

$\mathbf{D}$  diagonal degree matrix

$\mathbf{W}$  weight matrix

$D_{ii} = d^w(\tau_i)$  diagonal degree matrix entries

- $\mathbf{L}$  is a real symmetric, positive-semidefinite matrix;
- real non-negative eigenvalues  $\sigma(\mathbf{L}) = \{\lambda_\ell\}_{\ell=0,1,\dots,N-1}$ , which can be ordered  $0 = \lambda_0 < \lambda_1 \leq \dots \leq \lambda_{N-1} := \lambda_{\max}$
- corresponding orthogonal eigenvectors  $\{\mathbf{u}_\ell\}_{\ell=0,1,\dots,N-1}$ .



# Graph Fourier transform

# Fourier transform

$$f : \mathbb{R} \rightarrow \mathbb{R}$$

$$\begin{aligned}\widehat{f}(\xi) &= \langle f, e^{2\pi i \xi t} \rangle \\ &= \int_{\mathbb{R}} f(t) e^{-2\pi i \xi t} dt\end{aligned}$$

$$f : \mathcal{V} \rightarrow \mathbb{R}$$

$$\begin{aligned}\widehat{f}(\lambda_\ell) &= \langle \mathbf{f}, \mathbf{u}_\ell \rangle \\ &= \sum_{\tau_i \in \mathcal{V}} f(i) \mathbf{u}_\ell^\top(i)\end{aligned}$$

# Fourier transform

$$f : \mathbb{R} \rightarrow \mathbb{R}$$


$$\begin{aligned}\widehat{f}(\xi) &= \langle f, e^{2\pi i \xi t} \rangle \\ &= \int_{\mathbb{R}} f(t) e^{-2\pi i \xi t} dt\end{aligned}$$

$$f : \mathcal{V} \rightarrow \mathbb{R}$$


$$\begin{aligned}\widehat{f}(\lambda_\ell) &= \langle \mathbf{f}, \mathbf{u}_\ell \rangle \\ &= \sum_{\tau_i \in \mathcal{V}} f(i) \mathbf{u}_\ell^\top(i)\end{aligned}$$

$$\begin{bmatrix} \widehat{\mathbf{f}} \end{bmatrix} = \begin{bmatrix} \text{Red} & \text{Green} & \text{Blue} \\ \text{Orange} & \text{Yellow} & \text{Purple} \\ \text{Blue} & \text{Green} & \text{Red} \\ \text{Green} & \text{Blue} & \text{Orange} \\ \text{Blue} & \text{Red} & \text{Green} \end{bmatrix} \times \begin{bmatrix} \mathbf{f} \end{bmatrix}$$

# Example



$$f : \mathcal{V} \rightarrow \mathbb{R}$$



# Inverse Fourier transform

$$f : \mathbb{R} \rightarrow \mathbb{R}$$

$$f(t) = \int_{\mathbb{R}} \widehat{f}(\xi) e^{2\pi i \xi t} d\xi$$

$$f : \mathcal{V} \rightarrow \mathbb{R}$$

$$f(i) = \sum_{\ell=0}^{N-1} \widehat{f}(\lambda_\ell) \mathbf{u}_\ell(i)$$

$$\begin{bmatrix} f \end{bmatrix} = \begin{bmatrix} \text{U} \\ \text{U} \\ \text{U} \\ \text{U} \\ \text{U} \end{bmatrix} \times \begin{bmatrix} \widehat{f} \end{bmatrix}$$

## Frequency domain filtering on graphs

$$\widehat{f}_{out}(\lambda_l) = \widehat{f}_{in}(\lambda_l)\widehat{g}(\lambda_l)$$

$$f_{out}(i) = \sum_{l=0}^{N-1} \widehat{f}_{out}(\lambda_l) \mathbf{u}_l(i)$$

# Graph filtering

## Frequency domain filtering on graphs


$$\hat{f}_{out}(\lambda_l) = \hat{f}_{in}(\lambda_l)\hat{g}(\lambda_l)$$

$$f_{out}(i) = \sum_{l=0}^{N-1} \hat{f}_{out}(\lambda_l) \mathbf{u}_l(i)$$




$$\mathbf{f}_{out} = \mathbf{U} \underbrace{\begin{bmatrix} \hat{g}(\lambda_0) & & \mathbf{0} \\ & \ddots & \\ \mathbf{0} & & \hat{g}(\lambda_{N-1}) \end{bmatrix}}_{\mathbf{G}} \mathbf{U}^T \mathbf{f}_{in}$$

$$\mathbf{f}_{out} = \mathbf{U} \mathbf{G} \mathbf{U}^T \mathbf{f}_{in}$$




# Example





# Example




# Example





$$f : \mathcal{V} \rightarrow \mathbb{R}$$



# Example




$$f : \mathcal{V} \rightarrow \mathbb{R}$$








$$w_f(3) : \mathcal{V} \rightarrow \mathbb{R}$$

# Example




$$f : \mathcal{V} \rightarrow \mathbb{R}$$




$$w_f(4) : \mathcal{V} \rightarrow \mathbb{R}$$




# Example




$w_f(1) : \mathcal{V} \rightarrow \mathbb{R}$



$w_f(2) : \mathcal{V} \rightarrow \mathbb{R}$




$w_f(3) : \mathcal{V} \rightarrow \mathbb{R}$




$w_f(4) : \mathcal{V} \rightarrow \mathbb{R}$


# Example




$$w_f(1) : \mathcal{V} \rightarrow \mathbb{R}$$



$$w_f(2) : \mathcal{V} \rightarrow \mathbb{R}$$



$$w_f(3) : \mathcal{V} \rightarrow \mathbb{R}$$



$$w_f(4) : \mathcal{V} \rightarrow \mathbb{R}$$

Wavelet coefficients for  $f$ .

# Spectral graph Wavelets

# Spectral graph Wavelets

## Graph wavelet transform (Hammond et al., 2011)

Decompose a function  $f$  in terms of basis functions  $\{\psi_{s,1}, \dots, \psi_{s,n}\}$   
where each  $\psi_{s,i}$  depends on a scale  $s$  and a location  $\tau_i$ .

# Spectral graph Wavelets

## Graph wavelet transform (Hammond et al., 2011)

Decompose a function  $f$  in terms of basis functions  $\{\psi_{s,1}, \dots, \psi_{s,n}\}$   
where each  $\psi_{s,i}$  depends on a scale  $s$  and a location  $\tau_i$ .

Projecting the function  $f$  onto spaces with different scales is equivalent to band-pass filtering the function  $f$ .

# Spectral graph Wavelets

## Graph wavelet transform (Hammond et al., 2011)

Decompose a function  $f$  in terms of basis functions  $\{\psi_{s,1}, \dots, \psi_{s,n}\}$   
where each  $\psi_{s,i}$  depends on a scale  $s$  and a location  $\tau_i$ .

Projecting the function  $f$  onto spaces with different scales is equivalent to band-pass filtering the function  $f$ .

$$\widehat{T_g f}(\lambda_\ell) := \widehat{g}(\lambda_\ell) \widehat{f}(\lambda_\ell).$$

$$(T_g f)(i) = \sum_{\ell=0}^N \widehat{g}(\lambda_\ell) \widehat{f}(\lambda_\ell) \mathbf{u}_\ell(i).$$

# Spectral graph Wavelets

## Graph wavelet transform (Hammond et al., 2011)

Decompose a function  $f$  in terms of basis functions  $\{\psi_{s,1}, \dots, \psi_{s,n}\}$   
where each  $\psi_{s,i}$  depends on a scale  $s$  and a location  $\tau_i$ .

Projecting the function  $f$  onto spaces with different scales is equivalent to band-pass filtering the function  $f$ .

$$\widehat{T_g f}(\lambda_\ell) := \widehat{g}(\lambda_\ell) \widehat{f}(\lambda_\ell).$$

$$(T_g f)(i) = \sum_{\ell=0}^N \widehat{g}(\lambda_\ell) \widehat{f}(\lambda_\ell) \mathbf{u}_\ell(i).$$

$$\mathbf{G} = \begin{bmatrix} \widehat{g}(s\lambda_0) & & 0 \\ & \ddots & \\ 0 & & \widehat{g}(s\lambda_{N-1}) \end{bmatrix}$$

## Graph wavelet coefficients (Hammond et al., 2011)

Wavelet coefficients at scale  $s$  and node  $\tau_i$  are obtained through the dot product

$$\omega_f(s, i) = \psi_{s,i}^T f.$$

## Graph wavelet coefficients (Hammond et al., 2011)

Wavelet coefficients at scale  $s$  and node  $\tau_i$  are obtained through the dot product

$$\omega_f(s, i) = \psi_{s,i}^\top f.$$

$$w_f(s) = \mathbf{U}\mathbf{G}\mathbf{U}^\top \mathbf{f},$$


$$\mathbf{G} = \begin{bmatrix} \widehat{g}(s\lambda_0) & & 0 \\ & \ddots & \\ 0 & & \widehat{g}(s\lambda_{N-1}) \end{bmatrix}.$$

# Filter functions

$$\hat{h}(x) = \gamma \exp \left( \left( \frac{x}{0.6\lambda_{\min}} \right)^4 \right)$$

$$\hat{g}(x) = \begin{cases} x_1^{-2}x^2 & \text{for } x < x_1 \\ p(x) & \text{for } x_1 \leq x \leq x_2 \\ x_2^2x^{-2} & \text{for } x > x_2 \end{cases}$$

$$p(x) = -5 + 11x - 6x^2 + x^3$$



The scales are logarithmically sampled between


$$s_{\min} = s_1, s_2, \dots, s_m = s_{\max},$$

$$s_{\min} = x_2/\lambda_{\max}, \text{ and}$$

$$s_{\max} = 20x_2/\lambda_{\max}.$$

Hammond et al., "Wavelets on graphs via spectral graph theory", 2011.

# Example




Wavelet coefficients for  $f$ .




# Spatiotemporal visual analytics


# Example



# Example




# Node classification



Dimensional feature vectors characterizing four frequency classes.


# Node classification

- Supervised classification method.



Dimensional feature vectors characterizing four frequency classes.


# Node classification



Dimensional feature vectors characterizing four frequency classes.

- Supervised classification method.
- Pattern recognition neural network (PRNN).

# Node classification



Dimensional feature vectors characterizing four frequency classes.


- Supervised classification method.
- Pattern recognition neural network (PRNN).
- Training function: Scaled conjugate gradient <sup>1</sup>.

---

<sup>1</sup>Møller, "A scaled conjugate gradient algorithm for fast supervised learning", 1993.

# Node classification

- Supervised classification method.
- Pattern recognition neural network (PRNN).
- Training function: Scaled conjugate gradient <sup>1</sup>.
- 25 units in the hidden layer, 5 units in the output layer.




Dimensional feature vectors characterizing four frequency classes.


---

<sup>1</sup>Møller, "A scaled conjugate gradient algorithm for fast supervised learning", 1993.

# Example




Graph function.




Wavelet coefficients classification.

- █ High frequencies
- █ Mid-high frequencies
- █ Indeterminate
- █ Mid-low frequencies
- █ Low frequencies

# Time-varying data




$f : \mathcal{V}_G \times [a, b] \rightarrow \mathbb{R}$ , for every time  
t in the interval  $[a, b]$ , assigns a real scalar to each node  $\tau_i \in \mathcal{V}$ .



Cartesian product  
 $\mathcal{G} \times \mathcal{H}$ .

## Graph structure

- $\mathcal{G} = (\mathcal{V}_{\mathcal{G}}, \mathcal{E}_{\mathcal{G}})$ , with nodes  $\tau_i$ .
- $\mathcal{H} = (\mathcal{V}_{\mathcal{H}}, \mathcal{E}_{\mathcal{H}})$ , linear graph with nodes  $\iota_j$ .
- $\mathcal{G} \times \mathcal{H} = (\mathcal{V}_{\mathcal{H}}, \mathcal{E}_{\mathcal{H}})$ .  $\mathcal{V}_{\mathcal{H}} = \{\iota_1, \iota_2, \dots, \iota_r\}$  and edges  $\mathcal{E}_{\mathcal{H}} = \{e_{ii+1} = \iota_i \iota_{i+1}\}_{i=1, \dots, r-1}$ .
- $\mathcal{G} \times \mathcal{H}$  can be seen as copies of  $\mathcal{G}$  stacked according to the nodes of  $\mathcal{H}$ .




Cartesian product  
 $\mathcal{G} \times \mathcal{H}$ .

## Graph function

- $f : \mathcal{V}_{\mathcal{G}} \times [a, b] \rightarrow \mathbb{R}$ , for every time  $t$  in the interval  $[a, b]$ , assigns a real scalar to each node  $\tau_i \in \mathcal{V}$ .
- The time-varying function  $f$  can naturally be extended to  $\mathcal{G} \times \mathcal{H}$  through the function  $f_{\mathcal{G} \times \mathcal{H}} : \mathcal{V}_{\mathcal{G}} \times \mathcal{V}_{\mathcal{H}} \rightarrow \mathbb{R}$  such that  $f_{\mathcal{G} \times \mathcal{H}} ((\tau_i, \iota_j)) = f(\tau_i, t_j)$ .


# Time-varying data




Cartesian product  
 $\mathcal{G} \times \mathcal{H}$ .

## Spectrum of $\mathcal{G} \times \mathcal{H}$


- $\mathbf{u}_j, \lambda_j$  be the eigenvectors and eigenvalues of  $\mathcal{G}$  and
- $\mathbf{v}_k, \mu_k$  be the eigenvectors and eigenvalues of  $\mathcal{H}$ , then
- $\lambda_j + \mu_k$  is an eigenvalue of  $\mathcal{G} \times \mathcal{H}$  and
- $\mathbf{w}_{jk} = \mathbf{u}_j \otimes \mathbf{v}_k$  the corresponding eigenvector.



$$f_{\mathcal{G} \times \mathcal{H}} : \mathcal{V}_{\mathcal{G}} \times \mathcal{V}_{\mathcal{H}} \rightarrow \mathbb{R}$$



$$f_{\mathcal{G} \times \mathcal{H}} : \mathcal{V}_{\mathcal{G}} \times \mathcal{V}_{\mathcal{H}} \rightarrow \mathbb{R}$$




$$w_{\mathcal{G} \times \mathcal{H}} : \mathcal{V}_{\mathcal{G}} \times \mathcal{V}_{\mathcal{H}} \rightarrow \mathbb{R}$$

## Stacked graph

For each time  $t_i$ , we can count the number of nodes that belong to a specific class in that time.


# Stacked graph

For each time  $t_i$ , we can count the number of nodes that belong to a specific class in that time.



Stacked graph illustrating how each of the five classes evolve over time.

## Visual elements and linked views




# Pipeline




## Case studies

# NY graph



# NY graph



The dataset contains 14 attributes:

Information about the taxi and the driver: medallion, hack\_license, vendor\_id, rate\_code, store\_and\_fwd\_flag.

Information about the time of the trip: pickup\_datetime , dropoff\_datetime, trip\_time\_in\_secs.

Geographical start and end of each trip: pickup\_longitude, pickup\_latitude, dropoff\_longitude, dropoff\_latitude.

Other information: passenger\_count, trip\_distance.


The dataset contains 14 attributes:

Information about the taxi and the driver: medallion, hack\_license, vendor\_id, rate\_code, store\_and\_fwd\_flag.

Information about the time of the trip: **pickup\_datetime**, dropoff\_datetime, trip\_time\_in\_secs.


Geographical start and end of each trip: **pickup\_longitude**, **pickup\_latitude**, dropoff\_longitude, dropoff\_latitude.

Other information: passenger\_count, trip\_distance.




Stacked graph of taxi pickups from August 12th to 18th, 2013 ( $\sim 3M$  records).


Data aggregated in periods of thirty minutes:  $\mathcal{G} \times \mathcal{H}$  with  $\sim 1,5M$  nodes.



- Pattern of activity of each day.
- Difference between day and night.



- Predominance of low frequency.
- Temporal variation occurs as a large, uniform event, without many peaks of activity.




Wavelets Coefficients



Density graph

7:30am to 8am, Monday  
August 12, 2013



Wavelets Coefficients

Density graph

7:30am to 8am, Monday  
August 12, 2013




Wavelets Coefficients




Density graph


7:30am to 8am, Monday  
August 12, 2013

# NY Taxi



7:30am to 8am, Monday  
August 12, 2013






Wavelets Coefficients



Density graph


7:30pm to 8pm, Friday  
August 16, 2013



Wavelets Coefficients

Density graph

7:30pm to 8pm, Friday  
August 16, 2013



Wavelets Coefficients



Density graph

7:30pm to 8pm, Friday  
August 16, 2013

NY Taxi




Wavelets Coefficients



Density graph

1:30am to 2am, Saturday  
August 17, 2013




Wavelets Coefficients



Density graph

1:30am to 2am, Saturday  
August 17, 2013

NY Taxi



Wavelets Coefficients




Density graph

1:30am to 2am, Saturday  
August 17, 2013

# NY Taxi



1:30am to 2am, Saturday  
August 17, 2013



# Citi Bike NY



*Citi Bike NY* station map.

Stations from downtown Manhattan (pink markers) are considered in this study.

The dataset contains 15 attributes:

Information about the bike: bikeid.

Information about the user: usertype, birth\_year, gender.

Information about the time of the trip: starttime, stoptime , tripduration.

Information about the start station of each trip: start\_station\_id, start\_station\_name,  
start\_station\_latitude, start\_station\_longitude.

Information about the end station of each trip: end\_station\_id, end\_station\_name,  
end\_station\_latitude, end\_station\_longitude.

The dataset contains 15 attributes:

Information about the bike: bikeid.


Information about the user: usertype, birth\_year, gender.

Information about the time of the trip: **starttime**, **stoptime**, tripduration.

Information about the start station of each trip: start\_station\_id, start\_station\_name,  
**start\_station\_latitude**, **start\_station\_longitude**.


Information about the end station of each trip: end\_station\_id, end\_station\_name,  
**end\_station\_latitude**, **end\_station\_longitude**.

# Citi Bike NY




Stacked graph of bike activities from October 25th to 31st, 2013.  
Data aggregated in periods of one hour:  $\mathcal{G} \times \mathcal{H}$  with  $\sim 788k$  nodes.

# Citi Bike NY




- Pattern of activity of each day.
- Difference between working days and weekend.

# Citi Bike NY




- Working days: more activity during afternoon.
- Low frequency predominant in afternoons.

# Citi Bike NY



- Thursday 31st, morning and afternoon peaks are almost of the same size.



Wavelets Coefficients




Density graph

Citi Bike NY

8am to 9am, Monday  
October 28, 2013

# Citi Bike NY



Wavelets Coefficients



Density graph

5pm to 6pm, Monday  
October 28, 2013



# Citi Bike NY

Regions 1, 2, and 3 correspond to areas with a high concentration of bike lanes.  
Region 4 is next to the main bike lines.

## Discussion and limitations

- Large amounts of information.

## Discussion and limitations

- Large amounts of information.
- Visualization of spatiotemporal events, regardless of their size.

## Discussion and limitations

- Large amounts of information.
- Visualization of spatiotemporal events, regardless of their size.
- Algorithm to approximate routes.

## Discussion and limitations

- Large amounts of information.
- Visualization of spatiotemporal events, regardless of their size.
- Algorithm to approximate routes.
- Classification scheme turned out satisfactory.

## Discussion and limitations

- Large amounts of information.
- Visualization of spatiotemporal events, regardless of their size.
- Algorithm to approximate routes.
- Classification scheme turned out satisfactory.
- Training data.

## Discussion and limitations

- Large amounts of information.
- Visualization of spatiotemporal events, regardless of their size.
- Algorithm to approximate routes.
- Classification scheme turned out satisfactory.
- Training data.
- Stacked graph plot.

## Discussion and limitations

- Large amounts of information.
- Visualization of spatiotemporal events, regardless of their size.
- Algorithm to approximate routes.
- Classification scheme turned out satisfactory.
- Training data.
- Stacked graph plot.
- Discriminating spatial and temporal changes.

## Final considerations

A novel visual analytic methodology for analyzing time-varying data that combines graph wavelet theory, pattern classification, and stacked graph visual metaphor in a linked view visualization environment was described.

## Final considerations

A novel visual analytic methodology for analyzing time-varying data that combines graph wavelet theory, pattern classification, and stacked graph visual metaphor in a linked view visualization environment was described.

The described methodology has been conditionally accepted by the IEEE VAST 2015 Program Committee to be presented at IEEE VIS into the conference-only track.

# Research Planning

## Event mining

- Perform a deeper study of the resulting Wavelets coefficients in order to distinguish different events.
  - ▶ Identify and manually label events.
  - ▶ Use a clustering method, e.g., SOM, rather than the employed classification method.
- Discriminate spatial from temporal events. First extracting temporal information and then including the spatial dimensions could lead to a better understanding of the events.


## Data modeling

- Consider multivariate time series.
- Consider data from another context, such as LBSNs.

## Visual elements

- Another visual metaphor, in which classes with few elements are not hidden, to allow finding events in time-slices.
- Separation of spatial from temporal events will also have an impact in the visual elements employed.

# Proposed timeline



Obrigada!

 paolalv@icmc.usp.br

**Visual and Geometry Processing Group**

