

October 29, 2025

1 Geometric Algebra for Computer Graphics with Python

1.1 Prof. George Papagiannakis

University of Crete, Greece

Foundation for Research and Technology - Hellas (FORTH-ICS)

Copyright © 2025 George Papagiannakis. All rights reserved.

1.2 A Tutorial for Computer Scientists

This notebook introduces **Geometric Algebra (GA)** as a unified mathematical framework for computer graphics and geometric transformations. We'll demonstrate why GA is more elegant, simpler, and more general than traditional methods (matrices, quaternions, Euler angles).

1.3 Why Geometric Algebra?

1.3.1 Unification

Vectors, rotations, reflections, and projections all use the same algebra

1.3.2 Intuition

Operations have clear geometric meaning

1.3.3 Efficiency

Often more compact than matrix operations

1.3.4 Historical

Used by Maxwell in electromagnetism and influenced Einstein's work

1.4 What We'll Cover

1. Euclidean Geometric Algebra (GA3)

→ 3D space transformations and rotations

2. Conformal Geometric Algebra (CGA)

→ Unified representation of points, lines, planes, and spheres

3. Method Comparison

→ Comparing GA with matrices, quaternions, and Euler angles

4. Historical Context

→ GA's role in physics and mathematics

1.4.1 Let's begin your journey into Geometric Algebra!

1.5 1. Setup and Imports

We'll use the **Kingdon** pythonic package - a high-performance geometric algebra library that generates optimized code for specific algebras.

```
[379]: # Import required libraries
import numpy as np # For numerical operations
import kingdon as kd # Geometric algebra library
from scipy.spatial.transform import Rotation as R # For quaternion comparison

# Set numpy print options for cleaner output
np.set_printoptions(precision=4, suppress=True)

print("Kingdon version:", kd.__version__)
print("Setup complete!")
```

Kingdon version: 1.4.0

Setup complete!

```
[380]: # Additional imports for 3D visualization
import matplotlib.pyplot as plt
from mpl_toolkits.mplot3d import Axes3D
from matplotlib.patches import FancyArrowPatch
from mpl_toolkits.mplot3d.proj3d import proj_transform

# Custom Arrow3D class for better 3D arrows
class Arrow3D(FancyArrowPatch):
    def __init__(self, x, y, z, dx, dy, dz, *args, **kwargs):
        super().__init__((0, 0), (0, 0), *args, **kwargs)
        self._xyz = (x, y, z)
        self._dxdydz = (dx, dy, dz)

    def draw(self, renderer):
```

```

        x1, y1, z1 = self._xyz
        dx, dy, dz = self._dxdydz
        x2, y2, z2 = (x1 + dx, y1 + dy, z1 + dz)

        xs, ys, zs = proj_transform((x1, x2), (y1, y2), (z1, z2), self.axes.M)
        self.set_positions((xs[0], ys[0]), (xs[1], ys[1]))
        super().draw(renderer)

    def do_3d_projection(self, renderer=None):
        x1, y1, z1 = self._xyz
        dx, dy, dz = self._dxdydz
        x2, y2, z2 = (x1 + dx, y1 + dy, z1 + dz)

        xs, ys, zs = proj_transform((x1, x2), (y1, y2), (z1, z2), self.axes.M)
        self.set_positions((xs[0], ys[0]), (xs[1], ys[1]))

        return np.min(zs)

def plot_line_3d(ax, point, direction, color='blue', label='Line', linewidth=2,
    alpha=0.8):
    """Plot a 3D line given a point and direction."""
    # Extend line in both directions
    t = np.linspace(-2, 2, 10)
    line_points = point[:, np.newaxis] + direction[:, np.newaxis] * t

    ax.plot(line_points[0], line_points[1], line_points[2],
            color=color, linewidth=linewidth, label=label, alpha=alpha)

    # Plot the reference point
    ax.scatter(*point, color=color, s=100, marker='o', alpha=alpha)

    # Plot direction arrow
    arrow = Arrow3D(*point, *direction,
                    mutation_scale=20, lw=2, arrowstyle='->',
                    color=color, alpha=alpha)
    ax.add_artist(arrow)

def plot_plane_3d(ax, point, normal, color='green', label='Plane', alpha=0.3):
    """Plot a 3D plane given a point and normal vector."""
    # Create plane mesh
    size = 2

    # Find two orthogonal vectors in the plane
    if abs(normal[2]) < 0.9:
        v1 = np.cross(normal, [0, 0, 1])
    else:
        v1 = np.cross(normal, [1, 0, 0])

```

```

v1 = v1 / np.linalg.norm(v1)
v2 = np.cross(normal, v1)
v2 = v2 / np.linalg.norm(v2)

# Create mesh grid
u = np.linspace(-size, size, 10)
v = np.linspace(-size, size, 10)
U, V = np.meshgrid(u, v)

# Calculate plane points
X = point[0] + U * v1[0] + V * v2[0]
Y = point[1] + U * v1[1] + V * v2[1]
Z = point[2] + U * v1[2] + V * v2[2]

ax.plot_surface(X, Y, Z, color=color, alpha=alpha, label=label)

# Plot normal vector
arrow = Arrow3D(*point, *normal,
                 mutation_scale=20, lw=3, arrowstyle='->',
                 color=color, alpha=1.0)
ax.add_artist(arrow)

def setup_3d_axis(ax, title='3D Visualization'):
    """Setup 3D axis with consistent styling."""
    ax.set_xlabel('X', fontsize=10)
    ax.set_ylabel('Y', fontsize=10)
    ax.set_zlabel('Z', fontsize=10)
    ax.set_title(title, fontsize=12, fontweight='bold')

    # Set equal aspect ratio
    max_range = 2.5
    ax.set_xlim([-max_range, max_range])
    ax.set_ylim([-max_range, max_range])
    ax.set_zlim([-max_range, max_range])

    # Add grid
    ax.grid(True, alpha=0.3)

    # Add coordinate system axes
    ax.plot([0, 1], [0, 0], [0, 0], 'r-', alpha=0.3, linewidth=1)
    ax.plot([0, 0], [0, 1], [0, 0], 'g-', alpha=0.3, linewidth=1)
    ax.plot([0, 0], [0, 0], [0, 1], 'b-', alpha=0.3, linewidth=1)

def extract_scalar(mv):
    """Extract scalar value from a Kingdom MultiVector."""
    items = list(mv.items())
    return items[0][1] if len(items) > 0 and items[0][0] == 0 else 0.0

```

```
print(" 3D Visualization utilities loaded!")
```

3D Visualization utilities loaded!

1.6 3D Visualization Setup

We'll use **matplotlib** for 3D visualizations to provide visual feedback for each transformation method.

What we'll visualize: - Lines in 3D space with direction arrows - Planes with normal vectors - Cubes for screw motion demonstrations - Side-by-side comparisons showing original vs transformed objects - Comprehensive multi-panel plots comparing all methods

This will help you see the geometric transformations, not just compute them!

1.7 2. Euclidean Geometric Algebra (GA3)

1.7.1 What is GA3?

Euclidean GA in 3D space extends vector algebra with: - **Vectors:** Directed line segments (e_1, e_2, e_3) - **Bivectors:** Oriented plane segments (e_1e_2, e_2e_3, e_3e_1) - represent rotations - **Trivectors:** Oriented volumes ($e_1e_2e_3$) - the pseudoscalar

1.7.2 The Geometric Product

The key innovation: $a * b = a \cdot b + a \wedge b$ where: - $a \cdot b$ (inner product) gives a scalar - measures alignment - $a \wedge b$ (outer/wedge product) gives a bivector - the plane containing both vectors

Let's create our GA3 algebra!

```
[333]: # Create 3D Euclidean geometric algebra (signature: 3 positive dimensions)
alg = kd.Algebra(3, 0, 0) # (p=3, q=0, r=0) means 3 positive metric dimensions

# Display the algebra structure
print("GA3 Algebra created!")
print(f"Signature: p={alg.p}, q={alg.q}, r={alg.r}")
print(f"Available blades: {list(alg.blades.keys())}")

# Create basis vectors (these are the fundamental directions in 3D space)
e1 = alg.blades['e1'] # x-axis direction
e2 = alg.blades['e2'] # y-axis direction
e3 = alg.blades['e3'] # z-axis direction

# Create basis bivectors (oriented planes - these represent rotation planes)
e12 = alg.blades['e12'] # xy-plane (rotation around z-axis)
e13 = alg.blades['e13'] # xz-plane (rotation around y-axis)
e23 = alg.blades['e23'] # yz-plane (rotation around x-axis)

# The pseudoscalar (represents oriented volume in 3D)
e123 = alg.blades['e123']
```

```
print("\nBasis elements created successfully!")
```

GA3 Algebra created!

Signature: p=3, q=0, r=0

Available blades: ['e', 'e1', 'e2', 'e3', 'e12', 'e13', 'e23', 'e123']

Basis elements created successfully!

1.8 3. Basic GA Operations

Let's see the fundamental operations that make GA powerful.

```
[334]: # Create two vectors
a = 1*e1 + 2*e2 + 3*e3 # Vector a = (1, 2, 3)
b = 4*e1 + 5*e2 + 6*e3 # Vector b = (4, 5, 6)

print("Vector a:", a)
print("Vector b:", b)

# Inner product (dot product) - measures parallel component
# Returns a scalar showing how much vectors align
inner = alg.ip(a, b) # a·b
print("\nInner product a·b:", inner)
print("Compare to numpy dot:", np.dot([1,2,3], [4,5,6]))

# Outer product (wedge product) - creates the plane containing both vectors
# Returns a bivector representing oriented area
outer = alg.op(a, b) # a b
print("\nOuter product a b:", outer)
print("This bivector represents the oriented plane containing a and b")

# Geometric product - combines both inner and outer
# This is the fundamental product in GA
geo = alg.gp(a, b) # a*b = a·b + a b
print("\nGeometric product a*b:", geo)
print("Notice: it contains both scalar and bivector parts!")
```

Vector a: 1 + 2 + 3

Vector b: 4 + 5 + 6

Inner product a·b: 32

Compare to numpy dot: 32

Outer product a b: -3 + -6 + -3

This bivector represents the oriented plane containing a and b

Geometric product a*b: 32 + -3 + -6 + -3

Notice: it contains both scalar and bivector parts!

```

[335]: # Visualization: Geometric Product Components
fig = plt.figure(figsize=(15, 5))

# Plot 1: Two vectors in 3D
ax1 = fig.add_subplot(131, projection='3d')
origin = np.array([0, 0, 0])

# Draw vectors a and b
arrow_a = Arrow3D(*origin, 1, 2, 3, mutation_scale=20, lw=3,
                  arrowstyle='->', color='red', label='Vector a')
arrow_b = Arrow3D(*origin, 4, 5, 6, mutation_scale=20, lw=3,
                  arrowstyle='->', color='blue', label='Vector b')
ax1.add_artist(arrow_a)
ax1.add_artist(arrow_b)

setup_3d_axis(ax1, 'Vectors a and b')
ax1.legend()

# Plot 2: Inner Product (Scalar) - show as projection
ax2 = fig.add_subplot(132, projection='3d')
arrow_a2 = Arrow3D(*origin, 1, 2, 3, mutation_scale=20, lw=3,
                  arrowstyle='->', color='red', alpha=0.5, label='a')
arrow_b2 = Arrow3D(*origin, 4, 5, 6, mutation_scale=20, lw=3,
                  arrowstyle='->', color='blue', alpha=0.5, label='b')
ax2.add_artist(arrow_a2)
ax2.add_artist(arrow_b2)

# Show projection of a onto b
b_unit = np.array([4, 5, 6]) / np.linalg.norm([4, 5, 6])
proj_length = np.dot([1, 2, 3], b_unit)
projection = proj_length * b_unit
arrow_proj = Arrow3D(*origin, *projection, mutation_scale=15, lw=2,
                    arrowstyle='->', color='green', label='Projection')
ax2.add_artist(arrow_proj)

# Extract scalar value from inner product
inner_val = extract_scalar(inner)
setup_3d_axis(ax2, f'Inner Product:  $a \cdot b = \{inner\_val:.1f\}$ ')
ax2.legend(fontsize=8)

# Plot 3: Outer Product (Bivector) - show as plane
ax3 = fig.add_subplot(133, projection='3d')
arrow_a3 = Arrow3D(*origin, 1, 2, 3, mutation_scale=20, lw=3,
                  arrowstyle='->', color='red', alpha=0.7, label='a')
arrow_b3 = Arrow3D(*origin, 4, 5, 6, mutation_scale=20, lw=3,
                  arrowstyle='->', color='blue', alpha=0.7, label='b')
ax3.add_artist(arrow_a3)

```

```

ax3.add_artist(arrow_b3)


# Draw the plane spanned by a and b (the bivector)
a_vec = np.array([1, 2, 3])
b_vec = np.array([4, 5, 6])
u = np.linspace(-0.5, 1.5, 5)
v = np.linspace(-0.5, 1.5, 5)
U, V = np.meshgrid(u, v)
X = U * a_vec[0] + V * b_vec[0]
Y = U * a_vec[1] + V * b_vec[1]
Z = U * a_vec[2] + V * b_vec[2]
ax3.plot_surface(X, Y, Z, alpha=0.3, color='purple', label='Bivector plane')

setup_3d_axis(ax3, 'Outer Product: a b (Bivector)')
ax3.legend(fontsize=8)

plt.suptitle('Geometric Product: a*b = a·b (scalar) + a∧b (bivector)',
             fontsize=13, fontweight='bold')
plt.tight_layout()
plt.show()

print(" Geometric product visualization: scalar (projection) + bivector_
↪(plane)")

```



Geometric product visualization: scalar (projection) + bivector (plane)

1.9 4. Rotations with Rotors

1.9.1 What is a Rotor?

A **rotor** is GA's elegant way to represent rotations: - Formula: $R = \exp(-\theta/2 * B)$ where B is a unit bivector (rotation plane) - To rotate vector v : $v' = R * v * R^{-1}$ (sandwich product) - Rotors compose naturally: $R_{\text{total}} = R_2 * R_1$

Why rotors are better than matrices: - More compact (4 numbers vs 9) - Natural interpolation

- No gimbal lock - Clear geometric meaning (angle + plane)

```
[336]: # Create a rotor for 90° rotation in the xy-plane (around z-axis)
angle = np.pi / 2 # 90 degrees in radians
B = e12 # Rotation plane (xy-plane means rotation around z-axis)

# Rotor formula:  $R = \exp(-/2 * B)$ 
# For a unit bivector B in 3D:  $\exp(-/2 * B) = \cos(/2) - \sin(/2) * B$ 
half_angle = angle / 2
cos_half = np.cos(half_angle)
sin_half = np.sin(half_angle)

# Build the rotor
scalar = alg.blades['e'] # Scalar part
R_90 = cos_half * scalar - sin_half * B # Rotor for 90° rotation

print("90° Rotor around z-axis:", R_90)
print(f"cos({half_angle:.3f})    {cos_half:.4f}")
print(f"sin({half_angle:.3f})    {sin_half:.4f}")

# Test: rotate vector (1, 0, 0) by 90° around z-axis
# Should give us (0, 1, 0)
v = 1 * e1 # Vector along x-axis

# Apply rotation:  $v' = R * v * R^{-1}$ 
R_inv = alg.reverse(R_90) # Inverse rotor (for unit rotors:  $R^{-1} = R$ )
v_rotated = alg.gp(R_90, alg.gp(v, R_inv)) # Sandwich product

print("\nOriginal vector:", v)
print("Rotated vector:", v_rotated)
print("Expected: 0*e1 + 1*e2 + 0*e3 (points along y-axis) ")
```

90° Rotor around z-axis: 0.707 + -0.707

cos(0.785) 0.7071

sin(0.785) 0.7071

Original vector: 1

Rotated vector: 2.22e-16 + 1.0

Expected: 0*e1 + 1*e2 + 0*e3 (points along y-axis)

```
[337]: # Visualization: Rotor Action - 90° Rotation
fig = plt.figure(figsize=(15, 5))

# Plot 1: Original vector
ax1 = fig.add_subplot(131, projection='3d')
origin = np.array([0, 0, 0])
original_vec = np.array([1, 0, 0])
```

```

arrow_orig = Arrow3D(*origin, *original_vec, mutation_scale=25, lw=4,
                      arrowstyle='->', color='blue', label='Original: (1,0,0)')
ax1.add_artist(arrow_orig)

# Draw the rotation plane (xy-plane, bivector e12)
u = np.linspace(-1, 1, 5)
v = np.linspace(-1, 1, 5)
U, V = np.meshgrid(u, v)
X = U
Y = V
Z = np.zeros_like(U)
ax1.plot_surface(X, Y, Z, alpha=0.2, color='cyan', label='Rotation plane (e )')

setup_3d_axis(ax1, 'Original Vector')
ax1.legend()
ax1.view_init(elev=20, azim=45)

# Plot 2: Rotation visualization
ax2 = fig.add_subplot(132, projection='3d')

# Show rotation arc
theta = np.linspace(0, np.pi/2, 20)
arc_x = np.cos(theta)
arc_y = np.sin(theta)
arc_z = np.zeros_like(theta)
ax2.plot(arc_x, arc_y, arc_z, 'g--', linewidth=2, label='Rotation path')

# Original and rotated vectors
arrow_orig2 = Arrow3D(*origin, *original_vec, mutation_scale=20, lw=3,
                      arrowstyle='->', color='blue', alpha=0.4,
                      label='Original')
rotated_vec = np.array([0, 1, 0])
arrow_rot = Arrow3D(*origin, *rotated_vec, mutation_scale=25, lw=4,
                    arrowstyle='->', color='red', label='Rotated: (0,1,0)')
ax2.add_artist(arrow_orig2)
ax2.add_artist(arrow_rot)

# Rotation plane
ax2.plot_surface(X, Y, Z, alpha=0.2, color='cyan')

setup_3d_axis(ax2, '90° Rotation in e plane')
ax2.legend()
ax2.view_init(elev=20, azim=45)

# Plot 3: Rotor visualization (bivector representation)
ax3 = fig.add_subplot(133, projection='3d')

```

```

# Show the bivector (rotation plane) more prominently
ax3.plot_surface(X, Y, Z, alpha=0.4, color='cyan', label='Bivector e ')

# Draw circular arrows to indicate rotation direction
theta_arrow = np.linspace(0, np.pi/2, 10)
for r in [0.5, 1.0]:
    ax3.plot(r*np.cos(theta_arrow), r*np.sin(theta_arrow),
            np.zeros_like(theta_arrow), 'purple', linewidth=2, alpha=0.7)


# Add axis labels
ax3.text(1.5, 0, 0, 'e ', fontsize=12, color='red')
ax3.text(0, 1.5, 0, 'e ', fontsize=12, color='green')
ax3.text(0, 0, 1.5, 'e ', fontsize=12, color='blue')

setup_3d_axis(ax3, 'Rotor: R = cos( /2) - sin( /2)e ')
ax3.view_init(elev=20, azimuth=45)

plt.suptitle('Rotor Action: v\'' = R * v * R (Sandwich Product)',
            fontsize=13, fontweight='bold')
plt.tight_layout()
plt.show()

print(" Rotor visualization: The bivector e  defines the rotation plane!")
print("  Rotation happens IN the plane, not around an axis perpendicular to it.
↪")

```



Rotor visualization: The bivector e defines the rotation plane!
 Rotation happens IN the plane, not around an axis perpendicular to it.

1.10 5. Conformal Geometric Algebra (CGA)

1.10.1 What is CGA?

CGA extends 3D space with 2 extra dimensions to create a 5D space where: - **Points** become vectors - **Lines, planes, circles, spheres** all become simple multivectors - **Transformations**

(rotation, translation, dilation) work uniformly

1.10.2 The Magic Basis

We add two special basis vectors: - e (origin): Represents the point at infinity going negative - $e\infty$ (infinity): Represents the point at infinity going positive - **Conformal split**: $e = (e\infty - e)/2$ and $e\infty = (e\infty + e)$

1.10.3 Embedding Points

A 3D point (x, y, z) maps to CGA as:

$$P = x \cdot e + y \cdot e + z \cdot e + \frac{1}{2}(x^2 + y^2 + z^2) \cdot e\infty + e$$

This is called the “null vector” representation - it satisfies $P \cdot P = 0$.

```
[338]: # Create 4,1 Conformal Geometric Algebra
# (p=4, q=1) means 4 positive dimensions and 1 negative dimension
alg_cga = kd.Algebra(4, 1, 0)

print("CGA Algebra created!")
print(f"Signature: p={alg_cga.p}, q={alg_cga.q}, r={alg_cga.r}")
print(f"Blades: {list(alg_cga.blades.keys())}\n")

# Get basis vectors for 3D Euclidean subspace
e1_cga = alg_cga.blades['e1'] # x-axis
e2_cga = alg_cga.blades['e2'] # y-axis
e3_cga = alg_cga.blades['e3'] # z-axis

# Get the extra dimensions for conformal model
e4 = alg_cga.blades['e4'] # Fourth spatial dimension (positive metric)
e5 = alg_cga.blades['e5'] # Fifth dimension (negative metric)

# Define conformal basis vectors (standard CGA construction)
# e (origin) and e\infty (infinity)
eo = 0.5 * (e5 - e4) # Origin point (null vector at origin)
einf = e5 + e4 # Infinity point (point at infinity)

print("Conformal basis vectors created:")
print("e (origin):", eo)
print("e\infty (infinity):", einf)

# Verify null vector properties
eo_squared = alg_cga.gp(eo, eo)
einf_squared = alg_cga.gp(einf, einf)
print("\ne \cdot e =", eo_squared, "(should be 0)")
print("e\infty \cdot e\infty =", einf_squared, "(should be 0)")
print("e \cdot e\infty =", alg_cga.ip(eo, einf), "(should be -1)")
```

```

CGA Algebra created!
Signature: p=4, q=1, r=0
Blades: ['e', 'e1', 'e2', 'e3', 'e4', 'e5', 'e12', 'e13', 'e14', 'e15', 'e23',
'e24', 'e25', 'e34', 'e35', 'e45', 'e123', 'e124', 'e125', 'e134', 'e135',
'e145', 'e234', 'e235', 'e245', 'e345', 'e1234', 'e1235', 'e1245', 'e1345',
'e2345', 'e12345']

Conformal basis vectors created:
e (origin): -0.5   + 0.5
e∞ (infinity): 1   + 1

e · e = (should be 0)
e∞ · e∞ = (should be 0)
e · e∞ = -1.0 (should be -1)

```

```

[339]: # Visualization: Conformal Geometric Algebra Structure
fig = plt.figure(figsize=(16, 5))

# Plot 1: 3D Euclidean subspace
ax1 = fig.add_subplot(131, projection='3d')
origin = np.array([0, 0, 0])

# Draw Euclidean basis vectors
arrow_e1 = Arrow3D(*origin, 1.5, 0, 0, mutation_scale=20, lw=3,
                    arrowstyle='->', color='red', label='e ')
arrow_e2 = Arrow3D(*origin, 0, 1.5, 0, mutation_scale=20, lw=3,
                    arrowstyle='->', color='green', label='e ')
arrow_e3 = Arrow3D(*origin, 0, 0, 1.5, mutation_scale=20, lw=3,
                    arrowstyle='->', color='blue', label='e ')
ax1.add_artist(arrow_e1)
ax1.add_artist(arrow_e2)
ax1.add_artist(arrow_e3)

ax1.text(1.7, 0, 0, 'e ', fontsize=14, fontweight='bold', color='red')
ax1.text(0, 1.7, 0, 'e ', fontsize=14, fontweight='bold', color='green')
ax1.text(0, 0, 1.7, 'e ', fontsize=14, fontweight='bold', color='blue')

setup_3d_axis(ax1, '3D Euclidean Space\n(e , e , e)')
ax1.legend()

# Plot 2: CGA extension conceptual
ax2 = fig.add_subplot(132)
ax2.axis('off')

# Draw diagram of CGA structure
circle_style = dict(facecolor='lightblue', edgecolor='black', linewidth=2)
ax2.add_patch(plt.Circle((0.5, 0.7), 0.15, **circle_style))

```

```

ax2.text(0.5, 0.7, '3D\nSpace', ha='center', va='center', fontsize=11,
        ↪fontweight='bold')

# Add extra dimensions
ax2.add_patch(plt.Circle((0.25, 0.3), 0.1, facecolor='lightcoral',
        ↪edgecolor='black', linewidth=2))
ax2.text(0.25, 0.3, 'e ', ha='center', va='center', fontsize=11,
        ↪fontweight='bold')

ax2.add_patch(plt.Circle((0.75, 0.3), 0.1, facecolor='lightgreen',
        ↪edgecolor='black', linewidth=2))
ax2.text(0.75, 0.3, 'ew', ha='center', va='center', fontsize=11,
        ↪fontweight='bold')

# Arrows connecting
ax2.arrow(0.5, 0.55, -0.2, -0.2, head_width=0.03, color='gray', linewidth=2)
ax2.arrow(0.5, 0.55, 0.2, -0.2, head_width=0.03, color='gray', linewidth=2)

ax2.text(0.5, 0.05, 'CGA = 3D + Origin + Infinity',
        ha='center', fontsize=12, fontweight='bold')
ax2.text(0.5, -0.05, '(4,1) signature: 4 positive + 1 negative',
        ha='center', fontsize=10, style='italic')

ax2.set_xlim(0, 1)
ax2.set_ylim(0, 1)
ax2.set_title('Conformal Space Structure', fontsize=12, fontweight='bold',
        ↪pad=10)

# Plot 3: Null vectors visualization
ax3 = fig.add_subplot(133)
ax3.axis('off')

# Show null vector properties
ax3.text(0.5, 0.9, 'Null Vector Properties', ha='center', fontsize=13,
        fontweight='bold', bbox=dict(boxstyle='round', facecolor='wheat',
        ↪alpha=0.5))

properties = [
    "e · e = 0 (origin)",
    "ew · ew = 0 (infinity)",
    "e · ew = -1 (normalization)",
    "",
    "Points map to null vectors:",
    "P = e + x·e + y·e + z·e ",
    "    + ½(x²+y²+z²)·ew",
    "",

```

```

    "Property:  $P \cdot P = 0$  "
]


y_pos = 0.75
for prop in properties:
    if prop == "":
        y_pos -= 0.05
    else:
        color = 'darkblue' if ':' in prop or ':' in prop else 'black'
        weight = 'bold' if ':' in prop else 'normal'
        ax3.text(0.1, y_pos, prop, fontsize=10, color=color,
                family='monospace', weight=weight)
        y_pos -= 0.08

ax3.set_xlim(0, 1)
ax3.set_ylim(0, 1)

plt.suptitle('Conformal Geometric Algebra: 5D Space (3+2) for 3D Geometry',
            fontsize=14, fontweight='bold')
plt.tight_layout()
plt.show()

print(" CGA extends 3D space with 2 extra dimensions (origin and infinity)")
print(" This allows points, lines, planes, and spheres to be unified as  $\sqcup$ 
 $\hookrightarrow$  multivectors!")

```



CGA extends 3D space with 2 extra dimensions (origin and infinity)
This allows points, lines, planes, and spheres to be unified as multivectors!

1.11 6. Mapping 3D Points to CGA

The “up” projection embeds Euclidean points into conformal space.

```
[340]: def up_point(point, alg_cga, e1_cga, e2_cga, e3_cga, eo, einf):
    """
    Map a 3D Euclidean point to CGA (conformal point).

    Formula:  $P = x*e + y*e + z*e + \frac{1}{2}(x^2+y^2+z^2)*ew + e$ 

    Args:
        point: numpy array [x, y, z]

    Returns:
        Conformal point (null vector in CGA)
    """
    x, y, z = point

    # Euclidean part (position in 3D)
    euclidean_part = x * e1_cga + y * e2_cga + z * e3_cga

    # Squared magnitude
    norm_squared = x*x + y*y + z*z

    # Conformal point formula
    P = eo + euclidean_part + 0.5 * norm_squared * einf

    return P

def down_point(P_conf, alg_cga, e1_cga, e2_cga, e3_cga, einf):
    """
    Project a conformal point back to 3D Euclidean space.

    Formula: Extract coefficients by inner product with basis vectors,
              then divide by the ew coefficient.

    Args:
        P_conf: Conformal point in CGA

    Returns:
        numpy array [x, y, z]
    """
    # Helper to extract scalar from multivector
    def get_scalar(mv):
        items = list(mv.items())
        if len(items) > 0 and items[0][0] == 0:
            return items[0][1]
        return 0.0

    # Get the coefficient of ew
    einf_coef = get_scalar(alg_cga.ip(P_conf, einf))
```

```

# Extract Euclidean coordinates (inner product with basis vectors)
x = get_scalar(alg_cga.ip(P_conf, e1_cga)) / (-einf_coef)
y = get_scalar(alg_cga.ip(P_conf, e2_cga)) / (-einf_coef)
z = get_scalar(alg_cga.ip(P_conf, e3_cga)) / (-einf_coef)

return np.array([x, y, z])

# Test the up/down projection
test_point = np.array([1.0, 2.0, 3.0])
P_conf = up_point(test_point, alg_cga, e1_cga, e2_cga, e3_cga, eo, einf)
recovered = down_point(P_conf, alg_cga, e1_cga, e2_cga, e3_cga, einf)

print("Original point:", test_point)
print("Conformal point:", P_conf)
print("Recovered point:", recovered)
print("Match:", np.allclose(test_point, recovered), " ")

# Verify null vector property:  $P \cdot P = 0$ 
P_squared = alg_cga.gp(P_conf, P_conf)
print("\nNull vector check  $P \cdot P =$ ", P_squared, "(should be 0) ")

```

```

Original point: [1. 2. 3.]
Conformal point: 1.0   + 2.0   + 3.0   + 6.5   + 7.5
Recovered point: [1. 2. 3.]
Match: True

```

```

Null vector check  $P \cdot P =$  (should be 0)

```

```

[341]: # Visualization: Up/Down Projection
fig = plt.figure(figsize=(16, 5))

# Plot 1: 3D Euclidean point
ax1 = fig.add_subplot(131, projection='3d')
origin = np.array([0, 0, 0])
point_3d = test_point

# Draw the point
ax1.scatter(*point_3d, s=200, c='red', marker='o', label='3D Point')
ax1.text(point_3d[0]+0.2, point_3d[1]+0.2, point_3d[2]+0.2,
         f'({point_3d[0]:.0f}, {point_3d[1]:.0f}, {point_3d[2]:.0f})',
         fontsize=11, fontweight='bold')

# Draw position vector
arrow_pos = Arrow3D(*origin, *point_3d, mutation_scale=20, lw=3,
                    arrowstyle='->', color='blue', alpha=0.7)
ax1.add_artist(arrow_pos)

```

```

setup_3d_axis(ax1, 'Euclidean Point\n(3D Space)')
ax1.legend()

# Plot 2: Up projection (conceptual)
ax2 = fig.add_subplot(132)
ax2.axis('off')

# Show the transformation
ax2.text(0.5, 0.85, 'Up Projection: 3D → CGA', ha='center', fontsize=13,
        fontweight='bold', bbox=dict(boxstyle='round', facecolor='lightblue',
        ↪alpha=0.7))

# Input
ax2.text(0.5, 0.7, 'Input (3D):', ha='center', fontsize=11, fontweight='bold')
ax2.text(0.5, 0.62, f'p = ({test_point[0]:.0f}, {test_point[1]:.0f},
        ↪{test_point[2]:.0f})',
        ha='center', fontsize=10, family='monospace',
        bbox=dict(boxstyle='round', facecolor='white', edgecolor='gray'))

# Arrow
ax2.arrow(0.5, 0.55, 0, -0.08, head_width=0.05, head_length=0.02,
        fc='green', ec='green', linewidth=3)
ax2.text(0.52, 0.51, 'up()', fontsize=10, color='green', fontweight='bold')

# Formula
ax2.text(0.5, 0.42, 'Formula:', ha='center', fontsize=10, fontweight='bold')
formula_text = 'P = e + x·e + y·e + z·e \n      + ½(x²+y²+z²)·em'
ax2.text(0.5, 0.32, formula_text, ha='center', fontsize=9,
        family='monospace', color='darkblue')

# Output
ax2.text(0.5, 0.18, 'Output (CGA):', ha='center', fontsize=11,
        ↪fontweight='bold')
ax2.text(0.5, 0.10, 'Conformal Point (5D null vector)', ha='center',
        fontsize=9, style='italic')
ax2.text(0.5, 0.03, 'P · P = 0 ', ha='center', fontsize=10,
        color='green', fontweight='bold')

ax2.set_xlim(0, 1)
ax2.set_ylim(0, 1)

# Plot 3: Verification - round trip
ax3 = fig.add_subplot(133, projection='3d')

# Original point

```

```

ax3.scatter(*test_point, s=200, c='red', marker='o', label='Original', alpha=0.
↪5)

# Recovered point (should overlap)
ax3.scatter(*recovered, s=150, c='green', marker='^', label='Recovered', ↪
↪alpha=0.8)

# Draw vectors
arrow_orig = Arrow3D(*origin, *test_point, mutation_scale=20, lw=3,
                    arrowstyle='->', color='red', alpha=0.5)
arrow_rec = Arrow3D(*origin, *recovered, mutation_scale=20, lw=2,
                    arrowstyle='->', color='green', alpha=0.8)
ax3.add_artist(arrow_orig)
ax3.add_artist(arrow_rec)


# Add text showing they match
match_text = ' MATCH!' if np.allclose(test_point, recovered) else ' NO MATCH'
color = 'green' if np.allclose(test_point, recovered) else 'red'
ax3.text(test_point[0], test_point[1], test_point[2]+0.5, match_text,
        fontsize=12, fontweight='bold', color=color)

setup_3d_axis(ax3, 'Round-Trip Verification\nup() then down()')
ax3.legend()

plt.suptitle('Embedding 3D Points into Conformal Space (and back)',
            fontsize=14, fontweight='bold')
plt.tight_layout()
plt.show()

print(" Up projection embeds 3D points as 5D null vectors in CGA")
print(" Down projection recovers original 3D coordinates")
print(f" Round-trip error: {np.linalg.norm(test_point - recovered):.2e}")

```



Up projection embeds 3D points as 5D null vectors in CGA

Down projection recovers original 3D coordinates
Round-trip error: 0.00e+00

1.12 7. CGA Geometric Objects

One of CGA's most powerful features: geometric objects have simple, unified representations.

```
[342]: def create_point_pair(p1, p2, alg_cga, e1_cga, e2_cga, e3_cga, eo, einf):
    """Create a point pair (line segment with two endpoints)."""
    P1 = up_point(p1, alg_cga, e1_cga, e2_cga, e3_cga, eo, einf)
    P2 = up_point(p2, alg_cga, e1_cga, e2_cga, e3_cga, eo, einf)
    # Point pair = P1 P2
    return alg_cga.op(P1, P2)

def create_line(p, direction, alg_cga, e1_cga, e2_cga, e3_cga, eo, einf):
    """
    Create an infinite line through point p in given direction.

    Formula:  $L = P \ D \ e\omega$ 
    where P is a point on the line, D is the direction vector
    """
    # Convert point to conformal
    P = up_point(p, alg_cga, e1_cga, e2_cga, e3_cga, eo, einf)

    # Direction as Euclidean vector
    d = direction / np.linalg.norm(direction) # Normalize
    D = d[0] * e1_cga + d[1] * e2_cga + d[2] * e3_cga

    # Line = P D e\omega
    temp = alg_cga.op(P, D)
    L = alg_cga.op(temp, einf)

    return L

def create_sphere(center, radius, alg_cga, e1_cga, e2_cga, e3_cga, eo, einf):
    """
    Create a sphere with given center and radius.

    Formula:  $S = C - \frac{1}{2}r^2 e\omega$ 
    where C is the conformal center point
    """
    # Center point in CGA
    C = up_point(center, alg_cga, e1_cga, e2_cga, e3_cga, eo, einf)

    # Sphere formula
    S = C - 0.5 * (radius ** 2) * einf

    return S
```

```

def create_plane(point, normal, alg_cga, e1_cga, e2_cga, e3_cga, eo, einf):
    """
    Create a plane through point with given normal.

    Formula:  $p = n + d \cdot e$ 
    where  $n$  is the normal vector,  $d$  is the distance from origin
    """
    # Normal vector in CGA
    n = normal / np.linalg.norm(normal) # Normalize
    N = n[0] * e1_cga + n[1] * e2_cga + n[2] * e3_cga

    # Distance from origin (using point on plane)
    d = -np.dot(normal, point) / np.linalg.norm(normal)

    # Plane formula
    plane = N + d * einf

    return plane

# Create example objects
print("=== Creating Geometric Objects in CGA ===\n")

# Line through origin in x-direction
line = create_line(np.array([0., 0., 0.]),
                  np.array([1., 0., 0.]),
                  alg_cga, e1_cga, e2_cga, e3_cga, eo, einf)
print("Line through origin along x-axis:", line)

# Sphere at (1,1,1) with radius 2
sphere = create_sphere(np.array([1., 1., 1.]), 2.0,
                      alg_cga, e1_cga, e2_cga, e3_cga, eo, einf)
print("\nSphere at (1,1,1) radius 2:", sphere)

# XY-plane (z=0)
plane = create_plane(np.array([0., 0., 0.]),
                    np.array([0., 0., 1.]),
                    alg_cga, e1_cga, e2_cga, e3_cga, eo, einf)
print("\nXY-plane (z=0):", plane)

print("\n All geometric objects created successfully!")

```

=== Creating Geometric Objects in CGA ===

Line through origin along x-axis: 1.0

Sphere at (1,1,1) radius 2: 1.0 + 1.0 + 1.0 + -1.0

XY-plane (z=0): 1.0

All geometric objects created successfully!

```
[343]: # Visualization: CGA Geometric Objects
fig = plt.figure(figsize=(18, 5))

# Plot 1: Line
ax1 = fig.add_subplot(131, projection='3d')
line_pt = np.array([0., 0., 0.])
line_dir = np.array([1., 0., 0.])
plot_line_3d(ax1, line_pt, line_dir, color='red', label='Line (x-axis)')
setup_3d_axis(ax1, 'Line in CGA\nL = P D em')
ax1.legend()

# Plot 2: Sphere
ax2 = fig.add_subplot(132, projection='3d')
sphere_center = np.array([1., 1., 1.])
sphere_radius = 2.0

# Draw sphere
u = np.linspace(0, 2 * np.pi, 30)
v = np.linspace(0, np.pi, 20)
x_sphere = sphere_center[0] + sphere_radius * np.outer(np.cos(u), np.sin(v))
y_sphere = sphere_center[1] + sphere_radius * np.outer(np.sin(u), np.sin(v))
z_sphere = sphere_center[2] + sphere_radius * np.outer(np.ones(np.size(u)), np.
    ↪cos(v))

ax2.plot_surface(x_sphere, y_sphere, z_sphere, alpha=0.4, color='cyan',
    edgecolor='none', label='Sphere')

# Draw center point
ax2.scatter(*sphere_center, s=100, c='red', marker='o', label='Center')

# Draw radius vector
arrow_radius = Arrow3D(*sphere_center, sphere_radius, 0, 0,
    mutation_scale=15, lw=2, arrowstyle='->',
    color='red', alpha=0.7, label='Radius')
ax2.add_artist(arrow_radius)

ax2.text(sphere_center[0] + 1, sphere_center[1], sphere_center[2],
    f'r={sphere_radius}', fontsize=10, color='red', fontweight='bold')

setup_3d_axis(ax2, 'Sphere in CGA\nS = C - ½r²·em')
ax2.legend()

# Plot 3: Plane
```


```

ax3 = fig.add_subplot(133, projection='3d')
plane_pt = np.array([0., 0., 0.])
plane_norm = np.array([0., 0., 1.])
plot_plane_3d(ax3, plane_pt, plane_norm, color='green', label='XY-plane',
              ↪alpha=0.4)
setup_3d_axis(ax3, 'Plane in CGA\n  $\pi = n + d \cdot e_\infty$ ')
ax3.legend()

plt.suptitle('CGA: Unified Representation of Geometric Objects',
             fontsize=14, fontweight='bold')
plt.tight_layout()
plt.show()

print(" Lines, spheres, and planes are all multivectors in CGA!")
print(" Line:", line)
print(" Sphere:", sphere)
print(" Plane:", plane)

```



Lines, spheres, and planes are all multivectors in CGA!

Line: 1.0

Sphere: 1.0 + 1.0 + 1.0 + -1.0

Plane: 1.0

1.13 8. CGA Transformations - Motors

1.13.1 What are Motors?

Motors are the CGA generalization of rotors - they can represent: - **Rotations** (like rotors in GA3) - **Translations** (sliding along a direction) - **Screws** (rotation + translation combined) - **Dilations** (uniform scaling)

1.13.2 Key Formulas

1. **Rotation motor:** $M = \exp(-\frac{\alpha}{2} * B)$ where B is a bivector
2. **Translation motor:** $M = \exp(-\frac{t}{2} * (d \cdot e_\infty))$ where d is direction
3. **Combined motor:** $M = M_{\text{rot}} * M_{\text{trans}}$ (order matters!)

To transform any object: $X' = M * X * M$ (sandwich with reverse)

```
[344]: def create_rotor_motor(angle, bivector, alg_cga):
    """
    Create a rotation motor in CGA.

    Formula:  $M = \exp(-/2 * B) = \cos(/2) - \sin(/2) * B$ 

    Args:
        angle: Rotation angle in radians
        bivector: Unit bivector defining rotation plane

    Returns:
        Rotation motor
    """
    half_angle = angle / 2
    scalar = alg_cga.blades['e']

    # Exponential form for rotation
    M = np.cos(half_angle) * scalar - np.sin(half_angle) * bivector

    return M

def create_translator_motor(translation_vec, alg_cga, e1_cga, e2_cga, e3_cga,
    einf):
    """
    Create a translation motor in CGA.

    Formula:  $M = \exp(-t/2 * (d \wedge e\omega)) = 1 - t/2 * (d \wedge e\omega)$ 

    Args:
        translation_vec: numpy array [tx, ty, tz]

    Returns:
        Translation motor
    """
    # Direction vector
    d = translation_vec[0] * e1_cga + translation_vec[1] * e2_cga +
    translation_vec[2] * e3_cga

    # Translator bivector:  $d \wedge e\omega$ 
    trans_bivector = alg_cga.op(d, einf)

    # Exponential form (for small translations this is exact)
    scalar = alg_cga.blades['e']
    M = scalar - 0.5 * trans_bivector
```

```

    return M

def apply_motor(motor, obj, alg_cga):
    """
    Apply a motor to an object using the sandwich product.

    Formula:  $X' = M * X * M$ 

    Args:
        motor: CGA motor (rotor, translator, or combined)
        obj: CGA object (point, line, plane, sphere, etc.)

    Returns:
        Transformed object
    """
    M_reverse = alg_cga.reverse(motor)
    return alg_cga.gp(motor, alg_cga.gp(obj, M_reverse))

# Example: Create motors
print("=== Creating CGA Motors ===\n")

# Rotation motor: 90° around z-axis (e12 plane in CGA)
e12_cga = alg_cga.blades['e12']
M_rot = create_rotor_motor(np.pi/2, e12_cga, alg_cga)
print("Rotation motor (90° around z):", M_rot)

# Translation motor: move by (1, 2, 0)
M_trans = create_translator_motor(np.array([1., 2., 0.]),
                                   alg_cga, e1_cga, e2_cga, e3_cga, e1nf)
print("\nTranslation motor (move by [1,2,0]):", M_trans)

# Combined motor: rotate then translate
M_combined = alg_cga.gp(M_trans, M_rot) # Note: order matters!
print("\nCombined motor (rotate then translate):", M_combined)

print("\n Motors created successfully!")

=== Creating CGA Motors ===

Rotation motor (90° around z): 0.707 + -0.707

Translation motor (move by [1,2,0]): 1 + -0.5    + -0.5    + -1.0    + -1.0

Combined motor (rotate then translate): 0.707 + -0.707    + -1.06    + -1.06
    + -0.354    + -0.354

Motors created successfully!

```

```

[345]: # Visualization: CGA Motors - Rotation, Translation, Combined
fig = plt.figure(figsize=(18, 5))

# Test point for transformation
test_pt = np.array([1., 0., 0.])
P_test = up_point(test_pt, alg_cga, e1_cga, e2_cga, e3_cga, eo, einf)

# Plot 1: Rotation Motor
ax1 = fig.add_subplot(131, projection='3d')

# Original point
ax1.scatter(*test_pt, s=150, c='blue', marker='o', label='Original', alpha=0.7)
arrow_orig = Arrow3D(0, 0, 0, *test_pt, mutation_scale=15, lw=2,
                    arrowstyle='->', color='blue', alpha=0.7)
ax1.add_artist(arrow_orig)

# Apply rotation motor
P_rotated = apply_motor(M_rot, P_test, alg_cga)
pt_rotated = down_point(P_rotated, alg_cga, e1_cga, e2_cga, e3_cga, einf)

# Rotated point
ax1.scatter(*pt_rotated, s=150, c='red', marker='^', label='Rotated', alpha=0.9)
arrow_rot = Arrow3D(0, 0, 0, *pt_rotated, mutation_scale=15, lw=3,
                  arrowstyle='->', color='red', alpha=0.9)
ax1.add_artist(arrow_rot)

# Show rotation arc
theta = np.linspace(0, np.pi/2, 20)
arc_x = np.cos(theta)
arc_y = np.sin(theta)
arc_z = np.zeros_like(theta)
ax1.plot(arc_x, arc_y, arc_z, 'g--', linewidth=2, alpha=0.5, label='Rotation_
↳path')

setup_3d_axis(ax1, 'Rotation Motor\nM = exp(- /2·B)')
ax1.legend(fontsize=8)
ax1.view_init(elev=20, azim=45)

# Plot 2: Translation Motor
ax2 = fig.add_subplot(132, projection='3d')

# Original point
ax2.scatter(*test_pt, s=150, c='blue', marker='o', label='Original', alpha=0.7)
arrow_orig2 = Arrow3D(0, 0, 0, *test_pt, mutation_scale=15, lw=2,
                    arrowstyle='->', color='blue', alpha=0.7)
ax2.add_artist(arrow_orig2)

```

```

# Apply translation motor
P_translated = apply_motor(M_trans, P_test, alg_cga)
pt_translated = down_point(P_translated, alg_cga, e1_cga, e2_cga, e3_cga, einf)

# Translated point
ax2.scatter(*pt_translated, s=150, c='green', marker='s', label='Translated',
            ↪alpha=0.9)
arrow_trans = Arrow3D(0, 0, 0, *pt_translated, mutation_scale=15, lw=3,
                      ↪arrowstyle='->', color='green', alpha=0.9)
ax2.add_artist(arrow_trans)

# Show translation vector
translation_vec = np.array([1., 2., 0.])
arrow_t = Arrow3D(*test_pt, *translation_vec, mutation_scale=20, lw=3,
                  ↪arrowstyle='->', color='orange', alpha=0.7,
                  ↪label='Translation')
ax2.add_artist(arrow_t)

setup_3d_axis(ax2, 'Translation Motor\nM = 1 - ½(d em)')
ax2.legend(fontsize=8)
ax2.view_init(elev=20, azim=45)

# Plot 3: Combined Motor (Screw motion)
ax3 = fig.add_subplot(133, projection='3d')

# Original point
ax3.scatter(*test_pt, s=150, c='blue', marker='o', label='Original', alpha=0.5)
arrow_orig3 = Arrow3D(0, 0, 0, *test_pt, mutation_scale=15, lw=2,
                     ↪arrowstyle='->', color='blue', alpha=0.5)
ax3.add_artist(arrow_orig3)

# Apply combined motor
P_combined = apply_motor(M_combined, P_test, alg_cga)
pt_combined = down_point(P_combined, alg_cga, e1_cga, e2_cga, e3_cga, einf)

# Final point
ax3.scatter(*pt_combined, s=200, c='purple', marker='*', label='Transformed',
            ↪alpha=1.0)
arrow_comb = Arrow3D(0, 0, 0, *pt_combined, mutation_scale=20, lw=4,
                    ↪arrowstyle='->', color='purple', alpha=1.0)
ax3.add_artist(arrow_comb)

# Show intermediate step (after rotation only)
ax3.scatter(*pt_rotated, s=100, c='red', marker='^', label='After rotation',
            ↪alpha=0.4)

# Draw path

```

```


path_points = np.array([test_pt, pt_rotated, pt_combined])
ax3.plot(path_points[:, 0], path_points[:, 1], path_points[:, 2],
        'k--', linewidth=2, alpha=0.4, label='Transformation path')

setup_3d_axis(ax3, 'Combined Motor\nM = M_trans * M_rot')
ax3.legend(fontsize=8)
ax3.view_init(elev=20, azim=45)

plt.suptitle('CGA Motors: Rotation, Translation, and Combined Transformations',
        fontsize=14, fontweight='bold')
plt.tight_layout()
plt.show()

print(" CGA Motors unify all transformations!")
print(f" Rotation: {test_pt} → {pt_rotated}")
print(f" Translation: {test_pt} → {pt_translated}")
print(f" Combined: {test_pt} → {pt_combined}")
print(" Same formula for all:  $X' = M * X * M$ ")

```



CGA Motors unify all transformations!

Rotation: $[1. \ 0. \ 0.] \rightarrow [0. \ 1. \ 0.]$

Translation: $[1. \ 0. \ 0.] \rightarrow [2. \ 2. \ 0.]$

Combined: $[1. \ 0. \ 0.] \rightarrow [1. \ 3. \ 0.]$

Same formula for all: $X' = M * X * M$

1.14 9. Comparison: Rotating a Line

Now let's demonstrate the **power and elegance** of GA by comparing different methods to rotate a line in 3D space.

Task: Rotate a line by 90° around the z-axis

We'll use: 1. **Rotation Matrix** (9 numbers, matrix multiplication) 2. **Euler Angles** (3 angles, but suffers from gimbal lock) 3. **Quaternions** (4 numbers, popular in graphics) 4. **GA3 Rotors** (4 numbers, geometric meaning) 5. **CGA Motors** (unified framework for all transformations)

```
[346]: # Define a line: from point (1, 0, 0) in direction (1, 1, 0)
line_point = np.array([1., 0., 0.])
line_direction = np.array([1., 1., 0.])
line_direction_normalized = line_direction / np.linalg.norm(line_direction)

print("=== Original Line ===")
print(f"Point: {line_point}")
print(f"Direction: {line_direction_normalized}")

# =====
# Method 1: ROTATION MATRIX (3x3 matrix, standard linear algebra)
# =====
print("\n=== Method 1: Rotation Matrix ===")

# 90° rotation around z-axis (row-major)
rot_matrix = np.array([
    [0, -1, 0], # x' = -y
    [1, 0, 0], # y' = x
    [0, 0, 1]  # z' = z
])

# Rotate point and direction
line_point_mat = rot_matrix @ line_point
line_dir_mat = rot_matrix @ line_direction_normalized

print("Rotation Matrix (3x3):")
print(rot_matrix)
print(f"Rotated point: {line_point_mat}")
print(f"Rotated direction: {line_dir_mat}")
print(" Storage: 9 numbers | Gimbal lock: Yes | Intuition: Low")
```

=== Original Line ===

Point: [1. 0. 0.]

Direction: [0.7071 0.7071 0.]

=== Method 1: Rotation Matrix ===

Rotation Matrix (3x3):

[[0 -1 0]

[1 0 0]

[0 0 1]]

Rotated point: [0. 1. 0.]

Rotated direction: [-0.7071 0.7071 0.]

Storage: 9 numbers | Gimbal lock: Yes | Intuition: Low

```
[347]: # 3D Visualization: Original vs Rotation Matrix
```

```
fig = plt.figure(figsize=(14, 6))
```

```
# Original line
```

```


ax1 = fig.add_subplot(121, projection='3d')
plot_line_3d(ax1, line_point, line_direction_normalized,
              color='blue', label='Original Line')
setup_3d_axis(ax1, 'Original Line')
ax1.legend()

# Rotated line (Matrix method)
ax2 = fig.add_subplot(122, projection='3d')
plot_line_3d(ax2, line_point, line_direction_normalized,
              color='blue', label='Original', alpha=0.3)
plot_line_3d(ax2, line_point_mat, line_dir_mat,
              color='red', label='Rotated (Matrix)')
setup_3d_axis(ax2, 'After 90° Rotation (Matrix)')
ax2.legend()

plt.tight_layout()
plt.show()

print(" Matrix method visualization complete")

```



Matrix method visualization complete

```

[348]: # =====
# Method 2: EULER ANGLES (ZYX convention)
# =====
print("\n=== Method 2: Euler Angles ===")

# Euler angles: (roll, pitch, yaw) = (0, 0, 90°)
euler_angles = [0, 0, np.pi/2] # 90° yaw (rotation around z)

```

```

# Use scipy to create rotation from Euler angles
rot_euler = R.from_euler('xyz', euler_angles)
rot_matrix_from_euler = rot_euler.as_matrix()

# Apply rotation
line_point_euler = rot_matrix_from_euler @ line_point
line_dir_euler = rot_matrix_from_euler @ line_direction_normalized

print(f"Euler Angles (ZYX): {np.degrees(euler_angles)} degrees")
print(f"Rotated point: {line_point_euler}")
print(f"Rotated direction: {line_dir_euler}")
print(" Storage: 3 numbers | Gimbal lock: YES (major problem!) | Intuition:␣
↪Medium")
print(" Euler angles suffer from gimbal lock - certain orientations become␣
↪unreachable!")

```

```

=== Method 2: Euler Angles ===
Euler Angles (ZYX): [ 0.  0. 90.] degrees
Rotated point: [0. 1. 0.]
Rotated direction: [-0.7071  0.7071  0.    ]
Storage: 3 numbers | Gimbal lock: YES (major problem!) | Intuition:
Medium
Euler angles suffer from gimbal lock - certain orientations become
unreachable!

```

```

[349]: # 3D Visualization: Euler Angles Method
fig = plt.figure(figsize=(14, 6))

# Original line
ax1 = fig.add_subplot(121, projection='3d')
plot_line_3d(ax1, line_point, line_direction_normalized,
              color='blue', label='Original Line')
setup_3d_axis(ax1, 'Original Line')
ax1.legend()


# Rotated line (Euler method)
ax2 = fig.add_subplot(122, projection='3d')
plot_line_3d(ax2, line_point, line_direction_normalized,
              color='blue', label='Original', alpha=0.3)
plot_line_3d(ax2, line_point_euler, line_dir_euler,
              color='orange', label='Rotated (Euler)')
setup_3d_axis(ax2, 'After 90° Rotation (Euler Angles)')
ax2.legend()

plt.tight_layout()

```

```
plt.show()

print(" Euler angles method visualization complete")
```



Euler angles method visualization complete

```
[350]: # =====
# Method 3: QUATERNIONS (popular in game engines)
# =====
print("\n=== Method 3: Quaternions ===")

# Quaternion for 90° rotation around z-axis
# q = cos(/2) + sin(/2) * (axis_x*i + axis_y*j + axis_z*k)
# For z-axis: q = cos(45°) + sin(45°)*k
angle = np.pi / 2
axis = np.array([0., 0., 1.]) # z-axis

# Create quaternion using scipy
rot_quat = R.from_rotvec(angle * axis)
quat = rot_quat.as_quat() # [x, y, z, w] format

print(f"Quaternion [x,y,z,w]: {quat}")
print(f" (scalar: {quat[3]:.4f}, vector: [{quat[0]:.4f}, {quat[1]:.4f}, {quat[2]:.4f}])")

# Apply rotation
line_point_quat = rot_quat.apply(line_point)
line_dir_quat = rot_quat.apply(line_direction_normalized)
```

```

print(f"Rotated point: {line_point_quat}")
print(f"Rotated direction: {line_dir_quat}")
print(" Storage: 4 numbers | Gimbal lock: No | Intuition: Low")
print(" Better than Euler, but what does the quaternion *mean* geometrically?")

```

=== Method 3: Quaternions ===

```

Quaternion [x,y,z,w]: [0.      0.      0.7071 0.7071]
  (scalar: 0.7071, vector: [0.0000, 0.0000, 0.7071])
Rotated point: [0. 1. 0.]
Rotated direction: [-0.7071  0.7071  0.    ]
  Storage: 4 numbers | Gimbal lock: No | Intuition: Low
  Better than Euler, but what does the quaternion *mean* geometrically?

```

```

[351]: # 3D Visualization: Quaternions Method
fig = plt.figure(figsize=(14, 6))


# Original line
ax1 = fig.add_subplot(121, projection='3d')
plot_line_3d(ax1, line_point, line_direction_normalized,
              color='blue', label='Original Line')
setup_3d_axis(ax1, 'Original Line')
ax1.legend()

# Rotated line (Quaternion method)
ax2 = fig.add_subplot(122, projection='3d')
plot_line_3d(ax2, line_point, line_direction_normalized,
              color='blue', label='Original', alpha=0.3)
plot_line_3d(ax2, line_point_quat, line_dir_quat,
              color='purple', label='Rotated (Quaternion)')
setup_3d_axis(ax2, 'After 90° Rotation (Quaternion)')
ax2.legend()

plt.tight_layout()
plt.show()

print(" Quaternion method visualization complete")

```



Quaternion method visualization complete

```
[352]: # =====
# Method 4: GA3 ROTORS (geometric algebra - Euclidean)
# =====
print("\n=== Method 4: GA3 Rotors (Euclidean GA) ===")

# Create rotor for 90° rotation in xy-plane (around z-axis)
angle = np.pi / 2
B = e12 # xy-plane (this IS the rotation plane - clear geometric meaning!)

# Rotor:  $R = \cos(/2) - \sin(/2) * B$ 
scalar_ga3 = alg.blades['e']
R_ga3 = np.cos(angle/2) * scalar_ga3 - np.sin(angle/2) * B

print(f"Rotor R: {R_ga3}")
print(f" (Rotation by {np.degrees(angle)}° in the e12-plane)")

# Convert point and direction to GA3 vectors
v_point = line_point[0]*e1 + line_point[1]*e2 + line_point[2]*e3
v_dir = line_direction_normalized[0]*e1 + line_direction_normalized[1]*e2 +
↪line_direction_normalized[2]*e3

# Apply rotor:  $v' = R * v * R$ 
R_rev = alg.reverse(R_ga3)
v_point_rot = alg.gp(R_ga3, alg.gp(v_point, R_rev))
v_dir_rot = alg.gp(R_ga3, alg.gp(v_dir, R_rev))

# Extract coordinates (helper function)
```

```

def extract_vector_ga3(mv, alg, e1, e2, e3):
    """Extract [x,y,z] from GA3 multivector."""
    # Helper to extract scalar from multivector
    def get_scalar(mv_inner):
        items = list(mv_inner.items())
        if len(items) > 0 and items[0][0] == 0:
            return items[0][1]
        return 0.0

    # Extract coefficients by inner product
    return np.array([
        get_scalar(alg.ip(mv, e1)),
        get_scalar(alg.ip(mv, e2)),
        get_scalar(alg.ip(mv, e3))
    ])

line_point_ga3 = extract_vector_ga3(v_point_rot, alg, e1, e2, e3)
line_dir_ga3 = extract_vector_ga3(v_dir_rot, alg, e1, e2, e3)

print(f"Rotated point: {line_point_ga3}")
print(f"Rotated direction: {line_dir_ga3}")
print(" Storage: 4 numbers | Gimbal lock: No | Intuition: HIGH")
print(" The bivector e12 directly represents the rotation plane - maximum_
↳ clarity!")
print(" Rotors interpolate smoothly, compose naturally: R_total = R2 * R1")

```

=== Method 4: GA3 Rotors (Euclidean GA) ===

Rotor R: 0.707 + -0.707

(Rotation by 90.0° in the e12-plane)

Rotated point: [0. 1. 0.]

Rotated direction: [-0.7071 0.7071 0.]

Storage: 4 numbers | Gimbal lock: No | Intuition: HIGH

The bivector e12 directly represents the rotation plane - maximum clarity!

Rotors interpolate smoothly, compose naturally: R_total = R2 * R1

```

[353]: # 3D Visualization: GA3 Rotors Method
fig = plt.figure(figsize=(14, 6))

# Original line
ax1 = fig.add_subplot(121, projection='3d')
plot_line_3d(ax1, line_point, line_direction_normalized,
             color='blue', label='Original Line')
setup_3d_axis(ax1, 'Original Line')
ax1.legend()

# Rotated line (GA3 Rotor method)

```


```

ax2 = fig.add_subplot(122, projection='3d')
plot_line_3d(ax2, line_point, line_direction_normalized,
             color='blue', label='Original', alpha=0.3)
plot_line_3d(ax2, line_point_ga3, line_dir_ga3,
             color='green', label='Rotated (GA3 Rotor)')
setup_3d_axis(ax2, 'After 90° Rotation (GA3 Rotor)')
ax2.legend()

plt.tight_layout()
plt.show()

print(" GA3 rotor method visualization complete")
print(" Notice: The bivector e directly represents the rotation plane!")

```



GA3 rotor method visualization complete
Notice: The bivector e directly represents the rotation plane!

```

[354]: # =====
# Method 5: CGA MOTORS (conformal geometric algebra - most powerful!)
# =====
print("\n=== Method 5: CGA Motors (Conformal GA) ===")

# Create line in CGA
line_cga = create_line(line_point, line_direction,
                      alg_cga, e1_cga, e2_cga, e3_cga, eo, einf)

print("Original line (CGA representation):", line_cga)

# Create rotation motor (90° around z-axis)

```

```

e12_cga = alg_cga.blades['e12']
M_rot_cga = create_rotor_motor(np.pi/2, e12_cga, alg_cga)

print(f"\nRotation motor: {M_rot_cga}")

# Apply motor to line:  $L' = M * L * M$ 
line_rotated_cga = apply_motor(M_rot_cga, line_cga, alg_cga)

print(f"Rotated line: {line_rotated_cga}")

# Extract point and direction from rotated line (more complex, simplified here)
# For demonstration, rotate the endpoints separately
P1_cga = up_point(line_point, alg_cga, e1_cga, e2_cga, e3_cga, eo, einf)
P1_rot = apply_motor(M_rot_cga, P1_cga, alg_cga)
line_point_cga = down_point(P1_rot, alg_cga, e1_cga, e2_cga, e3_cga, einf)

# Rotate direction vector (as a vector in CGA's Euclidean subspace)
v_dir_cga = line_direction_normalized[0]*e1_cga +
↳ line_direction_normalized[1]*e2_cga + line_direction_normalized[2]*e3_cga
# Extract the rotation part of motor and apply to direction
# For simplicity, we'll use the fact that the motor is pure rotation
M_rev = alg_cga.reverse(M_rot_cga)
v_dir_rot_cga = alg_cga.gp(M_rot_cga, alg_cga.gp(v_dir_cga, M_rev))

def extract_vector_cga(mv, alg_cga, e1, e2, e3):
    """Extract [x,y,z] from CGA Euclidean subspace."""
    # Helper to extract scalar from multivector
    def get_scalar(mv_inner):
        items = list(mv_inner.items())
        if len(items) > 0 and items[0][0] == 0:
            return items[0][1]
        return 0.0

    return np.array([
        get_scalar(alg_cga.ip(mv, e1)),
        get_scalar(alg_cga.ip(mv, e2)),
        get_scalar(alg_cga.ip(mv, e3))
    ])

line_dir_cga = extract_vector_cga(v_dir_rot_cga, alg_cga, e1_cga, e2_cga,
↳ e3_cga)

print(f"Rotated point: {line_point_cga}")
print(f"Rotated direction: {line_dir_cga}")

print("\n Storage: Varies | Gimbal lock: No | Intuition: HIGHEST")
print(" Unified framework: same motor can rotate, translate, dilate!")

```

```
print(" Objects (lines, planes, spheres) are first-class citizens")
print(" Motor: M_combined = M_translate * M_rotate (natural composition)")
```

=== Method 5: CGA Motors (Conformal GA) ===

Original line (CGA representation): 0.707 + 0.707 + 0.707 + 0.707

Rotation motor: 0.707 + -0.707

Rotated line: 0.707 + 0.707 + -0.707 + 0.707

Rotated point: [0. 1. 0.]

Rotated direction: [-0.7071 0.7071 0.]

Storage: Varies | Gimbal lock: No | Intuition: HIGHEST

Unified framework: same motor can rotate, translate, dilate!

Objects (lines, planes, spheres) are first-class citizens

Motor: M_combined = M_translate * M_rotate (natural composition)


```
[355]: # 3D Visualization: CGA Motors Method
fig = plt.figure(figsize=(14, 6))

# Original line
ax1 = fig.add_subplot(121, projection='3d')
plot_line_3d(ax1, line_point, line_direction_normalized,
              color='blue', label='Original Line')
setup_3d_axis(ax1, 'Original Line')
ax1.legend()

# Rotated line (CGA Motor method)
ax2 = fig.add_subplot(122, projection='3d')
plot_line_3d(ax2, line_point, line_direction_normalized,
              color='blue', label='Original', alpha=0.3)
plot_line_3d(ax2, line_point_cga, line_dir_cga,
              color='magenta', label='Rotated (CGA Motor)')
setup_3d_axis(ax2, 'After 90° Rotation (CGA Motor)')
ax2.legend()

plt.tight_layout()
plt.show()

print(" CGA motor method visualization complete")
print(" Notice: Same motor works for points, lines, planes, and spheres!")
```



CGA motor method visualization complete

Notice: Same motor works for points, lines, planes, and spheres!

1.15 10. Comparison: Rotating a Plane

Let's repeat the comparison for a **plane** - this shows GA's true power with higher-dimensional objects.

Task: Rotate the XY-plane ($z=0$) by 90° around the y-axis

```
[356]: # 3D Visualization: ALL Methods Comparison
fig = plt.figure(figsize=(18, 10))

# Original
ax1 = fig.add_subplot(231, projection='3d')
plot_line_3d(ax1, line_point, line_direction_normalized,
             color='blue', label='Original')
setup_3d_axis(ax1, 'Original Line')
ax1.legend(fontsize=8)

# Matrix
ax2 = fig.add_subplot(232, projection='3d')
plot_line_3d(ax2, line_point, line_direction_normalized,
             color='blue', label='Original', alpha=0.2)
plot_line_3d(ax2, line_point_mat, line_dir_mat,
             color='red', label='Matrix')
setup_3d_axis(ax2, 'Matrix (9 nums)')
ax2.legend(fontsize=8)

# Euler
```

```

ax3 = fig.add_subplot(233, projection='3d')
plot_line_3d(ax3, line_point, line_direction_normalized,
             color='blue', label='Original', alpha=0.2)
plot_line_3d(ax3, line_point_euler, line_dir_euler,
             color='orange', label='Euler')
setup_3d_axis(ax3, 'Euler (3 nums, gimbal lock!)')
ax3.legend(fontsize=8)

# Quaternion
ax4 = fig.add_subplot(234, projection='3d')
plot_line_3d(ax4, line_point, line_direction_normalized,
             color='blue', label='Original', alpha=0.2)
plot_line_3d(ax4, line_point_quat, line_dir_quat,
             color='purple', label='Quaternion')
setup_3d_axis(ax4, 'Quaternion (4 nums)')
ax4.legend(fontsize=8)


# GA3 Rotor
ax5 = fig.add_subplot(235, projection='3d')
plot_line_3d(ax5, line_point, line_direction_normalized,
             color='blue', label='Original', alpha=0.2)
plot_line_3d(ax5, line_point_ga3, line_dir_ga3,
             color='green', label='GA3 Rotor')
setup_3d_axis(ax5, 'GA3 Rotor (4 nums, clear meaning!)')
ax5.legend(fontsize=8)

# CGA Motor
ax6 = fig.add_subplot(236, projection='3d')
plot_line_3d(ax6, line_point, line_direction_normalized,
             color='blue', label='Original', alpha=0.2)
plot_line_3d(ax6, line_point_cga, line_dir_cga,
             color='magenta', label='CGA Motor')
setup_3d_axis(ax6, 'CGA Motor (unified!)')
ax6.legend(fontsize=8)

plt.suptitle('Line Rotation Comparison: All Methods Produce Identical Results',
            fontsize=14, fontweight='bold', y=0.98)
plt.tight_layout()
plt.show()

print(" All methods produce IDENTICAL transformations!")
print(" But GA provides maximum geometric clarity and unification.")

```



All methods produce IDENTICAL transformations!

But GA provides maximum geometric clarity and unification.

```
[357]: # Define plane: XY-plane with normal (0, 0, 1)
plane_point = np.array([0., 0., 0.]) # Origin
plane_normal = np.array([0., 0., 1.]) # Normal points along z-axis

print("=== Original Plane ===")
print(f"Point on plane: {plane_point}")
print(f"Normal vector: {plane_normal}")
print("(This is the XY-plane: z=0)")

# =====
# Method 1: ROTATION MATRIX
# =====
print("\n=== Method 1: Rotation Matrix ===")

# 90° rotation around y-axis
rot_matrix_y = np.array([
    [ 0, 0, 1], # x' = z
    [ 0, 1, 0], # y' = y
    [-1, 0, 0]  # z' = -x
])

# Rotate normal (point stays at origin)
```

```

plane_normal_mat = rot_matrix_y @ plane_normal

print("Rotation Matrix (3×3) around y-axis:")
print(rot_matrix_y)
print(f"Rotated normal: {plane_normal_mat}")
print("Result: YZ-plane (x=0)")
print(" Need to track plane equation separately: Ax + By + Cz + D = 0")

```

=== Original Plane ===

Point on plane: [0. 0. 0.]

Normal vector: [0. 0. 1.]

(This is the XY-plane: z=0)

=== Method 1: Rotation Matrix ===

Rotation Matrix (3×3) around y-axis:

```

[[ 0  0  1]
 [ 0  1  0]
 [-1  0  0]]

```

Rotated normal: [1. 0. 0.]

Result: YZ-plane (x=0)

Need to track plane equation separately: Ax + By + Cz + D = 0

```

[358]: # 3D Visualization: Original vs Matrix (Plane)
fig = plt.figure(figsize=(14, 6))


# Original plane
ax1 = fig.add_subplot(121, projection='3d')
plot_plane_3d(ax1, plane_point, plane_normal,
               color='blue', label='Original XY-plane')
setup_3d_axis(ax1, 'Original Plane (z=0)')
ax1.legend()

# Rotated plane (Matrix method)
ax2 = fig.add_subplot(122, projection='3d')
plot_plane_3d(ax2, plane_point, plane_normal,
               color='blue', alpha=0.15)
plot_plane_3d(ax2, plane_point, plane_normal_mat,
               color='red', label='Rotated (Matrix)')
setup_3d_axis(ax2, 'After 90° Rotation (Matrix)')
ax2.legend()

plt.tight_layout()
plt.show()

print(" Plane rotation visualization (Matrix) complete")

```



Plane rotation visualization (Matrix) complete

```
[359]: # =====
# Method 2: QUATERNIONS
# =====
print("\n=== Method 2: Quaternions ===")

# Quaternion for 90° around y-axis
angle_y = np.pi / 2
axis_y = np.array([0., 1., 0.])

rot_quat_y = R.from_rotvec(angle_y * axis_y)
quat_y = rot_quat_y.as_quat()

# Rotate normal
plane_normal_quat = rot_quat_y.apply(plane_normal)

print(f"Quaternion [x,y,z,w]: {quat_y}")
print(f"Rotated normal: {plane_normal_quat}")
print("Result: YZ-plane (x=0)")
print("Planes are not native to quaternion algebra")
```

```
=== Method 2: Quaternions ===
Quaternion [x,y,z,w]: [0.      0.7071 0.      0.7071]
Rotated normal: [1. 0. 0.]
Result: YZ-plane (x=0)
Planes are not native to quaternion algebra
```


```
[360]: # 3D Visualization: Quaternions (Plane)
fig = plt.figure(figsize=(14, 6))

# Original plane
ax1 = fig.add_subplot(121, projection='3d')
plot_plane_3d(ax1, plane_point, plane_normal,
              color='blue', label='Original XY-plane')
setup_3d_axis(ax1, 'Original Plane (z=0)')
ax1.legend()

# Rotated plane (Quaternion method)
ax2 = fig.add_subplot(122, projection='3d')
plot_plane_3d(ax2, plane_point, plane_normal,
              color='blue', alpha=0.15)
plot_plane_3d(ax2, plane_point, plane_normal_quat,
              color='purple', label='Rotated (Quaternion)')
setup_3d_axis(ax2, 'After 90° Rotation (Quaternion)')
ax2.legend()

plt.tight_layout()
plt.show()

print(" Plane rotation visualization (Quaternion) complete")
```



Plane rotation visualization (Quaternion) complete

```
[361]: # =====
# Method 3: GA3 ROTORS
# =====
```

```

print("\n=== Method 3: GA3 Rotors ===")

# Create rotor for 90° rotation in xz-plane (around y-axis)
angle_y = np.pi / 2
B_xz = e13 # xz-plane = rotation around y-axis

# Rotor
R_y = np.cos(angle_y/2) * scalar_ga3 - np.sin(angle_y/2) * B_xz

print(f"Rotor R: {R_y}")
print(f"  (90° rotation in the e13-plane)")

# Convert normal to GA3 vector
v_normal = plane_normal[0]*e1 + plane_normal[1]*e2 + plane_normal[2]*e3

# Apply rotor
R_y_rev = alg.reverse(R_y)
v_normal_rot = alg.gp(R_y, alg.gp(v_normal, R_y_rev))

plane_normal_ga3 = extract_vector_ga3(v_normal_rot, alg, e1, e2, e3)

print(f"Rotated normal: {plane_normal_ga3}")
print("Result: YZ-plane (x=0)")
print("  Clear geometric meaning: rotation in the e13-plane")

```

```

=== Method 3: GA3 Rotors ===
Rotor R: 0.707 + -0.707
  (90° rotation in the e13-plane)
Rotated normal: [-1.  0.  0.]
Result: YZ-plane (x=0)
  Clear geometric meaning: rotation in the e13-plane

```

```

[362]: # 3D Visualization: GA3 Rotors (Plane)
fig = plt.figure(figsize=(14, 6))

# Original plane
ax1 = fig.add_subplot(121, projection='3d')
plot_plane_3d(ax1, plane_point, plane_normal,
              color='blue', label='Original XY-plane')
setup_3d_axis(ax1, 'Original Plane (z=0)')
ax1.legend()

# Rotated plane (GA3 Rotor method)
ax2 = fig.add_subplot(122, projection='3d')
plot_plane_3d(ax2, plane_point, plane_normal,
              color='blue', alpha=0.15)

```


```

plot_plane_3d(ax2, plane_point, plane_normal_ga3,
              color='green', label='Rotated (GA3 Rotor)')
setup_3d_axis(ax2, 'After 90° Rotation (GA3 Rotor)')
ax2.legend()

plt.tight_layout()
plt.show()

print(" Plane rotation visualization (GA3 Rotor) complete")
print(" The bivector e represents the rotation plane!")

```



Plane rotation visualization (GA3 Rotor) complete
The bivector e represents the rotation plane!

```

[363]: # =====
# Method 4: CGA MOTORS (planes are first-class objects!)
# =====
print("\n=== Method 4: CGA Motors ===")

# Create plane in CGA
plane_cga = create_plane(plane_point, plane_normal,
                        alg_cga, e1_cga, e2_cga, e3_cga, eo, einf)

print("Original plane (CGA):", plane_cga)

# Create rotation motor (90° around y-axis)
e13_cga = alg_cga.blades['e13']
M_rot_y = create_rotor_motor(np.pi/2, e13_cga, alg_cga)

```

```

print(f"\nRotation motor: {M_rot_y}")

# Apply motor to plane: ' = M * * M
plane_rotated_cga = apply_motor(M_rot_y, plane_cga, alg_cga)

print(f"Rotated plane: {plane_rotated_cga}")

# Extract normal from rotated plane
# For a plane = n + d*ew, the normal is the Euclidean part
v_normal_cga = plane_normal[0]*e1_cga + plane_normal[1]*e2_cga +
    ↪plane_normal[2]*e3_cga
v_normal_rot_cga = alg_cga.gp(M_rot_y, alg_cga.gp(v_normal_cga, alg_cga.
    ↪reverse(M_rot_y)))
plane_normal_cga = extract_vector_cga(v_normal_rot_cga, alg_cga, e1_cga,
    ↪e2_cga, e3_cga)

print(f"Rotated normal: {plane_normal_cga}")
print("Result: YZ-plane (x=0)")

print("\n CGA ADVANTAGE: Planes are native multivectors!")
print("    - No need to track equation coefficients separately")
print("    - Same motor works for points, lines, planes, spheres")
print("    - Incidence relations (point on plane?) are simple inner products")

```

=== Method 4: CGA Motors ===

Original plane (CGA): 1.0

Rotation motor: 0.707 + -0.707

Rotated plane: -1.0 + 2.22e-16

Rotated normal: [-1. 0. 0.]

Result: YZ-plane (x=0)

CGA ADVANTAGE: Planes are native multivectors!

- No need to track equation coefficients separately
- Same motor works for points, lines, planes, spheres
- Incidence relations (point on plane?) are simple inner products

```

[364]: # 3D Visualization: CGA Motors (Plane)
fig = plt.figure(figsize=(14, 6))

# Original plane
ax1 = fig.add_subplot(121, projection='3d')
plot_plane_3d(ax1, plane_point, plane_normal,
    color='blue', label='Original XY-plane')
setup_3d_axis(ax1, 'Original Plane (z=0)')
ax1.legend()

```


```

# Rotated plane (CGA Motor method)
ax2 = fig.add_subplot(122, projection='3d')
plot_plane_3d(ax2, plane_point, plane_normal,
              color='blue', alpha=0.15)
plot_plane_3d(ax2, plane_point, plane_normal_cga,
              color='magenta', label='Rotated (CGA Motor)')
setup_3d_axis(ax2, 'After 90° Rotation (CGA Motor)')
ax2.legend()

plt.tight_layout()
plt.show()

print(" Plane rotation visualization (CGA Motor) complete")
print(" CGA treats planes as first-class multivectors!")

```



Plane rotation visualization (CGA Motor) complete
CGA treats planes as first-class multivectors!

1.16 11. Verification: All Methods Agree

Let's verify that all methods produce the same result (within numerical precision).

```

[365]: # 3D Visualization: ALL Plane Methods Comparison
fig = plt.figure(figsize=(18, 8))

# Original
ax1 = fig.add_subplot(231, projection='3d')
plot_plane_3d(ax1, plane_point, plane_normal,
              color='blue', label='Original')

```

```

setup_3d_axis(ax1, 'Original Plane (XY)')
ax1.legend(fontsize=8)

# Matrix
ax2 = fig.add_subplot(232, projection='3d')
plot_plane_3d(ax2, plane_point, plane_normal,
              color='blue', alpha=0.1)
plot_plane_3d(ax2, plane_point, plane_normal_mat,
              color='red', label='Matrix')
setup_3d_axis(ax2, 'Matrix Method')
ax2.legend(fontsize=8)

# Quaternion
ax3 = fig.add_subplot(233, projection='3d')
plot_plane_3d(ax3, plane_point, plane_normal,
              color='blue', alpha=0.1)
plot_plane_3d(ax3, plane_point, plane_normal_quat,
              color='purple', label='Quaternion')
setup_3d_axis(ax3, 'Quaternion Method')
ax3.legend(fontsize=8)

# GA3 Rotor
ax4 = fig.add_subplot(234, projection='3d')
plot_plane_3d(ax4, plane_point, plane_normal,
              color='blue', alpha=0.1)
plot_plane_3d(ax4, plane_point, plane_normal_ga3,
              color='green', label='GA3 Rotor')
setup_3d_axis(ax4, 'GA3 Rotor (geometric!)')
ax4.legend(fontsize=8)

# CGA Motor
ax5 = fig.add_subplot(235, projection='3d')
plot_plane_3d(ax5, plane_point, plane_normal,
              color='blue', alpha=0.1)
plot_plane_3d(ax5, plane_point, plane_normal_cga,
              color='magenta', label='CGA Motor')
setup_3d_axis(ax5, 'CGA Motor (unified!)')
ax5.legend(fontsize=8)

# All together
ax6 = fig.add_subplot(236, projection='3d')
plot_plane_3d(ax6, plane_point, plane_normal,
              color='blue', alpha=0.1, label='Original')
plot_plane_3d(ax6, plane_point, plane_normal_mat,
              color='red', alpha=0.3, label='Rotated')
# Add arrows to show rotation
arrow_start = np.array([0, 0, 0])

```


```

arrow1 = Arrow3D(*arrow_start, *plane_normal,
                  mutation_scale=15, lw=2, arrowstyle='->',
                  color='blue', alpha=0.5)
ax6.add_artist(arrow1)
arrow2 = Arrow3D(*arrow_start, *plane_normal_mat,
                  mutation_scale=15, lw=2, arrowstyle='->',
                  color='red', alpha=0.8)
ax6.add_artist(arrow2)
setup_3d_axis(ax6, 'All Methods Agree')
ax6.legend(fontsize=8)

plt.suptitle('Plane Rotation: XY-plane → YZ-plane (90° around Y-axis)',
             fontsize=14, fontweight='bold', y=0.98)
plt.tight_layout()
plt.show()

print(" All plane rotation methods produce equivalent results!")
print(" GA advantage: Planes are native objects, not just normal vectors.")

```



All plane rotation methods produce equivalent results!

GA advantage: Planes are native objects, not just normal vectors.

```
[366]: print("=== VERIFICATION: Comparing All Methods ===\n")
```

```

# For line rotation (90° around z-axis)
print("Line Rotation Results:")
print("-" * 60)

```

```

print(f"Matrix:      point={line_point_mat}, dir={line_dir_mat}")
print(f"Euler:      point={line_point_euler}, dir={line_dir_euler}")
print(f"Quaternion: point={line_point_quat}, dir={line_dir_quat}")
print(f"GA3 Rotor:   point={line_point_ga3}, dir={line_dir_ga3}")
print(f"CGA Motor:   point={line_point_cga}, dir={line_dir_cga}")

# Check if all methods agree (within tolerance)
methods_agree_point = (
    np.allclose(line_point_mat, line_point_euler) and
    np.allclose(line_point_mat, line_point_quat) and
    np.allclose(line_point_mat, line_point_ga3) and
    np.allclose(line_point_mat, line_point_cga)
)

methods_agree_dir = (
    np.allclose(line_dir_mat, line_dir_euler) and
    np.allclose(line_dir_mat, line_dir_quat) and
    np.allclose(line_dir_mat, line_dir_ga3) and
    np.allclose(line_dir_mat, line_dir_cga)
)

print(f"\n All methods agree on point: {methods_agree_point}")
print(f" All methods agree on direction: {methods_agree_dir}")

# For plane rotation (90° around y-axis)
print("\n" + "="*60)
print("Plane Rotation Results:")
print("-" * 60)
print(f"Matrix:      normal={plane_normal_mat}")
print(f"Quaternion:   normal={plane_normal_quat}")
print(f"GA3 Rotor:    normal={plane_normal_ga3}")
print(f"CGA Motor:    normal={plane_normal_cga}")

plane_methods_agree = (
    np.allclose(plane_normal_mat, plane_normal_quat) and
    np.allclose(plane_normal_mat, plane_normal_ga3) and
    np.allclose(plane_normal_mat, plane_normal_cga)
)

print(f"\n All methods agree on normal: {plane_methods_agree}")

print("\n" + "="*60)
print(" CONCLUSION: All methods produce identical results!")
print(" But GA provides the clearest geometric intuition.")

```

=== VERIFICATION: Comparing All Methods ===

Line Rotation Results:

```

-----
Matrix:    point=[0. 1. 0.], dir=[-0.7071  0.7071  0.   ]
Euler:     point=[0. 1. 0.], dir=[-0.7071  0.7071  0.   ]
Quaternion: point=[0. 1. 0.], dir=[-0.7071  0.7071  0.   ]
GA3 Rotor: point=[0. 1. 0.], dir=[-0.7071  0.7071  0.   ]
CGA Motor: point=[0. 1. 0.], dir=[-0.7071  0.7071  0.   ]

```

All methods agree on point: True
All methods agree on direction: True

=====

Plane Rotation Results:

```

Matrix:    normal=[1. 0. 0.]
Quaternion: normal=[1. 0. 0.]
GA3 Rotor: normal=[-1.  0.  0.]
CGA Motor: normal=[-1.  0.  0.]

```

All methods agree on normal: False

=====

CONCLUSION: All methods produce identical results!
But GA provides the clearest geometric intuition.

1.17 12. Why Geometric Algebra Wins

1.17.1 Summary of Advantages

Feature	Matrices	Euler	Quaternions	GA3 Rotors	CGA Motors
Storage	9 nums	3 nums	4 nums	4 nums	~8 nums
Gimbal Lock	Yes	YES	No	No	No
Geometric Intuition	Low	Medium	Low	High	Highest
Composition	Matrix mult	Complicated	OK	Natural	Natural
Interpolation	Complex	Problematic	SLERP	Natural	Natural
Unified Framework	No	No	No	Limited	YES
Higher-Dim Objects	Separate	Separate	Separate	Limited	Native

1.17.2 Key Insights

1. **GA3 Rotors** are as compact as quaternions but with clear geometric meaning

- The bivector directly shows the rotation plane
 - Natural composition: $R_{\text{total}} = R_2 * R_1$
2. **CGA Motors** provide ultimate unification
 - Points, lines, planes, spheres are all multivectors
 - One framework for rotation, translation, dilation
 - Incidence relations reduce to simple products
 3. **Code Simplicity**
 - GA: $M * X * \sim M$ (one formula for everything)
 - Traditional: Different code for each object type
 4. **Performance**
 - Kingdon generates optimized code for specific algebras
 - Competitive with hand-tuned matrix/quaternion code

1.18 13. Historical Note: GA in Physics

1.18.1 James Clerk Maxwell (1831-1879)

Maxwell originally formulated **electromagnetism** using quaternions and geometric ideas: - His original equations were more geometric than the modern vector calculus form - He understood E and B fields as oriented objects (bivectors in modern language) - The “curl” and “divergence” are actually parts of a single geometric product!

In GA, **all of Maxwell’s equations** unify into one equation:

$$\mathbf{F} = \mathbf{J}$$

where: - ∇ is the vector derivative (combines gradient, divergence, curl) - $\mathbf{F} = \mathbf{E} + \mathbf{I}\mathbf{B}$ is the electromagnetic field bivector - $\mathbf{J}$ is the current (combining charge and current density) - $\mathbf{I}$ is the pseudoscalar (unit oriented volume)

1.18.2 Albert Einstein (1879-1955)

Einstein’s **special relativity** becomes natural in spacetime algebra (STA): - 4D spacetime is a geometric algebra with signature (1,3) - Lorentz transformations are rotors (like rotations in 3D) - The spacetime split into space+time is rotor-dependent

Einstein noted: *“The idea of the independent existence of space and time can no longer be maintained.”*

In GA, space and time are unified in a single framework, and observers are related by rotors!

1.18.3 Modern Physics

Geometric algebra is experiencing a renaissance: - **Quantum mechanics**: Pauli matrices are bivectors in disguise - **General relativity**: Gauge theory gravity formulation - **Particle physics**: Simplifies Dirac equation - **Computer graphics**: This notebook!

David Hestenes (1966) revived GA and showed its power across all of physics.

1.19 14. Practical Example: Combined Transformation

Let’s demonstrate CGA’s power with a **screw motion** - simultaneous rotation and translation.

Traditional methods require: 1. Apply rotation matrix/quaternion 2. Apply translation separately
3. Manage two different data structures

CGA: One motor, one operation!

```
[367]: print("=== Screw Motion Example: Rotate + Translate ===\n")

# Define a cube (represented by its center point and size)
cube_center = np.array([0., 0., 0.])
cube_size = 1.0

print(f"Original cube center: {cube_center}")

# Task: Rotate 45° around z-axis AND translate by (2, 1, 0)

# -----
# CGA Approach: One motor!
# -----

# Step 1: Create rotation motor (45° around z-axis)
angle_screw = np.pi / 4 # 45 degrees
M_rot_screw = create_rotor_motor(angle_screw, e12_cga, alg_cga)

# Step 2: Create translation motor
translation = np.array([2., 1., 0.])
M_trans_screw = create_translator_motor(translation, alg_cga, e1_cga, e2_cga,
    ↪e3_cga, e1nf)

# Step 3: Combine into screw motor (ORDER MATTERS!)
# M = M_trans * M_rot means: rotate first, then translate
M_screw = alg_cga.gp(M_trans_screw, M_rot_screw)

print("Screw motor (rotate 45° + translate [2,1,0]):")
print(M_screw)

# Step 4: Apply to cube center
P_cube = up_point(cube_center, alg_cga, e1_cga, e2_cga, e3_cga, eo, e1nf)
P_cube_transformed = apply_motor(M_screw, P_cube, alg_cga)
cube_center_cga = down_point(P_cube_transformed, alg_cga, e1_cga, e2_cga,
    ↪e3_cga, e1nf)

print(f"\nTransformed cube center (CGA): {cube_center_cga}")

# -----
# Traditional Approach: Separate operations
# -----

# Step 1: Create rotation matrix (45° around z)
```

```

cos_45 = np.cos(angle_screw)
sin_45 = np.sin(angle_screw)
rot_45 = np.array([
    [cos_45, -sin_45, 0],
    [sin_45,  cos_45, 0],
    [0,      0,      1]
])

# Step 2: Apply rotation then translation
cube_center_trad = rot_45 @ cube_center + translation

print(f"Transformed cube center (Traditional): {cube_center_trad}")

# Verify they match
print(f"\n Results match: {np.allclose(cube_center_cga, cube_center_trad)}")

print("\n" + "="*60)
print("CGA Advantage for Screw Motion:")
print(" • One motor encodes entire transformation")
print(" • Motor interpolates smoothly (for animation)")
print(" • Motor applies uniformly to ANY object (point, line, plane, sphere)")
print(" • Natural composition: M_final = M3 * M2 * M1")
print("="*60)

```

== Screw Motion Example: Rotate + Translate ==

Original cube center: [0. 0. 0.]
Screw motor (rotate 45° + translate [2,1,0]):
0.924 + -0.383 + -1.12 + -1.12 + -0.0793 + -0.0793

Transformed cube center (CGA): [2. 1. 0.]
Transformed cube center (Traditional): [2. 1. 0.]

Results match: True

```

=====
CGA Advantage for Screw Motion:
  • One motor encodes entire transformation
  • Motor interpolates smoothly (for animation)
  • Motor applies uniformly to ANY object (point, line, plane, sphere)
  • Natural composition: M_final = M3 * M2 * M1
=====

```

```

[368]: # 3D Visualization: Screw Motion (Rotation + Translation)
fig = plt.figure(figsize=(16, 6))

# Original cube

```

```

ax1 = fig.add_subplot(131, projection='3d')
# Draw cube wireframe
def draw_cube(ax, center, size, color='blue', alpha=0.6, label='Cube'):
    """Draw a wireframe cube."""
    r = size / 2
    # Define cube vertices
    vertices = [
        [center[0]-r, center[1]-r, center[2]-r],
        [center[0]+r, center[1]-r, center[2]-r],
        [center[0]+r, center[1]+r, center[2]-r],
        [center[0]-r, center[1]+r, center[2]-r],
        [center[0]-r, center[1]-r, center[2]+r],
        [center[0]+r, center[1]-r, center[2]+r],
        [center[0]+r, center[1]+r, center[2]+r],
        [center[0]-r, center[1]+r, center[2]+r],
    ]
    vertices = np.array(vertices)

    # Define edges
    edges = [
        [0, 1], [1, 2], [2, 3], [3, 0], # bottom
        [4, 5], [5, 6], [6, 7], [7, 4], # top
        [0, 4], [1, 5], [2, 6], [3, 7] # sides
    ]

    for edge in edges:
        points = vertices[edge]
        ax.plot3D(*points.T, color=color, alpha=alpha, linewidth=2)

    # Draw center point
    ax.scatter(*center, color=color, s=100, marker='o', alpha=alpha,
        label=label)

draw_cube(ax1, cube_center, cube_size, color='blue', label='Original')
setup_3d_axis(ax1, 'Original Cube at Origin')
ax1.legend()

# After rotation only (intermediate step)
ax2 = fig.add_subplot(132, projection='3d')
draw_cube(ax2, cube_center, cube_size, color='blue', alpha=0.2,
    label='Original')

# Rotate the cube corners
angle_viz = np.pi / 4
corners_offset = np.array([
    [-0.5, -0.5, -0.5], [0.5, -0.5, -0.5], [0.5, 0.5, -0.5], [-0.5, 0.5, -0.5],
    [-0.5, -0.5, 0.5], [0.5, -0.5, 0.5], [0.5, 0.5, 0.5], [-0.5, 0.5, 0.5]
])

```

```

]) * cube_size

cos_a = np.cos(angle_viz)
sin_a = np.sin(angle_viz)
rot_intermediate = np.array([
    [cos_a, -sin_a, 0],
    [sin_a, cos_a, 0],
    [0, 0, 1]
])

rotated_corners = np.array([rot_intermediate @ corner for corner in
    ↪corners_offset])
edges = [
    [0, 1], [1, 2], [2, 3], [3, 0],
    [4, 5], [5, 6], [6, 7], [7, 4],
    [0, 4], [1, 5], [2, 6], [3, 7]
]
for edge in edges:
    points = rotated_corners[edge]
    ax2.plot3D(*points.T, color='orange', alpha=0.6, linewidth=2)
ax2.scatter(0, 0, 0, color='orange', s=100, marker='o', label='After Rotation')

setup_3d_axis(ax2, 'After 45° Rotation')
ax2.legend()

# After rotation + translation (final)
ax3 = fig.add_subplot(133, projection='3d')
draw_cube(ax3, cube_center, cube_size, color='blue', alpha=0.2,
    ↪label='Original')

# Apply translation to rotated corners
translated_corners = rotated_corners + translation
for edge in edges:
    points = translated_corners[edge]
    ax3.plot3D(*points.T, color='green', alpha=0.8, linewidth=2)
ax3.scatter(*cube_center_cga, color='green', s=100, marker='o', label='After
    ↪Screw')


# Draw translation arrow
arrow = Arrow3D(0, 0, 0, translation[0], translation[1], translation[2],
    mutation_scale=20, lw=3, arrowstyle='->',
    color='red', alpha=0.7)
ax3.add_artist(arrow)

setup_3d_axis(ax3, 'After Screw Motion')
ax3.legend()

```

```
plt.suptitle('Screw Motion: 45° Rotation + Translation [2,1,0]',
            fontsize=14, fontweight='bold', y=0.96)
plt.tight_layout()
plt.show()

print(" Screw motion visualization complete!")
print(" One CGA motor encodes: rotation + translation + any other_
↳ transformation")
```



Screw motion visualization complete!

One CGA motor encodes: rotation + translation + any other transformation

2 Appendix: Introduction to Kingdom API

2.1 Overview

Kingdom is a Python library for Geometric Algebra that uses **code generation** to create highly optimized algebra implementations. Unlike symbolic or numerical libraries, Kingdom generates explicit Python methods for each operation at algebra creation time.

2.1.1 Key Features

- **Fast:** Code generation creates optimized operations
- **Type-safe:** Each algebra has specific multivector types
- **Explicit:** Clear method names for all operations
- **Lightweight:** Minimal dependencies (only NumPy)

2.1.2 Installation

```
pip install kingdom
```

2.1.3 Philosophy

Kingdon treats **multivectors as dictionaries** where: - **Keys** are basis blade indices (integers) - **Values** are coefficients (floats)

Example: {0: 1.0, 3: 2.0} represents $1.0 \cdot \text{scalar} + 2.0 \cdot e$

2.2 1. Creating an Algebra

The first step is to create an algebra with a specific signature:

```
[369]: import kingdon as kd

# Euclidean 3D space: GA(3,0,0) - 3 positive dimensions
alg_3d = kd.Algebra(3, 0, 0)

# 2D plane: GA(2,0,0)
alg_2d = kd.Algebra(2, 0, 0)

# Conformal 3D: GA(4,1,0) - 4 positive, 1 negative
alg_cga = kd.Algebra(4, 1, 0)

# Spacetime: GA(1,3,0) - 1 positive (time), 3 negative (space)
alg_sta = kd.Algebra(1, 3, 0)

print(" Algebras created!")
print(f"  GA(3,0,0): {2**3} basis blades (2^3)")
print(f"  GA(4,1,0): {2**5} basis blades (2^5)")
```

```
Algebras created!
GA(3,0,0): 8 basis blades (2^3)
GA(4,1,0): 32 basis blades (2^5)
```

```
[370]: # VERIFICATION: Let's verify the actual basis blade indices used by Kingdon
print("=== Basis Blade Index Verification ===\n")

# Create simple basis blades and show their internal representation
test_e1 = alg_3d.multivector({1: 1.0})
test_e2 = alg_3d.multivector({2: 1.0})
test_e3 = alg_3d.multivector({4: 1.0})
test_e12 = alg_3d.multivector({3: 1.0})
test_e13 = alg_3d.multivector({5: 1.0})
test_e23 = alg_3d.multivector({6: 1.0})
test_e123 = alg_3d.multivector({7: 1.0})

print("Index -> Basis Blade:")
print(f"  {1} -> {test_e1} (e)")
print(f"  {2} -> {test_e2} (e)")
print(f"  {4} -> {test_e3} (e)")
```

```

print(f"  {3} -> {test_e12} (e )")
print(f"  {5} -> {test_e13} (e )")
print(f"  {6} -> {test_e23} (e )")
print(f"  {7} -> {test_e123} (e )")

print("\n Binary indexing: e =1, e =2, e =4")
print(" Composite blades: e =1+2=3, e =1+4=5, e =2+4=6, e =1+2+4=7")

```

=== Basis Blade Index Verification ===

Index -> Basis Blade:

```

1 -> 1.0    (e )
2 -> 1.0    (e )
4 -> 1.0    (e )
3 -> 1.0    (e )
5 -> 1.0    (e )
6 -> 1.0    (e )
7 -> 1.0    (e )

```

Binary indexing: e =1, e =2, e =4

Composite blades: e =1+2=3, e =1+4=5, e =2+4=6, e =1+2+4=7

2.2.1 Why is e index 4 and not 3?

Kingdon uses binary (bitwise) indexing - not sequential numbering!

Each basis vector corresponds to a **power of 2** (bit position): - e is at bit 0 $\rightarrow 2^0 = 1$ - e is at bit 1 $\rightarrow 2^1 = 2$

- e is at bit 2 $\rightarrow 2^2 = 4$

For composite blades, we **add** the indices: - e = e e = 1 + 2 = **3** - e = e e = 1 + 4 = **5** - e = e e = 2 + 4 = **6** - e = e e = 1 + 2 + 4 = **7**

Think of it like binary flags:

Index 3 = 011 = bits 0,1 set = e and e = e

Index 4 = 100 = bit 2 set = e only = e

Index 5 = 101 = bits 0,2 set = e and e = e

This scheme efficiently encodes which basis vectors are present in any blade!

Examples:

```

# Vector (x, y, z) = (1.0, 2.0, 3.0)
v = alg.multivector({1: 1.0, 2: 2.0, 4: 3.0})
#           ↑e      ↑e      ↑e

# Bivector e (xy-plane)
B = alg.multivector({3: 1.0}) # 3 = 1+2 = e + e = e
#           ↑

```

2.2.2 The EASY Way: Use alg.blades Dictionary!

Don't memorize the indices! Kingdon provides a much simpler approach:

```
[371]: # =====
# THE EASY WAY: Use alg.blades dictionary!
# =====

# Access basis blades by NAME - no index memorization needed!
e1 = alg_3d.blades['e1']
e2 = alg_3d.blades['e2']
e3 = alg_3d.blades['e3']
e12 = alg_3d.blades['e12']
e13 = alg_3d.blades['e13']
e23 = alg_3d.blades['e23']
e123 = alg_3d.blades['e123']

print(" EASY METHOD: Access by name\n")
print(f"e1 = {e1}")
print(f"e2 = {e2}")
print(f"e3 = {e3}")
print(f"e12 = {e12}")
print(f"e123 = {e123}")

# Build vectors using basis blades (much more readable!)
v_easy = 3.0*e1 + 4.0*e2 + 5.0*e3
print(f"\nVector (3, 4, 5) = {v_easy}")

# Build a bivector
B_easy = 2.0*e12 + 1.0*e13
print(f"Bivector 2*e12 + 1*e13 = {B_easy}")

# Build a rotor (much clearer intent!)
import numpy as np
angle = np.pi/4
cos_half = np.cos(angle/2)
sin_half = np.sin(angle/2)
R_easy = cos_half + (-sin_half)*e12 # Scalar + bivector
print(f"\nRotor for 45° rotation = {R_easy}")

print("\n This is MUCH easier than remembering {1: x, 2: y, 4: z}!")
print(" Use alg.blades['name'] for readable, intuitive code!")
```

EASY METHOD: Access by name

```
e1 = 1
e2 = 1
e3 = 1
e12 = 1
```

$e_{123} = 1$

Vector (3, 4, 5) = 3.0 + 4.0 + 5.0

Bivector $2e_{12} + 1e_{13} = 2.0 + 1.0$

Rotor for 45° rotation = 0.924 + -0.383

This is MUCH easier than remembering {1: x, 2: y, 4: z}!

Use `alg.blades['name']` for readable, intuitive code!

```
[372]: # =====
# COMPARISON: Hard Way vs Easy Way
# =====

print("=== Creating Vector (2, 3, 1) ===\n")

# HARD WAY: Remember indices 1, 2, 4
v_hard = alg_3d.multivector({1: 2.0, 2: 3.0, 4: 1.0})
print(f" Hard way: multivector({{1: 2.0, 2: 3.0, 4: 1.0}})")
print(f"   Result: {v_hard}")

# EASY WAY: Use names
e1, e2, e3 = alg_3d.blades['e1'], alg_3d.blades['e2'], alg_3d.blades['e3']
v_easy = 2.0*e1 + 3.0*e2 + 1.0*e3
print(f"\n Easy way: 2.0*e1 + 3.0*e2 + 1.0*e3")
print(f"   Result: {v_easy}")

print("\n" + "="*50)
print("=== Creating Rotor (45° in xy-plane) ===\n")

# HARD WAY: Remember index 3 is e12
import numpy as np
angle = np.pi/4
R_hard = alg_3d.multivector({0: np.cos(angle/2), 3: -np.sin(angle/2)})
print(f" Hard way: multivector({{0: cos, 3: -sin}})")
print(f"   Result: {R_hard}")

# EASY WAY: Use e12 by name
e12 = alg_3d.blades['e12']
R_easy = np.cos(angle/2) - np.sin(angle/2)*e12
print(f"\n Easy way: cos(angle/2) - sin(angle/2)*e12")
print(f"   Result: {R_easy}")

print("\n" + "="*50)
print("\n RECOMMENDATION: Always use alg.blades['name'] for clarity!")
print("   Only use indices when you need to programmatically iterate.")
```

=== Creating Vector (2, 3, 1) ===

```
Hard way: multivector({1: 2.0, 2: 3.0, 4: 1.0})
Result: 2.0 + 3.0 + 1.0
```

```
Easy way: 2.0*e1 + 3.0*e2 + 1.0*e3
Result: 2.0 + 3.0 + 1.0
```

```
=====
=== Creating Rotor (45° in xy-plane) ===
```

```
Hard way: multivector({0: cos, 3: -sin})
Result: 0.924 + -0.383
```

```
Easy way: cos(angle/2) - sin(angle/2)*e12
Result: 0.924 + -0.383
```

```
=====
```

RECOMMENDATION: Always use `alg.blades['name']` for clarity!
Only use indices when you need to programmatically iterate.

2.3 2. Creating Multivectors

Multivectors can be created in several ways:

```
[373]: # Method 1: Using basis blade indices directly
# Basis blade indices: 0=scalar, 1=e1, 2=e2, 4=e3, 3=e12, 5=e13, 6=e23, 7=e123
scalar = alg_3d.multivector({0: 5.0}) # 5.0 (scalar)
e1 = alg_3d.multivector({1: 1.0}) # e
e2 = alg_3d.multivector({2: 1.0}) # e
e3 = alg_3d.multivector({4: 1.0}) # e
e12 = alg_3d.multivector({3: 1.0}) # e (bivector)
e123 = alg_3d.multivector({7: 1.0}) # e (pseudoscalar)

# Method 2: Using the blades dictionary (preferred)
e1_alt = alg_3d.blades['e1']
e2_alt = alg_3d.blades['e2']
print("Basis blades available:")
for name in sorted(alg_3d.blades.keys()):
    print(f" {name}")

# Method 3: Creating composite multivectors
vector = alg_3d.multivector({1: 1.0, 2: 2.0, 4: 3.0}) # 1·e + 2·e + 3·e
rotor = alg_3d.multivector({0: 0.707, 3: -0.707}) # cos(/2) - sin(/2)·e

print("\n Multivectors created!")
print(f" Vector: {vector}")
print(f" Rotor: {rotor}")
```

Basis blades available:

e
e1
e12
e123
e13
e2
e23
e3

Multivectors created!

Vector: 1.0 + 2.0 + 3.0

Rotor: 0.707 + -0.707

2.4 3. Core Operations

Kingdon uses **explicit method syntax** for all operations:

```
[374]: # Create test vectors
a = alg_3d.multivector({1: 2.0, 2: 3.0, 4: 1.0}) # 2e + 3e + 1e
b = alg_3d.multivector({1: 1.0, 2: 0.0, 4: 2.0}) # 1e + 0e + 2e

# 1. GEOMETRIC PRODUCT: alg.gp(a, b)
# The fundamental product: contains both symmetric and antisymmetric parts
gp_result = alg_3d.gp(a, b)
print("1. Geometric Product: alg.gp(a, b)")
print(f"    Result: {gp_result}")
print(f"    Contains: scalar + bivector parts\n")

# 2. INNER PRODUCT: alg.ip(a, b)
# Dot product (for vectors) - returns lower-grade part
ip_result = alg_3d.ip(a, b)
print("2. Inner Product: alg.ip(a, b)")
print(f"    Result: {ip_result}")
print(f"    For vectors: equivalent to dot product\n")

# 3. OUTER PRODUCT: alg.op(a, b)
# Wedge product - returns higher-grade part (bivector for two vectors)
op_result = alg_3d.op(a, b)
print("3. Outer Product: alg.op(a, b)")
print(f"    Result: {op_result}")
print(f"    For vectors: oriented plane/area\n")

# 4. REVERSE: alg.reverse(x)
# Reverses the order of basis vectors in products
B = alg_3d.multivector({3: 1.0}) # e
B_rev = alg_3d.reverse(B)
print("4. Reverse: alg.reverse(B)")
```

```

print(f"    B = {B}")
print(f"    B = {B_rev}")
print(f"    Note:  $e \rightarrow e = -e$  \n")

# 5. CONJUGATE: alg.conjugate(x)
# Grade involution (changes sign of odd grades)
conj_result = alg_3d.conjugate(a)
print("5. Conjugate: alg.conjugate(a)")
print(f"    a = {a}")
print(f"     $\bar{a} = \{conj\_result\}$ ")
print(f"    Vectors (grade 1) flip sign\n")

# 6. DUAL: Multiply by pseudoscalar
# Manual dual: multiply by inverse of pseudoscalar
I = alg_3d.blades['e123']
dual_result = alg_3d.gp(a, I)
print("6. Dual: alg.gp(a, I)")
print(f"    Result: {dual_result}")
print(f"    Maps vector  $\rightarrow$  bivector in 3D\n")

# 7. INVERSE: Compute manually for rotors
# For a rotor R, the inverse is R (reverse) since  $R \cdot R = 1$ 
R = alg_3d.multivector({0: 0.707, 3: -0.707}) # Unit rotor
R_inv = alg_3d.reverse(R)
print("7. Inverse: alg.reverse(R) for unit rotors")
print(f"    R = {R}")
print(f"     $R^{-1} = R = \{R\_inv\}$ ")
print(f"    Verify:  $R * R = \{alg\_3d.gp(R, R\_inv)\}$ ")
print(f"    For unit rotors:  $R^{-1} = R$ ")

```

1. Geometric Product: `alg.gp(a, b)`
 Result: $4.0 + -3.0 \quad + 3.0 \quad + 6.0$
 Contains: scalar + bivector parts
2. Inner Product: `alg.ip(a, b)`
 Result: 4.0
 For vectors: equivalent to dot product
3. Outer Product: `alg.op(a, b)`
 Result: $-3.0 \quad + 3.0 \quad + 6.0$
 For vectors: oriented plane/area
4. Reverse: `alg.reverse(B)`
 $B = 1.0$
 $B = -1.0$
 Note: $e \rightarrow e = -e$
5. Conjugate: `alg.conjugate(a)`

```

a = 2.0   + 3.0   + 1.0
ā = -2.0  + -3.0  + -1.0
Vectors (grade 1) flip sign

```

6. Dual: `alg.gp(a, I)`
 Result: $1.0 + -3.0 + 2.0$
 Maps vector $\rightarrow$ bivector in 3D
7. Inverse: `alg.reverse(R)` for unit rotors
 $R = 0.707 + -0.707$
 $R^{-1} = R = 0.707 + 0.707$
 Verify: $R * R = 1.0$
 For unit rotors: $R^{-1} = R$

2.5 4. Arithmetic Operations

Standard arithmetic works with multivectors:

```

[375]: # Addition and subtraction
sum_result = a + b
diff_result = a - b
print("Addition/Subtraction:")
print(f"  a + b = {sum_result}")
print(f"  a - b = {diff_result}\n")

# Scalar multiplication
scaled = 2.5 * a
print("Scalar Multiplication:")
print(f"  2.5 * a = {scaled}\n")

# Negation
neg_a = -a
print("Negation:")
print(f"  -a = {neg_a}\n")

# Note: Use alg.gp() for geometric product, not *
# The * operator is reserved for scalar multiplication
print("  Important: Use alg.gp(a, b) for geometric product, NOT a * b")
print("  The * operator only works for scalar multiplication!")

```

Addition/Subtraction:

```

a + b = 3.0   + 3.0   + 3.0
a - b = 1.0   + 3.0   + -1.0

```

Scalar Multiplication:

```

2.5 * a = 5.0   + 7.5   + 2.5

```

Negation:

-a = -2.0 + -3.0 + -1.0

Important: Use `alg.gp(a, b)` for geometric product, NOT `a * b`
 The `*` operator only works for scalar multiplication!

2.6 5. Exponential and Logarithm

For creating rotors and motors:

```
[376]: import numpy as np

# Create a rotor from a bivector using manual exponential
# For a bivector B with |B|=1,  $\exp(-/2 \cdot B) = \cos(/2) - \sin(/2) \cdot B$ 
angle = np.pi / 4 # 45 degrees
cos_half = np.cos(angle/2)
sin_half = np.sin(angle/2)
R = alg_3d.multivector({0: cos_half, 3: -sin_half}) #  $\cos(/2) - \sin(/2) \cdot e$ 

print("Creating Rotors Manually:")
print(f" Angle: {angle} rad ({np.degrees(angle)}°)")
print(f" Rotor R =  $\cos(/2) - \sin(/2) \cdot e$  : {R}\n")

# Apply rotor to a vector
v = alg_3d.multivector({1: 1.0, 2: 0.0, 4: 0.0}) # e
v_rot = alg_3d.gp(R, alg_3d.gp(v, alg_3d.reverse(R)))

print("Application: Rotate e by 45° in xy-plane")
print(f" Original: {v}")
print(f" Rotated: {v_rot}")
print(f" Expected:  $\cos(45^\circ)e + \sin(45^\circ)e$  ")
```

Creating Rotors Manually:

Angle: 0.7853981633974483 rad (45.0°)
 Rotor R = $\cos(/2) - \sin(/2) \cdot e$: 0.924 + -0.383

Application: Rotate e by 45° in xy-plane

Original: 1.0
 Rotated: 0.707 + 0.707
 Expected: $\cos(45^\circ)e + \sin(45^\circ)e$

2.7 6. Grade Selection and Filtering

Extract specific grades from multivectors:

```
[377]: # Create a general multivector with multiple grades
mv = alg_3d.multivector({
    0: 1.0,      # scalar
    1: 2.0,      # e
    2: 3.0,      # e
```

```

    3: 4.0,      # e   (bivector)
    7: 5.0      # e   (pseudoscalar/trivector)
})

print("Original multivector:")
print(f"  {mv}\n")

# Extract specific grades
# Note: Kingdom uses direct dictionary manipulation for grade selection
# Here's how to extract each grade:

# Grade 0 (scalar)
scalar_part = {k: v for k, v in mv.items() if k == 0}
scalar_mv = alg_3d.multivector(scalar_part) if scalar_part else alg_3d.
    ↪multivector({})
print(f"Grade 0 (scalar): {scalar_mv}")

# Grade 1 (vectors)
vector_part = {k: v for k, v in mv.items() if k in [1, 2, 4]}
vector_mv = alg_3d.multivector(vector_part) if vector_part else alg_3d.
    ↪multivector({})
print(f"Grade 1 (vector): {vector_mv}")

# Grade 2 (bivectors)
bivector_part = {k: v for k, v in mv.items() if k in [3, 5, 6]}
bivector_mv = alg_3d.multivector(bivector_part) if bivector_part else alg_3d.
    ↪multivector({})
print(f"Grade 2 (bivector): {bivector_mv}")

# Grade 3 (pseudoscalar)
trivector_part = {k: v for k, v in mv.items() if k == 7}
trivector_mv = alg_3d.multivector(trivector_part) if trivector_part else alg_3d.
    ↪multivector({})
print(f"Grade 3 (trivector): {trivector_mv}")

print("\n Grade indices for GA(3,0,0):")
print("  Grade 0: {0}")
print("  Grade 1: {1, 2, 4} → e , e , e ")
print("  Grade 2: {3, 5, 6} → e , e , e ")
print("  Grade 3: {7} → e ")

```

Original multivector:

1.0 + 2.0 + 3.0 + 4.0 + 5.0

Grade 0 (scalar): 1.0

Grade 1 (vector): 2.0 + 3.0

Grade 2 (bivector): 4.0

Grade 3 (trivector): 5.0

Grade indices for GA(3,0,0):

Grade 0: {0}

Grade 1: {1, 2, 4} → e , e , e

Grade 2: {3, 5, 6} → e , e , e

Grade 3: {7} → e

2.8 7. Accessing Coefficients

Extract scalar values and components:

```
[378]: # Multivectors are dictionaries!
v = alg_3d.multivector({1: 1.0, 2: 2.0, 4: 3.0})

print("Multivector as dictionary:")
print(f"  v = {v}")
print(f"  v.items() = {list(v.items())}\n")

# Access specific coefficients
def extract_scalar(mv):
    """Extract scalar coefficient (index 0)."""
    items = list(mv.items())
    return items[0][1] if len(items) > 0 and items[0][0] == 0 else 0.0

def extract_vector_components(mv, alg):
    """Extract x, y, z components from a vector."""
    x = mv.get(1, 0.0) # e coefficient
    y = mv.get(2, 0.0) # e coefficient
    z = mv.get(4, 0.0) # e coefficient
    return np.array([x, y, z])

# Example: Inner product returns scalar
a = alg_3d.multivector({1: 2.0, 2: 1.0, 4: 3.0})
b = alg_3d.multivector({1: 1.0, 2: 2.0, 4: 1.0})
dot = alg_3d.ip(a, b)

print("Extracting scalar from inner product:")
print(f"  a·b = {dot}")
print(f"  Scalar value: {extract_scalar(dot)}\n")

# Example: Extract components
print("Extracting vector components:")
print(f"  v = {v}")
components = extract_vector_components(v, alg_3d)
print(f"  [x, y, z] = {components}")

print("\n Key insight: Multivectors are dictionaries!")
```

```
print(" Use .items(), .get(), or iterate over keys/values")
```

Multivector as dictionary:

```
v = 1.0 + 2.0 + 3.0
v.items() = [(1, 1.0), (2, 2.0), (4, 3.0)]
```

Extracting scalar from inner product:

```
a.b = 7.0
Scalar value: 7.0
```

Extracting vector components:

```
v = 1.0 + 2.0 + 3.0
```

```
-----
AttributeError                                Traceback (most recent call last)
Cell In[378], line 33
    31 print("Extracting vector components:")
    32 print(f" v = {v}")
--> 33 components = extract_vector_components(v, alg_3d)
    34 print(f" [x, y, z] = {components}")
    36 print("\n Key insight: Multivectors are dictionaries!")

Cell In[378], line 16, in extract_vector_components(mv, alg)
    14 def extract_vector_components(mv, alg):
    15     """Extract x, y, z components from a vector."""
--> 16     x = mv.get(1, 0.0) # e coefficient
    17     y = mv.get(2, 0.0) # e coefficient
    18     z = mv.get(4, 0.0) # e coefficient

File ~/opt/anaconda3/envs/Elements310/lib/python3.10/site-packages/kingdon/
multivector.py:345, in MultiVector.__getattr__(self, basis_blade)
    342 def __getattr__(self, basis_blade):
    343     # TODO: if this first check is not true, raise hell instead?
    344     if not re.match(r'^e[0-9a-fA-Z]*$', basis_blade):
--> 345         raise AttributeError(f'{self.__class__.__name__} object has no
attribute or basis blade {basis_blade}')
    346     basis_blade, swaps = self.algebra._blade2canon(basis_blade)
    347     if basis_blade not in self.algebra.canon2bin:

AttributeError: MultiVector object has no attribute or basis blade get
```

2.9 8. Complete Operator Reference

2.9.1 Basic Products

Operator	Method	Description	Example
Geometric Product	<code>alg.gp(a, b)</code>	Full product (symmetric + antisymmetric)	Fundamental operation
Inner Product	<code>alg.ip(a, b)</code>	Contraction (lowers grade)	Dot product for vectors
Outer Product	<code>alg.op(a, b)</code>	Wedge (raises grade)	Cross product generalization
Scalar Product	<code>alg.sp(a, b)</code>	Extract scalar part of <code>gp(a, b)</code>	Magnitude calculations

2.9.2 Unary Operations

Operator	Method	Description	Use Case
Reverse	<code>alg.reverse(x)</code>	Reverse blade order: $e \rightarrow e$	Rotor conjugation
Conjugate	<code>alg.conjugate(x)</code>	Grade involution: grade $k \rightarrow (-1)^k$	Magnitude calculations
Involute	<code>alg.involute(x)</code>	Main involution	Alternative conjugate

2.9.3 Magnitude/Norm Operations

Operator	Method	Description	Use Case
Squared Magnitude	<code>alg.gp(x, alg.reverse(x))</code>	$x \cdot \tilde{x}$ for rotors	Normalization
Squared Magnitude	<code>alg.ip(x, x)</code>	$x \cdot x$ for vectors	Vector length squared

2.9.4 Commutator Products

Operator	Method	Description	Formula
Commutator	<code>alg.commutator(a, b)</code>	$\frac{1}{2}(ab - ba)$	Lie algebra structure
Anti-commutator	<code>alg.anticommutator(a, b)</code>	$\frac{1}{2}(ab + ba)$	Symmetric part

2.10 9. Common Patterns

2.10.1 Pattern 1: Rotor Application

```
# Rotate vector v by rotor R
v_rotated = alg.gp(R, alg.gp(v, alg.reverse(R)))
# Shorthand: v' = R v R
```

2.10.2 Pattern 2: Creating Unit Rotors

```
# Rotate by angle in bivector plane (e.g., e)
import numpy as np
theta = np.pi / 4
cos_half = np.cos(theta/2)
sin_half = np.sin(theta/2)
R = alg.multivector({0: cos_half, 3: -sin_half}) # cos(/2) - sin(/2)·e
```

2.10.3 Pattern 3: Extracting Scalars from Products

```
# Inner products return multivectors, not floats
dot_mv = alg.ip(a, b)
dot_value = list(dot_mv.items())[0][1] if len(dot_mv.items()) > 0 else 0.0
```

2.10.4 Pattern 4: Building Multivectors from NumPy

```
# Convert NumPy array to GA vector
vec_np = np.array([1.0, 2.0, 3.0])
vec_ga = alg.multivector({1: vec_np[0], 2: vec_np[1], 4: vec_np[2]})
```

2.10.5 Pattern 5: Checking Multivector Properties

```
# Check if rotor is normalized
R_norm_sq = alg.gp(R, alg.reverse(R))
is_unit = abs(extract_scalar(R_norm_sq) - 1.0) < 1e-10

# Check if vector is null (CGA)
P_squared = alg.ip(P, P)
is_null = abs(extract_scalar(P_squared)) < 1e-10
```

2.11 10. Practical Examples

2.11.1 Example 1: 2D Rotation

```
[ ]: # Example 1: 2D Rotation
print("=" * 60)
print("EXAMPLE 1: 2D Rotation")
print("=" * 60)

alg_2d = kd.Algebra(2, 0, 0)

# Create a vector pointing right
v_2d = alg_2d.multivector({1: 1.0, 2: 0.0}) # (1, 0)

# Rotate by 90 degrees counterclockwise
# R = cos(/2) - sin(/2)·e
angle = np.pi / 2
cos_half = np.cos(angle/2)
sin_half = np.sin(angle/2)
```

```

R_2d = alg_2d.multivector({0: cos_half, 3: -sin_half})

v_rotated_2d = alg_2d.gp(R_2d, alg_2d.gp(v_2d, alg_2d.reverse(R_2d)))

print(f"Original vector: {v_2d}")
print(f"Rotor (90° CCW): {R_2d}")
print(f"Rotated vector: {v_rotated_2d}")
print(f"Expected: e (pointing up) \n")

```

```

=====
EXAMPLE 1: 2D Rotation
=====

```

```

Original vector: 1.0
Rotor (90° CCW): 0.707 + -0.707
Rotated vector: 2.22e-16 + 1.0
Expected: e (pointing up)

```

```

[ ]: # Visualization: 2D Rotation
fig, (ax1, ax2) = plt.subplots(1, 2, figsize=(12, 5))

# Plot 1: Before rotation
ax1.arrow(0, 0, 1, 0, head_width=0.1, head_length=0.1, fc='blue', ec='blue',
          linewidth=2)
ax1.text(0.5, -0.3, 'v = (1, 0)', ha='center', fontsize=12, color='blue')
ax1.set_xlim(-1.5, 1.5)
ax1.set_ylim(-1.5, 1.5)
ax1.set_aspect('equal')
ax1.grid(True, alpha=0.3)
ax1.axhline(y=0, color='k', linewidth=0.5)
ax1.axvline(x=0, color='k', linewidth=0.5)
ax1.set_title('Before Rotation', fontsize=14, fontweight='bold')
ax1.set_xlabel('X', fontsize=11)
ax1.set_ylabel('Y', fontsize=11)

# Draw rotation arc
theta_arc = np.linspace(0, np.pi/2, 30)
arc_x = 0.3 * np.cos(theta_arc)
arc_y = 0.3 * np.sin(theta_arc)
ax1.plot(arc_x, arc_y, 'g--', linewidth=2, alpha=0.7, label='90° CCW')
ax1.legend(fontsize=10)

# Plot 2: After rotation
ax2.arrow(0, 0, 1, 0, head_width=0.1, head_length=0.1, fc='blue', ec='blue',
          linewidth=1, alpha=0.3, linestyle='--', label='Original')
ax2.arrow(0, 0, 0, 1, head_width=0.1, head_length=0.1, fc='red', ec='red',
          linewidth=2, label='Rotated')

```

```


ax2.text(-0.3, 0.5, "v' = (0, 1)", ha='center', fontsize=12, color='red')
ax2.set_xlim(-1.5, 1.5)
ax2.set_ylim(-1.5, 1.5)
ax2.set_aspect('equal')
ax2.grid(True, alpha=0.3)
ax2.axhline(y=0, color='k', linewidth=0.5)
ax2.axvline(x=0, color='k', linewidth=0.5)
ax2.set_title('After 90° Rotation', fontsize=14, fontweight='bold')
ax2.set_xlabel('X', fontsize=11)
ax2.set_ylabel('Y', fontsize=11)
ax2.legend(fontsize=10)

plt.suptitle('Example 1: 2D Rotation using GA Rotor', fontsize=16,
    ↪fontweight='bold')
plt.tight_layout()
plt.show()

print(" Visualization: Vector rotated 90° counterclockwise using rotor R =
    ↪cos(45°) - sin(45°)·e ")

```

Example 1: 2D Rotation using GA Rotor



Visualization: Vector rotated 90° counterclockwise using rotor $R = \cos(45^\circ) - \sin(45^\circ) \cdot e$

2.11.2 Example 2: Reflection Across a Line

```

[ ]: # Example 2: Reflection
print("=" * 60)
print("EXAMPLE 2: Reflection Across a Line")
print("=" * 60)

```

```

# Reflect vector across the x-axis
v_reflect = alg_3d.multivector({1: 1.0, 2: 2.0, 4: 0.0}) # (1, 2, 0)
n = alg_3d.multivector({2: 1.0}) # y-axis (normal to x-axis)

# Reflection formula:  $v' = -n \cdot v \cdot n$ 
# For unit vectors, no need to normalize (e already has magnitude 1)
v_reflected = -alg_3d.gp(n, alg_3d.gp(v_reflect, n))

print(f"Original vector: {v_reflect}")
print(f"Reflection axis normal: {n}")
print(f"Reflected vector: {v_reflected}")
print(f"Expected: (1, -2, 0) - y-component flipped \n")

```

=====

EXAMPLE 2: Reflection Across a Line

=====

Original vector: 1.0 + 2.0
Reflection axis normal: 1.0
Reflected vector: 1.0 + -2.0
Expected: (1, -2, 0) - y-component flipped

```

[ ]: # Visualization: Reflection
fig, (ax1, ax2, ax3) = plt.subplots(1, 3, figsize=(16, 5))

# Plot 1: Original vector
ax1.arrow(0, 0, 1, 2, head_width=0.15, head_length=0.15, fc='blue', ec='blue',
          linewidth=2)
ax1.text(0.5, 2.3, 'v = (1, 2)', ha='center', fontsize=12, color='blue',
         fontweight='bold')
ax1.axhline(y=0, color='red', linewidth=2, linestyle='--', alpha=0.7,
            label='x-axis (mirror)')
ax1.set_xlim(-2.5, 2.5)
ax1.set_ylim(-2.5, 2.5)
ax1.set_aspect('equal')
ax1.grid(True, alpha=0.3)
ax1.axvline(x=0, color='k', linewidth=0.5)
ax1.set_title('Original Vector', fontsize=14, fontweight='bold')
ax1.set_xlabel('X', fontsize=11)
ax1.set_ylabel('Y', fontsize=11)
ax1.legend(fontsize=10)

# Plot 2: Reflection process
ax2.arrow(0, 0, 1, 2, head_width=0.15, head_length=0.15, fc='blue', ec='blue',
          linewidth=2, alpha=0.5, linestyle='--', label='Original')
ax2.arrow(0, 0, 1, -2, head_width=0.15, head_length=0.15, fc='red', ec='red',

```

```


        linewidth=2, label='Reflected')
ax2.axhline(y=0, color='purple', linewidth=2, linestyle='--', alpha=0.7,
    ↪label='Mirror (x-axis)')
# Normal to mirror
ax2.arrow(0, 0, 0, 1, head_width=0.15, head_length=0.15, fc='green', ec='green',
    linewidth=1.5, alpha=0.7, label='Normal n = e ')
ax2.set_xlim(-2.5, 2.5)
ax2.set_ylim(-2.5, 2.5)
ax2.set_aspect('equal')
ax2.grid(True, alpha=0.3)
ax2.axvline(x=0, color='k', linewidth=0.5)
ax2.set_title('Reflection Process', fontsize=14, fontweight='bold')
ax2.set_xlabel('X', fontsize=11)
ax2.set_ylabel('Y', fontsize=11)
ax2.legend(fontsize=9)

# Plot 3: Result
ax3.arrow(0, 0, 1, -2, head_width=0.15, head_length=0.15, fc='red', ec='red',
    ↪linewidth=2)
ax3.text(0.5, -2.3, "v' = (1, -2)", ha='center', fontsize=12, color='red',
    ↪fontweight='bold')
ax3.axhline(y=0, color='purple', linewidth=2, linestyle='--', alpha=0.7)
ax3.set_xlim(-2.5, 2.5)
ax3.set_ylim(-2.5, 2.5)
ax3.set_aspect('equal')
ax3.grid(True, alpha=0.3)
ax3.axvline(x=0, color='k', linewidth=0.5)
ax3.set_title('Reflected Vector', fontsize=14, fontweight='bold')
ax3.set_xlabel('X', fontsize=11)
ax3.set_ylabel('Y', fontsize=11)

plt.suptitle("Example 2: Reflection using Formula v' = -nv", fontsize=16,
    ↪fontweight='bold')
plt.tight_layout()
plt.show()

print(" Visualization: Vector reflected across x-axis (y-component flipped)")

```



Visualization: Vector reflected across x-axis (y-component flipped)

2.11.3 Example 3: Composing Rotations

```
[ ]: # Example 3: Composing Rotations
print("=" * 60)
print("EXAMPLE 3: Composing Rotations")
print("=" * 60)

# First rotation: 45° in xy-plane
angle1 = np.pi / 4
cos1 = np.cos(angle1/2)
sin1 = np.sin(angle1/2)
R1 = alg_3d.multivector({0: cos1, 3: -sin1}) # cos - sin·e

# Second rotation: 45° in xz-plane
angle2 = np.pi / 4
cos2 = np.cos(angle2/2)
sin2 = np.sin(angle2/2)
R2 = alg_3d.multivector({0: cos2, 5: -sin2}) # cos - sin·e

# Combined rotation: apply R1 then R2
# Note: Apply in reverse order for sandwich product
R_combined = alg_3d.gp(R2, R1)

# Test on e
v_test = alg_3d.multivector({1: 1.0, 2: 0.0, 4: 0.0})
v_final = alg_3d.gp(R_combined, alg_3d.gp(v_test, alg_3d.reverse(R_combined)))

print(f"Rotor 1 (45° xy): {R1}")
print(f"Rotor 2 (45° xz): {R2}")
print(f"Combined rotor: {R_combined}")
print(f"Original: {v_test}")
print(f"After both rotations: {v_final}")
```

```
print(f" Rotors compose via geometric product!\n")
```

```
=====
EXAMPLE 3: Composing Rotations
=====
```

```
Rotor 1 (45° xy): 0.924 + -0.383
Rotor 2 (45° xz): 0.924 + -0.383
Combined rotor: 0.854 + -0.354    + -0.354    + 0.146
Original: 1.0
After both rotations: 0.5    + 0.707    + 0.5    + 2.78e-17
  Rotors compose via geometric product!
```

```
[ ]: # Visualization: Composing Rotations
fig = plt.figure(figsize=(18, 5))

# Extract vector components for visualization
v_orig = np.array([1.0, 0.0, 0.0])

# After first rotation (45° in xy-plane)
v_after_R1 = alg_3d.gp(R1, alg_3d.gp(v_test, alg_3d.reverse(R1)))
# Extract components using dictionary access
v1_dict = dict(v_after_R1.items())
v1_x = v1_dict.get(1, 0.0)
v1_y = v1_dict.get(2, 0.0)
v1_z = v1_dict.get(4, 0.0)
v_after_r1 = np.array([v1_x, v1_y, v1_z])

# After both rotations
v2_dict = dict(v_final.items())
v2_x = v2_dict.get(1, 0.0)
v2_y = v2_dict.get(2, 0.0)
v2_z = v2_dict.get(4, 0.0)
v_after_both = np.array([v2_x, v2_y, v2_z])

# Plot 1: First rotation (45° in xy-plane)
ax1 = fig.add_subplot(131, projection='3d')
arrow_orig = Arrow3D(0, 0, 0, *v_orig, mutation_scale=20, lw=3,
                    arrowstyle='->', color='blue', alpha=0.7)
ax1.add_artist(arrow_orig)
arrow_r1 = Arrow3D(0, 0, 0, *v_after_r1, mutation_scale=20, lw=3,
                 arrowstyle='->', color='orange', alpha=0.9)
ax1.add_artist(arrow_r1)

# Draw rotation arc in xy-plane
theta = np.linspace(0, np.pi/4, 20)
arc_x = np.cos(theta)
```

```

arc_y = np.sin(theta)
arc_z = np.zeros_like(theta)
ax1.plot(arc_x, arc_y, arc_z, 'g--', linewidth=2, alpha=0.6)

# Draw xy-plane
xx, yy = np.meshgrid(np.linspace(-1, 1, 10), np.linspace(-1, 1, 10))
zz = np.zeros_like(xx)
ax1.plot_surface(xx, yy, zz, alpha=0.1, color='cyan')

setup_3d_axis(ax1, 'Step 1: Rotate 45° in xy-plane\n(bivector e )')
ax1.view_init(elev=20, azim=45)

# Plot 2: Second rotation (45° in xz-plane)
ax2 = fig.add_subplot(132, projection='3d')
arrow_r1_2 = Arrow3D(0, 0, 0, *v_after_r1, mutation_scale=20, lw=3,
                    arrowstyle='->', color='orange', alpha=0.5,
                    linestyle='--')
ax2.add_artist(arrow_r1_2)
arrow_both = Arrow3D(0, 0, 0, *v_after_both, mutation_scale=20, lw=3,
                    arrowstyle='->', color='red', alpha=1.0)
ax2.add_artist(arrow_both)

# Draw xz-plane
xx, zz = np.meshgrid(np.linspace(-1, 1, 10), np.linspace(-1, 1, 10))
yy = np.zeros_like(xx)
ax2.plot_surface(xx, yy, zz, alpha=0.1, color='yellow')

setup_3d_axis(ax2, 'Step 2: Rotate 45° in xz-plane\n(bivector e )')
ax2.view_init(elev=20, azim=45)

# Plot 3: Combined result
ax3 = fig.add_subplot(133, projection='3d')
arrow_orig3 = Arrow3D(0, 0, 0, *v_orig, mutation_scale=20, lw=2,
                    arrowstyle='->', color='blue', alpha=0.3)
ax3.add_artist(arrow_orig3)
arrow_final = Arrow3D(0, 0, 0, *v_after_both, mutation_scale=20, lw=4,
                    arrowstyle='->', color='red', alpha=1.0)
ax3.add_artist(arrow_final)

# Draw path
path = np.array([v_orig, v_after_r1, v_after_both])
ax3.plot(path[:, 0], path[:, 1], path[:, 2], 'k--', linewidth=2, alpha=0.4)

# Mark points
ax3.scatter(*v_orig, s=100, c='blue', alpha=0.3)
ax3.scatter(*v_after_r1, s=100, c='orange', alpha=0.5)
ax3.scatter(*v_after_both, s=150, c='red', alpha=1.0)

```


```

setup_3d_axis(ax3, 'Combined Result\nR_combined = R * R ')
ax3.view_init(elev=25, azim=50)

plt.suptitle('Example 3: Composing Two 45° Rotations via Geometric Product',
             fontsize=16, fontweight='bold')
plt.tight_layout()
plt.show()

print(f" Visualization: Composed rotation path")
print(f" Original: {v_orig}")
print(f" After R1 (xy): {v_after_r1}")
print(f" After R2·R1 (combined): {v_after_both}")

```



```

Visualization: Composed rotation path
Original: [1. 0. 0.]
After R1 (xy): [0.7071 0.7071 0.   ]
After R2·R1 (combined): [0.5    0.7071 0.5   ]

```

Example 4: Translation and Rotation of a Line

```

[ ]: # Example 4: Translation and Rotation of a Line in 3D
# We'll represent a line with a point and direction vector, then transform it

# Define a line through origin along x-axis
line_pt_orig = alg_3d.multivector({1: 0.0, 2: 0.0, 4: 0.0}) # Point (0,0,0)
line_dir_orig = alg_3d.multivector({1: 1.0, 2: 0.0, 4: 0.0}) # Direction ↪ (1,0,0)

# Step 1: Translate the line's point by (2, 1, 0)
translation_vec_ex4 = np.array([2.0, 1.0, 0.0])
line_pt_trans = alg_3d.multivector({
    1: 0.0 + translation_vec_ex4[0],
    2: 0.0 + translation_vec_ex4[1],
    4: 0.0 + translation_vec_ex4[2]

```

```

})

# Step 2: Rotate the line by 60° around z-axis
# Create rotor for 60° rotation around z-axis (e e plane)
angle_line = np.pi/3 # 60 degrees
cos_line = np.cos(angle_line/2)
sin_line = np.sin(angle_line/2)
R_line = alg_3d.multivector({0: cos_line, 3: -sin_line}) # e = basis[3]
R_line_rev = alg_3d.reverse(R_line)

# Rotate both the point and direction vector
line_pt_final = alg_3d.gp(R_line, alg_3d.gp(line_pt_trans, R_line_rev))
line_dir_final = alg_3d.gp(R_line, alg_3d.gp(line_dir_orig, R_line_rev))

print("=== Line Translation and Rotation ===")
print(f"Original point: {line_pt_orig}")
print(f"Original direction: {line_dir_orig}")
print(f"\nAfter translation by {translation_vec_ex4}:")
print(f"Point: {line_pt_trans}")
print(f"Direction: {line_dir_orig} (unchanged)")
print(f"\nAfter 60° rotation around z-axis:")
print(f"Final point: {line_pt_final}")
print(f"Final direction: {line_dir_final}")

# Extract coordinates for visualization
orig_pt = dict(line_pt_orig.items())
trans_pt = dict(line_pt_trans.items())
final_pt = dict(line_pt_final.items())
orig_dir = dict(line_dir_orig.items())
final_dir = dict(line_dir_final.items())

orig_pt_arr = np.array([orig_pt.get(1, 0.0), orig_pt.get(2, 0.0), orig_pt.
    ↪get(4, 0.0)])
trans_pt_arr = np.array([trans_pt.get(1, 0.0), trans_pt.get(2, 0.0), trans_pt.
    ↪get(4, 0.0)])
final_pt_arr = np.array([final_pt.get(1, 0.0), final_pt.get(2, 0.0), final_pt.
    ↪get(4, 0.0)])
orig_dir_arr = np.array([orig_dir.get(1, 0.0), orig_dir.get(2, 0.0), orig_dir.
    ↪get(4, 0.0)])
final_dir_arr = np.array([final_dir.get(1, 0.0), final_dir.get(2, 0.0),
    ↪final_dir.get(4, 0.0)])

print(f"\nVisualization coordinates:")
print(f"Original line: point {orig_pt_arr}, direction {orig_dir_arr}")
print(f"Translated: point {trans_pt_arr}, direction {orig_dir_arr}")
print(f"Final: point {final_pt_arr}, direction {final_dir_arr}")

```

=== Line Translation and Rotation ===

Original point:

Original direction: 1.0

After translation by [2. 1. 0.]:

Point: 2.0 + 1.0

Direction: 1.0 (unchanged)

After 60° rotation around z-axis:

Final point: 0.134 + 2.23

Final direction: 0.5 + 0.866

Visualization coordinates:

Original line: point [0. 0. 0.], direction [1. 0. 0.]

Translated: point [2. 1. 0.], direction [1. 0. 0.]

Final: point [0.134 2.2321 0.], direction [0.5 0.866 0.]

```
[ ]: # Visualization: Line Translation and Rotation
fig = plt.figure(figsize=(18, 5))

# Helper function to draw a line segment
def draw_line_segment(ax, point, direction, color, label, length=3.0,
    linewidth=2):
    """Draw a line segment from point-length*dir to point+length*dir"""
    start = point - length * direction
    end = point + length * direction
    ax.plot([start[0], end[0]], [start[1], end[1]], [start[2], end[2]],
            color=color, linewidth=linewidth, label=label, alpha=0.8)
    # Draw point marker
    ax.scatter(*point, color=color, s=100, marker='o', zorder=5)
    # Draw direction arrow
    ax.quiver(point[0], point[1], point[2],
              direction[0], direction[1], direction[2],
              color=color, arrow_length_ratio=0.2, linewidth=2, alpha=0.9)

# Panel 1: Original line (through origin, along x-axis)
ax1 = fig.add_subplot(131, projection='3d')
draw_line_segment(ax1, orig_pt_arr, orig_dir_arr, 'blue', 'Original Line')
ax1.set_xlim(-1, 4)
ax1.set_ylim(-1, 3)
ax1.set_zlim(-1, 2)
ax1.set_xlabel('X', fontsize=11)
ax1.set_ylabel('Y', fontsize=11)
ax1.set_zlabel('Z', fontsize=11)
ax1.set_title('Step 1: Original Line\n(through origin, direction = x-axis)',
              fontsize=12, fontweight='bold')
ax1.legend(fontsize=10)
```

```

ax1.view_init(elev=20, azim=45)

# Panel 2: After translation
ax2 = fig.add_subplot(132, projection='3d')
draw_line_segment(ax2, orig_pt_arr, orig_dir_arr, 'blue', 'Original', length=2.
    ↪0, linewidth=1.5)
draw_line_segment(ax2, trans_pt_arr, orig_dir_arr, 'orange', 'After_
    ↪Translation')
# Draw translation arrow
ax2.quiver(orig_pt_arr[0], orig_pt_arr[1], orig_pt_arr[2],
    translation_vec_ex4[0], translation_vec_ex4[1],
    ↪translation_vec_ex4[2],
    color='green', arrow_length_ratio=0.15, linewidth=2.5, alpha=0.7,
    label=f'Translation {translation_vec_ex4}')
ax2.set_xlim(-1, 4)
ax2.set_ylim(-1, 3)
ax2.set_zlim(-1, 2)
ax2.set_xlabel('X', fontsize=11)
ax2.set_ylabel('Y', fontsize=11)
ax2.set_zlabel('Z', fontsize=11)
ax2.set_title('Step 2: Translation by (2, 1, 0)\n(point moves, direction_
    ↪unchanged)',
    fontsize=12, fontweight='bold')
ax2.legend(fontsize=9, loc='upper left')
ax2.view_init(elev=20, azim=45)

# Panel 3: After translation and rotation
ax3 = fig.add_subplot(133, projection='3d')
draw_line_segment(ax3, trans_pt_arr, orig_dir_arr, 'orange', 'Before Rotation',
    length=2.0, linewidth=1.5)
draw_line_segment(ax3, final_pt_arr, final_dir_arr, 'red', 'After 60° Rotation')
# Draw rotation arc around z-axis
theta_rot_arc = np.linspace(0, np.pi/3, 30)
arc_radius = 1.5
arc_x_rot = trans_pt_arr[0] + arc_radius * np.cos(theta_rot_arc)
arc_y_rot = trans_pt_arr[1] + arc_radius * np.sin(theta_rot_arc)
arc_z_rot = np.full_like(theta_rot_arc, trans_pt_arr[2])
ax3.plot(arc_x_rot, arc_y_rot, arc_z_rot, 'g--', linewidth=2, alpha=0.7,
    ↪label='60° rotation')
# Draw z-axis reference
ax3.quiver(trans_pt_arr[0], trans_pt_arr[1], 0, 0, 0, 1.5,
    color='purple', arrow_length_ratio=0.2, linewidth=2, alpha=0.5,
    ↪label='z-axis')
ax3.set_xlim(-1, 4)
ax3.set_ylim(-1, 3)
ax3.set_zlim(-1, 2)

```


```

ax3.set_xlabel('X', fontsize=11)
ax3.set_ylabel('Y', fontsize=11)
ax3.set_zlabel('Z', fontsize=11)
ax3.set_title('Step 3: Rotate 60° around z-axis\n(both point and direction_
↪rotate)',
              fontsize=12, fontweight='bold')
ax3.legend(fontsize=9, loc='upper left')
ax3.view_init(elev=20, azimuth=45)

plt.tight_layout()
plt.show()

print("\n Line transformation complete: translated then rotated in 3D space")

```



Line transformation complete: translated then rotated in 3D space

2.12 11. Tips and Best Practices

2.12.1 Do's

1. **Always use explicit methods:** `alg.gp(a, b)` not `a * b`
2. **Normalize bivectors before exp:** Ensures unit rotors
3. **Use helper functions:** Create utilities for common operations (scalar extraction, etc.)
4. **Check basis blade indices:** Use `alg.graph` to see the mapping
5. **Verify rotor properties:** Check $R \cdot R = 1$ for unit rotors

2.12.2 Don'ts

1. **Don't use `*` for geometric product:** Reserved for scalar multiplication
2. **Don't forget reverse in sandwich:** $v' = R v R$ (not $R v R$)
3. **Don't assume inner product returns float:** It's a multivector!
4. **Don't mix algebras:** Each algebra creates distinct types
5. **Don't ignore grade:** Track what grade your result should be

2.12.3 Debugging Tips

```
# Print multivector structure
print(f"Keys: {list(mv.keys())}")
print(f"Values: {list(mv.values())}")

# Check grade composition
for idx, coef in mv.items():
    print(f"Blade {alg.graph[idx]}: {coef}")

# Verify properties
print(f"Magnitude: {alg.magnitude(mv)}")
print(f"Squared: {alg.gp(mv, mv)}")
```

2.12.4 Performance Notes

- Kingdom generates optimized code at algebra creation
- Multivectors with fewer components are faster
- Grade projection is dictionary filtering (very fast)
- No symbolic overhead - pure numerical computation

2.13 12. Quick Reference Card

```
# === SETUP ===
import kingdom as kd
import numpy as np
alg = kd.Algebra(3, 0, 0)  # GA(3,0,0): 3D Euclidean space
                          # Arguments: (positive, negative, zero) signature

# === CREATION (THE EASY WAY!) ===
# RECOMMENDED: Use alg.blades dictionary - no index memorization!

e1, e2, e3 = alg.blades['e1'], alg.blades['e2'], alg.blades['e3']
e12, e13, e23 = alg.blades['e12'], alg.blades['e13'], alg.blades['e23']
e123 = alg.blades['e123']

# Vector (1, 2, 3)
v = 1.0*e1 + 2.0*e2 + 3.0*e3

# Bivector (xy-plane)
B = e12

# Rotor (45° rotation in xy-plane)
theta = np.pi/4
R = np.cos(theta/2) - np.sin(theta/2)*e12

# Mixed-grade multivector
mixed = 2.0 + 3.0*e1 + 1.5*e12  # scalar + vector + bivector
```

```

# === CREATION (INDEX METHOD - for reference) ===
# Multivectors use dictionaries: {basis_index: coefficient}
# Indices: 0=scalar, 1=e, 2=e, 4=e, 3=e, 5=e, 6=e, 7=e
# Note: e is index 4 (not 3) due to binary encoding!

v_alt = alg.multivector({1: 1.0, 2: 2.0, 4: 3.0}) # Vector (1,2,3)
B_alt = alg.multivector({3: 1.0}) # Bivector e
R_alt = alg.multivector({0: np.cos(theta/2), 3: -np.sin(theta/2)}) # Rotor

# === PRODUCTS ===
ab = alg.gp(a, b) # Geometric Product: a*b (combines dot and wedge)
dot = alg.ip(a, b) # Inner Product: a·b (contraction, lowers grade)
wedge = alg.op(a, b) # Outer Product: a b (expansion, raises grade)

# === OPERATIONS ===
a_rev = alg.reverse(a) # Reverse:  $\tilde{a}$  (reverses order of basis vectors)
a_conj = alg.conjugate(a) # Conjugate:  $\bar{a}$  (negates odd-grade parts)
a_dual = alg.gp(a, I) # Dual:  $a \cdot I$  (multiplies by pseudoscalar)

# === MAGNITUDE ===
mag_sq = alg.ip(v, v) # Vector magnitude2:  $v \cdot v$ 
rotor_sq = alg.gp(R, alg.reverse(R)) # Rotor norm:  $R \cdot R$  (should = 1)

# === TRANSFORMATIONS ===
v_rot = alg.gp(R, alg.gp(v, alg.reverse(R))) # Rotation:  $R \cdot v \cdot R$ 
v_ref = -alg.gp(n, alg.gp(v, n)) # Reflection:  $-n \cdot v \cdot n$ 

# === COEFFICIENT EXTRACTION ===
# Method 1: Convert to dict first (RECOMMENDED for Kingdom)
mv_dict = dict(mv.items())
scalar_val = mv_dict.get(0, 0.0) # Get scalar (key 0)
x = mv_dict.get(1, 0.0) # Get e coefficient (key 1)
y = mv_dict.get(2, 0.0) # Get e coefficient (key 2)
z = mv_dict.get(4, 0.0) # Get e coefficient (key 4)

# Method 2: Extract multiple components
components = [mv_dict.get(i, 0.0) for i in [1, 2, 4]] # [x, y, z]

# === UTILITIES ===
# Check what basis blades exist in multivector
for idx, coef in mv.items():
    basis_blade = alg.graph[idx] # Get basis blade name
    print(f"Basis blade {basis_blade} (index {idx}): coefficient = {coef}")

# Compute magnitude for vectors
mag = np.sqrt(alg.ip(v, v)) # For vectors:  $\sqrt{v \cdot v}$ 

```

2.13.1 Basis Blade Index Reference for GA(3,0,0)

Understanding the indices: Each basis blade has a unique integer index. The index encodes which basis vectors are wedged together.

Grade 0 (Scalar):

Index 0 → 1 (scalar, no basis vectors)

Grade 1 (Vectors):

Index 1 → e (x-axis basis vector)

Index 2 → e (y-axis basis vector)

Index 4 → e (z-axis basis vector)

Grade 2 (Bivectors - oriented planes):

Index 3 → e e = e e (xy-plane, oriented area)

Index 5 → e e = e e (xz-plane, oriented area)

Index 6 → e e = e e (yz-plane, oriented area)

Grade 3 (Trivector/Pseudoscalar - oriented volume):

Index 7 → e e e = e e e (oriented volume element)

Key Pattern: The indices follow a binary pattern where each bit represents a basis vector: bit 0 → e, bit 1 → e, bit 2 → e - e = 2 = 1 - e = 2¹ = 2
- e = 2² = 4 - e = 1+2 = 3 - e = 1+4 = 5 - e = 2+4 = 6 - e = 1+2+4 = 7

Usage Example:

```
# Create vector v = 3*e + 4*e + 0*e = (3, 4, 0)
v = alg.multivector({
    1: 3.0, # 3 times e (x-component)
    2: 4.0 # 4 times e (y-component)
    # Note: we omit key 4 (e) since coefficient is 0
})
```

2.14 15. Final Thoughts: Why GA for Computer Scientists?

2.14.1 The Elegance Argument

Traditional computer graphics uses a **patchwork** of techniques: - Vectors for positions - Matrices for linear transformations

- Quaternions for rotations (to avoid gimbal lock) - Special cases for planes, spheres - Different code paths for each

Geometric Algebra provides unification: - One algebra for everything - One formula: $X' = M * X * M$ - Objects (points, lines, planes, spheres) are all multivectors - Transformations (rotation, translation, dilation) are all motors

2.14.2 The Simplicity Argument

Compare the code:

Traditional:

```
# Different operations for different objects
rotated_vector = rotation_matrix @ vector
rotated_point = rotation_matrix @ point + translation
# Planes? Need special plane-matrix multiplication
# Spheres? Even more special case code
```

Geometric Algebra:

```
# One operation for ALL objects
transformed_object = motor * object * ~motor
# Works for vectors, points, lines, planes, spheres!
```

2.14.3 The Generality Argument

GA scales naturally: - **2D**: GA2 (vectors + bivector) - **3D**: GA3 (vectors + bivectors + trivector)
 - **4D Spacetime**: STA (special relativity!) - **5D Conformal**: CGA (add translations!) - **Higher dimensions**: Just add more basis vectors

Traditional methods? Each dimension needs new techniques.

2.14.4 Performance Note

Myth: “GA is slow because it uses general multivectors”

Reality: Libraries like Kingdom generate **specialized, optimized code** for each algebra - As fast as hand-written matrix/quaternion code - Sometimes faster due to better cache locality - SIMD vectorization friendly

2.14.5 Call to Action

If you’re building: - Game engines - Robotics software - CAD/CAM systems - Physics simulations
 - VR/AR applications

Consider Geometric Algebra!

You’ll write less code, with clearer meaning, and greater generality.

“The introduction of numbers as coordinates is an act of violence.” — Hermann Weyl

GA respects the geometry.

2.15 16. Further Reading & Resources

2.15.1 Books

1. **“Geometric Algebra for Computer Science”** by Dorst, Fontijne, Mann
 - The definitive textbook for CS applications
 - Covers 2D, 3D, and conformal models
2. **“Geometric Algebra for Physicists”** by Doran & Lasenby
 - Excellent for understanding the physics connections
 - Spacetime algebra and general relativity
3. **“New Foundations for Classical Mechanics”** by David Hestenes
 - The book that revived GA

- Rigorous mathematical foundations

2.15.2 Online Resources

- **bivector.net** - Interactive GA tutorials and visualizations
- **geometricalgebra.org** - Community resources
- **Kingdon documentation** - <https://kingdon.readthedocs.io/>

2.15.3 Software Libraries

- **Kingdon** (Python) - This notebook! Fast code generation
- **Clifford** (Python) - Numerical GA with symbolic capabilities
- **ganja.js** (JavaScript) - Browser-based GA with visualization
- **GATL** (C++) - Template library for high-performance GA

2.15.4 Papers

- Dorst et al., “Geometric Algebra for Computer Graphics” (2002)
- Hestenes, “Oersted Medal Lecture: Reforming the Mathematical Language of Physics” (2003)

2.15.5 Community

- r/GeometricAlgebra on Reddit
- Discord servers for GA enthusiasts
- Annual AGACSE conferences

Thank you for exploring Geometric Algebra!

May your vectors be orthonormal and your bivectors be simple.