

DEV_IMPL_GUIDE - DD: ILM-CFG-02 — Tech Region Registry

1. Purpose

This guide explains how to implement DD_ILM-CFG-02-Tech_Region_Registry-v1.0.md as executable SOPHIX behavior.

Use it with:

- DD_ILM-CFG-02-Tech_Region_Registry-v1.0.md
- DD_SUB-WF-FRAMEWORK-01-Subscription_Workflow_Framework-v1.0.md when this DD participates in subscription workflow operations.
- DD_SUB-WF-FRAMEWORK-01-WORKERS-v1.0.md when this DD references worker topics.

2. Runtime Actors

Runtime component	Responsibility
API pod / module service	Receives requests, validates, loads authoritative state, starts commands.
Owning module database	Stores tables/configuration owned by this DD.
Reference modules	Provide data through approved APIs/client wrappers.
Camunda	Runs BPMN process when this DD is workflow-driven.
Worker apps	Execute logical worker topics.
Drools	Evaluates packages when rules are declared.
Kafka/outbox	Publishes success/failure and integration events.

3. Before Implementation

Confirm these contracts from the DD:

Contract	Value
Endpoint scan reference	DELETE /api/tech-regions/{tech_region_id}/candidate-group-map/{taskType}
BPMN/process key	configured BPMN process
Drools package	configured Drools package
Tables	tech_region, tech_region_boundary, tech_region_candidate_group_map
Events	No explicit events declared

4. Execution Flow

1. Apply migrations and seed configuration/catalog rows.
2. Implement the module service/repository layer around the tables and invariants.
3. Implement public/internal APIs from the DD.
4. Implement rule evaluation if the DD defines Drools packages.
5. Implement event production/consumption through outbox where the DD defines events.
6. Add integration tests for table constraints, API validation, and event payloads.

5. API And Command Handling

Endpoints found in the DD:

- DELETE /api/tech-regions/{tech_region_id}/candidate-group-map/{taskType}

- GET /api/tech-regions/KE-NRB-LAVINGTON
- GET /api/tech-regions/{id}
- GET /api/tech-regions/{id}/candidate-group?taskType=X
- GET /api/tech-regions/{tech_region_id}
- GET /api/tech-regions/{tech_region_id}/candidate-group-map
- GET /api/tech-regions/{tech_region_id}/candidate-group?taskType=INSTALL
- GET /api/tech-regions?operatorCode=WIK&active=true
- GET /api/tech-regions?operatorCode=X
- PATCH /api/tech-regions/{tech_region_id}
- POST /api/em/contractor-availability
- POST /api/staff-notifications
- POST /api/tech-regions
- POST /api/tech-regions/check-footprint
- POST /api/tech-regions/resolve
- POST /api/work-orders/install
- PUT /api/tech-regions/{tech_region_id}/boundary
- PUT /api/tech-regions/{tech_region_id}/candidate-group-map/{taskType}

Implementation rules:

- Resolve actor user and role from auth context, not from public request body.
- Check idempotency before inserting a new operation or creating a side effect.
- Return the existing operation/result for the same idempotency key and same request hash.
- Return 409 IDEMPOTENCY_KEY_REUSED for the same key with a different request hash.
- Use transactions or unique constraints for concurrency-sensitive creation.

6. Data Loading

Load data in this order:

1. Authoritative aggregate state from the owning module.
2. Operator/module config from this DD's config tables.
3. Catalog/reference data from approved APIs or client wrappers.
4. Current in-flight operation state from the framework, where relevant.

Do not read current mutable state from cache for state-changing operations.

7. Drools Configuration

Packages found:

- No Drools package explicitly declared.

For each package:

- Define fact classes that mirror the request, current state, config, and reference data.
- Keep rule output as explicit decision fields.
- Unit-test accept and reject cases from the DD.
- BPMN should re-check critical rules after start if state may have changed.

8. BPMN And Worker Topics

Worker topics found:

- assign-contractor
- fiber-install
- ftth-cpe
- google-maps
- kenya-kyc-leaders
- kenya-l1-kyc
- vip-handling

Implementation rules:

- Model service tasks with `camunda:type="external"` and the exact topic string.
- Worker handler must validate required variables before calling downstream services.
- Store outputs as process variables with stable names.
- Use message correlation keys exactly as specified by the DD.
- Add compensation paths for each external side effect.

9. Events

Events found:

- No event explicitly declared.

Event rules:

- Emit success only after authoritative commit.
- Emit rejected/failure event only after compensation/final failure decision.
- Use the outbox table/dispatcher; do not publish directly inside the transaction boundary unless the platform standard allows it.

10. Smoke Tests

Add tests for:

- Happy path.
- Invalid role or trigger.
- Invalid state.
- Missing config/catalog row.
- Dependency failure.
- Retry/idempotency.
- Event payload correctness.
- Worker topic failure and compensation.

11. Common Mistakes

- Treating worker-topic names as shell commands.
- Querying another module's database directly.
- Reading current state from cache in a state-changing flow.
- Emitting success before final commit.
- Hiding manual recovery paths for partial external side effects.
- Creating one deployment per topic when a consolidated worker app would be easier to operate.