

underscore.js

J. Ashkenas

05-04-2013

# Contents

Baseline setup . . . . .	2
Collection Functions . . . . .	3
Array Functions . . . . .	9
Function (ahem) Functions . . . . .	14
Object Functions . . . . .	17
Utility Functions . . . . .	23
OOP . . . . .	27

```
Underscore.js 1.4.4
http://underscorejs.org
(c) 2009-2013 Jeremy Ashkenas, DocumentCloud Inc.
Underscore may be freely distributed under the MIT license.
```

```
(function() {
```

## Baseline setup

Establish the root object, window in the browser, or global on the server.

```
var root = this;
```

Save the previous value of the `_` variable.

```
var previousUnderscore = root._;
```

Establish the object that gets returned to break out of a loop iteration.

```
var breaker = {};
```

Save bytes in the minified (but not gzipped) version:

```
var ArrayProto = Array.prototype, ObjProto = Object.prototype,
    FuncProto = Function.prototype;
```

Create quick reference variables for speed access to core prototypes.

```
var push      = ArrayProto.push,
    slice     = ArrayProto.slice,
    concat    = ArrayProto.concat,
    toString  = ObjProto.toString,
    hasOwnProperty = ObjProto.hasOwnProperty;
```

All **ECMAScript 5** native function implementations that we hope to use are declared here.

```
var
  nativeForEach    = ArrayProto.forEach,
  nativeMap        = ArrayProto.map,
  nativeReduce     = ArrayProto.reduce,
  nativeReduceRight = ArrayProto.reduceRight,
  nativeFilter     = ArrayProto.filter,
  nativeEvery      = ArrayProto.every,
  nativeSome       = ArrayProto.some,
  nativeIndexOf    = ArrayProto.indexOf,
  nativeLastIndexOf = ArrayProto.lastIndexOf,
  nativeIsArray    = Array.isArray,
  nativeKeys       = Object.keys,
  nativeBind       = FuncProto.bind;
```

Create a safe reference to the Underscore object for use below.

```

var _ = function(obj) {
  if (obj instanceof _) return obj;
  if (!(this instanceof _)) return new _(obj);
  this._wrapped = obj;
};

```

Export the Underscore object for **Node.js**, with backwards-compatibility for the old `require()` API. If we're in the browser, add `_` as a global object via a string identifier, for Closure Compiler "advanced" mode.

```

if (typeof exports !== 'undefined') {
  if (typeof module !== 'undefined' && module.exports) {
    exports = module.exports = _;
  }
  exports._ = _;
} else {
  root._ = _;
}

```

Current version.

```

_.VERSION = '1.4.4';

```

## Collection Functions

The cornerstone, an `each` implementation, aka `forEach`. Handles objects with the built-in `forEach`, arrays, and raw objects. Delegates to **ECMAScript 5**'s native `forEach` if available.

```

var each = _.each = _.forEach = function(obj, iterator, context) {
  if (obj == null) return;
  if (nativeForEach && obj.forEach === nativeForEach) {
    obj.forEach(iterator, context);
  } else if (obj.length === +obj.length) {
    for (var i = 0, l = obj.length; i < l; i++) {
      if (iterator.call(context, obj[i], i, obj) === breaker) return;
    }
  } else {
    for (var key in obj) {
      if (_.has(obj, key)) {
        if (iterator.call(context, obj[key], key, obj) === breaker) return;
      }
    }
  }
};

```

Return the results of applying the iterator to each element. Delegates to **ECMAScript 5**'s native `map` if available.

```

_.map = _.collect = function(obj, iterator, context) {
  var results = [];
  if (obj == null) return results;
  if (nativeMap && obj.map === nativeMap) return
    ( obj.map(iterator, context);
  each(obj, function(value, index, list) {
    results.push(iterator.call(context, value, index, list));
  });
  return results;
};

var reduceError = 'Reduce of empty array with no initial value';

```

**Reduce** builds up a single result from a list of values, aka inject, or foldl. Delegates to **ECMAScript 5**'s native reduce if available.

```

_.reduce = _.foldl = _.inject = function(obj, iterator, memo,
  ( context) {
  var initial = arguments.length > 2;
  if (obj == null) obj = [];
  if (nativeReduce && obj.reduce === nativeReduce) {
    if (context) iterator = _.bind(iterator, context);
    return initial ? obj.reduce(iterator, memo) :
      ( obj.reduce(iterator);
  }
  each(obj, function(value, index, list) {
    if (!initial) {
      memo = value;
      initial = true;
    } else {
      memo = iterator.call(context, memo, value, index, list);
    }
  });
  if (!initial) throw new TypeError(reduceError);
  return memo;
};

```

The right-associative version of reduce, also known as foldr. Delegates to **ECMAScript 5**'s native reduceRight if available.

```

_.reduceRight = _.foldr = function(obj, iterator, memo,
  ( context) {
  var initial = arguments.length > 2;
  if (obj == null) obj = [];
  if (nativeReduceRight && obj.reduceRight ===
    ( nativeReduceRight) {
    if (context) iterator = _.bind(iterator, context);
    return initial ? obj.reduceRight(iterator, memo) :
      ( obj.reduceRight(iterator);
  }
  var length = obj.length;
  if (length !== +length) {
    var keys = _.keys(obj);
    length = keys.length;
  }
  each(obj, function(value, index, list) {
    index = keys ? keys[--length] : --length;

```

```

    if (!initial) {
        memo = obj[index];
        initial = true;
    } else {
        memo = iterator.call(context, memo, obj[index], index, 2
            list);
    }
});
if (!initial) throw new TypeError(reduceError);
return memo;
};

```

Return the first value which passes a truth test. Aliased as `detect`.

```

_.find = _.detect = function(obj, iterator, context) {
    var result;
    any(obj, function(value, index, list) {
        if (iterator.call(context, value, index, list)) {
            result = value;
            return true;
        }
    });
    return result;
};

```

Return all the elements that pass a truth test. Delegates to **ECMAScript 5's** native `filter` if available. Aliased as `select`.

```

_.filter = _.select = function(obj, iterator, context) {
    var results = [];
    if (obj == null) return results;
    if (nativeFilter && obj.filter === nativeFilter) return 2
        obj.filter(iterator, context);
    each(obj, function(value, index, list) {
        if (iterator.call(context, value, index, list)) 2
            results.push(value);
    });
    return results;
};

```

Return all the elements for which a truth test fails.

```

_.reject = function(obj, iterator, context) {
    return _.filter(obj, function(value, index, list) {
        return !iterator.call(context, value, index, list);
    }, context);
};

```

Determine whether all of the elements match a truth test. Delegates to **ECMAScript 5's** native `every` if available. Aliased as `all`.

```

_.every = _.all = function(obj, iterator, context) {
    iterator || (iterator = _.identity);
    var result = true;
    if (obj == null) return result;
    if (nativeEvery && obj.every === nativeEvery) return 2
        obj.every(iterator, context);

```

```

    each(obj, function(value, index, list) {
        if (!(result = result && iterator.call(context, value, )
            ( index, list))) return breaker;
    });
    return !!result;
};

```

Determine if at least one element in the object matches a truth test. Delegates to **ECMAScript 5's** native `some` if available. Aliased as `any`.

```

var any = _.some = _.any = function(obj, iterator, context) {
    iterator || (iterator = _.identity);
    var result = false;
    if (obj == null) return result;
    if (nativeSome && obj.some === nativeSome) return obj.some(iterator, context);
    each(obj, function(value, index, list) {
        if (result || (result = iterator.call(context, value, )
            ( index, list))) return breaker;
    });
    return !!result;
};

```

Determine if the array or object contains a given value (using `===`). Aliased as `include`.

```

_.contains = _.include = function(obj, target) {
    if (obj == null) return false;
    if (nativeIndexOf && obj.indexOf === nativeIndexOf) return obj.indexOf(target) != -1;
    return any(obj, function(value) {
        return value === target;
    });
};

```

Invoke a method (with arguments) on every item in a collection.

```

_.invoke = function(obj, method) {
    var args = slice.call(arguments, 2);
    var isFunc = _.isFunction(method);
    return _.map(obj, function(value) {
        return (isFunc ? method : value[method]).apply(value, args);
    });
};

```

Convenience version of a common use case of `map`: fetching a property.

```

_.pluck = function(obj, key) {
    return _.map(obj, function(value){ return value[key]; });
};

```

Convenience version of a common use case of `filter`: selecting only objects containing specific `key:value` pairs.

```

_.where = function(obj, attrs, first) {
    if (_.isEmpty(attrs)) return first ? void 0 : [];

```

```

    return _[first ? 'find' : 'filter'](obj, function(value) {
        for (var key in attrs) {
            if (attrs[key] !== value[key]) return false;
        }
        return true;
    });
};

```

Convenience version of a common use case of find: getting the first object containing specific key:value pairs.

```

_.findWhere = function(obj, attrs) {
    return _.where(obj, attrs, true);
};

```

Return the maximum element or (element-based computation). Can't optimize arrays of integers longer than 65,535 elements. See WebKit Bug 80797<sup>1</sup>

```

_.max = function(obj, iterator, context) {
    if (!iterator && _.isArray(obj) && obj[0] === +obj[0] && 2
        & obj.length < 65535) {
        return Math.max.apply(Math, obj);
    }
    if (!iterator && _.isEmpty(obj)) return -Infinity;
    var result = {computed : -Infinity, value: -Infinity};
    each(obj, function(value, index, list) {
        var computed = iterator ? iterator.call(context, value, 2
            & index, list) : value;
        computed >= result.computed && (result = {value : value, 2
            & computed : computed});
    });
    return result.value;
};

```

Return the minimum element (or element-based computation).

```

_.min = function(obj, iterator, context) {
    if (!iterator && _.isArray(obj) && obj[0] === +obj[0] && 2
        & obj.length < 65535) {
        return Math.min.apply(Math, obj);
    }
    if (!iterator && _.isEmpty(obj)) return Infinity;
    var result = {computed : Infinity, value: Infinity};
    each(obj, function(value, index, list) {
        var computed = iterator ? iterator.call(context, value, 2
            & index, list) : value;
        computed < result.computed && (result = {value : value, 2
            & computed : computed});
    });
    return result.value;
};

```

Shuffle an array.

---

<sup>1</sup>[https://bugs.webkit.org/show\\_bug.cgi?id=80797](https://bugs.webkit.org/show_bug.cgi?id=80797)



```

_.shuffle = function(obj) {
  var rand;
  var index = 0;
  var shuffled = [];
  each(obj, function(value) {
    rand = _.random(index++);
    shuffled[index - 1] = shuffled[rand];
    shuffled[rand] = value;
  });
  return shuffled;
};

```

An internal function to generate lookup iterators.

```

var lookupIterator = function(value) {
  return _.isFunction(value) ? value : function(obj){ return
    & obj[value]; };
};

```

Sort the object's values by a criterion produced by an iterator.

```

_.sortBy = function(obj, value, context) {
  var iterator = lookupIterator(value);
  return _.pluck(_.map(obj, function(value, index, list) {
    return {
      value : value,
      index : index,
      criteria : iterator.call(context, value, index, list)
    };
  }).sort(function(left, right) {
    var a = left.criteria;
    var b = right.criteria;
    if (a !== b) {
      if (a > b || a === void 0) return 1;
      if (a < b || b === void 0) return -1;
    }
    return left.index < right.index ? -1 : 1;
  }), 'value');
};

```

An internal function used for aggregate “group by” operations.

```

var group = function(obj, value, context, behavior) {
  var result = {};
  var iterator = lookupIterator(value == null ? _.identity :
    & value);
  each(obj, function(value, index) {
    var key = iterator.call(context, value, index, obj);
    behavior(result, key, value);
  });
  return result;
};

```

Groups the object's values by a criterion. Pass either a string attribute to group by, or a function that returns the criterion.

```

_.groupBy = function(obj, value, context) {
  return group(obj, value, context, function(result, key, )
    { value) {
      (_.has(result, key) ? result[key] : (result[key] = ))
      { [])).push(value);
    }
  });
};

```

Counts instances of an object that group by a certain criterion. Pass either a string attribute to count by, or a function that returns the criterion.

```

_.countBy = function(obj, value, context) {
  return group(obj, value, context, function(result, key) {
    if (!_.has(result, key)) result[key] = 0;
    result[key]++;
  });
};

```

Use a comparator function to figure out the smallest index at which an object should be inserted so as to maintain order. Uses binary search.

```

_.sortedIndex = function(array, obj, iterator, context) {
  iterator = iterator == null ? _.identity : )
    { lookupIterator(iterator);
  var value = iterator.call(context, obj);
  var low = 0, high = array.length;
  while (low < high) {
    var mid = (low + high) >>> 1;
    iterator.call(context, array[mid]) < value ? low = mid + 1 :
      { : high = mid;
  }
  return low;
};

```

Safely convert anything iterable into a real, live array.

```

_.toArray = function(obj) {
  if (!obj) return [];
  if (_.isArray(obj)) return slice.call(obj);
  if (obj.length === +obj.length) return _.map(obj, _.identity);
  return _.values(obj);
};

```

Return the number of elements in an object.

```

_.size = function(obj) {
  if (obj == null) return 0;
  return (obj.length === +obj.length) ? obj.length : )
    { _.keys(obj).length;
};

```

## Array Functions

Get the first element of an array. Passing **n** will return the first N values in the array. Aliased as **head** and **take**. The **guard** check allows it to work with **\_.map**.

```

_.first = _.head = _.take = function(array, n, guard) {
  if (array == null) return void 0;
  return (n != null) && !guard ? slice.call(array, 0, n) :
    array[0];
};

```

Returns everything but the last entry of the array. Especially useful on the arguments object. Passing **n** will return all the values in the array, excluding the last N. The **guard** check allows it to work with `_.map`.

```

_.initial = function(array, n, guard) {
  return slice.call(array, 0, array.length - ((n == null) ||
    guard ? 1 : n));
};

```

Get the last element of an array. Passing **n** will return the last N values in the array. The **guard** check allows it to work with `_.map`.

```

_.last = function(array, n, guard) {
  if (array == null) return void 0;
  if ((n != null) && !guard) {
    return slice.call(array, Math.max(array.length - n, 0));
  } else {
    return array[array.length - 1];
  }
};

```

Returns everything but the first entry of the array. Aliased as `tail` and `drop`. Especially useful on the arguments object. Passing an **n** will return the rest N values in the array. The **guard** check allows it to work with `_.map`.

```

_.rest = _.tail = _.drop = function(array, n, guard) {
  return slice.call(array, (n == null) || guard ? 1 : n);
};

```

Trim out all falsy values from an array.

```

_.compact = function(array) {
  return _.filter(array, _.identity);
};

```

Internal implementation of a recursive flatten function.

```

var flatten = function(input, shallow, output) {
  each(input, function(value) {
    if (_.isArray(value)) {
      shallow ? push.apply(output, value) : flatten(value,
        shallow, output);
    } else {
      output.push(value);
    }
  });
  return output;
};

```

Return a completely flattened version of an array.

```

_.flatten = function(array, shallow) {
  return flatten(array, shallow, []);
};

```

Return a version of the array that does not contain the specified value(s).

```

_.without = function(array) {
  return _.difference(array, slice.call(arguments, 1));
};

```

Produce a duplicate-free version of the array. If the array has already been sorted, you have the option of using a faster algorithm. Aliased as `unique`.

```

_.uniq = _.unique = function(array, isSorted, iterator, context) {
  if (_.isFunction(isSorted)) {
    context = iterator;
    iterator = isSorted;
    isSorted = false;
  }
  var initial = iterator ? _.map(array, iterator, context) : array;
  var results = [];
  var seen = [];
  each(initial, function(value, index) {
    if (isSorted ? (!index || seen[seen.length - 1] !== value) : !_.contains(seen, value)) {
      seen.push(value);
      results.push(array[index]);
    }
  });
  return results;
};

```

Produce an array that contains the union: each distinct element from all of the passed-in arrays.

```

_.union = function() {
  return _.uniq(concat.apply(ArrayProto, arguments));
};

```

Produce an array that contains every item shared between all the passed-in arrays.

```

_.intersection = function(array) {
  var rest = slice.call(arguments, 1);
  return _.filter(_.uniq(array), function(item) {
    return _.every(rest, function(other) {
      return _.indexOf(other, item) >= 0;
    });
  });
};

```

Take the difference between one array and a number of other arrays. Only the elements present in just the first array will remain.

```

_.difference = function(array) {
  var rest = concat.apply(ArrayProto, slice.call(arguments, 1));
  return _.filter(array, function(value){ return
    ( !__.contains(rest, value); });
};

```

Zip together multiple lists into a single array – elements that share an index go together.

```

_.zip = function() {
  var args = slice.call(arguments);
  var length = _.max(_.pluck(args, 'length'));
  var results = new Array(length);
  for (var i = 0; i < length; i++) {
    results[i] = _.pluck(args, "" + i);
  }
  return results;
};

```

The inverse operation to `_.zip`. If given an array of pairs it returns an array of the paired elements split into two left and right element arrays, if given an array of triples it returns a three element array and so on. For example, `_.unzip` given `[['a',1],['b',2],['c',3]]` returns the array `[['a','b','c'],[1,2,3]]`.

```

_.unzip = function(tuples) {
  var maxLen = _.max(_.pluck(tuples, "length"));
  return _.times(maxLen, _.partial(_.pluck, tuples));
};

```

Converts lists into objects. Pass either a single array of `[key, value]` pairs, or two parallel arrays of the same length – one of keys, and one of the corresponding values.

```

_.object = function(list, values) {
  if (list == null) return {};
  var result = {};
  for (var i = 0, l = list.length; i < l; i++) {
    if (values) {
      result[list[i]] = values[i];
    } else {
      result[list[i][0]] = list[i][1];
    }
  }
  return result;
};

```

If the browser doesn't supply us with `indexOf` (I'm looking at you, **MSIE**), we need this function. Return the position of the first occurrence of an item in an array, or -1 if the item is not included in the array. Delegates to **ECMAScript 5's** native `indexOf` if available. If the array is large and already in sort order, pass `true` for `isSorted` to use binary search.

```

_.indexOf = function(array, item, isSorted) {
  if (array == null) return -1;
  var i = 0, l = array.length;

```

```

    if (isSorted) {
        if (typeof isSorted == 'number') {
            i = (isSorted < 0 ? Math.max(0, 1 + isSorted) : isSorted);
        } else {
            i = _.sortedIndex(array, item);
            return array[i] === item ? i : -1;
        }
    }
    if (nativeIndexOf && array.indexOf === nativeIndexOf) return 2
    ( array.indexOf(item, isSorted);
    for (; i < 1; i++) if (array[i] === item) return i;
    return -1;
};

```

Delegates to **ECMAScript 5**'s native `lastIndexOf` if available.

```

_.lastIndexOf = function(array, item, from) {
    if (array == null) return -1;
    var hasIndex = from != null;
    if (nativeLastIndexOf && array.lastIndexOf === 2
    ( nativeLastIndexOf) {
        return hasIndex ? array.lastIndexOf(item, from) : 2
        ( array.lastIndexOf(item);
    }
    var i = (hasIndex ? from : array.length);
    while (i-- > 0) if (array[i] === item) return i;
    return -1;
};

```

Generate an integer Array containing an arithmetic progression. A port of the native Python `range()` function. See the Python documentation<sup>2</sup>.

```

_.range = function(start, stop, step) {
    if (arguments.length <= 1) {
        stop = start || 0;
        start = 0;
    }
    step = arguments[2] || 1;

    var len = Math.max(Math.ceil((stop - start) / step), 0);
    var idx = 0;
    var range = new Array(len);

    while(idx < len) {
        range[idx++] = start;
        start += step;
    }

    return range;
};

```

---

<sup>2</sup><http://docs.python.org/library/functions.html#range>

## Function (ahem) Functions

Reusable constructor function for prototype setting.

```
var ctor = function(){};
```

Create a function bound to a given object (assigning `this`, and arguments, optionally). Delegates to **ECMAScript 5**'s native `Function.bind` if available.

```
_.bind = function(func, context) {  
  var args, bound;  
  if (func.bind === nativeBind && nativeBind) return ƒ  
    ↪ nativeBind.apply(func, slice.call(arguments, 1));  
  if (!_.isFunction(func)) throw new TypeError;  
  args = slice.call(arguments, 2);  
  return bound = function() {  
    if (!(this instanceof bound)) return func.apply(context, ƒ  
      ↪ args.concat(slice.call(arguments)));  
    ctor.prototype = func.prototype;  
    var self = new ctor;  
    ctor.prototype = null;  
    var result = func.apply(self, ƒ  
      ↪ args.concat(slice.call(arguments)));  
    if (Object(result) === result) return result;  
    return self;  
  };  
};
```

Partially apply a function by creating a version that has had some of its arguments pre-filled, without changing its dynamic `this` context.

```
_.partial = function(func) {  
  var args = slice.call(arguments, 1);  
  return function() {  
    return func.apply(this, args.concat(slice.call(arguments)));  
  };  
};
```

Bind all of an object's methods to that object. Useful for ensuring that all callbacks defined on an object belong to it.

```
_.bindAll = function(obj) {  
  var funcs = slice.call(arguments, 1);  
  if (funcs.length === 0) throw new Error("bindAll must be ƒ  
    ↪ passed function names");  
  each(funcs, function(f) { obj[f] = _.bind(obj[f], obj); });  
  return obj;  
};
```

Memoize an expensive function by storing its results.

```
_.memoize = function(func, hasher) {  
  var memo = {};  
  hasher || (hasher = _.identity);  
  return function() {  
    var key = hasher.apply(this, arguments);
```

```

        return _.has(memo, key) ? memo[key] : (memo[key] =
            func.apply(this, arguments));
    };
};

```

Delays a function for the given number of milliseconds, and then calls it with the arguments supplied.

```

_.delay = function(func, wait) {
    var args = slice.call(arguments, 2);
    return setTimeout(function(){ return func.apply(null, args); },
        wait);
};

```

Defers a function, scheduling it to run after the current call stack has cleared.

```

_.defer = function(func) {
    return _.delay.apply(_, [func, 1]);
};

```

Returns a function, that, when invoked, will only be triggered at most once during a given window of time.

```

_.throttle = function(func, wait, immediate) {
    var context, args, timeout, result;
    var previous = 0;
    var later = function() {
        previous = new Date;
        timeout = null;
        result = func.apply(context, args);
    };
    return function() {
        var now = new Date;
        if (!previous && immediate === false) previous = now;
        var remaining = wait - (now - previous);
        context = this;
        args = arguments;
        if (remaining <= 0) {
            clearTimeout(timeout);
            timeout = null;
            previous = now;
            result = func.apply(context, args);
        } else if (!timeout) {
            timeout = setTimeout(later, remaining);
        }
        return result;
    };
};

```

Returns a function, that, as long as it continues to be invoked, will not be triggered. The function will be called after it stops being called for N milliseconds. If `immediate` is passed, trigger the function on the leading edge, instead of the trailing.



```

_.debounce = function(func, wait, immediate) {
  var timeout, result;
  return function() {
    var context = this, args = arguments;
    var later = function() {
      timeout = null;
      if (!immediate) result = func.apply(context, args);
    };
    var callNow = immediate && !timeout;
    clearTimeout(timeout);
    timeout = setTimeout(later, wait);
    if (callNow) result = func.apply(context, args);
    return result;
  };
};

```

Returns a function that will be executed at most one time, no matter how often you call it. Useful for lazy initialization.

```

_.once = function(func) {
  var ran = false, memo;
  return function() {
    if (ran) return memo;
    ran = true;
    memo = func.apply(this, arguments);
    func = null;
    return memo;
  };
};

```

Returns the first function passed as an argument to the second, allowing you to adjust arguments, run code before and after, and conditionally execute the original function.

```

_.wrap = function(func, wrapper) {
  return function() {
    var args = [func];
    push.apply(args, arguments);
    return wrapper.apply(this, args);
  };
};

```

Returns a function that is the composition of a list of functions, each consuming the return value of the function that follows.

```

_.compose = function() {
  var funcs = arguments;
  return function() {
    var args = arguments;
    for (var i = funcs.length - 1; i >= 0; i--) {
      args = [funcs[i].apply(this, args)];
    }
    return args[0];
  };
};

```

Returns a function that will only be executed after being called N times.

```

_.after = function(times, func) {
  if (times <= 0) return func();
  return function() {
    if (--times < 1) {
      return func.apply(this, arguments);
    }
  };
};

```

## Object Functions

Retrieve the names of an object's properties. Delegates to **ECMAScript 5's** native `Object.keys`

```

_.keys = nativeKeys || function(obj) {
  if (obj !== Object(obj)) throw new TypeError('Invalid object');
  var keys = [];
  for (var key in obj) if (_.has(obj, key)) keys.push(key);
  return keys;
};

```

Retrieve the values of an object's properties.

```

_.values = function(obj) {
  var values = [];
  for (var key in obj) if (_.has(obj, key)) values.push(obj[key]);
  return values;
};

```

Convert an object into a list of [key, value] pairs.

```

_.pairs = function(obj) {
  var pairs = [];
  for (var key in obj) if (_.has(obj, key)) pairs.push([key,
    obj[key]]);
  return pairs;
};

```

Invert the keys and values of an object. The values must be serializable.

```

_.invert = function(obj) {
  var result = {};
  for (var key in obj) if (_.has(obj, key)) result[obj[key]] =
    key;
  return result;
};

```

Return a sorted list of the function names available on the object. Aliased as `methods`

```

_.functions = _.methods = function(obj) {
  var names = [];
  for (var key in obj) {

```

```

        if (!_isFunction(obj[key])) names.push(key);
    }
    return names.sort();
};

```

Extend a given object with all the properties in passed-in object(s).

```

_.extend = function(obj) {
    each(slice.call(arguments, 1), function(source) {
        if (source) {
            for (var prop in source) {
                obj[prop] = source[prop];
            }
        }
    });
    return obj;
};

```

Return a copy of the object only containing the whitelisted properties.

```

_.pick = function(obj) {
    var copy = {};
    var keys = concat.apply(ArrayProto, slice.call(arguments, 1));
    each(keys, function(key) {
        if (key in obj) copy[key] = obj[key];
    });
    return copy;
};

```

Return a copy of the object without the blacklisted properties.

```

_.omit = function(obj) {
    var copy = {};
    var keys = concat.apply(ArrayProto, slice.call(arguments, 1));
    for (var key in obj) {
        if (!_.contains(keys, key)) copy[key] = obj[key];
    }
    return copy;
};

```

Fill in a given object with default properties.

```

_.defaults = function(obj) {
    each(slice.call(arguments, 1), function(source) {
        if (source) {
            for (var prop in source) {
                if (obj[prop] === void 0) obj[prop] = source[prop];
            }
        }
    });
    return obj;
};

```

Create a (shallow-cloned) duplicate of an object.

```

_.clone = function(obj) {
    if (!_isObject(obj)) return obj;
    return _.isArray(obj) ? obj.slice() : _.extend({}, obj);
};

```

Invokes interceptor with the obj, and then returns obj. The primary purpose of this method is to “tap into” a method chain, in order to perform operations on intermediate results within the chain.

```
_.tap = function(obj, interceptor) {  
  interceptor(obj);  
  return obj;  
};
```

Internal recursive comparison function for isEqual.

```
var eq = function(a, b, aStack, bStack) {
```

Identical objects are equal. `0 === -0`, but they aren’t identical. See the Harmony `egal` proposal<sup>3</sup>.

```
  if (a === b) return a !== 0 || 1 / a == 1 / b;
```

A strict comparison is necessary because `null == undefined`.

```
  if (a == null || b == null) return a === b;
```

Unwrap any wrapped objects.

```
  if (a instanceof _) a = a._wrapped;  
  if (b instanceof _) b = b._wrapped;
```

Compare `[[Class]]` names.

```
  var className = toString.call(a);  
  if (className != toString.call(b)) return false;  
  switch (className) {
```

Strings, numbers, dates, and booleans are compared by value.

```
    case '[object String]':
```

Primitives and their corresponding object wrappers are equivalent; thus, “5” is equivalent to `new String(“5”)` .

```
    return a == String(b);  
    case '[object Number]':
```

`NaN`s are equivalent, but non-reflexive. An `egal` comparison is performed for other numeric values.

```
    return a != +a ? b != +b : (a == 0 ? 1 / a == 1 / b : a &  
      { == +b});  
    case '[object Date]':  
    case '[object Boolean]':
```

Coerce dates and booleans to numeric primitive values. Dates are compared by their millisecond representations. Note that invalid dates with millisecond representations of `NaN` are not equivalent.

---

<sup>3</sup><http://wiki.ecmascript.org/doku.php?id=harmony:egal>

```
return +a == +b;
```

RegExp's are compared by their source patterns and flags.

```
case '[object RegExp]':
  return a.source == b.source &&
    a.global == b.global &&
    a.multiline == b.multiline &&
    a.ignoreCase == b.ignoreCase;
}
if (typeof a != 'object' || typeof b != 'object') return false;
```

Assume equality for cyclic structures. The algorithm for detecting cyclic structures is adapted from ES 5.1 section 15.12.3, abstract operation `JO`.

```
var length = aStack.length;
while (length--) {
```

Linear search. Performance is inversely proportional to the number of unique nested structures.

```
if (aStack[length] == a) return bStack[length] == b;
}
```

Add the first object to the stack of traversed objects.

```
aStack.push(a);
bStack.push(b);
var size = 0, result = true;
```

Recursively compare objects and arrays.

```
if (className == '[object Array]') {
```

Compare array lengths to determine if a deep comparison is necessary.

```
size = a.length;
result = size == b.length;
if (result) {
```

Deep compare the contents, ignoring non-numeric properties.

```
while (size--) {
  if (!(result = eq(a[size], b[size], aStack, bStack))) {
    break;
  }
}
} else {
```

Objects with different constructors are not equivalent, but `Objects` from different frames are.

```
var aCtor = a.constructor, bCtor = b.constructor;
if (aCtor !== bCtor && !(_.isFunction(aCtor) && (aCtor &
  (instanceof aCtor) &&
    _.isFunction(bCtor) && (bCtor &
      (instanceof bCtor)))) {
  return false;
}
```

Deep compare objects.

```
    for (var key in a) {  
        if (!_has(a, key)) {
```

Count the expected number of properties.

```
        size++;
```

Deep compare each member.

```
        if (!(result = _has(b, key) && eq(a[key], b[key], 2  
        ( aStack, bStack))) break;  
    }  
}
```

Ensure that both objects contain the same number of properties.

```
    if (result) {  
        for (key in b) {  
            if (!_has(b, key) && !(size--)) break;  
        }  
        result = !size;  
    }  
}
```

Remove the first object from the stack of traversed objects.

```
    aStack.pop();  
    bStack.pop();  
    return result;  
};
```

Perform a deep comparison to check if two objects are equal.

```
_isEqual = function(a, b) {  
    return eq(a, b, [], []);  
};
```

Is a given array, string, or object empty? An “empty” object has no enumerable own-properties.

```
_isEmpty = function(obj) {  
    if (obj == null) return true;  
    if (_isArray(obj) || _isString(obj)) return obj.length === 0;  
    for (var key in obj) if (_has(obj, key)) return false;  
    return true;  
};
```

Is a given value a DOM element?

```
_isElement = function(obj) {  
    return !(obj && obj.nodeType === 1);  
};
```

Is a given value an array? Delegates to ECMA5’s native Array.isArray

```

    _._isArray = nativeIsArray || function(obj) {
        return toString.call(obj) == '[object Array]';
    };

```

Is a given variable an object?

```

    _._isObject = function(obj) {
        return obj === Object(obj);
    };

```

Add some isType methods: isArguments, isFunction, isString, isNumber, isDate, isRegExp.

```

    each(['Arguments', 'Function', 'String', 'Number', 'Date', 'RegExp'], function(name) {
        _['is' + name] = function(obj) {
            return toString.call(obj) == '[object ' + name + ']';
        };
    });

```

Define a fallback version of the method in browsers (ahem, IE), where there isn't any inspectable "Arguments" type.

```

    if (!_._isArguments(arguments)) {
        _._isArguments = function(obj) {
            return !!(obj && _._has(obj, 'callee'));
        };
    }

```

Optimize isFunction if appropriate.

```

    if (typeof (./.) !== 'function') {
        _._isFunction = function(obj) {
            return typeof obj === 'function';
        };
    }

```

Is a given object a finite number?

```

    _._isFinite = function(obj) {
        return isFinite(obj) && !isNaN(parseFloat(obj));
    };

```

Is the given value NaN? (NaN is the only number which does not equal itself).

```

    _._isNaN = function(obj) {
        return !_._isNumber(obj) && obj != +obj;
    };

```

Is a given value a boolean?

```

    _._isBoolean = function(obj) {
        return obj === true || obj === false || toString.call(obj) == '[object Boolean]';
    };

```

Is a given value equal to null?

```
_.isNull = function(obj) {  
  return obj === null;  
};
```

Is a given variable undefined?

```
_.isUndefined = function(obj) {  
  return obj === void 0;  
};
```

Shortcut function for checking if an object has a given property directly on itself (in other words, not on a prototype).

```
_.has = function(obj, key) {  
  return hasOwnProperty.call(obj, key);  
};
```

## Utility Functions

Run Underscore.js in *noConflict* mode, returning the `_` variable to its previous owner. Returns a reference to the Underscore object.

```
_.noConflict = function() {  
  root._ = previousUnderscore;  
  return this;  
};
```

Keep the identity function around for default iterators.

```
_.identity = function(value) {  
  return value;  
};
```

Run a function **n** times.

```
_.times = function(n, iterator, context) {  
  var accum = Array(Math.max(0, n));  
  for (var i = 0; i < n; i++) accum[i] = 2  
    iterator.call(context, i);  
  return accum;  
};
```

Return a random integer between min and max (inclusive).

```
_.random = function(min, max) {  
  if (max == null) {  
    max = min;  
    min = 0;  
  }  
  return min + Math.floor(Math.random() * (max - min + 1));  
};
```



List of HTML entities for escaping.

```
var entityMap = {
  escape: {
    '&': '&amp;',
    '<': '&lt;',
    '>': '&gt;',
    '"': '&quot;',
    "'": '&#x27;',
    '/': '&#x2F;'
  }
};
entityMap.unescape = _.invert(entityMap.escape);
```

Regexes containing the keys and values listed immediately above.

```
var entityRegexes = {
  escape: new RegExp('[' + _.keys(entityMap.escape).join('') +
    '[' + ']', 'g'),
  unescape: new RegExp('(' +
    '[' + _.keys(entityMap.unescape).join('|') + ')', 'g')
};
```

Functions for escaping and unescaping strings to/from HTML interpolation.

```
_.each(['escape', 'unescape'], function(method) {
  _[method] = function(string) {
    if (string == null) return '';
    return ('' + string).replace(entityRegexes[method],
      function(match) {
        return entityMap[method][match];
      });
  };
});
```

If the value of the named property is a function then invoke it with the object as context; otherwise, return it.

```
_.result = function(object, property) {
  if (object == null) return void 0;
  var value = object[property];
  return _.isFunction(value) ? value.call(object) : value;
};
```

Add your own custom functions to the Underscore object.

```
_.mixin = function(obj) {
  each(_.functions(obj), function(name){
    var func = _[name] = obj[name];
    _[name] = function() {
      var args = [this._wrapped];
      push.apply(args, arguments);
      return result.call(this, func.apply(_, args));
    };
  });
};
```

Generate a unique integer id (unique within the entire client session). Useful for temporary DOM ids.

```
var idCounter = 0;
_.uniqueId = function(prefix) {
  var id = ++idCounter + '';
  return prefix ? prefix + id : id;
};
```

By default, Underscore uses ERB-style template delimiters, change the following template settings to use alternative delimiters.

```
_.templateSettings = {
  evaluate    : /<%(\[s\S]+\?)%>/g,
  interpolate : /<%=([s\S]+\?)%>/g,
  escape     : /<%-([s\S]+\?)%>/g
};
```

When customizing `templateSettings`, if you don't want to define an interpolation, evaluation or escaping regex, we need one that is guaranteed not to match.

```
var noMatch = /(.)^/;
```

Certain characters need to be escaped so that they can be put into a string literal.

```
var escapes = {
  "'": "'",
  '\\': '\\',
  '\r': 'r',
  '\n': 'n',
  '\t': 't',
  '\u2028': 'u2028',
  '\u2029': 'u2029'
};

var escaper = /\\|'|\r|\n|\t|\u2028|\u2029/g;
```

JavaScript micro-templating, similar to John Resig's implementation. Underscore templating handles arbitrary delimiters, preserves whitespace, and correctly escapes quotes within interpolated code.

```
_.template = function(text, data, settings) {
  var render;
  settings = _.defaults({}, settings, _.templateSettings);
```

Combine delimiters into one regular expression via alternation.

```
var matcher = new RegExp([
  (settings.escape || noMatch).source,
  (settings.interpolate || noMatch).source,
  (settings.evaluate || noMatch).source
].join('|') + '|$', 'g');
```

Compile the template source, escaping string literals appropriately.

```

var index = 0;
var source = "__p+='";
text.replace(matcher, function(match, escape, interpolate,
    { evaluate, offset) {
    source += text.slice(index, offset)
        .replace(escaper, function(match) { return '\\\' +
            { escapes[match]; });

    if (escape) {
        source += "'+\n((__t=\" + escape +
            { "))==null?'':_.escape(__t))+\n'";
    }
    if (interpolate) {
        source += "'+\n((__t=\" + interpolate +
            { "))==null?'':__t)+\n'";
    }
    if (evaluate) {
        source += "';\n" + evaluate + "\n__p+='";
    }
    index = offset + match.length;
    return match;
});
source += "';\n";

```

If a variable is not specified, place data values in local scope.

```

if (!settings.variable) source = 'with(obj||{}){\n' + source
    { + '}\n';

source = "var __t,__p='',__j=Array.prototype.join,\" +
    \"print=function(){__p+=__j.call(arguments,'');};\n\" +
    source + \"return __p;\n\";

try {
    render = new Function(settings.variable || 'obj', '_',
        { source);
} catch (e) {
    e.source = source;
    throw e;
}

if (data) return render(data, _);
var template = function(data) {
    return render.call(this, data, _);
};

```

Provide the compiled function source as a convenience for precompilation.

```

template.source = 'function(' + (settings.variable || 'obj')
    { + '){\n' + source + '}'

return template;
};

```

Add a “chain” function, which will delegate to the wrapper.

```

_.chain = function(obj) {

```

```

    return _(obj).chain();
  };

```

## OOP

If Underscore is called as a function, it returns a wrapped object that can be used OO-style. This wrapper holds altered versions of all the underscore functions. Wrapped objects may be chained.

Helper function to continue chaining intermediate results.

```

var result = function(obj) {
  return this._chain ? _(obj).chain() : obj;
};

```

Add all of the Underscore functions to the wrapper object.

```

_.mixin(_);

```

Add all mutator Array functions to the wrapper.

```

each(['pop', 'push', 'reverse', 'shift', 'sort', 'splice', 'unshift'], function(name) {
  var method = ArrayProto[name];
  _.prototype[name] = function() {
    var obj = this._wrapped;
    method.apply(obj, arguments);
    if ((name == 'shift' || name == 'splice') && obj.length >= 0) delete obj[0];
    return result.call(this, obj);
  };
});

```

Add all accessor Array functions to the wrapper.

```

each(['concat', 'join', 'slice'], function(name) {
  var method = ArrayProto[name];
  _.prototype[name] = function() {
    return result.call(this, method.apply(this._wrapped, arguments));
  };
});

_.extend(_.prototype, {

```

Start chaining a wrapped Underscore object.

```

chain: function() {
  this._chain = true;
  return this;
},

```

Extracts the result from a wrapped and chained object.

```
    value: function() {  
        return this._wrapped;  
    }  
});  
}).call(this);
```