

Page: 1/9
Revised edition no: 2.00
Revision date: 2018-04-25

Supersedes : 2015-03-02 **097A 09**

Country : DE / Language : EN

ALbee™ Flame O2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : ALbee™ Flame O2

SDS no : 097A_09 Chemical description : Oxygen

> CAS-No.: 7782-44-7 EC-No.: 231-956-9 EC Index-No.: 008-001-00-8

Registration-No. : Listed in Annex IV / V REACH, exempted from registration.

Chemical formula : O2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use.

Welding, cutting, heating and brazing.

Contact supplier for more information on uses.

Uses advised against : Consumer use.

1.3. Details of the supplier of the safety data sheet

Company identification

Supplier

AIR LIQUIDE Deutschland GmbH

Luise-Rainer-Straße 5

40235 Düsseldorf - GERMANY

T +49 (0)211 6699-0 - F +49 (0)211 6699-222

info@airliquide.de

E-Mail address (competent person) : info.SDB@airliquide.de

1.4. Emergency telephone number

Emergency telephone number : +49 (0)2151 398668

Availability (24 / 7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards Oxidising Gases, Category 1 H270

Gases under pressure: Compressed gas H280

2.2. Label elements

Signal word (CLP)

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS03

: Danger

Hazard statements (CLP) : H270 - May cause or intensify fire; oxidiser..

H280 - Contains gas under pressure; may explode if heated..

Precautionary statements (CLP)

- Prevention : P220 - Keep away from clothing and other combustible materials..

P244 - Keep valves and fittings free from oil and grease..

- Response : P370+P376 - In case of fire: stop leak if safe to do so..

- Storage : P403 - Store in a well-ventilated place..



Page: 2/9
Revised edition no: 2.00
Revision date: 2018-04-25
Supersedes: 2015-03-02

097A 09

Country: DE / Language: EN

ALbee™ Flame O2

2.3. Other hazards

: None.

SECTION 3: Composition/information on ingredients

3.1. Substances

Name	Product identifier	Composition [V-%]:	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Oxygen	(CAS-No.) 7782-44-7 (EC-No.) 231-956-9 (EC Index-No.) 008-001-00-8 (Registration-No.) *1	100	Ox. Gas 1, H270 Press. Gas (Comp.), H280

Contains no other components or impurities which will influence the classification of the product.

- *1: Listed in Annex IV / V REACH, exempted from registration.
- *2: Registration deadline not expired.

3.2. Mixtures : Not applicable.

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep

victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

Remove victim to uncontaminated area.

Skin contactEye contactAdverse effects not expected from this product.Adverse effects not expected from this product.

- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

: Continuous inhalation of concentrations higher than 75% may cause nausea, dizziness,

respiratory difficulty and convulsion.

Refer to section 11.

$\underline{\textbf{4.3. Indication of any immediate medical attention and special treatment needed}}$

: None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.

- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Specific hazards : Supports combustion.

Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products : None.

^{*3:} Registration not required: Substance manufactured or imported < 1t/y.



Page: 3/9
Revised edition no: 2.00
Revision date: 2018-04-25

Supersedes : 2015-03-02

097A_09

Country: DE / Language: EN

ALbee™ Flame O2

5.3. Advice for firefighters

Specific methods

: Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.

If possible, stop flow of product.

Use water spray or fog to knock down fire fumes if possible.

Move containers away from the fire area if this can be done without risk.

Special protective equipment for fire fighters

Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.

Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for

firefighters.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

: Try to stop release.

Evacuate area.

Monitor concentration of released product.

Wear self-contained breathing apparatus when entering area unless atmosphere is proved to

be safe.

Eliminate ignition sources.
Ensure adequate air ventilation.

Act in accordance with local emergency plan.

Stay upwind.

6.2. Environmental precautions

: Try to stop release.

6.3. Methods and material for containment and cleaning up

: Ventilate area.

6.4. Reference to other sections

: See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safe use of the product

: The product must be handled in accordance with good industrial hygiene and safety procedures.

Only experienced and properly instructed persons should handle gases under pressure.

Consider pressure relief device(s) in gas installations.

Ensure the complete gas system was (or is regularily) checked for leaks before use.

Do not smoke while handling product. Keep equipment free from oil and grease.

Use no oil or grease.

Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.

Use only oxygen approved lubricants and oxygen approved sealings.

Use only with equipment cleaned for oxygen service and rated for cylinder pressure.

Avoid suck back of water, acid and alkalis.

Do not breathe gas.

Safe handling of the gas receptacle

: Refer to supplier's container handling instructions.

Do not allow backfeed into the container.

Protect cylinders from physical damage; do not drag, roll, slide or drop.

When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed

to transport cylinders.

Leave valve protection caps in place until the container has been secured against either a wall



Page : 4/9
Revised edition no : 2.00
Revision date : 2018-04-25

Supersedes : 2015-03-02

097A_09Country : DE / Language : EN

ALbee™ Flame O2

or bench or placed in a container stand and is ready for use.

If user experiences any difficulty operating cylinder valve discontinue use and contact supplier.

Never attempt to repair or modify container valves or safety relief devices.

Damaged valves should be reported immediately to the supplier.

Keep container valve outlets clean and free from contaminants particularly oil and water.

Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to transfer gases from one cylinder/container to another.

Never use direct flame or electrical heating devices to raise the pressure of a container.

Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.

Suck back of water into the container must be prevented.

Open valve slowly to avoid pressure shock.

7.2. Conditions for safe storage, including any incompatibilities

: Observe all regulations and local requirements regarding storage of containers.

Containers should not be stored in conditions likely to encourage corrosion.

Container valve guards or caps should be in place.

Containers should be stored in the vertical position and properly secured to prevent them from falling over.

Stored containers should be periodically checked for general condition and leakage.

Keep container below 50°C in a well ventilated place.

Segregate from flammable gases and other flammable materials in store.

Store containers in location free from fire risk and away from sources of heat and ignition.

Keep away from combustible materials.

7.3. Specific end use(s)

: None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL (Occupational Exposure Limits): No data available.

DNEL (Derived-No Effect Level): No data available.

PNEC (Predicted No-Effect Concentration): No data available.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

: Provide adequate general and local exhaust ventilation.

Systems under pressure should be regularily checked for leakages.

Avoid oxygen rich (>23,5%) atmospheres.

Gas detectors should be used when oxidising gases may be released. Consider the use of a work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

: A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The

following recommendations should be considered:

PPE compliant to the recommended EN/ISO standards should be selected.

• Eye/face protection : Wear safety glasses with side shields.

Standard EN 166 - Personal eye-protection - specifications.

Skin protection

- Hand protection : Wear working gloves when handling gas containers.

Standard EN 388 - Protective gloves against mechanical risk.



Page: 5/9
Revised edition no: 2.00
Revision date: 2018-04-25

Supersedes : 2015-03-02 **097A 09**

Country: DE / Language: EN

ALbee™ Flame O2

: Consider the use of flame resistant safety clothing.

Standard EN ISO 14116 - Limited flame spread materials.

Wear safety shoes while handling containers.

Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

• Respiratory protection : None necessary.

• Thermal hazards : None in addition to the above sections.

8.2.3. Environmental exposure controls

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for

specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

- Other

• Physical state at 20°C / 101.3kPa : Gas.

• Colour : Colourless.

Odour : No odour warning properties.

Odour threshold : Odour threshold is subjective and inadequate to warn of overexposure.

Melting point $-219 \, ^{\circ}\text{C}$ Boiling point : $-183 \, ^{\circ}\text{C}$

Flash point : Not applicable for gases and gas mixtures.

Flammability range : Non flammable.

Relative vapour density at 20 °C : Not applicable.

Evaporation rate (ether=1) : Not applicable for gases and gas mixtures.

Vapour pressure [20°C] : Not applicable.

Vapour pressure [50°C] : Not applicable.

Relative density, gas (air=1) : 1.1

Relative density, liquid (water=1) : 1.1

Solubility in water : 39 mg/l

pH value : Not applicable for gases and gas mixtures.

Partition coefficient n-octanol/water [log Kow] : Not applicable for inorganic gases.

Decomposition point [°C] : Not applicable.

Auto-ignition temperature : Non flammable.

Viscosity [20°C] : No reliable data available.

Explosive Properties : Not applicable.

Oxidising Properties : Oxidiser.

- Coefficient of oxygen equivalency (Ci) :

9.2. Other information

Molar mass : 32 g/mol Critical temperature [°C] -118 °C

Other data : No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

: No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

: Stable under normal conditions.



Page : 6/9
Revised edition no : 2.00

Revision date : 2018-04-25 Supersedes : 2015-03-02

097A_09

Country : DE / Language : EN

ALbee™ Flame O2

10.3. Possibility of hazardous reactions

: Violently oxidises organic material.

10.4. Conditions to avoid

: Avoid moisture in installation systems.

10.5. Incompatible materials

May react violently with combustible materials.
 May react violently with reducing agents.
 Keep equipment free from oil and grease.

Consider the potential toxicity hazard due to the presence of chlorinated or fluorinated polymers

in high pressure (> 30 bar) oxygen lines in case of combustion. For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

: None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : No known toxicological effects from this product.

 Skin corrosion/irritation
 : No known effects from this product.

 Serious eye damage/irritation
 : No known effects from this product.

 Respiratory or skin sensitisation
 : No known effects from this product.

 Germ cell mutagenicity
 : No known effects from this product.

 Carcinogenicity
 : No known effects from this product.

Reproductive toxicity

Toxic for reproduction: Fertility
Toxic for reproduction: unborn child

STOT-single exposure
STOT-repeated exposure

SECTION 12: Ecological information

12.1. Toxicity

Assessment : No ecological damage caused by this product.

EC50 48h - Daphnia magna [mg/l] : No data available. EC50 72h - Algae [mg/l] : No data available. LC50 96 h - Fish [mg/l] : No data available.

12.2. Persistence and degradability

Assessment : No ecological damage caused by this product.

12.3. Bioaccumulative potential

Assessment : No data available.

12.4. Mobility in soil

Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution.

Partition into soil is unlikely.

12.5. Results of PBT and vPvB assessment



Page: 7/9
Revised edition no: 2.00
Revision date: 2018-04-25

Supersedes : 2015-03-02

097A_09

Country: DE / Language: EN

ALbee™ Flame O2

Assessment : No data available.

12.6. Other adverse effects

Other adverse effects : No known effects from this product.

Effect on the ozone layer : None.
Effect on global warming : None.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Contact supplier if guidance is required.

May be vented to atmosphere in a well ventilated place.

Do not discharge into any place where its accumulation could be dangerous.

Ensure that the emission levels from local regulations or operating permits are not exceeded.

Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at

http://www.eiga.org for more guidance on suitable disposal methods.

Return unused product in original cylinder to supplier.

List of hazardous waste codes (from Commission Decision 2001/118/EC)

13.2. Additional information

16 05 04 * : Gases in pressure containers (including halons) containing dangerous substances.

: External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information

14.1. UN number

UN-No. : 1072

14.2. UN proper shipping name

Transport by road/rail (ADR/RID)

Transport by air (ICAO-TI / IATA-DGR)

Transport by sea (IMDG)

OXYGEN, COMPRESSED

Oxygen, compressed

OXYGEN, COMPRESSED

14.3. Transport hazard class(es)

Labelling





2.2 : Non-flammable, non-toxic gases.

5.1: Oxidizing substances.

Transport by road/rail (ADR/RID)

Class : 2.
Classification code : 10.
Hazard identification number : 25.

Tunnel Restriction : E - Passage forbidden through tunnels of category E.

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)) : 2.2 (5.1)

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.2 (5.1)

Emergency Schedule (EmS) - Fire : F-C.

Emergency Schedule (EmS) - Spillage : S-W.



Page: 8/9
Revised edition no: 2.00

Revision date: 2018-04-25 Supersedes: 2015-03-02

097A_09

Country: DE / Language: EN

ALbee™ Flame O2

14.4. Packing group

Transport by road/rail (ADR/RID) : Not established.

Transport by air (ICAO-TI / IATA-DGR) : Not established.

Transport by sea (IMDG) : Not established.

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None.

Transport by air (ICAO-TI / IATA-DGR) : None.

Transport by sea (IMDG) : None.

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail (ADR/RID) : P200.

Transport by air (ICAO-TI / IATA-DGR)

Passenger and Cargo Aircraft : 200.
Cargo Aircraft only : 200.
Transport by sea (IMDG) : P200.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's

compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

Before transporting product containers:
- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.

- Ensure cylinder valve is closed and not leaking.

Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
 Ensure valve protection device (where provided) is correctly fitted.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Restrictions on use : None. Seveso Directive : 2012/18/EU (Seveso III) : Listed.

National regulations

National legislation : Ensure all national/local regulations are observed.

Germany

Water hazard class (WGK) : Water hazard class (WGK) nwg, Non-hazardous to water (Classification according to VwVwS,

Annex 1 or 2; ID No. 743)

Other information, restrictions and prohibition

regulations

: [German regulations] BetriebssicherheitsV mit TRBSen insbesondere TRBS 3145 / TRGS 725 Ortsbewegliche Druckgasbehälter", TRBS 2141, BGRegel 500 Teil 2.33: "Umgang mit Gasen", GefahrstoffV mit Technischen Regeln Gefährliche Stoffe TRGS insbesondere TRGS 407

"Tätigkeiten mit Gasen - Gefährdungsbeurteilung", TRGS 400, 500, 510, 900."

15.2. Chemical safety assessment

A CSA does not need to be carried out for this product.



Page: 9/9
Revised edition no: 2.00
Revision date: 2018-04-25
Supersedes: 2015-03-02

097A 09

Country: DE / Language: EN

ALbee™ Flame O2

SECTION 16: Other information

Indication of changes

: Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.

Abbreviations and acronyms

: ATE - Acute Toxicity Estimate

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC)

No 1907/2006

EINECS - European Inventory of Existing Commercial Chemical Substances

CAS# - Chemical Abstract Service number PPE - Personal Protection Equipment

LC50 - Lethal Concentration to 50 % of a test population

RMM - Risk Management Measures

PBT - Persistent, Bioaccumulative and Toxic vPvB - Very Persistent and Very Bioaccumulative

STOT- SE: Specific Target Organ Toxicity - Single Exposure

CSA - Chemical Safety Assessment

EN - European Standard UN - United Nations

ADR - European Agreement concerning the International Carriage of Dangerous Goods by

Road

IATA - International Air Transport Association

IMDG code - International Maritime Dangerous Goods

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

WGK - Water Hazard Class

: Ensure operators understand the hazard of oxygen enrichment.

: This Safety Data Sheet has been established in accordance with the applicable European

Union legislation.

Full text of H- and EUH-statements

Training advice

Further information

Ox. Gas 1	Oxidising Gases, Category 1	
Press. Gas (Comp.)	Gases under pressure : Compressed gas	
H270	May cause or intensify fire; oxidiser.	
H280	Contains gas under pressure; may explode if heated.	

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press.

Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.