

Page: 1/9 Revised edition no: 4.00

Revision date: 2018-11-23 Supersedes: 2014-09-04

201001

Country: DE / Language: EN

# ALbee™ Weld ArMix

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : ALbee™ Weld ArMix

SDS no . 201001

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Industrial and professional. Perform risk assessment prior to use.

Shield gas for welding processes.

Contact supplier for more information on uses.

Uses advised against Consumer use.

#### 1.3. Details of the supplier of the safety data sheet

Company identification

Supplier

AIR LIQUIDE Deutschland GmbH

Luise-Rainer-Straße 5 40235 Düsseldorf - GERMANY

T +49 (0)211 6699-0 - F +49 (0)211 6699-222

info@airliquide.de

E-Mail address (competent person) : info.SDB@airliquide.de

1.4. Emergency telephone number

Emergency telephone number : +49 (0)2151 398668

Availability (24/7)

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards Gases under pressure: Compressed gas H280

### 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)

GHS04

Signal word (CLP) : Warning

Hazard statements (CLP) : H280 - Contains gas under pressure; may explode if heated...

Precautionary statements (CLP)

- Storage: P403 - Store in a well-ventilated place..

### 2.3. Other hazards

: Asphyxiant in high concentrations.

In high concentrations CO2 causes rapid circulatory insufficiency even at normal levels of oxygen concentration. Symptoms are headache, nausea and vomiting, which may lead to

unconsciousness and death.

### **SECTION 3: Composition/information on ingredients**

3.1. Substances : Not applicable.



Page: 2/9
Revised edition no: 4.00
Revision date: 2018-11-23

Supersedes : 2014-09-04 201001

Country: DE / Language: EN

## **ALbee™ Weld ArMix**

#### 3.2. Mixtures

Name	Product identifier	Composition [V-%]:	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Argon	(CAS-No.) 7440-37-1 (EC-No.) 231-147-0 (EC Index-No.) (REACH-no) *1	82	Press. Gas (Comp.), H280
Carbon dioxide	(CAS-No.) 124-38-9 (EC-No.) 204-696-9 (EC Index-No.) (REACH-no) *1	18	Press. Gas (Liq.), H280

Full text of H-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

- \*1: Listed in Annex IV / V REACH, exempted from registration.
- \*2: Registration deadline not expired.
- \*3: Registration not required: Substance manufactured or imported < 1t/y.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep

victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing

stopped.

Skin contactEye contactAdverse effects not expected from this product.Adverse effects not expected from this product.

- Ingestion : Ingestion is not considered a potential route of exposure.

### 4.2. Most important symptoms and effects, both acute and delayed

: In high concentrations may cause asphyxiation. Symptoms may include loss of

mobility/consciousness. Victim may not be aware of asphyxiation.

Refer to section 11.

### 4.3. Indication of any immediate medical attention and special treatment needed

: None.

### **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.

- Unsuitable extinguishing media : Do not use water jet to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Specific hazards : Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products : None.

### 5.3. Advice for firefighters

Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat

radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and

drainage systems.

If possible, stop flow of product.

Use water spray or fog to knock down fire fumes if possible.

Move containers away from the fire area if this can be done without risk.

Special protective equipment for fire fighters

: In confined space use self-contained breathing apparatus.

Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire

fighters.

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

face mask.



Page: 3/9
Revised edition no: 4.00
Revision date: 2018-11-23
Supersedes: 2014-09-04

201001

Country : DE / Language : EN

## ALbee™ Weld ArMix

Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

: Try to stop release.

Evacuate area.

Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.

Ensure adequate air ventilation.

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

Act in accordance with local emergency plan.

Stay upwind.

Oxygen detectors should be used when asphyxiating gases may be released.

#### 6.2. Environmental precautions

: Try to stop release.

### 6.3. Methods and material for containment and cleaning up

: Ventilate area.

#### 6.4. Reference to other sections

: See also sections 8 and 13.

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Safe use of the product

: The product must be handled in accordance with good industrial hygiene and safety procedures.

Only experienced and properly instructed persons should handle gases under pressure.

Consider pressure relief device(s) in gas installations.

Ensure the complete gas system was (or is regularily) checked for leaks before use.

Do not smoke while handling product.

Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.

Avoid suck back of water, acid and alkalis.

Do not breathe gas.

Avoid release of product into atmosphere.

Safe handling of the gas receptacle : Refer to supplier's container handling instructions.

Do not allow backfeed into the container.

Protect cylinders from physical damage; do not drag, roll, slide or drop.

When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders

Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.

If user experiences any difficulty operating cylinder valve discontinue use and contact supplier.

Never attempt to repair or modify container valves or safety relief devices.

Damaged valves should be reported immediately to the supplier.

Keep container valve outlets clean and free from contaminants particularly oil and water.

Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to transfer gases from one cylinder/container to another.

Never use direct flame or electrical heating devices to raise the pressure of a container.

Do not remove or deface labels provided by the supplier for the identification of the cylinder

contents.



Page : 4/9
Revised edition no : 4.00
Revision date : 2018-11-23

Supersedes : 2014-09-04 201001

Country: DE / Language: EN

## ALbee™ Weld ArMix

Suck back of water into the container must be prevented.

Open valve slowly to avoid pressure shock.

### 7.2. Conditions for safe storage, including any incompatibilities

: Observe all regulations and local requirements regarding storage of containers.

Containers should not be stored in conditions likely to encourage corrosion.

Container valve guards or caps should be in place.

Containers should be stored in the vertical position and properly secured to prevent them from

falling over.

Stored containers should be periodically checked for general condition and leakage.

Keep container below 50°C in a well ventilated place.

Store containers in location free from fire risk and away from sources of heat and ignition.

Keep away from combustible materials.

7.3. Specific end use(s)

: None.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

Carbon dioxide (124-38-9)				
OEL : Occupational E	xposure Limits			
EU	TWA IOELV (EU) 8 h [mg/m³]	9000 mg/m³		
	TWA IOELV (EU) 8 h [ppm]	5000 ppm		
Germany	TWA (DE) OEL 8h [mg/m3] TRGS 900	9100 mg/m³		
	TWA (DE) OEL 8h [ppm] TRGS 900	5000 ppm		
	Peak exposure limitation factor (DE) OEL TRGS 900	2(II)		
	Remark (TRGS 900)	DFG.EU		

DNEL (Derived-No Effect Level) : No data available.

PNEC (Predicted No-Effect Concentration): No data available.

### 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

: Provide adequate general and local exhaust ventilation.

Systems under pressure should be regularily checked for leakages.

Ensure exposure is below occupational exposure limits (where available).

Oxygen detectors should be used when asphyxiating gases may be released.

Consider the use of a work permit system e.g. for maintenance activities.

## ${\bf 8.2.2.}\ Individual\ protection\ measures, e.g.\ personal\ protective\ equipment$

: A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The

following recommendations should be considered:

PPE compliant to the recommended EN/ISO standards should be selected.

• Eye/face protection : Wear safety glasses with side shields.

Standard EN 166 - Personal eye-protection - specifications.

Skin protection

Hand protection : Wear working gloves when handling gas containers.

Standard EN 388 - Protective gloves against mechanical risk.

- Other : Wear safety shoes while handling containers.

Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

Respiratory protection
 Gas filters may be used if all surrounding conditions e.g. type and concentration of the

contaminant(s) and duration of use are known.

Use gas filters with full face mask, where exposure limits may be exceeded for a short-term

period, e.g. connecting or disconnecting containers. Gas filters do not protect against oxygen deficiency.

Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be

used in oxygen-deficient atmospheres.



Page: 5/9 Revised edition no: 4.00 Revision date: 2018-11-23

Supersedes: 2014-09-04

## 201001

Country: DE / Language: EN

## ALbee™ Weld ArMix

Standard EN 14387 - Gas filter(s), combined filter(s) and standard EN136, full face masks. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

 Thermal hazards : None in addition to the above sections.

8.2.3. Environmental exposure controls

: None necessary.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Appearance

• Physical state at 20°C / 101.3kPa

 Colour Mixture contains one or more component(s) which have the following colour(s):

Colourless

Odour Odourless

Odour threshold : Odour threshold is subjective and inadequate to warn of overexposure.

Melting point Not applicable for gas mixtures. **Boiling point** : Not applicable for gas mixtures.

Flash point Not applicable for gases and gas mixtures.

Flammability range Non flammable. Relative vapour density at 20 °C Not applicable.

Evaporation rate (ether=1) : Not applicable for gases and gas mixtures.

Vapour pressure [20°C] Not applicable. Vapour pressure [50°C] : Not applicable. Relative density, gas (air=1) Heavier than air.

Solubility in water of component(s) of the mixture : Solubility in water

Carbon dioxide: 2000 mg/l Completely soluble. • Argon: 67.3 mg/l

pH value Not applicable for gases and gas mixtures.

Partition coefficient n-octanol/water [log Kow] : Not applicable for gas mixtures.

Decomposition point [°C] Not applicable. Auto-ignition temperature Non flammable.

Viscosity [20°C] No reliable data available.

**Explosive Properties** : Not applicable. Oxidising Properties : Not applicable.

9.2. Other information

Molar mass : Not applicable for gas mixtures.

Other data Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below

ground level.

### **SECTION 10: Stability and reactivity**

10.1. Reactivity

: No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

: Stable under normal conditions.

10.3. Possibility of hazardous reactions

: None under normal use.

10.4. Conditions to avoid

: Avoid moisture in installation systems.



Page : 6/9
Revised edition no : 4.00

Revision date : 2018-11-23 Supersedes : 2014-09-04

201001

Country: DE / Language: EN

## ALbee™ Weld ArMix

### 10.5. Incompatible materials

: For additional information on compatibility refer to ISO 11114.

#### 10.6. Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

**Acute toxicity** 

: Toxicological effects not expected from this product if occupational exposure limit values are not exceeded.

Unlike simple asphyxiants, carbon dioxide has the ability to cause death even when normal oxygen levels (20-21%) are maintained. 5% CO2 has been found to act synergistically to increase the toxicity of certain other gases (CO, NO2). CO2 has been shown to enhance the production of carboxy- or met-hemoglobin by these gases possibly due to carbon dioxide's stimulatory effects on the respiratory and circulatory systems.

For more information, see 'EIGA Safety Info 24: Carbon Dioxide, Physiological Hazards' at www.eiga.eu.

Skin corrosion/irritation: No known effects from this product.Serious eye damage/irritation: No known effects from this product.Respiratory or skin sensitisation: No known effects from this product.Germ cell mutagenicity: No known effects from this product.Carcinogenicity: No known effects from this product.

Reproductive toxicity

Toxic for reproduction : Fertility : No known effects from this product.

Toxic for reproduction : unborn child : No known effects from this product.

STOT-single exposure : No known effects from this product.

STOT-repeated exposure : No known effects from this product.

**Aspiration hazard** : Not applicable for gases and gas mixtures.

### **SECTION 12: Ecological information**

### 12.1. Toxicity

Assessment : No ecological damage caused by this product.

EC50 48h - Daphnia magna [mg/l] : No data available. EC50 72h - Algae [mg/l] : No data available. LC50 96 h - Fish [mg/l] : No data available.

### 12.2. Persistence and degradability

Assessment : No ecological damage caused by this product.

### 12.3. Bioaccumulative potential

Assessment : No data available.

#### 12.4. Mobility in soil

Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution.

Partition into soil is unlikely.

### 12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB.



Page: 7/9
Revised edition no: 4.00

Revision date : 2018-11-23 Supersedes : 2014-09-04

## 201001

Country: DE / Language: EN

## **ALbee™ Weld ArMix**

12.6. Other adverse effects

Other adverse effects : No known effects from this product.

Effect on the ozone layer : None.

Effect on global warming : Contains greenhouse gas(es).

### **SECTION 13: Disposal considerations**

13.1. Waste treatment methods

May be vented to atmosphere in a well ventilated place.

Do not discharge into any place where its accumulation could be dangerous.

Return unused product in original cylinder to supplier.

List of hazardous waste codes (from Commission Decision 2001/118/EC)

: 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.

13.2. Additional information

: External treatment and disposal of waste should comply with applicable local and/or national

regulations.

### **SECTION 14: Transport information**

### 14.1. UN number

UN-No. : 1956

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) : COMPRESSED GAS, N.O.S. (Argon, Carbon dioxide)

Transport by air (ICAO-TI / IATA-DGR) : Compressed gas, n.o.s. (Argon, Carbon dioxide)

Transport by sea (IMDG) : COMPRESSED GAS, N.O.S. (Argon, Carbon dioxide)

14.3. Transport hazard class(es)

Labelling



2.2: Non-flammable, non-toxic gases.

Transport by road/rail (ADR/RID)

Class : 2.
Classification code : 1A.
Hazard identification number : 20.

Tunnel Restriction : E - Passage forbidden through tunnels of category E.

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)) : 2.2

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.2
Emergency Schedule (EmS) - Fire : F-C.
Emergency Schedule (EmS) - Spillage : S-V.

14.4. Packing group

Transport by road/rail (ADR/RID) : Not established.

Transport by air (ICAO-TI / IATA-DGR) : Not established.

Transport by sea (IMDG) : Not established.

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None.

Transport by air (ICAO-TI / IATA-DGR) : None.



Page: 8/9
Revised edition no: 4.00

Revision date: 2018-11-23 Supersedes: 2014-09-04

## 201001

Country: DE / Language: EN

## ALbee™ Weld ArMix

Transport by sea (IMDG) : None.

#### 14.6. Special precautions for user

#### Packing Instruction(s)

Transport by road/rail (ADR/RID) : P200.

Transport by air (ICAO-TI / IATA-DGR)

Passenger and Cargo Aircraft : 200.
Cargo Aircraft only : 200.
Transport by sea (IMDG) : P200.

Special transport precautions

: Avoid transport on vehicles where the load space is not separated from the driver's

compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the

event of an accident or an emergency. Before transporting product containers:

- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure cylinder valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

: Not applicable.

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU-Regulations**

Restrictions on use : None.

Seveso Directive: 2012/18/EU (Seveso III) : Not covered.

#### **National regulations**

National legislation : Ensure all national/local regulations are observed.

### Germany

Water hazard class (WGK) : Water hazard class (WGK) nwg, Non-hazardous to water (Classification according to AwSV,

Annex 1)

Other information, restrictions and prohibition

regulations

: [German regulations] BetriebssicherheitsV mit TRBSen insbesondere TRBS 3145 / TRGS 725 Ortsbewegliche Druckgasbehälter", TRBS 2141, BGRegel 500 Teil 2.33: "Umgang mit Gasen", GefahrstoffV mit Technischen Regeln Gefährliche Stoffe TRGS insbesondere TRGS 407

"Tätigkeiten mit Gasen - Gefährdungsbeurteilung", TRGS 400, 500, 510, 900."

#### 15.2. Chemical safety assessment

A CSA does not need to be carried out for this product.

## **SECTION 16: Other information**

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.

Abbreviations and acronyms : ATE - Acute Toxicity Estimate

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC)

No 1907/2006

EINECS - European Inventory of Existing Commercial Chemical Substances

CAS# - Chemical Abstract Service number



Page: 9/9 Revised edition no: 4.00 Revision date: 2018-11-23

Supersedes: 2014-09-04

201001

Country: DE / Language: EN

ALbee™ Weld ArMix

PPE - Personal Protection Equipment

LC50 - Lethal Concentration to 50 % of a test population

RMM - Risk Management Measures

PBT - Persistent, Bioaccumulative and Toxic

vPvB - Very Persistent and Very Bioaccumulative

STOT- SE: Specific Target Organ Toxicity - Single Exposure

CSA - Chemical Safety Assessment

EN - European Standard

**UN - United Nations** 

ADR - European Agreement concerning the International Carriage of Dangerous Goods by

Road

IATA - International Air Transport Association

IMDG code - International Maritime Dangerous Goods

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

WGK - Water Hazard Class

The hazard of asphyxiation is often overlooked and must be stressed during operator training.

Classification using data from databases maintained by the European Industrial Gases Association (EIGA).

Classification in accordance with the calculation methods of Regulation (EC) 1272/2008 CLP.

Full text of H- and EUH-statements

Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
H280	Contains gas under pressure; may explode if heated.

DISCLAIMER OF LIABILITY

Training advice Further information

> : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press.

Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.